Based on the sources provided, here are the answers to your assignment questions:

1. Why we need inner class

We use inner classes when a particular class is **totally dependent on another class** or is intended to be used only for a specific purpose within that outer class. If a class has no need to exist independently outside of its relationship with another class, nesting it inside as an inner class keeps the structure logically grouped and organized.

2. When to use Anonymous inner class

You should use an **Anonymous inner class** in the following scenarios:

- **One-time implementation:** When you need a specific implementation of a class or behavior that will be used **only once**, making it unnecessary to create a separate, named class file.
- **Method overriding:** When you want to **change the behavior of a method** (overriding) for a specific object instance without defining a new subclass.
- **Implementing Abstract Classes or Interfaces:** It is a common practice to use anonymous inner classes to provide an immediate implementation for an **abstract class or an interface** without needing to create a concrete subclass.

3. When to use abstract keyword in Java

The abstract keyword is used in Java for several critical design purposes:

- **Declaring unimplemented methods:** Use abstract when you want to define that a certain feature (method) must exist, but you do **not yet know how to implement the logic** for it.
- **Enforcing a structure:** By marking a method as abstract, you force any **subclass to implement that method**, ensuring that the resulting objects follow a specific design or contract.
- **Restricting instantiation:** Use the abstract keyword on a class to **prevent anyone from creating an object** of that class directly. This is useful for classes that represent general concepts (like "Car") rather than specific, concrete things (like "WagonR").
- **Defining abstract methods:** If a class contains even one abstract method, the **class itself must be declared as abstract**. However, an abstract class can contain both abstract methods and normal (implemented) methods.