
Note to other teachers and users of these slides: We would be delighted if you found our material useful for giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <a href="http://www.mmds.org">http://www.mmds.org</a>

# Optimizing Submodular Functions

CS246: Mining Massive Datasets
Jure Leskovec, Stanford University
http://cs246.stanford.edu



# Announcement: Final Exam Logistics

## Final: Logistics

#### Date:

- Thursday, March 19, 12:15-3:15 PM PDT
- Location:
  - if SUNetID[0] in ['A', .. 'R'] then Cubberley Auditorium
  - if SUNetID[0] in ['S', .. 'Z'] then STLC114
- Alternate Date:
  - Wednesday, March 18, 6:00-9:00 PM PDT
  - Location:
    - Gates 104
    - There is still SOME SPACE LEFT!
- TAs will NOT answer questions during the final

#### Final: SCPD Logistics

#### You may come to Stanford to take the exam, or...

- Date:
  - From Wed, Mar 18, 6 PM to Thu, Mar 19, 6 PM (PDT)
  - Agree with your exam monitor on the most convenient 3-hour slot in that window of time
- Exam monitors will receive an email from SCPD with the final exam, which they will in turn forward to you right before the beginning of your 3-hour slot
- Once you completed the exam, make sure to send the file back to your exam monitor (high-quality scanned copy)
- Exam monitors will NOT answer questions during the final

#### Final: Instructions

- Final exam is open book and open notes
- A calculator or computer is REQUIRED
  - You may only use your computer to do arithmetic calculations (i.e., the buttons found on a standard scientific calculator)
  - You may also use your computer to read course notes or the textbook
  - But no Internet/Google/Python access is allowed
- Practice finals are posted on Piazza!
- We recommend bringing a power strip

# Optimizing Submodular Functions

CS246: Mining Massive Datasets
Jure Leskovec, Stanford University
http://cs246.stanford.edu



#### Recommendations: Diversity

Redundancy leads to a bad user experience


**Obama Calls for Broad Action on Guns** 

Obama unveils 23 executive actions, calls for assault weapons ban

Obama seeks assault weapons ban, background checks on all gun sales

- Uncertainty around information need => don't put all eggs in one basket
- How do we optimize for diversity directly?

# Covering the day's news




France intervenes

Chuck for Defense

Hagel expects fight

Monday, January 14, 2013

## Covering the day's news



France intervenes

Chuck for Defense

New gun proposals

Monday, January 14, 2013

# **Encode Diversity as Coverage**


- Idea: Encode diversity as coverage problem
- Example: Word cloud of news for a single day
  - Want to select articles so that most words are "covered"



# **Diversity as Coverage**

# What is being covered?

- Q: What is being covered?
- A: Concepts (In our case: Named entities)



- Q: Who is doing the covering?
- A: Documents

#### Simple Abstract Model

- Suppose we are given a set of documents D
  - Each document **d** covers a set  $X_d$  of words/topics/named entities **W**
- For a set of documents A ⊆D we define

$$F(A) = \left| \bigcup_{i \in A} X_i \right|$$


Goal: We want to

$$\max_{|A| \le k} F(A)$$

■ Note: F(A) is a set function: F(A): Sets  $\rightarrow \mathbb{N}$ 

## Maximum Coverage Problem

• Given universe of elements  $W = \{w_1, ..., w_n\}$  and sets  $X_1, ..., X_m \subseteq W$ 



- Goal: Find k sets X<sub>i</sub> that cover the most of W
  - More precisely: Find k sets X<sub>i</sub> whose size of the union is the largest
  - Bad news: A known NP-complete problem


#### Simple Heuristic: Greedy Algorithm:


- Start with  $A_0 = \{\}$
- For i = 1 ... k
  - Find set d that  $\max F(A_{i-1} \cup \{d\})$
  - Let  $A_i = A_{i-1} \cup \{d\}$


$$F(A) = \left| \bigcup_{d \in A} X_d \right|$$


#### Example:


- Eval.  $F(\{d_1\}), ..., F(\{d_m\})$ , pick best (say  $d_1$ )
- lacksquare Eval.  $F(\{d_1\}\cup\{d_2\}),\ldots$  ,  $F(\{d_1\}\cup\{d_m\})$  , pick best (say  $d_2$ )
- ullet Eval.  $F(\{d_1,d_2\}\cup\{d_3\})$ , ...,  $F(\{d_1,d_2\}\cup\{d_m\})$ , pick best
- And so on...












## When Greedy Heuristic Fails?



- Goal: Maximize the size of the covered area
- Greedy first picks A and then C
- But the optimal way would be to pick B and C

# **Approximation Guarantee**


- Greedy produces a solution A where:  $F(A) \ge (1-1/e)*OPT$   $(F(A) \ge 0.63*OPT)$  [Nemhauser, Fisher, Wolsey '78]
- Claim holds for functions F(·) with 2 properties:
  - F is monotone: (adding more docs doesn't decrease coverage) if  $A \subseteq B$  then  $F(A) \leq F(B)$  and  $F({}_{\{\}})=0$
  - F is submodular:
     adding an element to a set gives less improvement
     than adding it to one of its subsets

## Submodularity: Definition

#### **Definition:**

Set function F(·) is called submodular if: For all A,B⊆W:


$$F(A) + F(B) \ge F(A \cup B) + F(A \cap B)$$




# Submodularity: Or equivalently

- Diminishing returns characterization
   Equivalent definition:
- Set function F(·) is called submodular if: For all A⊆B:

$$F(A \cup \{d\}) - F(A) \ge F(B \cup \{d\}) - F(B)$$
Gain of adding  $d$  to a small set
Gain of adding  $d$  to a large set





#### Example: Set Cover


•  $F(\cdot)$  is submodular:  $A \subseteq B$ 

$$F(A \cup \{d\}) - F(A) \geq F(B \cup \{d\}) - F(B)$$

Gain of adding **d** to a small set


Gain of adding **d** to a large set

- Natural example:
  - Sets  $d_1, \ldots, d_m$
  - $F(A) = |\bigcup_{i \in A} d_i|$ (size of the covered area)
  - Claim: F(A) is submodular!



# Submodularity – Diminishing returns

Submodularity is discrete analogue of concavity



## Submodularity & Concavity

Marginal gain:


$$\Delta_F(d|A) = F(A \cup \{d\}) - F(A)$$

Submodular:

$$F(A \cup \{d\}) - F(A) \ge F(B \cup \{d\}) - F(B)$$

Concavity:

$$f(a+d)-f(a) \ge f(b+d)-f(b)$$



 $A \subseteq B$ 


 $a \leq b$ 

# Submodularity: Useful Fact

- Let  $F_1 \dots F_m$  be submodular and  $\lambda_1 \dots \lambda_m > 0$  then  $F(A) = \sum_{i=1}^m \lambda_i F_i(A)$  is submodular
  - Submodularity is closed under non-negative linear combinations!
- This is an extremely useful fact:
  - Average of submodular functions is submodular:  $F(A) = \sum_{i} P(i) \cdot F_{i}(A)$
  - Multicriterion optimization:  $F(A) = \sum_{i} \lambda_{i} F_{i}(A)$

#### Back to our problem

- Q: What is being covered?
- A: Concepts (In our case: Named entities)




Hagel expects fight

- Q: Who is doing the covering?
- A: Documents

### Back to our Concept Cover Problem


Objective: pick k docs that cover most concepts



- F(A): the number of concepts covered by A
  - Elements...concepts, Sets ... concepts in docs
  - F(A) is submodular and monotone!
  - We can use greedy algorithm to optimize F

#### The Set Cover Problem

Objective: pick k docs that cover most concepts



The good:

Penalizes redundancy
Submodular

The bad:

**Concept importance?** 

All-or-nothing too harsh

## Probabilistic Set Cover

#### Concept importance?


**Objective:** pick **k** docs that cover most concepts Pentagon Obama Zero Dark Thirty France Mali Hagel Romney **Enthusiasm for Inauguration wanes Inauguration weekend** 

ullet Each concept c has importance weight  $w_c$ 

#### All-or-nothing too harsh

Document coverage function

$$\operatorname{cover}_d(c) = \operatorname{probability} \operatorname{document} \operatorname{d} \operatorname{covers}$$
 
$$\operatorname{concept} \operatorname{c}$$
 [e.g., how strongly  $\operatorname{d} \operatorname{covers} \operatorname{c}$ ]



**Enthusiasm for Inauguration wanes** 

#### Probabilistic Set Cover

Document coverage function:

$$cover_d(c) =$$
**probability** document **d** covers concept **c**

- Cover<sub>d</sub>(c) can also model how relevant is concept c for user u
- Set coverage function:

$$\operatorname{cover}_{\mathcal{A}}(c) = 1 - \prod_{d \in \mathcal{A}} (1 - \operatorname{cover}_d(c))$$

Prob. that at least one document in A covers c

- Objective: concept weights 
$$\max_{\mathcal{A}:|\mathcal{A}|\leq k}F(\mathcal{A})=\sum_{c}w_{c}\operatorname{cover}_{\mathcal{A}}(c)$$


# Optimizing F(A)

$$\max_{\mathcal{A}:|\mathcal{A}|\leq k} F(\mathcal{A}) = \sum_{c} w_c \operatorname{cover}_{\mathcal{A}}(c)$$

- The objective function is also submodular
  - Intuitively, it has a diminishing returns property
  - Greedy algorithm leads to a  $(1 1/e) \sim 63\%$  approximation, i.e., a **near-optimal** solution

## Summary: Probabilistic Set Cover

Objective: pick k docs that cover most concepts



**Enthusiasm for Inauguration wanes** 

**Inauguration weekend** 

- Each concept c has importance weight w<sub>c</sub>
- Documents partially cover concepts:  $\mathbf{cover}_d(c)$

## Lazy Optimization of Submodular Functions

### **Submodular Functions**

#### Greedy

Marginal gain:  $F(A \cup x)-F(A)$ 











Add document with highest marginal gain

- Greedy algorithm is slow!
  - At each iteration we need to re-evaluate marginal gains of all remaining documents
  - Runtime  $O(|D| \cdot K)$  for selecting K documents out of the set of D of them

## Speeding up Greedy

- In round i: So far we have  $A_{i-1} = \{d_1, ..., d_{i-1}\}$ 
  - Now we pick  $\mathbf{d}_i = \arg\max_{d \in V} F(A_{i-1} \cup \{d\}) F(A_{i-1})$ 
    - Greedy algorithm maximizes the "marginal benefit"  $\Delta_i(d) = F(A_{i-1} \cup \{d\}) F(A_{i-1})$
- By submodularity property:

$$F(A_i \cup \{d\}) - F(A_i) \ge F(A_j \cup \{d\}) - F(A_j) \text{ for } i < j$$

Observation: By submodularity:

For every  $d \in D$ 

$$\Delta_i(d) \ge \Delta_j(d)$$
 for  $i < j$  since  $A_i \subseteq A_j$ 

 $\Delta_i(d) \ \geq \Delta_j(d)$ 

• Marginal benefits  $\Delta_i(d)$  only shrink!

d

(as i grows)

Selecting document **d** in step **i** covers more words than selecting **d** at step **j** (j>i)

## Lazy Greedy

#### Idea:

- Use  $\Delta_i$  as upper-bound on  $\Delta_j$  (j > i)
- Lazy Greedy:
  - Keep an ordered list of marginal benefits  $\Delta_i$  from previous iteration
  - Re-evaluate  $\Delta_i$  only for top element
  - Re-sort and prune

(Upper bound on) Marginal gain  $\Delta_1$ 



 $A_1 = \{a\}$ 







 $F(A \cup \{d\}) - F(A) \geq F(B \cup \{d\}) - F(B)$   $A \subseteq B$ 

## Lazy Greedy

#### Idea:

- Use  $\Delta_i$  as upper-bound on  $\Delta_j$  (j > i)
- Lazy Greedy:
  - Keep an ordered list of marginal benefits  $\Delta_i$  from previous iteration
  - Re-evaluate  $\Delta_i$  only for top element
  - Re-sort and prune

Upper bound on Marginal gain  $\Delta_2$ 



 $A_1 = \{a\}$ 









 $F(A \cup \{d\}) - F(A) \geq F(B \cup \{d\}) - F(B)$   $A \subseteq B$ 

## Lazy Greedy


#### Idea:

- Use  $\Delta_i$  as upper-bound on  $\Delta_j$  (j > i)
- Lazy Greedy:
  - Keep an ordered list of marginal benefits  $\Delta_i$  from previous iteration
  - Re-evaluate  $\Delta_i$  only for top element
  - Re-sort and prune

Upper bound on Marginal gain  $\Delta_2$ 




 $A_1 = \{a\}$ 



 $A_2 = \{a,b\}$ 






 $F(A \cup \{d\}) - F(A) \geq F(B \cup \{d\}) - F(B)$   $A \subseteq B$ 


## Summary so far

#### Summary so far:

- Diversity can be formulated as a set cover
- Set cover is submodular optimization problem
- Can be (approximately) solved using greedy algorithm
- Lazy-greedy gives significant speedup




# But what about personalization?



## **Concept Coverage**

#### We assumed same concept weighting for all users



## Personal Concept Weights

Each user has different preferences over concepts <u>Obama</u> Romney Zero Dark Thirty Pentagon Hagel politico Romney Zero Dark Thirty Mali <u>Obama</u> Hagel Pentagon movie buff

## Personal concept weights


• Assume each user u has **different** preference vector  $w_c^{(u)}$  over concepts c

$$\max_{\mathcal{A}:|\mathcal{A}| \leq k} F(\mathcal{A}) = \sum_{c} w_c \operatorname{cover}_{\mathcal{A}}(c)$$

$$\max_{\mathcal{A}:|\mathcal{A}| \leq k} F(\mathcal{A}) = \sum_{c} w_c^{(u)} \operatorname{cover}_{\mathcal{A}}(c)$$

 Goal: Learn personal concept weights from user feedback

## Interactive Concept Coverage



## Multiplicative Weights (MW)

#### Multiplicative Weights algorithm

- Assume each concept c has weight  $w_c$
- We recommend document  $m{d}$  and receive feedback, say  $m{r} = + {f 1}$  or  ${f 1}$
- Update the weights:
  - For each  $c \in X_d$  set  $w_c = \beta^r w_c$ 
    - If concept **c** appears in doc **d** and we received positive feedback **r=+1** then we increase the weight  $\mathbf{w}_{c}$  by multiplying it by  $\boldsymbol{\beta}$  ( $\boldsymbol{\beta} > 1$ ) otherwise we decrease the weight (divide by  $\boldsymbol{\beta}$ )
  - Normalize weights so that  $\sum_c w_c = 1$

## Summary of the Algorithm

#### Steps of the algorithm:

- 1. Identify **items** to recommend from
- 2. Identify concepts [what makes items redundant?]
- 3. Weigh concepts by general importance
- 4. Define item-concept coverage function
- 5. Select items using probabilistic set cover
- 6. Obtain **feedback**, **update** weights