



CS+Social Good
CS 106S Winter 2018

hi!!!!11!1!

we are so excited to meet you!



Ashi Agrawal
Stanford '19
ashia@stanford.edu



Ryan Cohen
Stanford '19
rrcohen@stanford.edu



Kevin Khieu
Stanford '18
kkhieu@stanford.edu




Matthew Sun
Stanford '20
mattsun@stanford.edu



why section?

well why not, HUH????



logistics

TIME

Thursdays, 4:30 – 6:20 PM

LOCATION

Littlefield 107

DURATION

10 weeks

CREDIT/GRADING

1 unit, Pass/Fail

GRADING

Attendance ($\geq 9/10$)

Checkoff forms

Final reflections

TEAM


Ashi Agrawal, Ryan Cohen

Kevin Khieu, Matthew Sun


Bring your laptops to every class!



the good stuff!



the good stuff!



the good stuff!



JavaScript

FROM WIKIPEDIA:

**high-level, dynamic,
untyped, and interpreted
programming language**

**prototype-based with first-
class functions**

**supports object-oriented
programming**



let's program some stuff!

...but first, open
repl.it/languages/javascript



JavaScript variables

```
var x; // dynamic typing
typeof x; // should print out 'undefined'
x = 42; // typeof x == 'number'
x = "CS106S rocks" // typeof x == 'string'
x = true; // typeof x == 'boolean'
```



Variable Scoping

// **Two scopes:** global and function local


```
var globalVar;  
function() {  
    var localVar;  
    if(globalVar > 0) {  
        var localVar2 = 2;  
    }  
}
```



Variable Scoping (cont.)

// All var statements **hoisted** to top of scope

```
function foo() {  
  var x;  
  x = 2;  
}
```



```
function foo() {  
  x = 2;  
  var x;  
}
```



number

- no distinction between int and double
- stored in floating point
 - Watch out! `(0.1 + 0.2) == 0.3` is `false`
- interesting: `NaN`, `Infinity` are numbers
 - `1/0 == Infinity`
 - `Math.sqrt(-1) == NaN`



string

```
var valleyQuote = 'Our startup is like Uber for  
blockchain and it's going to revolutionize the  
way we deliver pizza. #investpls'
```

```
valleyQuote.length // 108
```

- variable length
- + is string concat operator // 'CS' + 'SG' == 'CSSG'
- useful methods: indexOf(), charAt(), search(), replace(), toUpperCase(), substr(), etc.



boolean

```
var cs = true;  
var socialGood = true;  
var cssg = cs && socialGood; // true
```

- Either true or false
- Values are classified as **truthy** or **falsy**:
 - Used when values are converted to a boolean
- Falsy: false, 0, "", null, undefined, NaN
- Truthy: anything that isn't falsy



object

```
var berkeley = {intelligence: 0, tears: Infinity};  
var stanford = {intelligence: 100, smiles: Infinity};
```

- Unordered collection of name-value pairs called **properties**
- Name can be any string: `var x = { "": "empty", "---": "dashes" }`
- Referenced either like a structure or like a hash table with string keys:
 - `stanford.smiles` or `stanford["smiles"]`



object

- Properties can be added or deleted

```
var queen = {};
```

```
queen.name = "Beyonce"; // queen.name returns "Beyonce"
```

- To remove use delete:

```
delete queen.name; // queen is now an empty object
```

- To enumerate use Object.keys():

```
Object.keys({name: "Alice", age: 23}) = ["name", "age"]
```



Arrays

```
var youIs = ['smart', 'kind', 'important',];
```

- Special objects: `typeof youIs == 'object'`
- Zero-indexed
- Can be **sparse** and **polymorphic**
 - `youIs[5] = 100; // ['smart', 'kind', 'important',,, 100]`
- Like strings, have many methods: `youIs.length == 3`
 - `push`, `pop`, `shift`, `unshift`, `sort`, `reverse`, `splice`



Checking Equality

Who would win: `==` or `===`

`==` (loose equality)

- Compares two values for equality, *after* converting both values to a common type
 - `3 == '3' // true`

`===` (strict equality)

- Neither value is implicitly converted before comparison
- Different types → unequal
 - `3 === '3' // false`



undefined and null

- `undefined` – does not have a value assigned

```
var x; // x has a value of undefined
```

```
x = undefined; // can be explicitly stored
```

```
typeof x == 'undefined'
```

- `null` – a value that represents whatever the user wants it to (sentinel)

```
typeof null = 'object'
```

- Both are falsy but not equal (`null == undefined`,
`null !== undefined`)



Conditionals & Loops (you know the drill...)

```
if (condition) {  
    // do something  
}
```

```
for (var i = 0; i < 10; i++) {  
    // do something 10 times  
}
```

```
while (condition) {  
    // do something  
    // while condition  
    // is truthy  
}
```



function type

```
// untyped parameters
function isGoodPerson(isIn106S) {
    if(isIn106S) {
        return 'Definitely. No question.';
    } else {
        return 'Maybe? Like, it's possible.';
    }
}

// all functions return a value; default is undefined
```



First-class function example


```
function myFunc(routine) {  
    console.log('Called with', routine.toString());  
    var retVal = routine(10);  
    console.log('retVal', retVal);  
}  
myFunc(function (x) {  
    console.log('Called with', x);  
    return x+1;  
})  
);
```



Console

Chrome:

Right click → Inspect Element *or*
command + alt + i (Mac) or ctrl + shift + i (Windows)



funzo assignment time

Let's put your knowledge to the test by making a program that helps your friends feel better!

Copy the code at bit.ly/cssgnicebot into a repl.it and fill in the code for saySomethingNice, upliftingQuote, inspiringQuote, and soothingQuote.





See you next time, friends!

Before next time:

Install Python 3

Install Node.js