



BIRMINGHAM CITY
University

Using supervised learning for the binary classification of Type 2 Diabetes

Lewis Higgins - Student ID 22133848

CMP6202 - Artificial Intelligence & Machine Learning

Module Coordinator: Nouh Elmitwally

Contents

1	Introduction	1
1.1	Dataset Identification	2
1.2	Supervised learning task identification	3
2	Exploratory Data Analysis	4
2.1	Data Integration	4
2.2	Question identification and assumptions	5
2.3	Splitting the dataset	7
2.4	EDA process and results	8
2.5	EDA conclusions	9
3	Experimental Design	11
3.1	Identification of chosen algorithms	11
3.2	Identification of appropriate evaluation techniques	11
3.3	Data Cleaning and Pre-processing Transformations	11
3.4	Limitations and Options	11
4	Model Development	12
4.1	Predictive modelling process	12
4.2	Results on seen data	12
5	Evaluation and further improvements	13
6	Conclusion	14
6.1	Summary of results	14
6.2	Reflection on Individual Learning	14
	Appendix A - EDA Process and Results	15
A.1	Identification of missing or impossible values	15
A.2	Target univariate analysis	17
A.3	Multivariate analysis	18
A.3.1	Data distributions by Outcome	18
A.3.2	Pair plot	21
A.3.3	Correlation Matrix	23

Abstract

Probably would benefit from an abstract. You can't really write this until the very end though, so return to it then. **The example work is from a previous year wherein this assessment was a group task. You can see that each group member developed one ML model, but you seem to be developing all of them yourself, so don't be misled by the report titles only mentioning one model.**

Introduction

Diabetes mellitus, or type 2 diabetes, accounts for 90% of the 4.4 million cases of diabetes in the UK, and it is estimated that there are 1.2 million undiagnosed cases of type 2 diabetes across the country (Diabetes UK, 2024a). The rate of type 2 diabetes per 100,000 individuals is rapidly increasing, with Khan et al. (2020)'s analysis projecting that by 2030, the rate will reach 7,079 per 100,000. Many people with diabetes suffer immensely reduced quality of life, with approximately 50% of patients suffering from peripheral neuropathy (Dhanapalaratnam et al., 2024), an irreversible disability which causes immense pain due to nerve damage from high blood sugar (NHS, 2022), which can occur when the patient was unaware they even had diabetes.

Therefore, it is imperative that systems are put in place to enable the swift diagnosis of diabetes, especially type 2 diabetes given its major prevalence. This can be accomplished by training machine learning models on existing clinical datasets to identify common trends in those with and without type 2 diabetes. This report will document the planning, development and evaluation of multiple machine learning models in their classification of whether individuals have type 2 diabetes based on multiple clinical factors, specifically through the stages of:

- Dataset Identification
- Data Integration
- Data Preprocessing
- Exploratory Data Analysis (EDA)
- Model Development
- Model Evaluation
- Research Conclusions

1.1 Dataset Identification

Machine learning models require large amounts of data to train upon, meaning a dataset must be identified consisting of many rows and features. This project identified two datasets which could be integrated into one larger dataset, the first of which being the well-reputed Pima Indian Diabetes Database (UCI Machine Learning, 2024), downloaded from [Kaggle](#), a platform for students and researchers alike to download and upload datasets and code for research purposes. The data originates from the National Institute of Diabetes and Digestive and Kidney Diseases, who collected this data from Pima Indian¹ women aged 21 and over in hospitals in Phoenix, Arizona, USA, and it has previously seen wide use across academic literature relating to machine learning (AlZu'bi et al. (2023), Zou, Zhang, and Chen (2024), Joshi and Dhakal (2021), Hayashi and Yukita (2016)), where other researchers have also aimed to solve the problem of diabetes classification via supervised learning. This dataset contains 768 rows with 9 features.

This project also includes a second dataset, also from [Kaggle](#), that has been previously used in literature by Zou, Zhang, and Chen (2024). This dataset (John DaSilva, 2024) is based on data from female patients in Frankfurt, Germany, and includes the same 9 features as the Pima Indian dataset, but includes 2000 rows. By integrating these two datasets into one larger dataset of 2768 rows, it will be possible to give the machine learning models more data to train upon.

Table 1.1 details the 9 features seen in both datasets and their descriptions.

Feature	Description
Pregnancies	The number of pregnancies the patient has had.
Glucose	Plasma glucose concentration over 2 hours in an oral glucose tolerance test.
BloodPressure	Diastolic blood pressure in mm/Hg.
SkinThickness	Triceps skin fold thickness (mm)
Insulin	2-hour serum insulin.
BMI	Body Mass Index, calculated from the patient's weight and height.
DiabetesPedigreeFunction	The product of a function to ascertain the probability of diabetes based on family genetics. (Akmeşe, 2022)
Age	The patient's age.
Outcome	Whether the patient is likely to develop diabetes.

Table 1.1: The features seen in both datasets.

¹"Pima Indian" refers to a specific Native American ethnic group rather than people from India.

1.2 Supervised learning task identification

As previously mentioned, it is possible for patients to have diabetes without knowing. Therefore, it is paramount that swift and simple diagnosis methods are put in place, which can be achieved through the use of supervised learning classification models. This requires the existence of the "ground truth", which refers to the label given to data that indicates its class (c3.ai, 2024). Within these datasets, the ground truth is present as the 'Outcome' feature, which will be used as the target variable for the produced classification models.

Exploratory Data Analysis

This chapter details the EDA processes undertaken with the datasets, including key questions that will be answered by the process, as well as the splitting of the data into training and testing sets.

2.1 Data Integration

The two datasets must first be merged into one to allow for an overall analysis to be performed. This is a simple process because they both contain the same 9 features, and is detailed in Figure 2.1.

```
pima_df = pd.read_csv("Data/pima.csv")
pima_df.shape
✓ 0.0s
(768, 9)

frankfurt_df = pd.read_csv("Data/frankfurt.csv")
frankfurt_df.shape
✓ 0.0s
(2000, 9)

df = pd.concat([pima_df, frankfurt_df], axis = 0, ignore_index = True)
df.shape
✓ 0.0s
(2768, 9)
```

Figure 2.1: Integrating the two separate datasets into one larger dataset.

2.2 Question identification and assumptions

The key factors involved in the diagnosis of diabetes are critical to understand, which can be solved through EDA on these datasets. It is possible to make various assumptions based on topical background research of each of the features in the dataset, detailed in Table 2.1

Feature	Research-based assumptions
Pregnancies	Approximately 13.4% of pregnant women develop a temporary condition known as Gestational Diabetes Mellitus (GDM), which typically subsides after birth (Adam et al., 2023). However, research by (Dennison et al., 2021) indicates that 33% of women who develop GDM will go on to develop permanent diabetes mellitus within 15 years. Therefore, it is assumed that pregnancies will positively correlate with the diabetes outcome. It is also expected that pregnancies should naturally positively correlate with age.
Glucose	Glucose concentrations are an enormous factor in the diagnosis of diabetes mellitus, being one of the main metrics used to certify the condition, where results over 200mg/dL mean an absolute diagnosis ¹ (Aftab et al., 2021). It is therefore assumed that the glucose concentrations will be one of the strongest influences of the outcome, and that it will also correlate heavily with insulin levels.
BloodPressure	Diastolic blood pressure (DBP) does influence the diagnosis of diabetes mellitus, as 56.2% of recently diagnosed patients presented with elevated DBP in Nelaj et al. (2023)'s limited study of 126 patients, but it is not a decisive factor by itself. Therefore, it is assumed that there will be some correlation between DBP and the outcome, but not as major as other factors like plasma glucose levels.
SkinThickness	It is a frequent assumption even non-academically that people who weigh more, and by consequence have higher skin thickness in certain areas such as the triceps, have a higher risk of developing conditions like type 2 diabetes. This is backed by a study by Ruiz-Alejos et al. (2020), which found strong associations between skin thickness and diabetes mellitus, as well as high blood pressure. Therefore, it is assumed that there will be a strong correlation between tricep skin thickness and the outcome, as well as an expectation of strong correlations between thickness, BMI and blood pressure.
Insulin	Diabetes mellitus is directly associated with insulin deficiency, and as such, it is assumed that this factor will be the strongest influence in the outcome. This is because 2-hour serum insulin tests, as used in this dataset, are frequently part of HOMA-IR ² assessments.

¹The other main metric is insulin deficiency, meaning that the patient could have glucose levels lower than 200mg/dL and still be diagnosed if they are instead insulin deficient. (Aftab et al., 2021).

²Homeostasis Model Assessment of Insulin Resistance, used to measure insulin resistance (Tahapary et al., 2022), which can be used in both type 1 and type 2 diabetes diagnosis (Khalili et al., 2023).

BMI	BMI is likely to be a significant factor in the outcome, which is backed by previous academic studies indicating that 71% of studied individuals showed increases in BMI prior to diagnosis (Donnelly, McCrimmon, and Pearson, 2024). Additionally, BMI is used in insulin resistance measurement assessments, which are key assessments in diabetes diagnosis, meaning that it is a safe assumption that BMI will be a large factor in the outcome.
DiabetesPedigree-Function	People are more likely to develop diabetes mellitus if there is a family genetic history of the condition, though it is not directly caused by any one particular gene (Diabetes UK, 2024b). With the pedigree function aiming to quantify the inheritance probability, it can be assumed that it will likely correlate heavily with the outcome.
Age	Suastika et al. (2012) studied the effects of age as a risk factor for diabetes mellitus, finding that many natural associated factors of ageing including increases in body fat and decreases in lipid metabolism had considerable influence on the development of insulin resistance and diabetes mellitus by consequence. Therefore, it is likely that there will be a noticeable correlation between a patient's age and the outcome.

Table 2.1: Research-based assumptions prior to any EDA.

Based on these assumptions, the questions that this EDA process aims to answer are:

ID	Research-based assumptions
1	Are there any missing values or values that are not physically possible?
2	Are there any significant outliers?
3	Is the dataset evenly balanced in terms of the outcome? If not, what should be done?
4	Does the rate of diabetes positively correlate with the amount of pregnancies a woman has had?
5	Does the amount of pregnancies influence any of the other features?
6	What is the distribution of blood glucose levels in patients with and without diabetes?
7	Does BMI influence glucose levels?
8	Is diastolic blood pressure a worthwhile diagnosis method in this dataset?
9	Is the average skin thickness of those with diabetes actually higher than those without?
10	How does the relationship between insulin and glucose change between those with and without diabetes?

Table 2.2: The questions that this EDA process aims to answer.

2.3 Splitting the dataset

It is good practice to first split the data into training and testing sets before performing exploratory data analysis to avoid conceptual overfitting, also known as data leakage. Conceptual overfitting occurs when insights gained from the entire dataset influence model development decisions, which may eventually lead to actual overfitting. By excluding the training data from the analysis, it effectively simulates a real-world environment where the data being given to the model is not known, even to its developers.

Splitting the data is a mandatory process when developing supervised learning models, primarily for the prevention of overfitting. Overfitting is a significant challenge in machine learning, where models can perform exceptionally well on their original training data but are unable to generalize to unseen data, making them unsuitable for deployed use. The training set must consist of a large portion of the data so that the model has enough information to analyse and discover trends within, whereas the testing set is a smaller, unseen remainder of the data that the model's predictions can be evaluated against using various metrics. A key point of determination is the proportions of the dataset that should go in each set - there is no 'one-size-fits-all' percentage that can provide the best results for every possible dataset (Sivakumar, Parthasarathy, and Padmapriya, 2024), and factors such as the size of the dataset play a large part in this. Most commonly, splits are either 70:30 or 80:20 for training and testing sets respectively.

The integrated dataset for this project is 2,768 rows. This is considered to be a small dataset, and as such, it will be best to maximize the size of the training split, so a split of 80% training and 20% testing was used, visualized in Figure 2.2.




Figure 2.2: A visual representation of the train/test split.

To accomplish this, the data must first be split into X and y tables, where X consists of the eight features, and y is the target variable. After the data is split to X and y , it can be split into training and testing sets through Scikit-Learn's "train_test_split" method, as depicted in Figure 2.3

```
X = df.drop(columns = "Outcome", axis = 1)
y = df["Outcome"]
✓ 0.0s

print(X.shape)
print(y.shape) # No columns because y is now a Series consisting only of the Outcome column.
✓ 0.0s

(2768, 8)
(2768,)

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.2, random_state = 42)
✓ 0.0s

print(f"X_train: {X_train.shape}")
print(f"y_train: {y_train.shape}")
print(f"X_test: {X_test.shape}")
print(f"y_test: {y_test.shape}")
✓ 0.0s

X_train: (2214, 8)
y_train: (2214,)
X_test: (554, 8)
y_test: (554,)
```

Figure 2.3: Splitting the data at an 80:20 ratio.

By default, this method will first shuffle all rows in the dataset before splitting it, which introduces an element of randomness which can damage reproducibility. To combat this, the "random_state" parameter can be set to ensure that the same shuffle will occur every time.

2.4 EDA process and results

Exploratory Data Analysis is a key step in machine learning projects to gain a thorough understanding of the datasets used. In the interest of report conciseness, the full EDA process and results accompany this report as Appendix A. They were performed using the Seaborn Python library, which uses Matplotlib to produce convenient visualisations to answer each question posed in Table 2.2. The topics and issues identified during the process are solved in Section 3.3.

2.5 EDA conclusions

The extensive EDA conducted in Appendix A provided clear answers to each question posed in Table 2.2, which are detailed below in Table 2.3.

ID	EDA-based answer
1	There are missing values in the dataset that were not originally presented as such; they were instead 0s in columns where this would be physically impossible. After converting the impossible 0s to missing values with NumPy, it was established that there were 18 missing Glucose values, 125 missing BloodPressure values, 800 missing SkinThickness values, 1330 missing Insulin values, and 39 missing BMI values.
2	The analysis identified significant outliers across various features using box plots. Particularly extremely outliers were noted in the SkinThickness, BMI, and Insulin columns. These outliers could affect data scaling and model performance, and will need to be transformed in data cleaning.
3	The dataset is imbalanced, with 65.5% of rows in the training set having an outcome of 0, while the remaining 35.5% had an outcome of 1.
4	The EDA did show a somewhat positive correlation between the number of pregnancies and diabetes outcomes, although pregnancies alone are not decisive in predicting diabetes.
5	Pregnancies are found to correlate with age, as expected, but do not significantly influence other features.
6	There is a clear and significant distinction in glucose levels between diabetic and non-diabetic individuals, with higher levels being mostly present in those with diabetes, making it a strong indicator.
7	A slight positive correlation is observed between BMI and glucose levels, indicating that higher BMI could be associated with higher glucose levels.
8	Blood pressure shows some correlation with diabetes outcomes but is not a strong standalone diagnostic factor. However, like pregnancies, previously mentioned academic research specifies that it is still a useful feature to keep for the models.
9	Individuals with diabetes tend to have higher skin thickness on average, although this feature contains significant high outliers in both individuals with and without diabetes.
10	The relationship between insulin and glucose varies between diabetic and non-diabetic individuals, with diabetic individuals showing higher glucose levels as a result of lower insulin levels, which is expected of type 2 diabetes.

Table 2.3: Answers to the questions after the completion of the EDA process.

Overall, the EDA process conducted in Appendix A has been highly beneficial for many reasons. Firstly, it identified critical data issues, such as the abundance of missing values and outliers, which are essential to address to improve model accuracy and reliability. By recognizing these issues early, the EDA ensures that data preprocessing steps can be effectively planned to mitigate their impact. Secondly, the EDA highlighted significant correlations between features and the diabetes outcome, such as the strong influence of glucose levels and BMI on diabetes diagnosis. Understanding these relationships helps in feature selection and engineering, which are crucial for building effective predictive models. Additionally, the EDA revealed class imbalances in the dataset, guiding the development of strategies to handle this imbalance during model training to prevent biased predictions.

The insights gained from the EDA therefore provide a solid foundation for informed decision-making in the experimental design and model development, ensuring that the models are trained on clean, balanced, and relevant data, ultimately enhancing their predictive performance. This is especially crucial given that the models would be used in the medical field, where incorrect predictions could have life-changing ramifications.

Experimental Design

This chapter details the planned algorithms to be leveraged against this dataset, as well as the metrics to evaluate them. Furthermore, the data cleaning and preprocessing stages will be deeply explored, as well as some potential limitations relating to their use.

3.1 Identification of chosen algorithms

3.2 Identification of appropriate evaluation techniques

3.3 Data Cleaning and Pre-processing Transformations

3.4 Limitations and Options

Model Development

This chapter details the training and evaluation processes of the original produced models before any iterative improvements such as hyperparameter tuning.

4.1 Predictive modelling process

4.2 Results on seen data

Evaluation and further improvements

This chapter details the extensive evaluation of each model, as well as iterative improvements that were made to enhance their performance.

Conclusion

6.1 Summary of results

6.2 Reflection on Individual Learning

Appendix A - EDA Process and Results

Problems identified through the EDA conducted in this Appendix were resolved in Section 3.3.

A.1 Identification of missing or impossible values

An initial glance at the dataset would make it appear as though as there are not any missing values in the dataset, as shown in Figure A.1.

```
df.isna().sum()
✓ 0.0s
Pregnancies      0
Glucose           0
BloodPressure     0
SkinThickness     0
Insulin           0
BMI               0
DiabetesPedigreeFunction  0
Age               0
Outcome           0
```

Figure A.1: An initial count of missing values before any further analysis.

This would be very good - if it were true. Instead of missing values, this dataset contains impossible values in five columns, highlighted in red in Figure A.2.¹

```
df.describe()
```

	Pregnancies	Glucose	BloodPressure	SkinThickness	Insulin	BMI	DiabetesPedigreeFunction	Age	Outcome
count	2768.000000	2768.000000	2768.000000	2768.000000	2768.000000	2768.000000	2768.000000	2768.000000	2768.000000
mean	3.742775	121.102601	69.134393	20.824422	80.127890	32.137392	0.471193	33.132225	0.343931
std	3.323801	32.036508	19.231438	16.059596	112.301933	8.076127	0.325669	11.777230	0.475104
min	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.078000	21.000000	0.000000
25%	1.000000	99.000000	62.000000	0.000000	0.000000	27.300000	0.244000	24.000000	0.000000
50%	3.000000	117.000000	72.000000	23.000000	37.000000	32.200000	0.375000	29.000000	0.000000
75%	6.000000	141.000000	80.000000	32.000000	130.000000	36.625000	0.624000	40.000000	1.000000
max	17.000000	199.000000	122.000000	110.000000	846.000000	80.600000	2.420000	81.000000	1.000000

Figure A.2: The overall dataset description. Physically impossible values are in red.

It is not possible for a living person to have a 0 in any of the five highlighted columns, and these datasets do not contain information of the deceased. Therefore, it can be deduced that

¹The mean of the outcome is highlighted in blue, as the fact that it is under 0.5 indicates that there are more cases of outcome 0 (no diabetes) than 1 (diabetes). This will be further analysed in Section ??.

these values are erroneous, and should be treated as though they are missing. It is theorised by some in Kaggle discussions of these datasets that the zeroes in the Insulin column actually meant "imperceptible levels", which would have been useful data. However, a further review of literature around the datasets, especially Hayashi and Yukita (2016)'s paper, led to the discovery that these zeroes truly are missing values that were missing due to experimental invalidity at the time of their collection.

```
df[["Glucose", "Insulin", "BloodPressure", "SkinThickness", "BMI"]] = df[["Glucose", "Insulin", "BloodPressure", "SkinThickness", "BMI"]].replace(0, np.nan)
```

✓ 0.0s

Figure A.3: Converting the impossible values to NaNs which are recognised by Pandas.

Now that there are officially recognised missing values, they can be visualised using the Missingno package, which can produce a matrix of missing values by column, seen in Figure A.4.



Figure A.4: A Missingno matrix of the missing data per column.

This matrix shows that the Insulin and SkinThickness columns contain considerable amounts of missing data alongside many missing rows of BloodPressure, and some missing rows of BMI and Glucose, which will need to be fixed before any model can be trained. This is accomplished through imputation in Section 3.3.

A.2 Target univariate analysis

Binary classification models can develop bias if they do not have enough data of both classes to accurately predict what combinations of values should determine each class. Therefore, it is essential to view the balance between classes as in Figure A.6.

```
# We're only performing EDA on the training set. Y_train consists of the training set's Outcome column.
print(y_train.value_counts())
sns.countplot(X_train, x = y_train, color = "cyan")
```

Outcome	count
0	1449
1	765

Figure A.5: The code to produce Figure A.6.




Figure A.6: The class distribution of the training set (0: 1449, 1: 765).

The dataset is imbalanced, favouring an outcome of 0. The exact percentages of each class can be calculated as seen below.

$$\text{Outcome 0} = \frac{1449}{2214} = 0.655 \times 100\% = 65.5\% \quad (\text{A.1})$$

$$\text{Outcome 1} = \frac{765}{2214} = 0.345 \times 100\% = 34.5\% \quad (\text{A.2})$$

The training set is 80% of the data, hence why it is 2214 rows rather than 2768. From these calculations, it can be determined that there is an imbalance present in the training set, and we can also assume there will be a similar imbalance in the unseen testing set, as the `train_test_split` method aims to maintain the original class balances where possible. The class imbalance will be resolved in Section 3.3.

A.3 Multivariate analysis

To compare each variable to each other and the outcome, a deep copy of the training set was created which merged `X_train` and `y_train` without affecting the originals.

```
# It's important to make a deep copy, so that none of the data is tampered with.  
fullTrainSet = X_train.copy(deep = True)  
fullTrainSet["Outcome"] = y_train.values  
✓ 0.0s
```

Figure A.7: Creating a variable to hold a copy of `X_train` and `y_train`.

A.3.1 Data distributions by Outcome


It is important to identify significant outliers in the dataset so that models do not become skewed by the inflated variance, standard deviation and mean that they cause. Outliers that are very high in comparison to the primary distribution of the data will cause the standard deviation and mean to increase, whereas low outliers will make them decrease. Their identification is important not only for data analysis, but also for model development, as outliers can cause some algorithms to perform poorly or overfit, most notably distance-based algorithms such as K-Nearest Neighbours (KNN) and Support Vector Machines (SVM), which is further discussed in Section 3.1.

The simplest way to visualise outliers in the dataset is through box plots, which present the spread and skewness of numerical data in a simple visual format by showing the inter-quartile range (IQR), with rows outside of these being outliers. The boxplots of each column in the training set are shown below in Figure A.9. Each of the plots contains two boxplots, where one is for individuals without diabetes, and one is for those with diabetes.


In the figure, it can be seen that all columns contain some outliers. However, most of these outliers are still relevant statistical data that would be possible, such as the outliers in Age being elderly people. Some of these outliers are less feasible, however; most notably the extreme high outliers in SkinThickness, BMI, and Insulin. Leaving these outliers in would affect the scaling of the data, and because it is generally ill-advised to remove rows of data especially with smaller datasets, they could instead be transformed to the upper bound to give a more even distribution. This will be accomplished in Section 3.3.

```
# Iterates through each column, producing a boxplot titled "Distributions of [column name]"  
# Only iterates through X_train so that it doesn't produce one for the Outcome column itself.  
for col in X_train:  
    plt.figure(figsize = (10, 5))  
    sns.boxplot(data = fullTrainSet, y = col, x = "Outcome", hue = "Outcome")  
    plt.title(f'Distributions of {col}')  
    plt.show()  
✓ 0.7s
```


Figure A.8: The code used to produce Figure A.9.




(a) Pregnancies




(b) Glucose




(c) BloodPressure




(d) SkinThickness




(e) Insulin



(f) BMI



(g) DiabetesPedigreeFunction



(h) Age

Figure A.9: Boxplots of all features by the outcome (Blue: No diabetes, Orange: Diabetes).

Pregnancies

It was assumed in Table 2.1 that the amount of pregnancies a woman has had may bear a strong correlation on whether they develop type 2 diabetes. This box plot does support the original assumption that the amount of pregnancies can positively correlate with the diabetes outcome, as the median and upper quartiles of the distributions of those with diabetes are higher than those without, though it also confirms that pregnancies are not a decisive factor on their own, as some patients had many pregnancies without having diabetes.

Glucose

This feature clearly shows a direct and strong correlation with the outcome; individuals with diabetes have much higher glucose values, with a clear upward shift in both the median and interquartile range (IQR). The lower whisker of the boxplots begins much higher with patients with diabetes, which implies that low glucose is a strong indicator that a patient does not have diabetes.

BloodPressure

Blood pressure values are fairly similar between the two groups, though individuals with diabetes show a slightly higher median. Both groups have similar variability and range, indicating that blood pressure is not as strong a distinguishing factor. However, this slight correlation is still useful information, so this column should be kept.

SkinThickness

This column contains significant outliers that will cause issues with data scaling. Aside from these outliers, it does appear that skin thickness positively correlates with the outcome.

Insulin

This column contains many outliers, with some of these being extremely high. Aside from these, the main IQRs of the plots appear to indicate that higher insulin values are indicative of diabetes, showing a positive correlation.

BMI

Individuals with diabetes tend to have higher BMI values on average. The median BMI for the diabetic group is higher, with a slightly larger IQR, showing that BMI is an important factor in distinguishing diabetes outcomes.

DiabetesPedigreeFunction

The diabetes pedigree function has a slightly higher median for individuals with diabetes, but the difference is not substantial. Both groups share significant overlap, suggesting that this feature alone may not strongly differentiate between outcomes, which differs from the original assumption.

Age

Individuals with diabetes tend to be older on average, as indicated by a higher median age for the diabetic group, and the fact that the IQR for the diabetic group is shifted upwards. However, many outliers without diabetes exist.

A.3.2 Pair plot

To view every column in the dataset plotted against each other, a pair plot can be created using Seaborn, pictured in Figure A.11.

```
# Produces a pair plot of all columns, colouring each point by the outcome.
sns.pairplot(fullTrainSet, hue = "Outcome")
```

✓ 12.7s

Figure A.10: The code to produce Figure A.11.




Figure A.11: The pair plot of the full training set (Blue: No diabetes, Orange: Diabetes).

There are multiple observations on the relationships between features to be made from this pair plot, such as:

- Glucose, BMI and Outcome
 - Glucose and BMI appear to be the two strongest predictors, with there being more cases of diabetes as each of these features increase, shown by the higher clustering of points.
 - Glucose also appears to slightly increase as BMI increases, suggesting a slight positive correlation between the two features.
- Pregnancies and Age
 - As expected, pregnancies do typically increase with age.
- Pregnancies and Outcome
 - There is no clear separation in the outcome based on pregnancies alone, suggesting it may not be a decisive factor.
- Age
 - While a person's age appears to not be directly relevant to them having diabetes, it instead appears that older individuals instead typically have higher glucose levels and BMI, which are decisive factors.
- Insulin
 - Appears to be a good predictor, but not quite as much as glucose. Most rows where Insulin is between 400 and 600 are diabetic.
- SkinThickness and BMI
 - As expected, these two features are closely interlinked as seen by the mostly tight clustering between them in their associated plot.

Relation between Insulin and Glucose by Outcome

A particular relation of note given the subject matter is the relation between insulin and glucose dependent on whether the individual has diabetes or not. Type 2 diabetes is characterised by insulin resistance and underproduction, meaning that lower insulin values are expected as glucose rises. Figure A.13 details this relation in patients with and without diabetes.

```
# Scatter plot using Linear Regression to produce a line of best fit.  
# "scatter_kws" refers to keywords for the scatter points. "s: 5" makes the points smaller.  
sns.lmplot(x = "Glucose", y = "Insulin", data = fullTrainSet, hue = "Outcome", scatter_kws={"s": 8})  
✓ 0.2s
```

Figure A.12: The code to produce Figure A.13.




Figure A.13: A scatter plot with lines of best fit to show the trends in Insulin and Glucose.

The expectation is matched, as glucose rises more than insulin in patients with diabetes, and slower than insulin in patients without diabetes.

A.3.3 Correlation Matrix

An alternative and simpler way to visualise the correlations between features in a dataset is through a correlation matrix as pictured in Figure A.15. The matrix uses the full training set created earlier to show the correlations between the dataset's features in an annotated heatmap format, quantifying each correlation as a number. Correlation matrices only work with numerical features, though all features are numeric in this dataset which enables the matrix to show all features.

```
sns.heatmap(fullTrainSet.corr(), annot = True)
```

✓ 0.2s

Figure A.14: The code to produce Figure A.15.




Figure A.15: The correlation matrix of the full training set.

The correlation matrix reflects many of the observations noted in the pair plot and data distributions. It shows the relationships between all features, including many expected relations like those of Glucose and Outcome, Pregnancies and Age, and BMI and SkinThickness. However, the matrix also reveals insights that subvert the previous assumptions about the dataset, such as the pedigree function actually having the weakest correlation with the outcome. This can be explained through other insights in the data as well as academic research.

Mambiya et al. (2019) argue that diabetes mellitus can be caused by genetic predisposition, which is represented by the pedigree function in this dataset, though lifestyle factors such as weight gain and poor dietary variance can be a more significant factor in the cause of the disease in both those with and without genetic predispositions. Their findings are also echoed within this dataset, with high BMIs representing overweightness/obesity and high Glucose values representing high sugar intake, which are the two most significant factors in the outcome according to the correlation matrix.

Bibliography

- Adam, Sumaiya, Harold David McIntyre, Kit Ying Tsoi, Anil Kapur, Ronald C. Ma, Stephanie Dias, Pius Okong, Moshe Hod, Liona C. Poon, Graeme N. Smith, Lina Bergman, Esraa Algurjia, Patrick O'Brien, Virna P. Medina, Cynthia V. Maxwell, Lesley Regan, Mary L. Rosser, Bo Jacobsson, Mark A. Hanson, Sharleen L. O'Reilly, Fionnuala M. McAuliffe, and the FIGO Committee on the Impact of Pregnancy on Long-term Health and the FIGO Division of Maternal and Newborn Health (2023). "Pregnancy as an opportunity to prevent type 2 diabetes mellitus: FIGO Best Practice Advice". In: *International Journal of Gynecology & Obstetrics* 160 (S1), pp. 56–67. ISSN: 1879-3479. DOI: [10.1002/ijgo.14537](https://doi.org/10.1002/ijgo.14537).
- Aftab, Shabib, Saad Alanazi, Munir Ahmad, Muhammad Adnan Khan, Areej Fatima, and Nouh Sabri Elmitwally (2021). "Cloud-Based Diabetes Decision Support System Using Machine Learning Fusion". In: *Computers, Materials & Continua* 68 (1), pp. 1341–1357. ISSN: 1546-2226. DOI: [10.32604/cmc.2021.016814](https://doi.org/10.32604/cmc.2021.016814).
- Akmeşe, Ömer Faruk (Mar. 30, 2022). "Diagnosing Diabetes with Machine Learning Techniques". In: *Hittite Journal of Science and Engineering* 9 (1), pp. 9–18. ISSN: 2148-4171. DOI: [10.17350/HJSE19030000250](https://doi.org/10.17350/HJSE19030000250).
- AlZu'bi, Shadi, Mohammad Elbes, Ala Mughaid, Noor Bdair, Laith Abualigah, Agostino Forestiero, and Raed Abu Zitar (Feb. 2023). "Diabetes Monitoring System in Smart Health Cities Based on Big Data Intelligence". In: *Future Internet* 15 (2). Number: 2 Publisher: Multidisciplinary Digital Publishing Institute, p. 85. ISSN: 1999-5903. DOI: [10.3390/fi15020085](https://doi.org/10.3390/fi15020085).
- c3.ai (2024). *What is Ground Truth? / Machine Learning Glossary Definition*. C3 AI. URL: <https://c3.ai/glossary/machine-learning/ground-truth/> (visited on 12/09/2024).
- Dennison, Rebecca A., Eileen S. Chen, Madeline E. Green, Chloe Legard, Deeya Kotecha, George Farmer, Stephen J. Sharp, Rebecca J. Ward, Juliet A. Usher-Smith, and Simon J. Griffin (Jan. 2021). "The absolute and relative risk of type 2 diabetes after gestational diabetes: A systematic review and meta-analysis of 129 studies". In: *Diabetes Research and Clinical Practice* 171, p. 108625. ISSN: 01688227. DOI: [10.1016/j.diabres.2020.108625](https://doi.org/10.1016/j.diabres.2020.108625).
- Dhanapalaratnam, Roshan, Tushar Issar, Leiao Leon Wang, Darren Tran, Ann M. Poynten, Kerry-Lee Milner, Natalie C.G. Kwai, and Arun V. Krishnan (Aug. 21, 2024). "Effect of Metformin on Peripheral Nerve Morphology in Type 2 Diabetes: A Cross-Sectional Observational Study". In: *Diabetes* 73 (11), pp. 1875–1882. ISSN: 0012-1797. DOI: [10.2337/db24-0365](https://doi.org/10.2337/db24-0365).
- Diabetes UK (2024a). *How many people in the UK have diabetes?* Diabetes UK. URL: <https://www.diabetes.org.uk/about-us/about-the-charity/our-strategy/statistics> (visited on 11/27/2024).
- Diabetes UK (2024b). *What causes type 2 diabetes?* Diabetes UK. URL: <https://www.diabetes.org.uk/about-diabetes/type-2-diabetes/causes> (visited on 12/14/2024).
- Donnelly, Louise A., Rory J. McCrimmon, and Ewan R. Pearson (2024). "Trajectories of BMI before and after diagnosis of type 2 diabetes in a real-world population". In: *Diabetologia* 67 (10), pp. 2236–2245. ISSN: 0012-186X. DOI: [10.1007/s00125-024-06217-1](https://doi.org/10.1007/s00125-024-06217-1).
- Hayashi, Yoichi and Shonosuke Yukita (Jan. 1, 2016). "Rule extraction using Recursive-Rule extraction algorithm with J48graft combined with sampling selection techniques for the diagnosis of type 2 diabetes mellitus in the Pima Indian dataset". In: *Informatics in Medicine Unlocked* 2, pp. 92–104. ISSN: 2352-9148. DOI: [10.1016/j.imu.2016.02.001](https://doi.org/10.1016/j.imu.2016.02.001).

- John DaSilva (2024). *Frankfurt Diabetes Dataset*. diabetes. URL: <https://www.kaggle.com/datasets/johndasilva/diabetes> (visited on 11/25/2024).
- Joshi, Ram D. and Chandra K. Dhakal (July 9, 2021). “Predicting Type 2 Diabetes Using Logistic Regression and Machine Learning Approaches”. In: *International Journal of Environmental Research and Public Health* 18 (14), p. 7346. ISSN: 1661-7827. DOI: [10.3390/ijerph18147346](https://doi.org/10.3390/ijerph18147346).
- Khalili, Davood, Marjan Khayamzadeh, Karim Kohansal, Noushin Sadat Ahanchi, Mitra Hasheminia, Farzad Hadaegh, Maryam Tohidi, Fereidoun Azizi, and Ali Siamak Habibi-Moeini (Feb. 14, 2023). “Are HOMA-IR and HOMA-B good predictors for diabetes and pre-diabetes subtypes?” In: *BMC Endocrine Disorders* 23, p. 39. ISSN: 1472-6823. DOI: [10.1186/s12902-023-01291-9](https://doi.org/10.1186/s12902-023-01291-9).
- Khan, Moien Abdul Basith, Muhammad Jawad Hashim, Jeffrey Kwan King, Romona Devi Govender, Halla Mustafa, and Juma Al Kaabi (Mar. 2020). “Epidemiology of Type 2 Diabetes – Global Burden of Disease and Forecasted Trends”. In: *Journal of Epidemiology and Global Health* 10 (1), pp. 107–111. ISSN: 2210-6006. DOI: [10.2991/jegh.k.191028.001](https://doi.org/10.2991/jegh.k.191028.001).
- Mambiya, Michael, Mengke Shang, Yue Wang, Qian Li, Shan Liu, Luping Yang, Qian Zhang, Kaili Zhang, Mengwei Liu, Fangfang Nie, Fanxin Zeng, and Wanyang Liu (Nov. 19, 2019). “The Play of Genes and Non-genetic Factors on Type 2 Diabetes”. In: *Frontiers in Public Health* 7. Publisher: Frontiers. ISSN: 2296-2565. DOI: [10.3389/fpubh.2019.00349](https://doi.org/10.3389/fpubh.2019.00349).
- Nelaj, Ergita, Margarita Gjata, Irida Kecaj, Ilir Gjermani, and Mihal Tase (June 2023). “HIGH BLOOD PRESSURE IN THE NEWLY DIAGNOSED TYPE 2 DIABETES PATIENTS”. In: *Journal of Hypertension* 41 (Suppl 3), e172. ISSN: 0263-6352. DOI: [10.1097/01.hjh.0000940640.80128.7a](https://doi.org/10.1097/01.hjh.0000940640.80128.7a).
- NHS (Oct. 16, 2022). *Peripheral neuropathy - Causes*. nhs.uk. Section: conditions. URL: <https://www.nhs.uk/conditions/peripheral-neuropathy/causes/> (visited on 12/04/2024).
- Ruiz-Alejos, Andrea, Rodrigo M Carrillo-Larco, J Jaime Miranda, Robert H Gilman, Liam Smeeth, and Antonio Bernabé-Ortiz (Jan. 2020). “Skinfold thickness and the incidence of type 2 diabetes mellitus and hypertension: an analysis of the PERU MIGRANT study”. In: *Public Health Nutrition* 23 (1), pp. 63–71. ISSN: 1368-9800. DOI: [10.1017/S1368980019001307](https://doi.org/10.1017/S1368980019001307).
- Sivakumar, Muthuramalingam, Sudhaman Parthasarathy, and Thiyagarajan Padmapriya (Sept. 6, 2024). “Trade-off between training and testing ratio in machine learning for medical image processing”. In: *PeerJ Computer Science* 10, e2245. ISSN: 2376-5992. DOI: [10.7717/peerj-cs.2245](https://doi.org/10.7717/peerj-cs.2245).
- Suastika, Ketut, Pande Dwipayana, Made Siswadi, and R.A. Tuty (Dec. 12, 2012). “Age is an Important Risk Factor for Type 2 Diabetes Mellitus and Cardiovascular Diseases”. In: *Glucose Tolerance*. Ed. by Sureka Chackrewarthy. InTech. ISBN: 978-953-51-0891-7. DOI: [10.5772/52397](https://doi.org/10.5772/52397).
- Tahapary, Dicky Levenus, Livy Bonita Pratisthita, Nissha Audina Fitri, Cicilia Marcella, Syahidatul Wafa, Farid Kurniawan, Aulia Rizka, Tri Juli Edi Tarigan, Dante Saksono Harbuwono, Dyah Purnamasari, and Pradana Soewondo (Aug. 1, 2022). “Challenges in the diagnosis of insulin resistance: Focusing on the role of HOMA-IR and Tryglyc-

- eride/glucose index”. In: *Diabetes & Metabolic Syndrome: Clinical Research & Reviews* 16 (8), p. 102581. ISSN: 1871-4021. DOI: [10.1016/j.dsx.2022.102581](https://doi.org/10.1016/j.dsx.2022.102581).
- UCI Machine Learning (2024). *Pima Indians Diabetes Database*. Pima Indians Diabetes Database. URL: <https://www.kaggle.com/datasets/uciml/pima-indians-diabetes-database> (visited on 11/25/2024).
- Zou, Qiong, Yang Zhang, and Chang Sheng Chen (Feb. 13, 2024). “Construction and Application of a Machine Learning Prediction Model Based on Unbalanced Diabetes Data Fusion”. In: *Proceedings of the 2023 International Joint Conference on Robotics and Artificial Intelligence*. JCRAI '23. New York, NY, USA: Association for Computing Machinery, pp. 114–123. ISBN: 979-8-4007-0770-4. DOI: [10.1145/3632971.3633348](https://doi.org/10.1145/3632971.3633348).