



**BIRMINGHAM CITY
University**

CMP5352 Report - TITLE NEEDED

DRAFT VERSION

Lewis Higgins - Student ID 22133848

Word count: XXXX

Abstract

text

text

text

Contents

Introduction	1
Motivation and objectives	3
Experimental results	5
Summary and conclusion	13

Introduction

Text text text

Text text text

aaa

Motivation and objectives

```
library(ggplot2)
ggplot(diamonds, aes(x = carat, fill = color)) +
  geom_histogram(bins = 30)
```




Figure 1: Plot 1

Figure 1 shows that...

```
ggplot(diamonds, aes(x = carat, y = price)) +  
  geom_point(aes(color = cut)) +  
  geom_smooth()
```




Figure 2: Plot 1

Figure 2 instead shows that...

Experimental results

```
library(ggplot2)

# Side-note that if you run this as a file and not in the IDE the plots will
# actually be put into a PDF for you in the active working directory (here).

# We can use a randomly selected sample of the dataset for the graph.
# However, because the results should be reproducible, we should set an RNG seed.
set.seed(1000)

# Select the numbered rows of the numbers produced by sample.
# Sample picks 100 random numbers.
dsmall <- diamonds[sample(nrow(diamonds), 100),]
# The random comma at the end tells R that you're selecting ROWS, not columns.
# If you don't put this comma it assumes you're looking to select the columns.

qplot(log(carat), log(price), data = dsmall, geom = "smooth")
```




Figure 3: Figure AAA

```
# Can supply multiple geoms in a vector
qplot(log(carat), log(price), data = dsmall, geom = c("point", "smooth"))
```





Figure 4: Figure AAA

Different smooth line?

*# Span varies the smoothness of geom_smooth from 0 to 1 where 1 is the smoothest.
 # It states that span is an unknown parameter, yet this does actually
 # modify the produced graph. 0.2 is the minimum before R throws warnings.
 # 0.1 works with warnings, but anything lower produces no smooth line.
 # Though, using 0.1 means you might as well not even put a smooth line.*

```
qplot(log(carat), log(price), data = dsmall, geom = c("point", "smooth"), span = 0.2)
```




Figure 5: Figure AAA

You can also fit a linear model to the graph via lm.

```
qplot(log(carat), log(price), data = dsmall, geom = c("point", "smooth"), method = "lm")
```




Figure 6: Figure AAA

Scatterplotting a different dataset, ggplot's builtin mpg (car fuel economy data)

```
qplot(displ, hwy, data = mpg, color = drv)
```




Figure 7: Figure AAA

If you provided a color argument to this, it would draw one smooth for every color.

```
qplot(displ, hwy, data = mpg, geom = c("point", "smooth"))
```




Figure 8: Figure AAA

```
# Answers the question "How are engine size and fuel economy related?"
# Turning cylinder into a factor (categorical data).
# Basically counts the appearances of each value.
qplot(displ, hwy, data = mpg, color = factor(cyl))
```




Figure 9: Figure AAA

```
# We can use all arguments previously shown at once.
# Note that there aren't enough 5 cylinders to fit a line, so there isn't one.
qplot(displ, hwy, data = mpg, color = factor(cyl),
      geom = c("point", "smooth"), method = "lm")
```




Figure 10: Figure AAA

```
### --- Faceting --- ###
```

```
# . acts as a placeholder, indicating that there's no variable.
# Results in three separate histograms, one of each drive class.
qplot(hwy, data = mpg, facets = drv ~ ., binwidth = 2)
```




Figure 11: Figure AAA

```
# Could add colors. Doesn't help much though.
```

Flips sideways. displ is displacement. Air movement per engine rev possibly
`qplot(displ, hwy, data = mpg, facets = . ~ drv, geom = c("point", "smooth"))`




Figure 12: Figure AAA

Reusing the diamond set.
`qplot(carat, data = diamonds, facets = color ~ ., geom = "histogram")`




Figure 13: Figure AAA

..density.. tells ggplot to map the density as the Y-axis, instead of just counting
`qplot(carat, ..density.., data = diamonds, facets = color ~ ., geom = "histogram")`




Figure 14: Figure AAA

Plots thirty five histograms by also grouping by cut.

```
qplot(carat, data = diamonds, facets = color ~ cut, geom = "histogram")
```




Figure 15: Figure AAA



Figure 16: A nice image.

Summary & conclusion

text text text
text text text