StatM • Research tables

Dataset: Iris.csv | Version: 269359a5-19fe-465c-984f-c36e29873013 | Run: 2026-10-14T08:15:12.314943+00:00

Eigenvalues and variance explained

Component	Eigenvalue	Variance explained (%)	Cumulative variance (%)	Retained
PC1	2.918	72.962	72.962	Yes
PC2	0.914	22.851	95.813	Yes
PC3	0.147	3.669	99.482	Yes
PC4	0.021	0.518	100.000	Yes

Loading matrix

Variable	PC1	PC2	PC3	PC4
sepal_length	0.890	0.361	0.276	-0.038
sepal_width	-0.460	0.883	-0.094	0.018
petal_length	0.992	0.023	-0.054	0.115
petal_width	0.965	0.064	-0.243	-0.075

Correlation matrix

Variable	sepal_length	sepal_width	petal_length	petal_width
sepal_length	1.000	-0.118	0.872	0.818
sepal_width	-0.118	1.000	-0.428	-0.366
petal_length	0.872	-0.428	1.000	0.963
petal_width	0.818	-0.366	0.963	1.000

Preprocessing: sample-standardized variables; eigenvalues correspond to the sample correlation matrix.

Variance explained and cumulative variance are reported as percentages. Loadings = eigenvectors × sqrt(eigenvalues); signs may reverse without changing the PCA solution.

Complete-case analysis: 0 rows excluded.

Displayed values are rounded; raw results retain full precision. — means unavailable. No significance stars are added.