

FUNDAMENTALS

Tour of Heroes App

Introduction

The Application Shell

1. The Hero Editor

2. Displaying a List

3. Master/Detail Components

4. Services

5. Routing

6. HTTP

Architecture

Components & Templates

Forms

Observables & RxJS

The Hero Editor

Create the heroes component

Add a hero property

Show the hero

Show the HeroesComponent view

Create a Hero class

Format with the *UppercasePipe*

Edit the hero

Two-way binding

The missing *FormsModule*

AppModule

Import *FormsModule*

Declare HeroesComponent

Final code review

Summary

The Hero Editor

The application now has a basic title. Next you will create a new component to display hero information and place that component in the application shell.

Create the heroes component

Using the Angular CLI, generate a new component named `heroes`.

```
ng generate component heroes
```

The CLI creates a new folder, `src/app/heroes/`, and generates the three files of the `HeroesComponent` along with a test file.

The `HeroesComponent` class file is as follows:

```
app/heroes/heroes.component.ts (initial version)

import { Component, OnInit } from '@angular/core';

@Component({
  selector: 'app-heroes',
  templateUrl: './heroes.component.html',
  styleUrls: ['./heroes.component.css']
})
export class HeroesComponent implements OnInit {

  constructor() { }

  ngOnInit() {
  }

}
```

You always import the `Component` symbol from the Angular core library and annotate the component class with `@Component`.

`@Component` is a decorator function that specifies the Angular metadata for the component.

The CLI generated three metadata properties:

1. `selector`—the component's CSS element selector
2. `templateUrl`—the location of the component's template file.
3. `styleUrls`—the location of the component's private CSS styles.

The `CSS element selector`, `'app-heroes'`, matches the name of the HTML element that identifies this component within a parent component's template.

The `ngOnInit()` is a [lifecycle hook](#). Angular calls `ngOnInit()` shortly after creating a component. It's a good place to put initialization logic.

Always export the component class so you can import it elsewhere ... like in the `AppModule`.

Add a hero property

Add a hero property to the `HeroesComponent` for a hero named "Windstorm."

```
heroes.component.ts (hero property)

hero = 'Windstorm';
```

Show the hero

Open the `heroes.component.html` template file. Delete the default text generated by the Angular CLI and replace it with a data binding to the new hero property.

```
heroes.component.html

{{hero}}
```

Show the HeroesComponent view

To display the `HeroesComponent`, you must add it to the template of the shell `AppComponent`.

Remember that `app-heroes` is the [element selector](#) for the `HeroesComponent`. So add an `<app-heroes>` element to the `AppComponent` template file, just below the title.

```
src/app/app.component.html

<h1>{{title}}</h1>
<app-heroes></app-heroes>
```

Assuming that the CLI `ng serve` command is still running, the browser should refresh and display both the application title and the hero name.

Create a Hero class

A real hero is more than a name.

Create a `Hero` class in its own file in the `src/app` folder. Give it `id` and `name` properties.

```
src/app/hero.ts

export class Hero {
  id: number;
  name: string;
}
```

Return to the `HeroesComponent` class and import the `Hero` class.

Refactor the component's hero property to be of type `Hero`. Initialize it with an `id` of 1 and the name `Windstorm`.

The revised `HeroesComponent` class file should look like this:

```
src/app/heroes/heroes.component.ts

import { Component, OnInit } from '@angular/core';
import { Hero } from '../hero';

@Component({
  selector: 'app-heroes',
  templateUrl: './heroes.component.html',
  styleUrls: ['./heroes.component.css']
})
export class HeroesComponent implements OnInit {
  hero: Hero = {
    id: 1,
    name: 'Windstorm'
  };

  constructor() { }

  ngOnInit() {
  }

}
```

The page no longer displays properly because you changed the hero from a string to an object.

Show the hero object

Update the binding in the template to announce the hero's name and show both `id` and `name` in a details layout like this:

```
heroes.component.html (HeroesComponent's template)

<h2>{{hero.name}} Details</h2>
<div><span>id: </span>{{hero.id}}</div>
<div><span>name: </span>{{hero.name}}</div>
```

The browser refreshes and displays the hero's information.

Format with the *UppercasePipe*

Modify the `hero.name` binding like this.

```
src/app/heroes/heroes.component.html

<h2>{{hero.name | uppercase}} Details</h2>
```

The browser refreshes and now the hero's name is displayed in capital letters.

The word `uppercase` in the interpolation binding, right after the pipe operator (`|`), activates the built-in `UppercasePipe`.

[Pipes](#) are a good way to format strings, currency amounts, dates and other display data. Angular ships with several built-in pipes and you can create your own.

Edit the hero

Users should be able to edit the hero name in an `<input>` textbox.

The textbox should both *display* the hero's name property and *update* that property as the user types. That means data flows from the component class *out to the screen* and from the screen *back to the class*.

To automate that data flow, setup a two-way data binding between the `<input>` form element and the `hero.name` property.

Two-way binding

Refactor the details area in the `HeroesComponent` template so it looks like this:

```
src/app/heroes/heroes.component.html (HeroesComponent's template)

<div>
  <label>name:
  <input [(ngModel)]="hero.name" placeholder="name"/>
</label>
</div>
```

`[(ngModel)]` is Angular's two-way data binding syntax.

Here it binds the `hero.name` property to the HTML textbox so that data can flow *in both directions*: from the `hero.name` property to the textbox, and from the textbox back to the `hero.name`.

The missing *FormsModule*

Notice that the app stopped working when you added `[(ngModel)]`.

To see the error, open the browser development tools and look in the console for a message like

```
Template parse errors:
Can't bind to 'ngModel' since it isn't a known property of 'input'.
```

Although `ngModel` is a valid Angular directive, it isn't available by default.

It belongs to the optional `FormsModule` and you must *opt-in* to using it.

AppModule

Angular needs to know how the pieces of your application fit together and what other files and libraries the app requires. This information is called *metadata*.

Some of the metadata is in the `@Component` decorators that you added to your component classes. Other critical metadata is in `@NgModule` decorators.

The most important `@NgModule` decorator annotates the top-level `AppModule` class.

The Angular CLI generated an `AppModule` class in `src/app/app.module.ts` when it created the project. This is where you *opt-in* to the `FormsModule`.

Import *FormsModule*

Open `AppModule` (`app.module.ts`) and import the `FormsModule` symbol from the `@angular/forms` library.

```
app.module.ts (FormsModule symbol import)

import { FormsModule } from '@angular/forms'; // <-- NgModel lives here
```

Then add `FormsModule` to the `@NgModule` metadata's `imports` array, which contains a list of external modules that the app needs.

```
app.module.ts (@NgModule imports)

imports: [
  BrowserModule,
  FormsModule
],
```

When the browser refreshes, the app should work again. You can edit the hero's name and see the changes reflected immediately in the `<h2>` above the textbox.

Declare HeroesComponent

Every component must be declared in *exactly one* `NgModule`.

You didn't declare the `HeroesComponent`. So why did the application work?

It worked because the Angular CLI declared `HeroesComponent` in the `AppModule` when it generated that component.

Open `src/app/app.module.ts` and find `HeroesComponent` imported near the top.

```
src/app/app.module.ts

import { HeroesComponent } from '../heroes/heroes.component';
```

The `HeroesComponent` is declared in the `@NgModule.declarations` array.

```
src/app/app.module.ts

declarations: [
  AppComponent,
  HeroesComponent
],
```

Note that `AppModule` declares both application components, `AppComponent` and `HeroesComponent`.

Final code review

Your app should look like this [live example](#) / [download example](#). Here are the code files discussed on this page.

```
< src/app/heroes/heroes.component.ts src/app/heroes/heroes.component.html src/app/app.module.ts >

import { Component, OnInit } from '@angular/core';
import { Hero } from '../hero';

@Component({
  selector: 'app-heroes',
  templateUrl: './heroes.component.html',
  styleUrls: ['./heroes.component.css']
})
export class HeroesComponent implements OnInit {
  hero: Hero = {
    id: 1,
    name: 'Windstorm'
  };

  constructor() { }

  ngOnInit() {
  }

}
```

Summary

- You used the CLI to create a second `HeroesComponent`.
- You displayed the `HeroesComponent` by adding it to the `AppComponent` shell.
- You applied the `UppercasePipe` to format the name.
- You used two-way data binding with the `ngModel` directive.
- You learned about the `AppModule`.
- You imported the `FormsModule` in the `AppModule` so that Angular would recognize and apply the `ngModel` directive.
- You learned the importance of declaring components in the `AppModule` and appreciated that the CLI declared it for you.

The Hero Editor

Create the heroes component

Add a hero property

Show the hero

Show the HeroesComponent view

Create a Hero class

Show the hero object

Format with the *UppercasePipe*

Edit the hero

Two-way binding

The missing *FormsModule*

AppModule

Import *FormsModule*

Declare HeroesComponent

Final code review

Summary