

# Week Twelve PHY-480

Lewis

November 2025

## 1 Class 22

### Q22.1

Show that the matrix operation  $H0$  gives the uniform superposition state of a qubit, where  $H$  is the Hadamard matrix.

The Hadamard matrix for a single qubit is

$$H = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}$$

Applying  $H$  to the ground state  $0 = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$  gives

$$H0 = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 \\ 1 \end{pmatrix} = \frac{1}{\sqrt{2}}(0 + 1).$$

Hence,  $H0$  produces the **uniform superposition state**, where the qubit has equal probability of being in 0 or 1.

### Q22.2

Give a concise statement of the amplitude amplification strategy used in designing quantum algorithms.

Amplitude amplification is a general quantum strategy for **increasing the probability amplitude** of target states within a quantum superposition while **suppressing all others**. It repeatedly applies a combination of:

- a **phase inversion** about the target state, and
- a **reflection** about the average amplitude,

thereby rotating the state vector toward the target in Hilbert space. Grover's algorithm is the canonical example, achieving a quadratic speedup over classical unstructured search.

### Q22.3

Outline a Python algorithm for a simulation of the Grover algorithm on a classical computer using matrices of dimension  $2^n$ , where  $n$  is the number of qubits.

1. Set the number of qubits  $n$  and compute  $N = 2^n$ .
2. Define the Hadamard matrix:

$$H = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix}, \quad H^{\otimes n} = \text{Kronecker product of } n \text{ copies of } H.$$

2. Define the initial state  $0^{\otimes n}$  and compute the uniform superposition:

$$\psi_0 = H^{\otimes n} 0^{\otimes n}.$$

3. Construct the target oracle:

$$U_{tar} = -I_N + 2E_{tar,tar},$$

where  $E_{tar,tar}$  is a matrix with a single 1 at the target index.

4. Construct the diffusion operator:

$$D = H^{\otimes n} (2I_N - I_N) H^{\otimes n}.$$

5. Define the Grover operator:

$$G = D U_{tar}.$$

6. Apply  $G$  repeatedly:

$$\psi_t = G^t \psi_0.$$

7. After each iteration, record the probability of the target state:

$$P_{tar}(t) = |\langle tar | \psi_t \rangle|^2.$$

8. Plot  $P_{tar}(t)$  versus  $t$  to observe amplitude amplification.

#### Q22.4

**Explain the expected behavior of the output-state probability of the target state as a function of  $t$ , the number of times the Grover operator is applied.**

Each application of the Grover operator  $G$  performs a **rotation in a two dimensional subspace** spanned by the target state  $tar$  and the average of all non-target states. The probability of measuring the target state increases sinusoidally with the number of iterations  $t$ :

$$P_{tar}(t) = \sin^2((2t+1)\theta),$$

where  $\sin^2(\theta) = 1/N$  and  $N = 2^n$  is the total number of states. The probability reaches its maximum near

$$t_{opt} = \left\lfloor \frac{\pi}{4} \sqrt{N} \right\rfloor,$$

after which additional iterations will begin to decrease the success probability again (overshooting the target).

**Summary:** The amplitude amplification process boosts the likelihood of finding the target state up to near certainty after  $\sim \frac{\pi}{4} \sqrt{N}$  iterations.