EE341 Fall 2019 HW 1

Lewis Collum

Updated: October 31, 2019

import api.homework_1 as api

3.1

```
Solution:
```

```
unit = api.unit
t = {
    "-55C": unit.Quantity(-55, unit.celsius).to('kelvin'),
    "OC": unit.Quantity(0, unit.celsius).to('kelvin'),
    "20C": unit.Quantity(20, unit.celsius).to('kelvin'),
    "75C": unit.Quantity(75, unit.celsius).to('kelvin'),
    "125C": unit.Quantity(125, unit.celsius).to('kelvin')
}
for key, kelvin in t.items():
    intrinsicConcentration = api.Silicon.intrinsicConcentrationFromKelvin(kelvin)
    ionizationRatio = intrinsicConcentration / api.Silicon.densityOfAtoms
   print(f"Case {key} ({kelvin:.5}): {intrinsicConcentration:.2E}")
    print(f"Fraction of atoms ionized: ni/N = \{ionizationRatio:.2E\}\n")
Answer:
Case -55C (218.15 kelvin): 2.72E+06 / centimeter ** 3
Fraction of atoms ionized: ni/N = 5.43E-17 / centimeter ** 3
Case OC (273.15 kelvin): 1.53E+09 / centimeter ** 3
Fraction of atoms ionized: ni/N = 3.07E-14 / centimeter ** 3
Case 20C (293.15 kelvin): 8.64E+09 / centimeter ** 3
Fraction of atoms ionized: ni/N = 1.73E-13 / centimeter ** 3
Case 75C (348.15 kelvin): 3.71E+11 / centimeter ** 3
Fraction of atoms ionized: ni/N = 7.42E-12 / centimeter ** 3
Case 125C (398.15 kelvin): 4.73E+12 / centimeter ** 3
Fraction of atoms ionized: ni/N = 9.46E-11 / centimeter ** 3
```

Thermal excitation of electrons in the valence band is a consequence of raising the temperature. As such, the number of possible conducting states increase, as does the probability that those states are occupied by electrons; this implies a greater intrinsic density.

3.3

Solution:

```
import api.homework_1 as api
unit = api.unit

acceptorDopantConcentration = 5e18 / unit.centimeters**3
systemKelvin = 300 * unit.kelvin
intrinsicConcentration = api.Silicon.intrinsicConcentrationFromKelvin(300*unit.kelvin)
electronConcentration = intrinsicConcentration**2/acceptorDopantConcentration

print(f"P-type Electron Concentration: {electronConcentration:.4}")
print(f"P-type Hole Concentration: {acceptorDopantConcentration:.4}")

Answer:
P-type Electron Concentration: 44.04 / centimeter ** 3
P-type Hole Concentration: 5e+18 / centimeter ** 3
```

3.5

Solution:

```
import api.homework_1 as api
from api import unit

donorDopantConcentration = 10e17 / unit.centimeters**3
print(f"N-type Electron Concentration: {donorDopantConcentration:.4} @ 27C and 125C")

t = {
    '27C': unit.Quantity(27, unit.celsius).to('kelvin'),
    '125C': unit.Quantity(125, unit.celsius).to('kelvin')
}

for label, kelvin in t.items():
    intrinsicConcentration = api.Silicon.intrinsicConcentrationFromKelvin(kelvin)
    holeConcentration = intrinsicConcentration**2/donorDopantConcentration
    print(f"N-type Hole Concentration: {holeConcentration:.4} @ {label}")
```

Answer:

```
N-type Electron Concentration: 1e+18 / centimeter ** 3 @ 27C and 125C N-type Hole Concentration: 225.4 / centimeter ** 3 @ 27C N-type Hole Concentration: 2.238e+07 / centimeter ** 3 @ 125C
```

3.21

Solution:

```
import api.homework_1 as api
unit = api.unit

carrierConcentration = {
    '300K': api.Silicon.intrinsicConcentrationFromKelvin(300 * unit.kelvin),
```

```
'305K': api.Silicon.intrinsicConcentrationFromKelvin(305 * unit.kelvin)
}
factor = carrierConcentration['305K']**2 / carrierConcentration['300K']**2
print(f"Factor: {factor.magnitude:.3}")
```

Answer:

Factor: 2.14

4.18

$$\begin{split} v &= V_T \ln \frac{i}{I_S} \\ v &= V_T \ln \frac{10000 I_S}{I_S} \\ v &= V_T \ln 10000 \text{ assume } V_T = 25 \text{mV} \\ \hline v &= 0.025 \cdot \ln 10000 = 0.23 \text{V} \\ \hline i &= I_S \cdot e^{v/V_T} \\ i &= I_S \cdot e^{0.7/0.025} \\ \hline i &= 1.45 \times 10^{12} I_S \end{split}$$

4.19

$$\begin{split} \frac{I_2}{I_1} &= e^{(V_2 - V_1)/V_T} \\ I_2 &= e^{(0.5 - 0.7)/0.025)} \cdot 1 \text{mA} \\ \hline I_2 &= 335 \mu \text{A} \end{split}$$

4.23

The voltage across each diode, V_d , is $V_o/3 = 0.67$.

$$\begin{split} I &= I_S \cdot e^{V_d/V_T} \\ I &= 10^{-14} \mathrm{A} \cdot e^{0.67/0.025} \\ \hline I &= 4.4 \mathrm{mA} \end{split}$$

If 1mA is drawn, I=4.4mA -1mA =3.4mA

$$V_o = V_T \cdot \ln \frac{I}{I_S} \cdot 3$$

$$V_o = 0.025 \cdot \ln \frac{0.0034}{10^{-14}} \cdot 3$$

$$V_o = 1.991 \text{V}$$

Output voltage changed by $2-1.991 = \boxed{9.0 \text{mV}}$

4.25

$$I_{D1} = I_{S1} \cdot e^{V_D/V_T}$$

$$I_{D2} = I_{S2} \cdot e^{V_D/V_T}$$

$$V_D = V_T \ln \frac{I_{D1}}{I_{S1}}$$

4.28

$$\begin{split} I &= I_1 + I_2 \text{ by KCL} \\ I_1 &= V/R \text{ by Ohm's law} \\ V &= V_2 - V_1 \text{ by KVL} \\ e^{(V_2 - V_1)/V_T} &= e^{V/V_T} = \frac{I_2}{I_1} = \frac{I - I_1}{I_1} = \frac{I}{I_1} - 1 \\ \frac{I \cdot R}{V} - 1 &= e^{V/V_T} \to R = \frac{V}{I} \cdot (e^{V/V_T} + 1) \\ \hline R &= \frac{0.05 \text{V}}{0.01 \text{A}} (e^{0.05 \text{V}/0.025 \text{V}} + 1) = 42 \Omega \end{split}$$

4.29

According to the text book:

At a given constant diode current, the voltage drop across the diode decreases by approximately 2 mV for every 1°C increase in temperature.

Case $T = -20^{\circ}C$:

$$\Delta T = -40^{\circ} \mathrm{C}$$

$$V = 690 \mathrm{mV} + 2 \mathrm{mV} \cdot 40^{\circ} \mathrm{C}$$

$$\boxed{=770 \mathrm{mV}}$$

Case $T = +85^{\circ}C$:

$$\begin{split} \Delta T &= +65^{\circ} \mathrm{C} \\ V &= 690 \mathrm{mV} - 2 \mathrm{mV} \cdot 65^{\circ} \mathrm{C} \\ \hline &= 560 \mathrm{mV} \end{split}$$

```
APPENDIX: CODE
from __future__ import annotations
import math
import pint
unit = pint.UnitRegistry()
def densityOfStates(materialConstant: float, kelvinOfSystem: float) -> float:
    return materialConstant/unit.kelvin**(3/2)/unit.centimeters**3 * kelvinOfSystem**(3/2)
class Boltzmann:
    @classmethod
    def probability(cls, stateEnergy: float, kelvinOfSystem: float) -> float:
        return math.exp(-stateEnergy*unit.eV/(kelvinOfSystem * unit.boltzmann_constant))
class Silicon:
    densityOfStatesMaterialConstant = 7.3e15
    densityOfAtoms = 5e22
    holeMobility = 480 * unit.centimeters**2 / (unit.volts*unit.seconds)
    electronMobility = 1350 * unit.centimeters**2 / (unit.volts*unit.seconds)
    @classmethod
    def intrinsicConcentrationFromKelvin(cls, kelvin: float) -> float:
        siliconDensityOfStates = densityOfStates(
            materialConstant=Silicon.densityOfStatesMaterialConstant,
            kelvinOfSystem=kelvin)
        distribution = Boltzmann.probability(
            stateEnergy=1.12,
            kelvinOfSystem=kelvin) ** (1/2)
        return siliconDensityOfStates * distribution
```