

MULTIHULL



NIGEL IRENS 82

Allegra - SUI 888

Salesman Quinny Houry

HELIX J-Zero 3Di RAW 760 \ 29,400 Dpi

Fastcat Ltd (GRIMM, ROB)

Designer Sørensen, Heine (North Sails A/S)

OE #: OSP7068-002

Wkt Created 03/02/2026

RIG DATA

Isp: 31.003 **Spl:** 11.736 **P:** 31.4 **E:** 10.9 **LOA:** 24

3DI

Tape RAW Black

Location	Wad
Head	-
Tack	-
Clew	-

MISCELLANEOUS ITEMS

3Di : HEAD WADS*	Black 150D TF 800mm radius INTERNAL
3Di : TACK WADS*	Black 150D TF 700mm radius INTERNAL
3Di : CLEW WADS*	Black 150D TF 800mm radius INTERNAL
3Di : LUFF STRAINERS*	Black 150D TF, 300mm wide on PORT, 350mm wide on STBD. INTERNAL
3Di : LEECH STRAINERS*	Black 150D TF, 600 mm wide on PORT, 700 mm wide on STBD. INTERNAL
3Di : FOOT STRAINERS*	Black 150D TF, 200mm wide on PORT, 250mm wide on STBD. INTERNAL
3Di : Spreader patch*	Add internal spreader impact patch and 150d TF external spreader chafe protection. Spreader position is marked in mould

FURLING

NESTING

HEADSAIL SIZING

Completed By _____ Date _____

	FINISHED	REDUCTIONS	MOLDED		Head Back	0 mm
Head	0.100	0.000	0.100		Head Down	0 mm
Luff	29.950	0.040	29.910		Tack Cut Back (From Front of Luff Tape)	60 mm
Leech	24.550	0.040	24.510		Tack Cut Up	0 mm
Foot	15.050	0.000	15.050			
LP	12.520	0.000	12.520			

Girth Type	Max Length	Measured	Luff Position	Leech Position	Notes
7/8 Girth	1.570 m	Measured AS LP	-	-	
3/4 Girth	3.080 m	Measured AS LP	-	-	
1/2 Girth	6.100 m	Measured AS LP	-	-	
1/4 Girth	9.150 m	Measured AS LP	-	-	

NOTES

50mm luff tape offset.

BATTENS & POCKETS

DOWNWIND GRAPHICS

Completed By _____ Date _____

North Sails Tack Logo

2 x 09

Trim Stripes				Windows					
#	Primary Stripe	Width	Secondary Stripe	#	Type	Item	Location	Vertical Distance	Distance Back
1	White (Vinyl)	150 mm	Glow Fast	1	TellTale	TTW3DL-BK	Below 1/4 Stripe/Position	600 mm	600 mm
2	White (Vinyl)	125 mm	Glow Fast	2	TellTale	TTW3DL-BK	Below 1/2 Stripe/Position	600 mm	600 mm
3	White (Vinyl)	100 mm	Glow Fast						

REINFORCEMENTS

Completed By _____ Date _____

GENOA EDGES

Completed By _____ Date _____

Location	Primary Tape	Start Point	Secondary Tape	Cord	Adjuster	Cord Purchase	Place At	Overhead Tape	Overhead Line
Luff	P810BK ■	-	P42BK ■	LPSP004	-	-	-	P43BK ■	OH line : LD75C004*
Leech	P63BKF ■	-	-	SY Leech Sling*	TOWL25SBK	SYPUOH41-FR x 1000 mm*	TackLuff	-	-
Foot	P63BKF ■	-	-	LV004	TOWL25SBK	SYPU41-FR x 750 mm*	TackFoot	-	-

BLUE BOOK REFERENCES

19.15 Bottom Up Furling - Long Cable

1/3-2/3 fold, big half on Starboard

NOTES

LUFF: P42BK secondary tape is the luff capping tape. Finish site to supply LPSP004 mouse line only. Luff tape is offset-folded has to be 1/3 - 2/3 folded. Big half on STBD. Front of luff tape sits 50mm forward of cut luff. LTE at head & tack = 200mm. OH tunnel on STBD

LEECH: Leech sling on STBD. 15cm lashing at clew TOWL w/velcro cover

FOOT: Foot line on STBD.

ATTACHMENTS/HARDWARE				Completed By _____ Date _____	
Location	Style	Attachment	Strapping	Hardware	Hardware Attachment
Head	Webbing Loop	5.4 x YSSW38B	6 x - x 900mm	-	-
Tack	Webbing Loop	4.8 x YSSW38B	6 x - x 800mm	-	-
Clew	Webbing Loop	7.2 x YSSW38B	8 x - x 900mm	-	-

BLUE BOOK REFERENCES		NOTES
<u>18.24 Twisted Loop</u>	Tack	Head: Per BB 19.15 head finishing, but with head web loops extending 40mm above cut head. Tack: Twisted Loop - cutout (loop size) 60mm Clew: standard soft clew - cutout 60mm
<u>18.14 Soft Clew</u>	Clew	
<u>19.15 Bottom Up Furling - Long Cable</u>	Head with loops extending above cut head	

POST PRODUCTION				Completed By _____ Date _____	
Sail Bag Measurement Stamp	NSFGC2H-C	Sail Tie Bag Code	5 x YST45SA	Measurement Rule	MORC
	OSMSV2		J-0 2026		

BLUE BOOK REFERENCES	
<u>13.14 3Di Upwind Furling Velcro Clew</u>	

SPREADER PATCH LOCATIONS

EXTRAS			
Bag Code Labeling	Bag Color Option	Furling Box Bag	3 X Glowfast Trim Stripes
HELIX Structured Luff	Overhead Leech Cord	RAW Black	SY Leech Line Sling
Spreader Patches	Standard Measurement	2 X TT Windows	Velcro RF Clew Patch
3 X Vinyl Trim Stripes			

CUSTOM/COMPOSITE ITEMS				
CustomItem Dsc	Notes	Sub Items		
*SYPUOH41-FR x 1000 mm		Item	Qty	Notes
		19mm Black Spectra Tie Off 10cm	1 Each	
		25mm Black Spectra Tie Off 15cm	2 Each	
		3Di SY Velcro Purchase Cover 100cm Narrow - Black	1 Each	
		5mm Dyneema SK-75 Cord	2.5 mtr	
		SY 4:1 Overhead Purchase Hardware Low Friction Rings	1 Each	
		SY Line Bag - Black	1 Each	
*SYPU41-FR x 750 mm		Item	Qty	Notes
		25mm Black Spectra Tie Off 15cm	3 Each	
		3Di SY Velcro Purchase Cover 75cm Narrow - Black	1 Each	
		SY 4:1 Purchase Hardware Low Friction Rings	1 Each	
*SY Leech Sling		Item	Qty	Notes
		Superyacht Leech Sling EA of 2.1 made of SC PBO	22.95 mtr	
*OH line : LD75C004		Item	Qty	Notes
		Braid Core Dyneema Excel Racing, LS4-SD3, 4mm	33 mtr	
*3Di : CLEW WADS	Black 150D TF 800mm radius INTERNAL	No Sub Items.		
*3Di : FOOT STRAINERS	Black 150D TF, 200mm wide on PORT, 250mm wide on STBD. INTERNAL	No Sub Items.		
*3Di : HEAD WADS	Black 150D TF 800mm radius INTERNAL	No Sub Items.		
*3Di : LEECH STRAINERS	Black 150D TF, 600 mm wide on PORT, 700 mm wide on STBD. INTERNAL	No Sub Items.		
*3Di : LUFF STRAINERS	Black 150D TF, 300mm wide on PORT, 350mm wide on STBD. INTERNAL	No Sub Items.		
*3Di : TACK WADS	Black 150D TF 700mm radius INTERNAL	No Sub Items.		
*3Di : Spreader patch	Add internal spreader impact patch and 150d TF external spreader chafe protection. Spreader position is marked in mould	No Sub Items.		

MULTIHULL



NIGEL IRENS 82

Allegra - SUI 888

Salesman Quinny Houry

HELIX J-Zero 3Di RAW 760 \ 29,400 Dpi

Fastcat Ltd (GRIMM, ROB)

OE #: OSP7068-002

Designer Sørensen, Heine (North Sails A/S)

Wkt Created 03/02/2026

HEADSAIL QC

	Spec	Actual
Tack Ring	YSSW38B	
Luff Reinforced & Seized @ Head/Tack		
Head Ring	YSSW38B	
Leech Tape Correct & Smooth		
Leech Cord Correct & Tensioned		
Leech Cord Cleat & Purchase System		
Foot Tape Correct & Smooth		
Foot Cord Correct & Tensioned		
Foot Cord Cleat & Purchase System		
Clew Ring	YSSW38B	
Logo applied with OE#		
Sail Number & Color		
Sail Number Type	Insignia	
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Corner Code		
Tell Tales Applied		
Tell Tale Window	TTW3DL-BK	
Tell Tale Window	TTW3DL-BK	
Head, Tack, Clew Corner Labels		
Sail Is Clean		
All threads cut on patches and tapes		
All corner patches taped and sewn		

	Spec	Actual
Finished Luff	29.950 m	
Finished Leech	24.550 m	
Finished Foot	15.050 m	
Finished Head	0 m	
7/8 Girth	1.57	
3/4 Girth	3.08	
1/2 Girth	6.1	
1/4 Girth	9.15	
Tack Back	60 mm	
Tack Up	0 mm	
Sail Area	188.400 sq m	
Sail Bag	NSFGC2H-C	
Bag Label	J-0 2026	
Sail Ties	5 x YST45SA	
NS Purchasers Package		
Sail Weight		

Notes:

Sail Approved By: _____

Date: _____