

PREMIER RACE



GP 42
CONFLUENCE - ITA 4202

Salesman Northsails Marseille (GATE, Charles)

Jib Light/Medium 3Di RAW 870 \ 14,700 Dpi
North Sails Marseille

Designer Guillaud, Mathieu (Palma)

OE #: OFR18307-001

Wkt Created 17/02/2026

RIG DATA

I: 16,2 **J:** 5 **P:** 16,8 **E:** 5,9 **LOA:** 12,8

3DI

Tape RAW Black

Location	Wad
Head	H5-25
Tack	T3-25
Clew	C5-25

NOTES

1 layer of PCWT6 200mm and 1 layer PCWT6 300mm under the head wad

MISCELLANEOUS ITEMS

CT200EXT-PCWT6 *

FURLING

NESTING

HEADSAIL SIZING

Completed By _____ Date _____

	FINISHED	REDUCTIONS	MOLDED
Head	0,250	0,000	0,222
Luff	15,750	0,030	15,720
Leech	14,480	0,030	14,450
Foot	5,607	0,028	5,579
LP	5,250	0,028	5,222

Head Back	0 mm
Head Down	0 mm
Tack Cut Back (From Front of Luff Tape)	60 mm
Tack Cut Up	0 mm

Girth Type	Max Length	Measured	Luff Position	Leech Position	Notes
7/8 Girth	0,873 m	Measured AS LP	-	-	
3/4 Girth	1,523 m	Measured AS LP	-	-	
1/2 Girth	2,760 m	Measured AS LP	-	-	
1/4 Girth	3,989 m	Measured AS LP	-	-	

BLUE BOOK REFERENCES

05.07 Headsail Tack Fairing

NOTES

Luff length does NOT include head pennant
Leech length measured to the front of head, at the luff

BATTENS & POCKETS

Completed By _____ Date _____

Type	Length	Batten	Pocket	Chafe		Style	Slide	Hardware	Closures	Reinforcements	End Caps
Full	1358mm	E15200C1600	901006 (70mm)	-	FRONT	Closed	-	-	iBPE70CL-BK	iBPR70LU-BK	-
				-	REAR	Wing Tip		-	iBPE70WT-BK	-	BT15300
Leech	1200mm	CB15200F1200	901006 (70mm)	-	FRONT	Closed	-	-	iBPE70CL-BK	iBPR70IN-BK	-
				-	REAR	Wing Tip		-	iBPE70WT-BK	-	BT15300
Leech	1350mm	CB15250F1500	901006 (70mm)	-	FRONT	Closed	-	-	iBPE70CL-BK	iBPR70IN-BK	-
				-	REAR	Wing Tip		-	iBPE70WT-BK	-	BT15300
Leech	1350mm	CB15250F1500	901006 (70mm)	-	FRONT	Closed	-	-	iBPE70CL-BK	iBPR70IN-BK	-
				-	REAR	Wing Tip		-	iBPE70WT-BK	-	BT15300

Batten Hollows

Production Will Calculate Batten Hollows as per BB standard.

GENOA GRAPHICS

Completed By _____ Date _____

North Sails Tack Logo

2 x 06

Trim Stripes			
#	Primary Stripe	Width	Secondary Stripe
1	White (Dacron)	75 mm	
2	White (Dacron)	50 mm	
3	White (Dacron)	25 mm	
4	White (Dacron)	25 mm	

Windows					
#	Type	Item	Location	Vertical Distance	Distance Back
1	TellTale	TTW3D-BK	Below 1/4 Stripe/Position	700 mm	300 mm
2	TellTale	TTW3D-BK	Below 1/2 Stripe/Position	700 mm	300 mm

NOTES

Leech tell tails at every battens

REINFORCEMENTS

Completed By _____ Date _____

SPREADER/STANCHION CONFIGURATION:

Max Hoist

0,000 m

Chainplate Aft

0,000 m

Max Hoist To Chainplate

0,000 m

STANCHION PATCHES			
#	Patch	Distance Back	Distance Up
1	SP90-8	0 mtr	0 mtr
2	SP90-8	0 mtr	0 mtr

NOTES

Stanchion patches loose in the bag

GENOA EDGES

Completed By _____ Date _____

Location	Primary Tape	Tape Offset	Start Point	Cord	Adjuster	Cord Purchase	Place At
Luff	PLL6	28 mm	Tape From Tack: 1000 mm	-	-	-	-
Leech	P62HBK		-	LDX75-003	FCL241	CPS31SV-BK	-
Foot	P62HBK		-	LD003	FCL241	CPS21SC-BK	-

NOTES

Reinforcement on the luff tape on the top and bottom 500mm with light spectra PSA

ATTACHMENTS/HARDWARE

Completed By _____ Date _____

Location	Style	Attachment	Strapping	Hardware	Hardware Attachment
Head	Webbing Loop	3,15 x YSSW19B	3 x - x 1050mm	-	-
Tack	'O' Ring	GR30S	4 x YSSW19B x 350mm	-	-
Clew	'O' Ring	GR31S	6 x YSSW19B x 450mm	-	-

BLUE BOOK REFERENCES

18.26 Headsail Webbing Head Pennant	A = 280mm, B = 40mm
18.27 Clew Corner Cover	Black

POST PRODUCTION

Completed By _____ Date _____

Sail Bag

ZZJ20L

Sail Tie

YST25SA

Measurement Rule

IRC

IHC Sticker

ORIHC

CUSTOM/COMPOSITE ITEMS

CustomItem Dsc	Notes	Sub Items		
		Item	Qty	Notes
* CT200EXT-PCWT6		PCWT6 layer 200mm wad	2 Each	
* GTSM-25		No Sub Items.		

EXTRAS

Full Battens	IHC Measurement Certificate & Sticker	3 X Leech Battens (RBS Carbon)	Padded Clew Cover
RAW Black	Stanchion Patches	2 X TT Windows	4 X Trim Stripes
Zip Bag			

SPREADER PATCH LOCATIONS

PREMIER RACE



GP 42

CONFLUENCE - ITA 4202

Salesman Northsails Marseille (GATE, Charles)

Jib Light/Medium 3Di RAW 870 \ 14,700 Dpi

North Sails Marseille

Designer Guillaud, Mathieu (Palma)

OE #: OFR18307-001

Wkt Created 17/02/2026

HEADSAIL QC

	Spec	Actual
Tack Ring	GR30S	
Luff Reinforced & Seized @ Head/Tack		
Head Ring	YSSW19B	
Leech Tape Correct & Smooth		
Leech Cord Correct & Tensioned		
Leech Cord Cleat & Purchase System		
Foot Tape Correct & Smooth		
Foot Cord Correct & Tensioned		
Foot Cord Cleat & Purchase System		
Clew Ring	GR31S	
Logo applied with OE#		
Sail Number & Color		
Sail Number Type	DefaultProductSpec	
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Corner Code		
Tell Tales Applied		
Tell Tale Window	TTW3D-BK	
Tell Tale Window	TTW3D-BK	
Head, Tack, Clew Corner Labels		
Sail Is Clean		
All threads cut on patches and tapes		
All corner patches taped and sewn		

	Spec	Actual
Finished Luff	15,750 m	
Finished Leech	14,480 m	
Finished Foot	5,607 m	
Finished Head	0 m	
7/8 Girth	0,873	
3/4 Girth	1,523	
1/2 Girth	2,76	
1/4 Girth	3,989	
Tack Back	60 mm	
Tack Up	0 mm	
Sail Area	0,000 sq m	

	Spec	Fit	Label	Caps
Batten	RBS Batten 15x200 Compression 1600mm			
Batten	RBS Carbon Batten 15x200 Flex 1200mm			
Batten	RBS Carbon Batten 15x250 Flex 1500mm			
Batten	RBS Carbon Batten 15x250 Flex 1500mm			

Stanchion Patches	SP90-8	
Stanchion Patches	SP90-8	

Sail Bag	ZZJ20L	
Bag Label		
Sail Ties	1 x YST25SA	
NS Purchasers Package		
Sail Weight		

Notes:

Sail Approved By: _____ Date: _____