



X-YACHT X-412-MH STANDARD

[No Name] Sail #: GER 3949

Salesman Balser, Bertil

Mainsail 3Di ENDURANCE EDGE \ 16,400 Dpi

Philip Kliefoth

Designer Hama, Christian (North Sails GmbH)

OE #: ODE17472-001

Wkt Created 05.03.2026

RIG DATA

I: 16,41 J: 4,88 P: 14,4 E: 4,7 LOA: 12,512

3DI

Tape Black Exterior (0505) Reef Diamonds 6 x RM1-BK

Location	Wad
Head	H7-25
Cunningham	Cu3-25
Tack	T3-25
Clew	C3-25
LuffReef	LU7-25
LeechReef	Le00-25

FURLING

NESTING

MAINSAIL SIZING

Completed By _____ Date _____

	FINISHED	REDUCTIONS	MOLDED
Head	0,150	0,000	0,150
Luff	15,400	0,000	15,400
Leech	16,050	0,000	16,050
Foot	4,650	0,000	4,650

Head Back	0 mm
Head Down	0 mm
Tack Cut Back (From Front of Luff Tape)	50 mm
Tack Cut Up	0 mm
Cunningham Height	400 mm
Cunningham Back	40 mm

Girth Type	Max Length	Measured	Luff Position	Leech Position	Notes
7/8 Girth	1,021 m	Measured AS LP	-	-	
3/4 Girth	1,825 m	Measured AS LP	-	-	
1/2 Girth	3,102 m	Measured AS LP	-	-	
1/4 Girth	3,987 m	Measured AS LP	-	-	

Reef	Luff Height	Leech Height	Reef Back	Single Line Reefing?
FirstReef	2,002 m	2,078 m	40 mm (From Front of Luff Tape)	False
SecondReef	4,158 m	4,311 m	40 mm (From Front of Luff Tape)	False

BLUE BOOK REFERENCES

01.18 Mainsail Hollow Between Luff Slides

BATTENS & POCKETS Completed By _____ Date _____

Date _____

Type	Length	Batten	Pocket	Chafe		Style	Slide	Hardware	Closures	Reinforcements	End Caps
Full	1338mm	E15265C1350	901006 (70mm)	-	FRONT	Batten Box (Standard)	-	NSBB15-10 20mm	BP70BRE-BK	iBPR70LU-BK	-
				-	REAR	Closed		-	iBPE70CL-BK	iBPR70LE-BK	-
Full	2328mm	E15300C2400	901006 (70mm)	-	FRONT	Batten Box (Standard)	-	NSBB15-10 20mm	BP70BRE-BK	iBPR70LU-BK	-
				-	REAR	Closed		-	iBPE70CL-BK	iBPR70LE-BK	-
Leech	1800mm	E19300F1800	901007 (95mm)	-	FRONT	Closed		-	iBPE95CL-BK	iBPR95IN-BK	-
				-	REAR	Wing Tip		-	iBPE95WT-BK	-	BT19300
Leech	2100mm	E19350F2100	901007 (95mm)	-	FRONT	Closed		-	iBPE95CL-BK	iBPR95IN-BK	-
				-	REAR	Wing Tip		-	iBPE95WT-BK	-	BT19300
Leech	2400mm	E19400F2400	901007 (95mm)	-	FRONT	Closed		-	iBPE95CL-BK	iBPR95IN-BK	-
				-	REAR	Wing Tip		-	iBPE95WT-BK	-	-

Batten Hollows
Production Will Calculate Batten Hollows as per BB standard.

Production Will Calculate Batten Hollows as per BB standard.

BLUE BOOK REFERENCES	
<u>20.10 NSBB Batten Spacers</u>	

NOTES

Battenslide will be installed by dealer! Place batten retainer 20mm back from front of lufftape to meet slide offset!

Battenslide will be installed by dealer! Place batten retainer 20mm back from front of lufftape to meet slide offset!

MAINSAIL GRAPHICS Completed By _____ Date _____

Date _____

Sail Number	GER 3949	Color	White	Size	457	Type	Insignia
	North Sails Tack Logo		2 x 06		Insignia		
Trim Stripes							
#	Primary Stripe	Width	Secondary Stripe				
1	White (Dacron)	75 mm					
2	White (Dacron)	50 mm					
3	White (Dacron)	25 mm					

REINFORCEMENTS Completed By _____ Date _____

Date _____

SPREADER DOTS			
#	Patch	Distance Out	Distance Down
1	GPAD30-17	0 mtr	0 mtr
2	GPAD30-17	0 mtr	0 mtr
3	GPAD30-17	0 mtr	0 mtr

NOTES
preader tip patches loose to the sail!

Spreader tip patches loose to the sail!

MAINSAIL EDGES Completed By _____ Date _____

Date _____

Location	Primary Tape	Start Point	Cord	Adjuster	Cord Purchase	Place At	Reef Cleat	Overhead Tape	Overhead Line	Slide
Luff	P84BK 	Slide From Tack: 1250 mm	LD005	TOWL19SBK	-	TackLuff	FCL258	P42HBK 	LPSP004	S511-719 Offset: 0mm
Leech	P62HBK 	-	LDX75-003	FCL241	CPS21MCO-BK	TackLuff	-	-	-	-
Foot	P63BK 	-	LPSP004	FCL241	CPS21SC-BK	TackFoot	-	-	-	-

BLUE BOOK REFERENCES	
<u>11.13 Standard Mainsail Overhead Leech Line</u>	
<u>19.02 Mainsail Luff Cord Installation - Adjustable</u>	

NOTES

Sail will get Selden MDS 45/68 sliders, all cars are on the mast. Only install bushes and retainers. Bush is S511-719. Slide offset is 35mm. Distance from front of lufftape to center of bush: 14mm. Place retainer 20mm back from front of lufftape to meet slide offset. Drill 13mm hole in HB, 40mm back and 95mm down from upper front corner of sailhead. Pigtail in luff, follow BB page 01.18. to cut negative between slides. Finish luff according to BB page 19.02.

Sail will get Selden MDS 45/68 sliders, all cars are on the mast. Only install bushes and retainers. Bush is S511-719. Slide offset is 35mm. Distance from front of lifftape to center of bush: 14mm. Place retainer 20mm back from front of lifftape to meet slide offset. Drill 13mm hole in HB, 40mm back and 95mm down from upper front corner of sailhead. Pigtail in luff, follow BB page 01.18. to cut negative between slides. Finish luff according to BB page 19.02.

ATTACHMENTS/HARDWARE						Completed By _____	Date _____
Location	Style	Attachment	Strapping	Hardware	Hardware Attachment		
Head	Std Headboard	GHB15B	3 x YSSW25B x 450mm	-	-		
Cunningham	Press Ring	GSR20	2 x YSSW19B x 350mm	-	-		
Tack	'O' Ring	GR31S	4 x YSSW19B x 350mm	-	-		
Clew	'O' Ring With Boom Strap	GR40HS	5 x YSSW25B x 450mm	CS25-200	-		
Luff Location	Luff Attachment	Luff Attachment Strapping	Luff Floppy	Luff Hardware	Side		
1st Reef	GSR25	2 x YSSW19B x 400mm	2 x GR31S		Na		
2nd Reef	GSR25	2 x YSSW19B x 400mm	2 x GR31S		Na		
Leech Location	Leech Attachment	Leech Attachment Strapping	Leech Hardware	Side			
1st Reef	iFRR10-BK	-	-	Na			
2nd Reef	iFRR10-BK	-	-	Na			

BLUE BOOK REFERENCES

17.26 FRR10 FRR14 Installation

NOTES

Drill 13mm hole in HB, 40mm back and 95mm down from upper front corner of sailhead.

POST PRODUCTION				Completed By _____	Date _____
Sail Bag	ZD-5	Sail Tie	4 x YST25SA	Measurement Rule	ORC
BLUE BOOK REFERENCES 21.16 Standard Certified Measurement					

EXTRAS			
Black Exterior (0505)	Country Code	Cunningham	Drawstring Sailbag
2 X Full Battens	Insignia	3 X Leech Battens	Mainsail Spreader Tip Patches
Overhead Leech Cord	Sail Numbers	2 X Standard Reef(s)	3 X Trim Stripes

CUSTOM/COMPOSITE ITEMS				
CustomItem Dsc	Notes	Sub Items		
*NO (Head Slide)	Customer Supplied Head Slide	No Sub Items.		
*S511-719		Item	Qty	Notes
		Selden BUSHING 10/6.5-19 PA	10 Each	

**X-YACHT X-412-MH STANDARD**

[No Name] Sail #: GER 3949

Salesman Balser, Bertil

Mainsail 3Di ENDURANCE EDGE \ 16,400 Dpi

Philip Kliefoth

OE #: ODE17472-001

Designer Hamma, Christian (North Sails GmbH)

Wkt Created 05.03.2026

MAINSAIL QC

	Spec	Actual
Tack Ring	GR31S	
Cunningham	GSR20	
Luff Reinforced & Seized @ Head/Tack		
Luff Hardware	S511-719	
Head Ring	GHB15B	
Leech Tape Correct & Smooth		
Leech Cord Correct & Tensioned		
Leech Cord Cleat & Purchase System		
Foot Tape Correct & Smooth		
Foot Cord Correct & Tensioned		
Foot Cord Cleat & Purchase System		
Clew Ring	GR40HS	
Logo applied with OE#		
Sail Number & Color	GER 3949	
Sail Number Type	Insignia	
Insignia	INSCUSTOM (White)	
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Draft stripe color & mid stripe points		
Corner Code		
Tell Tales Applied		
Head, Tack, Clew Corner Labels		
Sail Is Clean		
All threads cut on patches and tapes		
All corner patches taped and sewn		

	Spec	Actual
Finished Luff	15,400 m	
Finished Leech	16,050 m	
Finished Foot	4,650 m	
Finished Head	0 m	
7/8 Girth	1,021	
3/4 Girth	1,825	
1/2 Girth	3,102	
1/4 Girth	3,987	
Tack Back	50 mm	
Tack Up	0 mm	

	Spec	Fit	Label	Caps
Batten	RBS Batten 15x265 Compression 1350mm			
Batten	RBS Batten 15x300 Compression 2400mm			
Batten	RBS Batten 19x300 Flex 1800mm			
Batten	RBS Batten 19x350 Flex 2100mm			
Batten	RBS Batten 19x400 Flex 2400mm			

Spreader Dots	GPAD30-17	
Spreader Dots	GPAD30-17	
Spreader Dots	GPAD30-17	

Sail Bag	ZD-5	
Bag Label		
Sail Ties	4 x YST25SA	
NS Purchasers Package		
Sail Weight		

Notes:

Sail Approved By: _____

Date: _____