Online Banking Enterprise™

ISO File Layout Specification - Payments

February 2017

FNB
First National Bank

how can we help you?

Table of Contents

1.1 ISO PAIN File Structure Files - PAIN.001.001.03 3
1.2 ISO PAIN File Structure Files - PAIN.002.001.03 – Final 12
1.3 Status Codes 14
1.4 ISO Error Codes.....14

1.1 ISO PAIN File Structure Files - PAIN.001.001.03

XML Element	Mult.	Data Type	FRB Limits	Comment	Example
<CstmrCdtTrfInitn>	1..1				
<GrpHdr>	1..1			Set of characteristics shared by all individual transactions included in the message.	
<MsgId>	1..1	Text: 1..35		Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.	M1
<CreDtTm>	1..1	DateTime: ISODateTime		Date and time at which the message was created.	2015-01-07T14:07:00
<NbOfTxs>	1..1	Numeric Text: 1..15		Number of individual transactions contained in the message.	2
<CtrlSum>	1..1	Decimal Number Total Digits: 18 Fraction Digits: 17		Total of all individual amounts included in the message, irrespective of currencies. Local Rule: Mandatory	10100.01
<InitgPty>	1..1			Party that initiates the payment.	
<Nm>	1..1	Text: 1..140		Name by which a party is known and which is usually used to identify that party. Local Rule: Mandatory	Initiator Inc
<PmtInf>	1..*			Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.	
<PmtInfId>	1..1	Text: 1..35	Text: 1..19	Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.	P1

		<PmtMtd>				1..1	Code Text: 3..3		• CHK: Cheque • TRA: Transfer Advise • TRF: Credit Transfer	TRF
		<BtchBookg>				0..1			Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. • true = Consolidated • false = Itemized	true
		<NbOfTxs>				1..1	Max15NumericText		Number of individual transactions contained in the payment information group. Local Rule: Mandatory	1
		<CtrlSum>				1..1	Decimal Number Total Digits: 18 Fraction Digits: 17		Total of all individual amounts included in the group, irrespective of currencies. Local Rule: Mandatory	10000.01
		<PmtTpInf>				1..1			Set of elements used to further specify the type of transaction. Local Rule: Mandatory	
			<SvcLvl>			1..1			Agreement under which or rules under which the transaction should be processed.	

				<Cd>			1..1	Text: 1..4		Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. Options: • SDVA: Same Day Value • ONED: One Day • TWOD: Two Day • URGP: RTGS (not currently available via Fintegrate Gateway) • RTCL: Pay & Clear (not currently available via Fintegrate Gateway)	SDVA
		<ReqdExctnDt>					1..1	DateTime: ISODateTime		Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited.	2015-01-08
		<Dbtr>					1..1			Party that owes an amount of money to the (ultimate) creditor.	
			<Nm>				1..1	Text: 1..35		Name by which a party is known and which is usually used to identify that party. Local Rule: Mandatory	Debtor Inc
		<DbtrAcc>					1..1			Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.	
			<Id>				1..1			Unique and unambiguous identification for the account between the account owner and the account servicer.	
				<Othr>			1..1			Unique identification of an account, as assigned by the account servicer, using an identification scheme.	
					<Id>		1..1	Text: 1..34	Text: 1..23	Identification assigned by an institution.	123456789
			<Tp>				1..1			Specifies the nature, or use of the account.	
				<Cd>			1..1	Text: 4..4		Account type, in a coded form. CACC: Current Account (Account must be a Current Account)	CACC

		<DbtrAgt>				1..1			Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.	
			<FinInstnId>			1..1	empty		Future: This to be used for Universal Branch Code in future version with <MmbId>	
			<BrnchId>						Identifies a specific branch of a financial institution.	
				<Id>		1..1	Text: 1..35	Text: 1..6	Unique and unambiguous identification of a branch of a financial institution. 6 character Branch Code	250655
		<CdtTrfTxInf>				1..1			Set of elements used to provide information on the individual transaction(s) included in the message.	
			<PmtId>			1..1			Set of elements used to reference a payment instruction.	
				<EndtoEndId>		1..1	Text: 1..35	Text: 1..20	Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.	T1
			<Amt>			1..1			Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.	
				<InstdAmt>		1..1	Numeric Total Digits: 18 Fraction Digits: 5 Min Inclusive: 0	Numeric (15.2) Total Digits: 17 Fraction Digits: 2	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Decimal seperator is a dot. Amount element must contain XML Attribute "Ccy" to indicate Currency Code. Currency Code must comply with ISO 4217. E.g. "ZAR"	10000.01 <InstdAmt Ccy="ZAR">10000.01</InstdAmt>
			<CdtrAgt>			1..1			Financial institution servicing an account for the creditor.	

				<FinInstnId>			1..1	empty		Future: This to be used for Universal Branch Code in future version with <MmbId>	
				<BrnchId>			1..1	Text: 1..35	Text: 1..6	Identifies a specific branch of a financial institution. Branch Code of Financial Organisation. E.g. 250655	250655
			<Cdtr>				1..1			Party to which an amount of money is due.	
				<Nm>			1..1	Text: 1..35		Name by which a party is known and which is usually used to identify that party. Local Rule: Mandatory	Creditor One Pty Ltd
			<CdtrAcct>				1..1			Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.	
				<Id>			1..1			Unique and unambiguous identification for the account between the account owner and the account servicer.	
					<Other>		1..1			Unique identification of an account, as assigned by the account servicer, using an identification scheme.	
						<Id>	1..1	Text: 1..35	Text: 1..23	Identification assigned by an institution.	123456789
				<Tp>			1..1			Specifies the nature, or use of the account. Use <Cd> for accounts that exist in PAIN specifications, or <Prtry> for those that don't.	
					<Cd>		1..1	Text: 1..4		Account type, in a coded form. If the account type is not a Current or Savings account, then the Prtry code as below must be used. • CACC: Current Account • SVGS: Savings Account	{OR} CACC

					<Prtry>		1..1	Text: 1..35		Nature or use of the account in a proprietary form. If the account is not a Current Account (CACC) or Savings Account (SVGS) then this tag must be used to indicate Account Type. Either the Cd or the Prtry tag may be used, but not both. • BOND: Bond Account (Not currently supported) • TRNS: Transmission Account (Not currently supported) • CCRD: Card Account (Not currently supported) • SBSH: Subscription Share (Not currently supported) For the convenience of clients using any of the above account types, this list may be extended with CACC and SVGS in order that only one tag (<Prtry>) be supported.	{OR} BOND
			<RmtInf>				1..1			Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.	
				<Ustrd>			1..1	Text: 1..140	Text: 1..20	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Local Rule: Mandatory	Inv: 1/1
		<CdtTrfTxInf>					1..1			Set of elements used to provide information on the individual transaction(s) included in the message.	
			<PmtId>				1..1			Set of elements used to reference a payment instruction.	

				<EndtoEndId>		1..1	Text: 1..35	Text: 1..20	Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.	T2
			<Amt>			1..1			Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.	
				<InstdAmt>		1..1	Numeric Total Digits: 18 Fraction Digits: 5 Min Inclusive: 0	Numeric (15.2) Total Digits: 17 Fraction Digits: 2	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Decimal seperator is a dot. Amount element must contain XML Attribute "Ccy" to indicate Currency Code. Currency Code must comply with ISO 4217. E.g. "ZAR"	100.00 <InstdAmt Ccy="ZAR">100.00</InstdAmt>
			<CdtrAgt>			1..1			Financial institution servicing an account for the creditor.	
				<FinInstnId>		1..1	empty		Future: This to be used for Universal Branch Code in future version with <MmbId>	
				<BrnchId>		1..1	Text: 1..35	Text: 1..6	Identifies a specific branch of a financial institution. Branch Code of Financial Organisation. E.g. 250655	250655
			<Cdtr>			1..1			Party to which an amount of money is due.	
				<Nm>		1..1	Text: 1..35		Name by which a party is known and which is usually used to identify that party. Local Rule: Mandatory	Creditor Two Pty Ltd
			<CdtrAcct>			1..1			Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.	

				<Id>			1..1			Unique and unambiguous identification for the account between the account owner and the account servicer.	
					<Other>		1..1			Unique identification of an account, as assigned by the account servicer, using an identification scheme	
						<Id>	1..1	Text: 1..35	Text: 1..23	Identification assigned by an institution.	234567891
				<Tp>			1..1			Specifies the nature, or use of the account. Use <Cd> for accounts that exist in PAIN specifications, or <Prtry> for those that don't.	
					<Cd>		1..1	Text: 1..4		Account type, in a coded form. If the account type is not a Current or Savings account, then the Prtry code as below must be used. • CACC: Current Account • SVGS: Savings Account	{OR} CACC

					<Prtry>		1..1	Text: 1..35		Nature or use of the account in a proprietary form. If the account is not a Current Account (CACC) or Savings Account (SVGS) then this tag must be used to indicate Account Type. Either the Cd or the Prtry tag may be used, but not both. • BOND: Bond Account (Not currently supported) • TRNS: Transmission Account (Not currently supported) • CCRD: Card Account (Not currently supported) SBSH: Subscription Share (Not currently supported) For the convenience of clients using any of the above account types, this list may be extended with CACC and SVGS in order that only one tag (<Prtry>) be supported.	{OR} BOND
			<RmtInf>				1..1			Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.	
				<Ustrd>			1..1	Text: 1..140	Text: 1..20	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Local Rule: Mandatory	Inv: 2/1

1.2 ISO PAIN File Structure Files - PAIN.002.001.03 – Final

XML Element	Mult.	Data Type	Comment	Example
<CstmrPmtStsRpt>	1..1			
<GrpHdr>	1..1			
<MsgId>	1..1	Text: 1..35	Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party.	M4
<CreDtTm>	1..1	ISODateTime	Date and time at which the message was created.	2015-09-15T14:50:00
<OrgnlGrpInfAndSts>	1..1		Original group information concerning the group of transactions, to which the status report message refers to.	
<OrgnlMsgId>	1..1	Text: 1..35	Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.	M1
<OrgnlMsgNmId>	1..1	Text: 1..35	Specifies the original message name identifier to which the message refers	PAIN.008.001.02
<OrgnlPmtInfAndSts>	0..n		Information concerning the original payment information, to which the status report message refers.	
<OrgnlPmtInfId>	1..1	Text: 1..35	Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group.	P1
<TxInfAndSts>	0..n		Set of elements used to provide information on the original transactions to which the status report message refers.	
<OrgnlEndToEndId>	0..1	Text: 1..35	Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction	T1
<TxSts>	0..1	Text: 4..4	Specifies the status of a transaction, in a coded form. (TransactionIndividualStatus3Codevalues - see Status Codes spreadsheet)	RJCT
<StsRsnInf>	0..1		Set of elements used to provide detailed information on the status reason.	
<Rsn>	0..1		Specifies the reason for the status report.	
<Cd>	1..1	Text: 4..4	Reason for the status, as published in an external reason code list. (ExternalStatusReason1Code - see Status Reason Code spreadsheet)	AM05

	<OrgnlPmtInfAndSts>					0..n		Information concerning the original payment information, to which the status report message refers.	
		<OrgnlPmtInfId>				1..1	Text: 1..35	Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group.	P1
		<TxInfAndSts>				0..n		Set of elements used to provide information on the original transactions to which the status report message refers.	
			<OrgnlEndToEndId>			0..1	Text: 1..35	Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction	T2
			<TxSts>			0..1	Text: 4..4	Specifies the status of a transaction, in a coded form. (TransactionIndividualStatus3Codevalues - see Status Codes spreadsheet)	ACSC

1.3 Status Codes

Code	Name	Definition
ACTC	AcceptedTechnicalValidation	Message Level: Authentication and syntactical and semantical validation are successful.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

1.4 ISO Error Codes

ISO Error Codes	Definition
AC01	Format of the account number specified is not correct.
DT01	Invalid date (eg, wrong settlement date).
AM16	Control Sum at the Group level is invalid.
FF03	Payment Type Information is missing or invalid. Generic usage if cannot specify Service Level or Local Instrument code.
AC12	Account type is missing or invalid.
CL01	Invalid Abbreviated Name
FF10	File or transaction cannot be processed due to technical issues at the bank side.
AC02 (collections)	Debtor account number invalid or missing.
AC03 (payments)	Creditor account number invalid or missing.