IPC322LB-SF28(40)-A

2MP Vandal-resistant Network IR Fixed Dome Camera

• High quality image with 2MP, 1/2.8"CMOS sensor
• 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
• Ultra 265, H.265, H.264
• Smart IR, up to 30m (98ft) IR distance
• Day/night functionality
• 2D/3D DNR (Digital Noise Reduction)
• IP67 protection
• IK10 vandal resistant
• Support PoE power supply
• 2-Axis

المواصفات   الملحقات   تنزيل

	IPC322LB-SF28-A	IPC322LB-SF40-A
Camera		
Sensor	1/2.8", progressive scan, 2.0 megapixel, CMOS	
Lens	2.8mm@F2.0	4.0mm@F2.0

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	43.4	17.4	8.7	4.3
	4.0	62.1	24.8	12.4	6.2

Angle of View (H)	106.7°	87.5°
Angle of View (V)	57.1°	46.3°
Adjustment angle	Pan: 3° ~ 360°	Tilt: 0° ~ 75°
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR	
Day/Night	IR-cut filter with auto switch (ICR)	
Digital noise reduction	2D/3D DNR	
S/N	>52dB	
IR Range	Up to 30m (98ft) IR range	
Wavelength	850nm	
IR On/Off Control	Auto/Manual	

WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps
	Sub Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°
Dewarping	N/A
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
Compatible Integration	API
Client	EZStation
	EZView
	EZLive
Web Browser	Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+
Interface	
Network	10/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5.0W

Material	Metal + Plastic
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Strorage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	N/A

Want to learn more?

💬 Contact sales

المنتجات ذات الصلة

روابط سريعة

غرفة الأخبار

شركتنا

Subscriber

✉ النشرة الإخبارية Subscriber

المنتجات

الدعم

كيفية الشراء