Reproducible Research

A brief overview of
Literate Programming via R and knitr
and
Version control via git

Peter DeWitt

University of Colorado Anschutz Medical Campus Department of Biostatistics


29 January 2014

Presentation Outline

- 1 Introduction
- 2 Hello World
- 3 Design
- 4 Options
 - Chunk Options
 - Language Options
 - Collaborations
- **5** Editors
- 6 Examples
- **7** git



A little humor





www.xkcd.com/1301

Alt Text: I have never been lied to by data in a .txt file which has been hand-aligned.

The image itself is a .png

A little humor





www.xkcd.com/1319

Alt Text: 'Automating' comes from the roots 'auto; meaning 'self-', and 'mating', meaning 'screwing'.

Literate Programming

Introduction

- Originally intended for software development
- Mix source code (for the computer) and documentation (for the humans) together
- Sweave built on this paradigm but with a different focus: reproducible data analysis and statistical reports.
- knitr, developed by Yihui Xie, expands on the concept of Sweave.
- 'designed to give the user access to every part of the process of dealing with a literate programming document'
- o package homepage http://yihui.name/knitr/

Dynamic Report Writing

- Pros:
 - Reproducible reports
 - Contextual commenting
 - · knitr is flexible enough to allow for multiple analysis languages and multiple markup languages.

• Cons:

- Not all analysis languages are ideally suited for this paradigm.
- Collaborations with others using WYSIWYG editors requires some additional work and breaks automation/reproducibility.
- Additional Tools: Version control, e.g., git or svn.
- Every project is different; use the tools that will work best.

Why knitr?

- Incorporate both the analysis code and the manuscript writing into one file.
- Contextually commented analysis code.
- Fully documented and reproducible reports.

Example: Code for the next two frames

```
\begin{frame}[fragile]
<<"cars", fig.width = 3.5, fig.height = 3.25, results = "asis">>=
fit <- lm(dist ~ speed, data = cars)</pre>
latex(cbind(coef(fit), confint(fit)),
      file = "", title = "", ctable = TRUE,
      caption = "Regression Estimates",
      digits = 3, colhead = c("Est", "LCL", "UCL"))
0
The expected stopping distance for a car during the 1920s
increased by \Sexpr{round(coef(fit)[2], 2)} feet for every
additional mph increase in speed.
\end{frame}
\begin{frame}[fragile]
<<"cars_plot", fig.width = 3.5, fig.height = 2.75>>=
qplot(speed, dist, data = cars) + geom_smooth(method = "lm")
0
```


```
fit <- lm(dist ~ speed, data = cars)
latex(cbind(coef(fit), confint(fit)),
      file = "", title = "", ctable = TRUE,
      caption = "Regression Estimates",
      digits = 3, colhead = c("Est", "LCL", "UCL"))
```

Table: Regression Estimates

	Est	LCL	UCL
(Intercept)	-17.58	-31.2	-3.99
speed	3.93	3.1	4.77

The expected stopping distance for a car during the 1920s increased by 3.93 feet for every additional mph increase in speed.

qplot(speed, dist, data = cars) + geom_smooth(method = "lm")



How does knitr work?

- One input file with
 - o an analysis language (R, Python, awk, SAS, ...) and
 - an output markup language (LATEX, html, Markdown, ...)
- knitr determines the appropriate set of patterns (regular expression to extract analysis language and options from the input file)
- The input file is knitted..., analysis language is evaluated and the appropriate output markup results are placed into a .tex, .html, .md, \dots , file.
- Final document (the .tex, .html, .md, ...) is ready for release or post processing as needed.

For Rnw files:

```
<<"chunk_label", echo = FALSE, results = "asis">>=
@
```

- Chunk options must be a single line; no line breaks.
- Options must be valid R expressions.
- Chunk options can be specified for each individual chunk.
- Global options are set via opts_chunk\$set()

Full details for all the chunk options see http://yihui.name/knitr/options

- Code Evaluation
- How to display results
- Code Decoration
- Cache
- Plots
- Animation
- Chunk References
- Child Documents
- Language Engines
- Extracting source code

Input/Analysis Language

- R is the 'default' language for analysis
- Other options are available, including SAS. The chunk option 'engine' allows for different languages to be used.

engine: ('R'; character) the language name of the code chunk; currently other possible values are 'python' and 'awk'/'gawk'; the object knit_engines in this package can be used to set up engines for other languages¹

• Pick the right language for the job. R is great, but every now and then SAS would be preferable.

¹http://yihui.name/knitr/options

- Pros:
 - easy to send to others,
 - comments in html,
 - great for tutorials or anything that will be published online.
- Cons:
 - Clunky (in my opinion),
 - not apt for large data analysis reports.
- html code can be placed natively in markdown, ergo, markdown has supplanted html.

Language Options

Markup Language

• Pros:

- Easy to learn
- Simple and versatile
- Growing user community
- Via pandoc, easy to convert to many other file formats such as LaTeX, html, or .docx.

• Cons:

- no native comments.
- 'too minimal'
- pandoc may require additional scripting to format output as needed for .docx or other file types.

• Pros:

- Intended use: technical report writing and typesetting.
- Comments.
- Many tools exist for formating R output well in LATEX files.
- Cross referencing, citations.
- pdflatex produces a file that is almost platform independent.

• Cons:

- Difficulties will be encountered when collaborating with Microsoft Office users.
- R is small, Tex Live, MacTeX, and proTeX are not.
- Steepest learning curve

- LATEX is my preferred markup language for data analysis reports and presentations (via beamer).
- Markdown is my preferred markup language for developing a web page. Easier to work in than html and more flexible.

- LATEX pdfs are not always easy to transfer to MS Word
- Local html pages are easy to break.
- Misconceptions about viewing local files versus remote files in a web browser.
- \circ .doc(x) are 'accidentally' editable.
- What about Google docs?
- What about track changes in Office?

Suggested Development Environments

- I prefer the Vim editor and with the vim-r-plugin.
 - Vim Editor: www.vim.org/index.php
 - vim-r-plugin: www.vim.org/scripts/script.php?script_id=2628
 - Completely customizable.
- If you are not a Vim or Emacs user, then RStudio is the <u>premier</u> R IDE for you.
 - Download and info: www.rstudio.com
 - Built in tools for version control, projects, knitting...
- RStudio is the better R development environment.
- Vim is a better text editor.
- A pseudo WYSIWYG editor for LATEX which will work well with knitr is LyX.

Reproducible examples

These slides, and the following examples, can be downloaded/cloned, from

https://github.com/dewittpe/knitrexamples

- A simple data analysis report using R, and three different markup languages, LATEX, html, and Markdown.
- An example of using SAS within knitr.
- An example of a more complex and extensive data analysis report.

Version Control with git

- Distributed version control: everything is local and can be synced with a remote server.
- Simple to use.
 - Built in GUI with RStudio
 - Only need five commands to be able to use git.
 - 1 git status
 - 2 git log
 - 3 git add
 - 4 git pull
 - 5 git push
 - Other very helpful commands: tag, fetch, merge, mergetool, and branch

git

Do you need a server?

- The repositories are local, so servers are not needed.
- Servers to host a central repository are helpful for collaborations.
- Read/Write permissions can be set for different users.
- There are options to put a git enterprise on a server behind our firewall, but it's expensive.
- github.com has free public repos, pay for private repos
- bitbucket.org has free public and private repos.
- Visit http://git-scm.com/book for documentation on git.

git