

Six-DoF Hand-Based Teleoperation for Omnidirectional Aerial Robots

Jinjie LI[†], Jiaxuan LI[†], Haokun Liu, Kotaro Kaneko, Liming Shu, Moju Zhao



LI, Jinjie

Doctoral Student
DRAGON Lab

Department of Mechanical Engineering
The University of Tokyo




LI, Jiaxuan


Master Student
IntE MeD Lab

Department of Mechanical Engineering
Dalian University of Technology

Introduction – Omnidirectional Teleoperation




Demos



$$\mathbb{R}^2 \times \mathbb{R}^2 \times \mathbb{R}^2 \cong \mathbb{R}^6$$

Not Equal !

$$SE(3) \cong \mathbb{R}^3 \times SO(3)$$




Introduction – Omnidirectional Teleoperation

Haptic Devices



J. Mellet, M. Tognon, et al., arXiv, 2024




Lambda

J. Lee, et al., T-Field Robotics, 2024



Space Joystick




M. Allenspach, M. Tognon, et al., ICRA, 2022




The fingers are constrained.

- ✓ Hand **position**
- ✓ Hand **orientation**
- Hand **gesture**



Finger freedom matters.

Omnidirectional Aerial Teleoperation




Hand-Based Interaction

$$\mathbf{p}_{B_c} = \hat{\mathbf{p}}_B(t_0) + \mathbf{k} \cdot (\hat{\mathbf{p}}_H(t) - \hat{\mathbf{p}}_H(t_0)),$$

$${}^W_B \mathbf{q}_c = {}^W_H \hat{\mathbf{q}}.$$

Precise Operation


Long-Range Moving




$$\mathbf{p}_{B_c} = \hat{\mathbf{p}}_B(t_0),$$

$${}^W_B \mathbf{q}_c = {}^W_B \hat{\mathbf{q}}(t_0).$$


Cartesian Mode



Spherical Mode



Omnidirectional Aerial Teleoperation





Six-DoF Hand-Based Teleoperation for Omnidirectional Aerial Robots

Jinjie Li^{1†*}, Jiaxuan Li^{2†}, Kotaro Kaneko^{1,3}, Haokun Liu¹, Liming Shu², and Moju Zhao¹




[†]Equal Contributions

¹DRAGON Lab, Department of Mechanical Engineering, The University of Tokyo

²Intelligent Equipment and Medical Device Lab, Department of Mechanical Engineering, Dalian University of Technology

³HNL Lab, Department of Mechanical Engineering, The University of Tokyo

Result



- ❑ Control is stable but has offset
- ❑ RMSEs (all positional axes) are over 3 cm, $>$ maximum tolerance
- ❑ Human operator can deal with this offset and ensure the safety

Conclusion

Six-DoF Hand-Based Teleoperation for Omnidirectional Aerial Robots

IROS 2025, Hangzhou

Key Takeaways

- To our best knowledge, this is **the first time** the rotational dexterity of human wrist → an omnidirectional aerial robot.
- Precise operation: Locking mode matters!
- Long-range moving: Spherical mode → natural, and Cartesian mode → moving along regular geometries like squares.

Future Directions

- Shared control: rotations that exceed the natural flexibility
- Force and torque support
- Fully onboard flight; video streaming

Workshop Friday 106 ~12:30



Time: 2025.02.26 Night

Thank you!