

- Numerous single pole-single throw momentary configurations.
- Excellent tactile feed-back (Snap dome).
- Ultra-compact size.
- Long operating life for high reliability.
- Molded-in terminals minimize wicking of flux or solder.

MATERIALS Case: Thermoplastic, color black. UL94HB Standard.

Actuator: Thermoplastic, color black unless otherwise specfied.

Cover/Bracket: PET film, tin plated brass or stainless steel.

Terminals: Silver plated brass.

Shorting Contact: Phosphor bronze or stainless steel with silver plating.

L.E.D. rating: Forward voltage- 2.1 V (3.0 V Max.). Cont. fwd. current 20mA max.@ 25°C.

GENERAL SPECIFICATIONS

ELECTRICALS

Contact rating: 50 mA @ 12 VDC

Insulation resistance: 100 megohms min. (100 VDC)

Dielectric withstanding voltage: 250 VAC for 1 minute

Contact resistance: 100 milliohms max. @ 5 VDC, 10 mA

Electrical life: 100,000 cycles min. (except models MJTP1243 & 1250- 50,000 cycles)

1,000,000 cycles available - consult factory

Contact bounce: less than 10 msec.

MECHANICALS, THERMALS, ENVIRONMENTALS

Plunger travel: .010"+ .008", - .004" (0,25 +0,2, -0,1 mm)

Actuation force: 160 grams ±30 grams

Operating temperature range: -20°C to +70°C

Storage temperature range: -30°C to +80°C for 96 hours

Shock resistance: 30G per method 213, MIL-STD-202 Vibration resistance: passes method 201, MIL-STD-202

SOLDERING (note - non-washable except for models indicated 'process compatible' below).


IR reflow soldering: 240°C max. for 20 seconds max. Wave soldering: 255°C max. for 5 seconds max.


Hand soldering: 320°C max. for 3.5 seconds max. (40 watt iron max.)

MJTP1105T

Right angle, grounding









Caps available see end of section. Bulk packaged.

US # MJTP1109 EU # PHAP3350

Process compatible, grounding









US Model	Dim.	EU Model
No.	L (In./mm)	No.
MJTP1109	.197 (5.0)	PHAP3350
MJTP1109A	.354 (9.0)	PHAP3350A
MJTP1109B	.512 (13.0)	PHAP3350B

US # MJTP1117 EU # PHAP3363

Right angle, grounding









Bulk packaged.

US # MJTP1119 EU # PHAP3351

Process compatible








US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1119	.197 (5.0)	PHAP3351
MJTP1119A	.354 (9.0)	PHAP3351A
MJTP1119B	.512 (13.0)	PHAP3351B


Bulk packaged.

US # MJTP1129 EU # PHAP1152

Right angle, grounding, process compatible








US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1129	.171 (4.35)	PHAP3352
MJTP1129A	.329 (8.35)	PHAP3352A
MJTP1129B	.486 (12.35)	PHAP3352B

Bulk packaged.

US # MJTP1141 EU # PHAP3307 Long terminals







US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1141	.169 (4.3)	PHAP3307
MJTP1141A	.197 (5.0)	PHAP3307A

Packaged on tape. Note: other models available with this tape packaging - consult factory.

US # MJTP1193 EU # PHAP3308 With L.E.D.









US Model	L.E.D.	EU Model
No.	Color	No.
MJTP1193	No L.E.D.	PHAP3308
MJTP11936	Red	PHAP3308R
MJTP11935	Yellow	PHAP3308Y
MJTP11933	Green	PHAP3308G

Caps available with lens - see end of section.
Bulk packaged.

US # MJTP1230 EU # PHAP3301









US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1230	.170 (4,3)	PHAP3301
MJTP1230A	.197 (5,0)	PHAP3301A
MJTP1230B	.374 (9,5)	PHAP3301B
MJTP1230C	.315 (8,0)	PHAP3301C
MJTP1230D	.512 (13,0)	PHAP3301D
MJTP1230E	.287 (7,3)	PHAP3301E
MJTP1230F	.335 (8,5)	PHAP3301F
MJTP1230G	.275 (7,0)	N/A

Bulk packaged.

US # MJTP1232 EU # PHAP3302 Grounding









US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1232	.170 (4,3)	PHAP3302
MJTP1232A	.197 (5,0)	PHAP3302A
MJTP1232B	.374 (9,5)	PHAP3302B
MJTP1232C	.315 (8,0)	PHAP3302C
MJTP1232D	.512 (13,0)	PHAP3302D
MJTP1232E	.287 (7,3)	PHAP3302E
MJTP1232F	.335 (8,5)	PHAP3302F
MJTP1232G	.275 (7,0)	PHAP3302G

Bulk packaged.

US # MJTP1234 EU # PHAP3303








US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1234	.094 (2,4)	PHAP3303
MJTP1234A	.110 (2,8)	PHAP3303A

Caps available see end of section. Bulk packaged.








US Model	Dim.	EU Model
No.	L (in./mm)	No.
MJTP1236	.124 (3,1)	PHAP3305
MJTP1236A	.152 (3,9)	PHAP3305A
MJTP1236B	.329 (8,4)	PHAP3305B
MJTP1236C	.270 (6,9)	PHAP3305C
MJTP1236D	.466 (11,9)	PHAP3305D
MJTP1236E	.244 (6,2)	PHAP3305E
MJTP1236F	.289 (7,3)	N/A
MJTP1236G	.230 (5,8)	N/A
	Bulk packag	ed.

US # MJTP1243 & MJTP1250








US # Model	Dim.	Dim.
No.	L1 (in./mm)	L (in./mm)
MJTP1243	.169 (4,3)	.307 (7,8)
MJTP1250	.197 (5,0)	.335 (8,5)

Bulk packaged.






US Model	Dim.		EU Model
No.	L (in	./mm)	No.
MJTP2205	.124	(3,15)	PHAP3306
MJTP2205A	.152	(3,85)	PHAP3306A
MJTP2205B	.329	(8,35)	PHAP3306B
MJTP2205C	.270	(6,85)	PHAP3306C
MJTP2205D	.466	(11,85)	PHAP3306D
MJTP2205E	.242	(6,15)	PHAP3306E


Bulk packaged.

US#MJTPSHW

Process compatible







US#Model	Dim.
No.	L (in./mm)
MJTPSHW	.122 (3,1)
MJTPSHWA	.091 (2,3)
MJTPSHWB	.146 (3,8)

Bulk packaged.


CAPS	(for MJTP1105T a	and MJTP1234 only)
------	------------------	--------------------


CAPS (for MJTP1193 only)

New!


CAP COLORS

MJ61 Square cap





MJ3 Square cap (w/clear lens in center for LED illumination)





Note - add digit from table to cap part number for color. Example - MJ612 indicates square black cap.


No.	Color
1	blue
2	black
3	green
5	yellow
6	red
7	ivory

SCHEMATICS

MJTP1109	MJTP1234
MJTP1119	MJTP2205
MJTP1193	MJTP4102

MJTP1230 MJTP5302 MJTP1232 **MJTPSHW**


Note: LED is for MJTP1193 only.





MJTP1105	MJTP1236
MJTP1117	MJTP1243
MJTP1129	MJTP1250
MJTP1141	MJTP2205
MJTP1144	MJTP4102
MJTP1145	MJTP5302


PRINTED CIRCUIT BOARD LAYOUTS


Layout tolerances; Linear: $\pm .004$ " (± 0.1 MM) Holes: $\pm .002$ " (± 0.05 MM)











MJTP1129


MJTP1105T


MJTP1109






MJTP1119











MJTP1243

MJTP1230




MJTP1232







MJTP1236



MJTP1250



MJTP1234



MJTP2205