

Supplementary Note 1 - NetID User Guide

Li Chen, Ziyang Chen

5/31/2021

A primary goal of liquid chromatography-high resolution mass spectrometry (LC-MS)-based metabolomics is to identify all metabolites, but most LC-MS peaks remain unidentified. Here, we present a global network optimization approach, NetID, to annotate untargeted LC-MS metabolomics data. We consider all experimentally observed ion peaks together, and assign annotations to all of them simultaneously so as to maximize a score that considers properties of peaks (known masses, retention times, MS/MS fragmentation patterns). Global optimization results in accurate peak assignment and trackable peak-peak relationships in the output network. Applying this approach to yeast and mouse data, we identify 5 novel metabolites, including thiamine and taurine derivatives. Isotope tracer studies indicate active flux through these metabolites. Thus, NetID applies existing metabolomic knowledge and global optimization to annotate untargeted metabolomics data, revealing novel metabolites. Citation: <https://www.biorxiv.org/content/10.1101/2021.01.06.425569v1>
Git-hub: <https://github.com/LiChenPU/NetID>

1 Environment Setup

This section provides step-by-step instructions to set up the environment to run NetID algorithm in a local computer. A Windows system is recommended. Typical install time on a “normal” desktop computer is within a few hours.

1.1 Software installation

- Install R, Rstudio, Rtools40, ILOG CPLEX Optimization Studio (CPLEX), preferably at default location.

R(4.0 or later): <https://www.r-project.org/>

RStudio: <https://rstudio.com/products/rstudio/download>

Rtools40: <https://cran.r-project.org/bin/windows/Rtools/ow>

CPLEX(12.8 or later): <https://www.ibm.com/academic/technology/data-science>

- You need to add R and Rtools40 to Environmental Variables PATH, with instruction provided at the end.

1.2 Code download

1.2.1 Via Git (recommended)

1. Install **git** via <https://support.rstudio.com/hc/en-us/articles/200532077?version=1.3.1093&mode=desktop>
2. In Rstudio, go to File → New project → Version control → Git, enter <https://github.com/LiChenPU/NetID.git> for URL, select a subdirectory, and create project.

Supplementary Note 1 - NetID User Guide

3. You should be able to see all files in place under your selected subdirectory. Use pull option to check for latest updates.

1.2.2 Via Github

1. Go to website <https://github.com/LiChenPU/NetID>, hit the green `code` button, select download zip, and unzip files.

1.3 Package dependency installation

Most of the dependent packages can be installed by running the R script `NetID_packages.R` in the `get` started folder. See **Troubleshooting** section for possible errors.

The package, **cplexAPI**, connecting R to CPLEX, requires additional installation steps.

1. Go to website: <https://cran.r-project.org/web/packages/cplexAPI/index.html>, look for `Package source`, and download `cplexAPI_1.4.0.tar.gz`. In the same page, look for `Materials`, and open the `INSTALL` link
2. Unzip the folder `cplexAPI` to the **desktop**, follow the installation guide to modify the file `Makevars.win`.

Note: Replace `\` in the `Makevars.win` file into `/` in order for R to recognize the path.

- For example, the `-I"${CPLX_STUDIO_DIR}\cplex\include"` should be replaced with path such as:
`-I"C:/Program Files/IBM/IOG/CPLEX_Studio1210/cplex/include"`
 - The `-L"${CPLX_STUDIO_LIB}"` should be replaced with path such as:
`-L"C:/Program Files/IBM/IOG/CPLEX_Studio1210/cplex/bin/x64_win64"`
3. In command line, run line below to build package, change `${Username}` to actual name.
`R CMD build --no-build-vignettes --no-manual --md5 "C:\Users\${Username}\Desktop\cplexAPI"`
a new package `cplexAPI_1.4.0.tar.gz` will be built under the default path (for example, `C:\Users\${Username}`)
 4. In command line, run line below to install package.
`R CMD INSTALL --build --no-multiarch .\cplexAPI_1.4.0.tar.gz`
If you see `DONE (cplexAPI)`, then the package installation is successful.
 - *Note:* if error occurs relating to `__declspec(dllimport deprecated)`, you need to go to `C:\Program Files\IBM\IOG\CPLEX_Studio1210\cplex\include\ilcplex` (or other installation path), open the file `cpxconst.h`, go to the line indicated in the error message or search for `__declspec(dllimport deprecated)`, add `_` to `__declspec(dllimport deprecated)`, making it to `__declspec(dllimport_deprecated)`. Save file and repeat *step 4*.
 5. To take a short venture using CPLEX in R, refer to **Package cplexAPI – Quick Start** in <https://cran.r-project.org/web/packages/cplexAPI/index.html>.

2 Using NetID

This section will use yeast negative-mode dataset and mouse liver negative-mode dataset as examples to walk through the NetID workflow.

- *Note 1: If other EI-MAVEN version was used, check the "raw_data.csv" for the column number where the first sample is located, and specify that in the NetID_run_script.R file. For example, In EI-MAVEN (version 7.0), first_sample_col_num is set at 15 as default. If EI-MAVEN (version 12.0) is used, first_sample_col_num should be set at 16.*
- *Note 2: for more advanced uses, scoring and other parameters can be edited in NetID_function.R and NetID_run_script.R. Read the manuscript method section for detailed explanation on parameters.*

2.1 Yeast negative-mode dataset

In the Sc_neg folder, file raw_data.csv is the output from **Elmaven** recording MS information, and is the input file for **NetID**. MS2 is not collected for this dataset.

2.1.1 Running the code

1. Open code folder → NetID_run_script.R
2. In the # Setting path ##### section, set work_dir as "../Sc_neg/".

```
# Setting path #####
{
  setwd(dirname(rstudioapi::getSourceEditorContext()$path))
  source("NetID_function.R")

  work_dir = "../Sc_neg/"
  setwd(work_dir)
  printtime = Sys.time()
}
```

3. In the # Read data and files ##### section, set filename as "raw_data.csv", set MS2_folder as "".
set ion_mode as -1 if negative ionization data is loaded, and 1 if positive ionization data loaded.

```
# Read data and files #####
{
  Mset = list()
  # Read in files
  Mset = read_files(filename = "raw_data.csv",
                    LC_method = "Hilic_25min_QE",
                    ion_mode = -1 # 1 for pos mode and -1 for neg mode
                    )
  Mset = read_MS2data(Mset,
                     MS2_folder = "") # MS2
}
```

4. Keep all other parameters as default, and run all lines.

2.1.2 Expected outputs

1. In the console, error message should not occur. If optimization step is successful, you will see messages in the following format.

```
"Optimization ended successfull - integer optimal, tolerance - OBJ_value = 2963.71
(bestobjective - bestinteger) / (1e-10 + |bestinteger|) = 0.000048268"
95.74 sec elapsed
```

2. Three files will be generated in the `Sc_neg` folder. Expected run time on a "normal" desktop computer should be within an hour.
 - `NetID_output.csv` contains the annotation information for each peak.
 - `NetID_output.RData` contains node, edge and network information. The file will be used for network visualization in Shiny R app.
 - `.RData` records the environmental information after running codes. The file is mainly used for development and debugging.

2.2 Your own dataset

2.2.1 MS1 dataset preparation

1. File conversion. Use software **ProteoWizard**40 (version 3.0.11392) to convert LC-MS raw data files (.raw) into mzXML format. A command line script specifies the conversion parameter. Assuming the raw data are in `D:/MS data/test`. Type in the scripts below.

```
D:
cd D:/MS data/test
"C:/Program Files/ProteoWizard/ProteoWizard 3.0.11392/msconvert.exe"
*.raw --filter "peakPicking true 1-" --simAsSpectra --srmAsSpectra --mzXML
```

If **ProteoWizard** is installed in location other than `C:/Program Files/ProteoWizard/ProteoWizard 3.0.11392/msconvert.exe`, specify your path to where you can find the `msconvert.exe` file. Expected outputs will be `.mzXML` files from `.raw` data.

2. **EI-MAVEN (version 7.0)** is used to generate a peak table containing m/z, retention time, intensity for peaks. Detailed guides for peak picking can be found in <https://elucidatainc.github.io/EIMaven/faq/>. After peak picking and a peak table tab has shown up, click `export to CSV`. Choose `export all groups`. In the pop-up saved window, choose format `Groups Summary Matrix` Format `Comma Delimited`. Save to the desired path.
3. Under the `NetID` folder, create a new folder `NetID_test`, copy the csv file from *step 2* into the folder, and change the filename into `raw_data.csv`.

2.2.2 MS2 dataset preparation

NetID currently utilizes targeted MS2 data for better MS2 quality, and will incorporate data-dependent MS2 data in the future.

1. Prepare MS2 inclusion list
For targeted MS2 analysis, from the peak list generated in *step 1*, select the peaks (m/z, RT) that you want to perform MS2, and arrange them into multiple csv files

Supplementary Note 1 - NetID User Guide

that will serve as the inclusion lists to set up the PRM method on **Thermo QExactive** instrument. Instruction can be found in https://proteomicsresource.washington.edu/docs/protocols05/PRM_QExactive.pdf.

Note: Arrange the parent ions so as to avoid to perform many PRMs at same time. An example is shown below with the start and End time set as RT-1.5 and RT+1.5 (min) to have good chromatogram coverage.

```
library(readr)
read_csv("example.csv")
##
## -- Column specification -----
## cols(
##   Mass = col_double(),
##   Formula = col_logical(),
##   Formula_type = col_logical(),
##   Species = col_logical(),
##   CS = col_logical(),
##   Polarity = col_character(),
##   Start = col_double(),
##   End = col_double(),
##   CE = col_double(),
##   CE_type = col_character(),
##   MSXID = col_logical(),
##   Comment = col_character()
## )
## # A tibble: 16 x 12
##   Mass Formula Formula_type Species CS Polarity Start End CE CE_type
##   <dbl> <lgl> <lgl> <lgl> <lgl> <chr> <dbl> <dbl> <dbl> <chr>
## 1 499. NA NA NA NA Negative 0.456 3.46 30 NCE
## 2 722. NA NA NA NA Negative 0.733 3.73 30 NCE
## 3 403. NA NA NA NA Negative 1.06 4.06 30 NCE
## 4 211. NA NA NA NA Negative 1.20 4.20 30 NCE
## 5 328. NA NA NA NA Negative 1.40 4.40 30 NCE
## 6 149. NA NA NA NA Negative 1.59 4.59 30 NCE
## 7 151. NA NA NA NA Negative 2.69 5.69 30 NCE
## 8 335. NA NA NA NA Negative 2.70 5.70 30 NCE
## 9 143. NA NA NA NA Negative 4.07 7.07 30 NCE
## 10 89.0 NA NA NA NA Negative 5.67 8.67 30 NCE
## 11 283. NA NA NA NA Negative 6.92 9.92 30 NCE
## 12 202. NA NA NA NA Negative 8.79 11.8 30 NCE
## 13 160. NA NA NA NA Negative 10.3 13.3 30 NCE
## 14 216. NA NA NA NA Negative 11.4 14.4 30 NCE
## 15 125. NA NA NA NA Negative 12.0 15.0 30 NCE
## 16 230. NA NA NA NA Negative 12.9 15.9 30 NCE
## # ... with 2 more variables: MSXID <lgl>, Comment <chr>
```

2. Instrument setup

Set up the **QExactive** instrument so that it contains both "Full MS" and "PRM" scan events. For PRM setup, use the above file as inclusion list to perform targeted MS2 analysis. We typically use the following setting for MS2 analysis: resolution 17500, AGC

Supplementary Note 1 - NetID User Guide

target 1e6, Maximum IT 500 ms, isolation window 1.5 m/z. For a total of 1500 parent ions and 15 parent ions for each method, it requires a total of 100 runs, or ~42 hours using a 25-min LC method.

3. MS2 file conversion.

RawConverter (version 1.2.0.1, <http://fields.scripps.edu/rawconv/>) is used to convert the `.raw` file into `.mzXML` file that contains MS2 information. Keep the default parameters except setting `Environment Type` as `Data Independent`, and `Output Formats` as `mzXML`.

4. MS2 reading and cleaning.

A matlab code is used for MS2 reading and cleaning, which can be found in **CodeOcean** as a published capsule (<https://codeocean.com/capsule/1048398/tree/v1>). The `csv` files from 1 paired with the MS2 data files in `mzXML` format from 3 are the required input data. Refer to capsule description and `readme.md` file for more details of how the code works. In Brief,

- Prepare filename. Filenames for both `csv` and `mzXML` files should be named as `prefixNNN`, where `prefix` is the given file name and `NNN` is the 3 digits number in continuous order (e.g. `M001.csv`, `M002.csv`,... and `M001.mzXML`, `M002.mzXML`,... in the `/data` folder).
- Duplicate the capsule to your own account so you can edit and use the capsule. Upload your own files and remove the previous files in `/data` folder.
- Specify the prefix and the range of numbers at the beginning section of the main code `Main_example.m`.
- Set the main code as file to run in Code Ocean using the dropdown menu next to main code.
- Click `reproducible run` to perform the batch processing.
- The resulting output files in `.xlsx` format with the same filenames will appear in the timeline. Each `xlsx` file contains multiple tabs of cleaned MS2 spectra. The names of the tabs correspond to the row numbers of the `csv` file specifying the individual parent peak information.

5. Save files to folders.

Back to the `NetID_test` folder, create a new folder `MS2`, download all `xlsx` files from 4 into the folder.

2.2.3 Running the code

1. Open code folder → `NetID_run_script.R`.
2. In the `# Setting path ####` section, set `work_dir` as `"../NetID_test/"`.
3. In the `# Read data and files ####` section,
set `filename` as `raw_data.csv`, set `MS2_folder` as `MS2`.
set `LC_method` to specify column to read for the retention time of known standards. (In folder `NetID` → `dependent` → `known_library.csv`, update the retention time info as needed.)
set `ion_mode` as `-1` if negative ionization data is loaded, and `1` if positive ionization data loaded.

Supplementary Note 1 - NetID User Guide

4. Keep all other parameters as default, and run all lines.

2.2.4 Expected outputs

Similar to the `demo` file, the console will print out message indicating optimization step is successful, and three files `NetID_output.csv`, `NetID_output.RData` and `.RData` will be generated in the `NetID_test` folder

2.3 Other Settings

2.3.1 Compound libraries

2.3.1.1 Other provided libraries NetID provides 4 libraries for the user to choose: **HMDB**, **YMDB**, **PubChem**, **PubChem Bio-pathway only**.

To select the desired database, change `HMDB_library_file = "../dependent/hmdb_library.csv"` to `../dependent/ymdb_library.csv`, `../dependent/pbcm_library.csv` or `../dependent/pbcm_library_bio.csv`.

```
Mset = read_files(filename = "raw_data.csv",
                  LC_method = "Hilic_25min_QE",
                  ion_mode = -1, # 1 for pos mode and -1 for neg mode
                  HMDB_library_file = "../dependent/hmdb_library.csv"
                  )
```

2.3.1.2 Design your own library

1. A workable library requires following columns.

```
read_csv("../..//dependent/hmdb_library.csv")
##
## -- Column specification -----
## cols(
##   accession = col_character(),
##   iupac_name = col_character(),
##   name = col_character(),
##   SMILES = col_character(),
##   status = col_character(),
##   formula = col_character(),
##   mass = col_double(),
##   rdbe = col_double(),
##   category = col_character()
## )
## # A tibble: 114,014 x 9
##   accession iupac_name      name SMILES      status formula  mass  rdbe category
##   <chr>      <chr>          <chr> <chr>      <chr>  <chr>  <dbl> <dbl> <chr>
## 1 HMDB000000~ (2S)-2-amino~ 1-Me~ CN1C=NC(~ quant~ C7H11N~ 169.    4 Metabol~
## 2 HMDB000000~ propane-1,3-d~ 1,3~ NCCCN      quant~ C3H10N2 74.1    0 Metabol~
## 3 HMDB000000~ 2-oxobutanoic~ 2-Ke~ CCC(=O)C~ quant~ C4H6O3 102.    2 Metabol~
## 4 HMDB000000~ 2-hydroxybuta~ 2-Hy~ CCC(O)C(~ quant~ C4H8O3 104.    1 Metabol~
## 5 HMDB000000~ (1S,10R,11S,1~ 2-Me~ [H][C@@]~ quant~ C19H24~ 300.    8 Metabol~
## 6 HMDB000000~ (3R)-3-hydrox~ (R)~ C[C@@H](~ quant~ C4H8O3 104.    1 Metabol~
```

Supplementary Note 1 - NetID User Guide

```
## 7 HMDB000000~ 1-[(2R,4S,5R)~ Deox~ OC[C@H]1~ quant~ C9H12N~ 228.      5 Metabol~
## 8 HMDB000000~ 4-amino-1-[(2~ Deox~ NC1=NC(=~ quant~ C9H13N~ 227.      5 Metabol~
## 9 HMDB000000~ (1S,2R,10R,11~ Cort~ [H][C@@]~ quant~ C21H30~ 346.      7 Metabol~
## 10 HMDB000000~ (1S,2R,10S,11~ Deox~ [H][C@@]~ quant~ C21H30~ 330.      7 Metabol~
## # ... with 114,004 more rows
```

2. To build your own library, make a csv file in the same format as the one shown above, and set `HMDB_library_file = "../dependent/hmdb_library.csv"` to your desired directory in `NetID_run_script.R`.

2.3.2 Modifying `empirical_rules.csv`

`empirical_rules.csv` can also be created or modified to support specific biotransformation. A workable `empirical_rules` requires following columns. * `name` and `note` is not necessary. * `category` includes: Biotransform, Natural_abundance, Adduct, Fragment and Radical * `rbde` is calculated using the `formula_rbde` function of the package `lc8` * `direction` states the possible direction of transformation: 1 means from larger mass to smaller mass; 0 means the opposite; -1 means both direction are possible.

```
read_csv("../..//dependent/empirical_rules.csv")
##
## -- Column specification -----
## cols(
##   category = col_character(),
##   name = col_character(),
##   formula = col_character(),
##   mass = col_double(),
##   direction = col_double(),
##   rdbe = col_double(),
##   note = col_character()
## )
## # A tibble: 84 x 7
##   category    name formula    mass direction  rdbe note
##   <chr>      <chr> <chr>      <dbl>      <dbl> <dbl> <chr>
## 1 Biotransform O-HN  O1N-1H-1  0.984        0      0 Deamination
## 2 Biotransform NH3-O N1H3O-1  1.03        0     -1 Transamination
## 3 Biotransform H2     H2       2.02        0     -1 Hydrogenation
## 4 Biotransform CH2    C1H2     14.0        0      0 Methylation
## 5 Biotransform NH     N1H1     15.0        0      0 Amination
## 6 Biotransform O      O1       16.0        0      0 Hydroxylation
## 7 Biotransform N1H3   N1H3     17.0        0     -1 Amination (+NH3)
## 8 Biotransform H2O    H2O1     18.0        0     -1 Hydration
## 9 Biotransform C0     C1O1     28.0        0      1 Formylation (+C0)
## 10 Biotransform C2H4  C2H4     28.0        0      0 Beta oxidation
## # ... with 74 more rows
```

2.3.3 Retention time list

2.3.3.1 Customize your own RT table

1. In the dependent folder, open the `known_library_customized.csv` file


```
read_csv("../..dependent/known_library_customized.csv")[1:5,]
##
## -- Column specification -----
## cols(
##   name = col_character(),
##   HMDB = col_character(),
##   formula = col_character(),
##   SMILES = col_character(),
##   Hilic_25min_QE = col_double(),
##   No_RT = col_logical()
## )
## # A tibble: 5 x 6
##   name          HMDB    formula    SMILES    Hilic_25min_QE No_RT
##   <chr>         <chr>    <chr>    <chr>    <dbl> <lgl>
## 1 1-Methyl imidazolacetic~ HMDB000~ C6H8N2O2 CN1C=C(N=C1~    9.05 NA
## 2 5-L-Hydroxytryptophan <NA>    C11H12N2O3 <NA>    10.2 NA
## 3 ADP          <NA>    C10H15N5O~ <NA>    13.9 NA
## 4 CDP          <NA>    C9H15N3O1~ <NA>    NA NA
## 5 CDP-choline <NA>    C14H26N4O~ <NA>    NA NA
```

2. Column Name, formula are required. Column HMDB, SMILES are optional. For each RT list (e.g. Hilic_25min_QE), record the retention time under the column. Multiple RT lists can be stored by adding additional columns. Empty retention time is allowed for a entry.

2.3.3.2 Skip RT table Setting the LC_method = "No_RT". Then RT information will not be considered in the algorithm.

```
Mset = read_files(filename = "raw_data.csv",
                  LC_method = "No_RT",
                  ion_mode = -1, # 1 for pos mode and -1 for neg mode
                  HMDB_library_file = "../dependent/hmdb_library.csv"
                  )
```

2.3.4 Score Setting

See Supplementary Note 2 of NetID paper for explanation of how scores work

3 NetID Visualization

This section provides instruction to visualize and explore **NetID** output results in either **Cytoscape** software or interactive **Shiny R app**. After running **NetID** algorithm, it will export one .R and two .csvfiles (cyto_node.csv and cyto_edges.csv), storing the nodes and edges of the output network.

3.1 Cytoscape

0. What is **Cytoscape** For more info regarding what is **Cytoscape**, check https://cytoscape.org/what_is_cytoscape.html.

Supplementary Note 1 - NetID User Guide

1. install **Cytoscape** Download **Cytoscape** (<https://cytoscape.org/download.html>) and follow installation instruction to install onto your computer.
2. Load the example **NetID** output into **Cytoscape**
 - Run **Cytoscape**, click `import network from file system`, and load `cyto_edges.csv`, set `edge_id` column as the key, set `node1` as source node, set `node2` column as target node, and the rest columns as edge attribute.
 - Click `import table from file`, load `cyto_node.csv`, set `node_id` column as the key, and the rest columns as node attribute.
 - Select `subnetwork`, set `styles`, and explore the network with various functionalities inside **Cytoscape**.
3. Explore in Cytoscape
<http://manual.cytoscape.org/en/stable/index.html> provides all you need to know about exploring in **Cytoscape**. (This writer knew little about this cool software, so all he could give was this link and *may the Force be with you.*)
4. Export
The network as well as the curated subnetworks can be exported for future analysis or sharing with others. An example network file `example.cys` is included along with the two `.csv` files, which is created using **Cytoscape** version 3.8.2

3.2 Shiny App

This part provides instruction to visualize and explore **NetID** output results in the interactive **Shiny R app**. A 21-inch or larger screen is recommended for best visualization.

3.2.1 Runing Shiny App

1. Open code folder → `R_shiny_App.R`.
2. In the `# Read in files ####` section, set datapath as `../Sc_neg/`
3. Keep all other parameters as default, and run all lines.
4. A Shiny app will pop up.

3.2.2 Searching peaks of interest

1. On the left panel, you can enter a m/z or a formula to search your peak of interest. For example, 180.0631 or C₆H₁₂O₆ will automatically update the data table on the right. Enter 0 to restore full list for the data table.
2. Change ionization and ppm window to adjust calculated m/z . W
3. On the right, you can explore the peak list in an interactive data table, including global text search on top right, specifying ranges for numeric column or searching text within character columns, ranking each column etc.

The screenshot displays the Shiny R app interface. On the left, there are three input fields: 'Enter a m/z or formula of interest' (containing 'C6H12O6'), 'Select ionization' (a dropdown menu with 'M' selected), and 'ppm' (a text input with '3'). On the right, there is a data table with columns: peak_id, medMz, medRt, log10_inten, class, formula, and ppm_error. The table shows one entry for peak_id 5587. Above the table is a search bar and a 'Show 5 entries' dropdown. Below the table are filters for each column, all set to 'All'. At the bottom, it says 'Showing 1 to 1 of 1 entries' with 'Previous' and 'Next' buttons.


peak_id	medMz	medRt	log10_inten	class	formula	ppm_error
5587	180.0631	13.61	5.3	Metabolite	C6H12O6	1.6

3.2.3 Network Visualization

1. Peak ID, formula and class determines the center node for the network graph. Peak ID will be automatically updated by the first line in the data table if a m/z or formula is given. Alternatively, you can manually enter Peak ID.
2. The degree parameter controls how far the network expands from the center node. Degree 1 means only nodes directly connected to the center node will be shown and degree 2 means nodes connected to degree 1 will be shown, etc.
3. Biochemical graph shows biochemical connections. Abiotic graph shows abiotic connections. Node labels and Edge labels determines if the graph show node or edge labels. Optimized only determines whether to show only the optimal annotations or all possible annotations in the network.
4. When setting parameters, hit plot to see the network graph.

The screenshot shows a web interface for setting network visualization parameters. It includes dropdown menus for Peak ID (5587), Formula (C6H12O6), and Class (Metabolite). A Degree input field is set to 1. Checkboxes for Biochemical graph, Node labels, Edge labels, and Optimized only are checked, while Abiotic graph is unchecked. A large blue 'Plot' button is on the right.

5. A sample network graph is shown below (a different center node may give less complicated graph). You may edit the nodes or edges (top left), move figures with the arrow buttons (bottom left), and zoom in/out or center figure (bottom right).




6. You can use the “Download plot” button to download a html webpage to visualize the network graph independent of the Shiny app, and the “Download csv” button to download the information of the nodes in the network. The download buttons will appear after hitting the plot button. Note: edits within the Shiny app will not go into the html file.

3.2.4 Possible structures exploration

A figure + data table is provided to explore structures of the selected node in the network graph.

1. The figure shows the chemical structure of the annotated metabolites. If the node is annotated as a putative metabolite, only the known parts of the putative metabolite will be shown.
Scroll left or right, or select the entry number, to visualize different annotations. Right click and select to save image.
2. In the data table, class has 3 possible entries: Metabolite if it is documented in database such as HMDB library; Putative metabolite if it is transformed from a metabolite through a biotransformation edge; and Artifact if it is transformed by an abiotic edge.
Use the download button to download the data table

a



D-Glucose C6H12O6

<- 1 -> Download csv

b

Show 10 entries Search:

	class	annotation	origin	note
1	Metabolite	D-Glucose C6H12O6	HMDB_library	HMDB0000122
2	Metabolite	D-Galactose C6H12O6	HMDB_library	HMDB0000143
3	Metabolite	D-Mannose C6H12O6	HMDB_library	HMDB0000169
4	Metabolite	myo-Inositol C6H12O6	HMDB_library	HMDB0000211
5	Metabolite	3-Deoxyarabinohexonic acid C6H12O6	HMDB_library	HMDB0000346

4 Troubleshooting

4.1 Failing to install package `lc8`

Reinstall the packages `devtools` and `digest`.

4.2 Cannot find `cplexAPI` even if the installation seems successful

Check **R** version used in **RStudio** to see if `cplexAPI` is installed under the same R version library. Which R library `cplexAPI` goes to depends on the R path specified in `Environment Variables`.

4.3 Add **R** to `PATH`

- Go to Environment Variables:
 search `PATH` in windows → open edit Environment Variables → Environment Variables or
 control panel → system and security → System → Advanced system Settings (on your left) → Advanced → Environment Variables

Supplementary Note 1 - NetID User Guide

2. In the lower Panel select the `Path Variable` and select `Edit`, add the R path (`C:\Program Files\R\R-4.0.3\bin\x64`, if installed at default location) to the `Path Variable`.
3. You may need to restart computer for the R path to take effect.

4.4 Add Rtools40 to PATH

1. Add the path `C:\Rtools\bin` to the `Path Variable` in `Environment Variables`
2. Run the line in **R**:

```
writelnLines('PATH="{RT00LS40_HOME}\\usr\\bin;${PATH}"', con = "~/.Renvi  
ron")
```

Use the line below in R console to check for successfully adding Rtools40

```
Sys.which("make")
```

Expected output: `## "C:\\rtools40\\usr\\bin\\make.exe`