

# Gesture Alignment Using Hidden Markov Models

Andrew Hershberger   Salman Ahmad  
{andrew.hershberger, saahmad}@cs.stanford.edu

Stanford University  
CS228: Probabilistic Graphical Methods - Winter 2011

## Abstract

SALMAN:

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

## 1 Introduction

SALMAN:

Kinect, data, problem setup, main goal (align gestures, why this is necessary for classification).

## 2 Related Work

ANDREW:

Dynamic Time Warping [Listgarten *et al.*, 2005]  
Learning Control [Coates *et al.*, 2008]  
Probabilistic Graphical Models: Principles and Techniques [Koller and Friedman, 2009]  
Dynamic Bayesian Networks: Representation, Inference and Learning [Murphy, 2002]  
Hidden Conditional Random Fields for Gesture Recognition [Wang *et al.*, 2006]

## 3 Graphical Model

SALMAN:

images of the model before and after dynamic programming approach to DTW  
It's an alignment HMM

## 4 Algorithm

ANDREW:

What we did: EM, DTW  
Optimizing the algorithm when calculating  $q(:, :)$ ,  $\tau$ ;  
Different smoothing  
no prior knowledge of optimal trajectory  
not using a bias function  
Tried different allowed step sizes for  $d$

## 5 Results

SALMAN:

Figures, writeup (we are geniuses).

## 6 Discussion and Future Work

ANDREW:

Why didn't it work very well? Smoothing made things worse.

Use different smoothing

Add prior knowledge of optimal trajectory: can incorporate effects of gravity - don't want things to hang in mid air.

Application to classification problem

Add more data (training data)

Add features to detect particular aspects of gestures.

Detect orientation differences

## 7 Conclusion

SALMAN:

## References

- [Coates *et al.*, 2008] Adam Coates, Pieter Abbeel, and Andrew Y. Ng. Learning for control from multiple demonstrations. In *Proceedings of the 25th international conference on Machine learning*, ICML '08, pages 144–151, New York, NY, USA, 2008. ACM.
- [Koller and Friedman, 2009] D. Koller and N. Friedman. *Probabilistic Graphical Models: Principles and Techniques*. MIT Press, 2009.
- [Listgarten *et al.*, 2005] Jennifer Listgarten, Radford M. Neal, Sam T. Roweis, and Andrew Emili. Multiple alignment of continuous time series. In *Advances in Neural Information Processing Systems*, pages 817–824. MIT Press, 2005.
- [Murphy, 2002] Kevin Patrick Murphy. Dynamic bayesian networks: Representation, inference and learning, 2002.
- [Wang *et al.*, 2006] Sy Bor Wang, A. Quattoni, L.-P. Morency, D. Demirdjian, and T. Darrell. Hidden conditional random fields for gesture recognition. In *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on*, volume 2, pages 1521 – 1527, 2006.