Reverse a doubly linked list

224 more points to get your next star!

Rank: 873831 | Points: 251/475

Problem Solving

Your Reverse a doubly linked list submission got 5.00 points. Share Post

You are now 224 points away from the 4th star for your problem solving badge.

Try the next challenge

Problem Submissions Leaderboard Editorial

This challenge is part of a tutorial track by MyCodeSchool

Given the pointer to the head node of a doubly linked list, reverse the order of the nodes in place. That is, change the next and prev pointers of the nodes so that the direction of the list is reversed. Return a reference to the head node of the reversed list.

Note: The head node might be NULL to indicate that the list is empty.

Function Description

Complete the reverse function in the editor below.

reverse has the following parameter(s):

- DoublyLinkedListNode head: a reference to the head of a DoublyLinkedList

Returns

- DoublyLinkedListNode: a reference to the head of the reversed list

Input Format

The first line contains an integer t, the number of test cases.

Each test case is of the following format:

- The first line contains an integer n, the number of elements in the linked list.
- The next n lines contain an integer each denoting an element of the linked list.

Constraints

- $1 \leq t \leq 10$
- $0 \leq n \leq 1000$
- $0 \leq DoublyLinkedListNode.data \leq 1000$

Output Format

Return a reference to the head of your reversed list. The provided code will print the reverse array as a one line of space-separated integers for each test case.

Sample Input

```
1
4
1
2
3
4
```

Sample Output

```
4 3 2 1
```

Explanation

The initial doubly linked list is: $\mathbf{1} \leftrightarrow \mathbf{2} \leftrightarrow \mathbf{3} \leftrightarrow \mathbf{4} \rightarrow \boldsymbol{NULL}$

The reversed doubly linked list is: $\mathbf{4} \leftrightarrow \mathbf{3} \leftrightarrow \mathbf{2} \leftrightarrow \mathbf{1} \rightarrow \boldsymbol{NULL}$

Change Theme Language Python 3

```
#!/bin/python3…

#
# Complete the 'reverse' function below.
#
# The function is expected to return an INTEGER_DOUBLY_LINKED_LIST.
# The function accepts INTEGER_DOUBLY_LINKED_LIST llist as parameter.
#

#
# For your reference:
#
# DoublyLinkedListNode:
#     int data
#     DoublyLinkedListNode next
#     DoublyLinkedListNode prev
#
#

def reverse(llist):
    # Write your code here
    if llist is None:
        return

    cur = llist
    head = cur.prev
    while cur:
        cur.next, cur.prev = cur.prev, cur.next
        head = cur
        cur = cur.prev
    return head
if __name__ == '__main__':…
```

EMACS Line: 1 Col: 1

Upload Code as File Test against custom input Run Code Submit Code

You have earned 5.00 points!

You are now 224 points away from the 4th star for your problem solving badge.

19% 251/475

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge

- Test case 0
- Test case 1
- Test case 2
- Test case 3
- Test case 4
- Test case 5
- Test case 6

Compiler Message

```
Success
```

Input (stdin) Download

```
1
4
1
2
3
4
```

Expected Output Download

```
4 3 2 1
```