# Runguo Li

M.S. Student, University of Illinois Urbana-Champaign | Champaign, IL, USA
runguo.ai@gmail.com | runguol2@illinois.edu | runguoli.com | github.com/LiRunGuo | Google Scholar

## Research Interests

**Machine learning systems for large models**: efficient long-context LLM inference (sparse attention, KV-cache compression, quantization), systems for LLM agents, distributed training and RL post-training infrastructure, and the correctness of ML compilers and GPU kernels.

## Education

**University of Illinois Urbana-Champaign (UIUC)** — Aug 2026 – Present
*M.S. in Information Management (expected Jul 2028)* — Urbana-Champaign, IL, USA

**Shanghai University of Finance and Economics (SUFE)** — Sep 2022 – Jun 2026
*B.S. in Business Analytics, GPA: 3.71/4.0* — Shanghai, China

## Publications and Preprints

(* equal contribution)

[1] **Runguo Li**. **Certified Sparse Attention via Perturbed Retrieval**. *arXiv preprint arXiv:2610.24991, 2026.* [arXiv] [PDF]
Sparse attention with per-head error certificates; 4.6–7.9× lower tail error than the best of 15 baseline families at 16K–128K tokens.

[2] **Runguo Li**. **Spend Bytes on Breadth: Precision–Count Trade-offs for Decode-Time KV Compression in Long Chain-of-Thought Reasoning**. *arXiv preprint arXiv:2610.05685, 2026.* [arXiv] [PDF]
Splits a fixed KV byte budget between token count and precision; beats eviction alone in 17 of 18 settings.

[3] **Runguo Li**. **How Much Does Random Rotation Help GPTQ? Sharp Worst-Case Rate Gaps in the High-Rate Regime**. *Under review, 2026; arXiv:2611.01669.* [arXiv] [PDF]
Sharp worst-case rate gap between randomly rotated GPTQ and WaterSIC, answering an open question.

[4] **Runguo Li**. **AXR: Reusing Intermediate Results for LLM Agents in PostgreSQL**. *Under review, 2026.* [PDF]
PostgreSQL extension that reuses plan-subtree results across agent attempts; 6.5–51.0% less database time.

[5] Zhi Yang*, **Runguo Li***, et al. **FinVault: Benchmarking Financial Agent Safety in Execution-Grounded Environments**. *Under review, 2026; arXiv:2601.07853.* [arXiv] [Code]
Execution-grounded safety benchmark for financial agents (31 sandbox scenarios, 963 test cases).

[6] Yeheng Chen*, **Runguo Li***, et al. **VeriBRT: Plan-Guided, Evidence-Based Automated Bug Reproduction**. *Under review, 2026.* [PDF]
Plan-guided bug-reproducing test generation; 341 of 433 issues on SWT-Bench Verified.

[7] Yutao Hou*, **Runguo Li***, et al. **Reasoning-Visual Critical Token Fine-Tuning for Multimodal Reasoning**. *Under review, 2026.* [PDF]
Supervises only reasoning-relevant and visually sensitive chain-of-thought tokens.

[8] **Runguo Li**. **Interrupt Budgets for Pre-Execution AI Control Monitors**. *Under review, 2026.* [PDF]
Per-step 1% threshold interrupts 14–37% of benign LinuxArena runs; trajectory-level budgets reduce attack catch rate from 0.79 to 0.59 at 5%.

[9] **Runguo Li**. **Trust but Verify: Diagnosing Causal Prior-Data Fitted Networks and Testing When to Defer**. *Under review, 2026.* [PDF]
Diagnostics for three causal PFNs plus a retraining-free, region-wise deferral wrapper with a paired doubly robust test.

## Research Experience

**University of Illinois Urbana-Champaign** — Aug 2026 – Present
*Research Intern, advised by Prof. Minjia Zhang* — Urbana-Champaign, IL, USA

- Efficient long-context inference: certified sparse attention [1] and decode-time KV-cache compression for long chain-of-thought reasoning [2].

**Shanghai Jiao Tong University** — Mar 2026 – Jul 2026
*Research Intern, advised by Prof. Xiaodong Gu* — Shanghai, China

- LLMs for code: co-first author of **VeriBRT** [6] on automated bug reproduction; built the SWT-Bench Verified evaluation harness.

**Tencent Youtu AI Lab** Oct 2025 – May 2026
*Research Intern* Shanghai, China

- Co-first author of **RVCFT** [7] on multimodal chain-of-thought fine-tuning; adversarial data synthesis and multilingual content-safety moderation.

## Open-Source Contributions

22 public merged pull requests across 14 upstream projects (private repositories excluded; project names link to merged PRs):

*Inference and serving*

- **vLLM-Omni**: block-sparse attention in the Qwen2.5-Omni Token2Wav DiT, 3.5–6.4× lower per-request latency on H200 (#7975, #7959).
- **vLLM**: fixed int4 per-token-head KV-cache quantization for non-power-of-two head sizes (#56198).
- **SGLang**: stopped DeepEP import-time failures from crashing servers that never use DeepEP (#40671).
- **FlashInfer**: normalized strided attention-plan metadata before planning and kernel use, preventing illegal memory access and wrong output across ragged, paged, and block-sparse backends (#5385).

*Distributed training and post-training*

- **Megatron-LM**: 165× faster MoE state-dict conversion and 3.4× shorter blocking async save on 8×H200 (#7287).
- **DeepSpeed**: fixed a ZeRO-3 rollout deadlock and unsafe Hybrid Engine policy injection (#8264, #8265).

*Compilers and kernels*

- **FlashAttention**: block-sparse tiling and causal-mask skipping in the SM90 forward kernel (#2903, #2904).
- **Triton**: a nested-loop fusion miscompile (#11521) and fp64 atomic exchange on AMD GPUs (#11904).
- **LLVM**: ValueTracking inference for $x \neq y$ (#225200) and an Attributor crash fix (#225290).

**Also**: colibri (MoE expert streaming), JAX (batched `jax.scipy.linalg.lu`), Apache TVM (ONNX Hardmax with symbolic shapes), LMCache (allocator free-list corruption), and verl (FSDP critic loading).

## Honors and Awards

National Encouragement Scholarship | People's Scholarship | Shanghai Municipal Scholarship
Social Practice Scholarship

## Skills

Python, C, CUDA, Triton, SQL; PyTorch, JAX, vLLM, SGLang, DeepSpeed, Megatron-LM, MLIR, LLVM; NVIDIA and AMD GPUs.