

3D Object Detection of 9-million LiDAR Point Cloud Using Semi-Supervised Machine Learning

Siamak Rabienia



The Data Incubator

A Pragmatic Institute Company

Spring 2020




Problem Definition

Objective: Reconstruct the 3D objects in a local neighborhood with minimum dimension

Motivation: Minimize the Misclassification


Applications:

- **Autonomous Driving**
(LYCMU, CVPR '19), (CKZBMFU, NIPS '15), (FDU, NIPS '12)
- **Digital Photogrammetry**
(HH, ISPRS '18)
- **Forestry & Vegetation**
(DMS, CVPR '12)



Data Collection & Preparation

- The dataset are acquired by HDL-32E
 - ± 2 cm accuracy
 - 32 Channels
 - 80m-100m Range
 - 700,000 Points per Second
 - 360° Horizontal FOV
 - $+10^\circ$ to -30° Vertical FOV
- The dataset has been labeled
- **Metric:** Misclassification Rate




9-Million LiDAR Point cloud

Northwestern Ave West Lafayette
(Length: 300 m)





Method




Dynamic PCA

- Local Point Density (LPD)
- Local Point Spacing (LPS)
- Update the radius of Search




Result

Top View




Side View




Original Data

Top View




Side View




Fix PCA 70-NN

Result

Top View




Side View




LAS Tool

Top View



Side View



Dynamic PCA

Misclassification

Misclassification Rate: $\frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i)$

