

Algorithms for Decision Support


Online Algorithms (3/3)

Bin Packing and Paging


Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**


Research cycle of online algorithms




Research cycle of online algorithms



Research cycle of online algorithms




Research cycle of online algorithms




Online Bin Packing Problem

- There are infinite number of **capacity-1** *bins*




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$





Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity



Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity





Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity



Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity (we may need to *open* a new bin)




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity (we may need to *open* a new bin)




Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity (we may need to *open* a new bin)



Online Bin Packing Problem

- There are infinite number of capacity-1 *bins*
- The *items* i arrive online, each with *size* r_i between $(0,1]$
- Once an item arrives, we have to put it into a bin without exceeding the bin capacity (we may need to *open* a new bin)
- The objective is to **put all items in a minimum number of bins**



Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**

FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in

FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in




FirstFit Algorithm

FirstFit:

Once an item arrives:

Scan through all (opened) bins and put it into the first bin that can accommodate it

If there is no such a bin, open a new bin and put it in



Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$


<Proof idea>

- Observation: There is at most one bin at least *half empty*

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>


- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>


- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)




Prove by contradiction: Assume that there are two bins with size less than $1/2$

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)




Prove by contradiction: Assume that there are two bins with size less than $1/2$

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)




Prove by contradiction: Assume that there are two bins with size less than $1/2$

According to the FirstFit algorithm,
the items in the second bin can be put in the first (half-empty) bin

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>


- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**.



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . There is at most one bin B_j such that $s_j \leq 1/2$)
- Let k be the number of bins opened by **FirstFit**. Total size of all items $\geq (k - 1) \cdot \frac{1}{2}$





$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items $\geq (k - 1) \cdot \frac{1}{2}$**

Even when the optimal algorithm has superpower to cut the items, it needs **Total size** of bins to accommodate all the items





$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items** $\geq (k - 1) \cdot \frac{1}{2}$
- **OPT** $\geq (\text{total size of all items})/1$



Even when the optimal algorithm has superpower to cut the items, it needs **Total size** of bins to accommodate all the items



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>


- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items** $\geq (k - 1) \cdot \frac{1}{2}$
- **OPT** $\geq (\text{total size of all items})/1 \geq (k - 1)/2$



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>



- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items** $\geq (k - 1) \cdot \frac{1}{2}$
- **OPT** $\geq (\text{total size of all items})/1 \geq (k - 1)/2 \iff \text{FirstFit} = k \leq 2 \cdot \text{OPT} + 1$



$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items** $\geq (k - 1) \cdot \frac{1}{2}$
- **OPT** $\geq (\text{total size of all items})/1 \geq (k - 1)/2 \iff \text{FirstFit} = k \leq 2 \cdot \text{OPT} + 1$





Even when the optimal algorithm has superpower to cut the items,
 it needs Total size of bins to accommodate all the items

$$\text{FirstFit} \leq 2 \cdot \text{OPT} + 1$$

<Proof idea>

- Observation: There is at most one bin at least *half empty* (that is, let s_j be the total size of the items in bin B_j . **There is at most one bin B_j such that $s_j \leq 1/2$**)
- Let k be the number of bins opened by **FirstFit**. **Total size of all items** $\geq (k - 1) \cdot \frac{1}{2}$
- **OPT** $\geq (\text{total size of all items})/1 \geq (k - 1)/2 \iff \text{FirstFit} = k \leq 2 \cdot \text{OPT} + 1$



What Happened

- To analyze the competitive ratio of FirstFit, we assume that it takes k bins
- By the property of FirstFit, at most one bin is half-empty
 - The total size of all items is bounded by below, so is the number of bins optimal solution needs


Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**

FirstFit is at least 1.667-competitive

- Consider a sequence of requests


- 6k items, each with size $\frac{1}{6} - 2\epsilon$



FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$



FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$



FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$
 - 6k items, each with size $\frac{1}{2} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$

- 6k items, each with size $\frac{1}{3} + \epsilon$

- 6k items, each with size $\frac{1}{2} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$

- 6k items, each with size $\frac{1}{3} + \epsilon$

- 6k items, each with size $\frac{1}{2} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$

- 6k items, each with size $\frac{1}{3} + \epsilon$


- 6k items, each with size $\frac{1}{2} + \epsilon$



OPT = 6k

FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$


FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$
 - 6k items, each with size $\frac{1}{2} + \epsilon$



FirstFit is at least 1.667-competitive

- Consider a sequence of requests
 - 6k items, each with size $\frac{1}{6} - 2\epsilon$
 - 6k items, each with size $\frac{1}{3} + \epsilon$
 - 6k items, each with size $\frac{1}{2} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$

- 6k items, each with size $\frac{1}{3} + \epsilon$

- 6k items, each with size $\frac{1}{2} + \epsilon$




FirstFit is at least 1.667-competitive

- Consider a sequence of requests

- 6k items, each with size $\frac{1}{6} - 2\epsilon$

- 6k items, each with size $\frac{1}{3} + \epsilon$

- 6k items, each with size $\frac{1}{2} + \epsilon$



$$\frac{\text{FirstFit}}{\text{OPT}} = \frac{10}{6} = 1.667$$

Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**

Any deterministic online algorithm
is at least 1.333-competitive

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea>

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3 - \epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3 - \epsilon)$ -competitive for the whole instance.

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea>

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$
$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \uparrow$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2}$$


$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \uparrow$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$
$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m$ 

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$


$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \uparrow$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$$= a_1 + a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$



Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$

$$\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon$$

m

↑

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$


$$= a_1 + a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

There are m items



Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:


$$\text{OPT}(I) = \frac{m}{2}$$
$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \uparrow$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$
$$= a_1 + a_2 = m - a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$



Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2}$$
$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \uparrow$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$
$$= a_1 + a_2 = m - a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$$= a_1 + a_2 = m - a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$


$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x$$



Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$


$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$



Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m$$

$\text{OPT}(I) = \frac{m}{2}$

$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$

$= a_1 + a_2 = m - a_2$

a_1 : #bins with 1 item in $\text{ALG}(I)$
 a_2 : #bins with 2 items in $\text{ALG}(I)$
 $m = a_1 + 2a_2$

$\text{OPT}(I+I) = m$

$\text{ALG}(I+I) = \underbrace{a_1 + a_2 + x}_{\geq a_2 + m} \geq a_2 + m$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{OPT}(I) = \frac{m}{2}$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$$= a_1 + a_2 = m - a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I)$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{OPT}(I) = \frac{m}{2}$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$$= a_1 + a_2 = m - a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

$$a_2 < \frac{m}{3}$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{OPT}(I) = \frac{m}{2}$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

$$a_2 < \frac{m}{3} \iff \text{ALG}(I) = m - a_2 > \frac{2}{3} \cdot m$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{OPT}(I) = \frac{m}{2}$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

$$a_2 < \frac{m}{3} \iff \text{ALG}(I) = m - a_2 > \frac{2}{3} \cdot m$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m, \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\text{OPT}(I) = \frac{m}{2}$$

$$\text{ALG}(I) < \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m$$

$$= a_1 + a_2 = m - a_2$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

Contradiction!

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

$$a_2 < \frac{m}{3} \iff \text{ALG}(I) = m - a_2 > \frac{2}{3} \cdot m$$

Any deterministic online algorithm is at least 1.333-competitive

<Proof idea> Assume ALG is $(4/3-\epsilon)$ -competitive

Prove by contradiction: design an instance such that any algorithm ALG that is $(4/3-\epsilon)$ -competitive for the first half of the instance, it cannot be $(4/3-\epsilon)$ -competitive for the whole instance. Consider the adversarial input:

$$\text{OPT}(I) = \frac{m}{2} \quad \underbrace{\frac{1}{2} - \epsilon, \frac{1}{2} - \epsilon, \dots, \frac{1}{2} - \epsilon}_m \quad \underbrace{\frac{1}{2} + \epsilon, \frac{1}{2} + \epsilon, \dots, \frac{1}{2} + \epsilon}_m \quad \uparrow \quad \text{OPT}(I+I) = m$$

$$\begin{aligned} \text{ALG}(I) &< \frac{4}{3} \cdot \frac{m}{2} = \frac{2}{3} \cdot m \\ &= a_1 + a_2 = m - a_2 \end{aligned}$$

a_1 : #bins with 1 item in $\text{ALG}(I)$

a_2 : #bins with 2 items in $\text{ALG}(I)$

$$m = a_1 + 2a_2$$

$$\text{ALG}(I+I) = a_1 + a_2 + x \geq a_2 + m$$

$$\text{ALG}(I+I) < \frac{4}{3} \cdot \text{OPT}(I+I) = \frac{4}{3} \cdot m$$

$$a_2 < \frac{m}{3} \iff \text{ALG}(I) = m - a_2 > \frac{2}{3} \cdot m \quad \square$$


Outline

- **Bin Packing** problem
 - Assume that we know the **ALG** cost
- **Paging** problem
 - We know very little about the **ALG** or the **OPT**

Paging


Paging

- In computer systems, the memory system is two-level
 - Data (in blocks) are stored in the **memory**, which cannot be accessed directly
 - A block of data is called a page
 - The **cache** can be accessed directly and is fast, but very small



Paging

- In computer systems, the memory system is two-level
 - Data (in blocks) are stored in the **memory**, which cannot be accessed directly
 - A block of data is called a **page**
 - The **cache** can be accessed directly and is fast, but very small





Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache


Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache





Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache



Request page 2


Cache



Memory


Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache





Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache



Request page 2


Cache



Memory


Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache




Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache




Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache
 - If the cache is full, one of the pages in the cache has to be evicted




Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache
 - If the cache is full, one of the pages in the cache has to be evicted




Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache
 - If the cache is full, one of the pages in the cache has to be evicted




Paging

- When the processor needs a page p_i ...
 - If p_i is in the cache (called a **hit**), the system needs not do anything
 - If p_i is not in the cache (a **miss**), the system incurs one **page fault** and must copy the page p_i from the slow memory to the fast cache
 - If the cache is full, one of the pages in the cache has to be evicted



Paging

- Given a sequence of n requests of pages r_1, r_2, \dots, r_n , revealed one by one
 - Set of pages = $\{1, 2, 3, \dots, n\}$
- With a size- k cache, the algorithm has to serve all the requests with a minimum number of page faults
 - Choose which page to evict wisely



Paging Algorithms


- LIFO (Last-In-First-Out)
- FIFO (First-In-First-Out)
- LFU (Least-Frequently-Used)
- LRU (Least-Recently-Used)
- CLOCK (CLOCK-replacement)
- LFD (Longest-Forward-Distance)

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)




LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)




LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)




LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)




LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Page fault

Cache




Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)





1, 3



Page fault

Cache




Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache



Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache



Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache



Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed



Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5



Cache



Memory

LFU (Least-Frequently-Used)



LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:


Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:


Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2

Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed



Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2, 1



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed


Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2, 1



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:

Every page has a **counter** that keep the number of times it has been accessed


Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2, 1, 1



Cache




Memory

LFU (Least-Frequently-Used)

LFU (Least-Frequently-Used) algorithm:



Every page has a **counter** that keep the number of times it has been accessed

Once a page fault is incurred, evict the one with the lowest counter value (break tie arbitrarily)



1, 3, 3, 3, 5, 4, 3, 3, 3, 5, 2, 1, 1, 3

Cache



Memory

LFU competitive ratio is unbounded

LFU competitive ratio is unbounded



- Consider the sequence of requests:

$\underbrace{1, 1, \dots, 1}_{m \times 1's}, \underbrace{2, 2, \dots, 2}_{m \times 2's}, \underbrace{3, 3, \dots, 3}_{m \times 3's}, \dots, \underbrace{k-1, k-1, \dots, k-1}_{m \times k-1's}, \underbrace{k, k+1, k, k+1, \dots, k, k+1}_{m \times (k, k+1)'s}$

LFU competitive ratio is unbounded

- Consider the sequence of requests:

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$
 $m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





LFU competitive ratio is unbounded

- Consider the sequence of requests:

↓

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$

$m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





LFU competitive ratio is unbounded

- Consider the sequence of requests:

↓

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$

$m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





LFU competitive ratio is unbounded

- Consider the sequence of requests:

↓

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$

$m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





LFU competitive ratio is unbounded

- Consider the sequence of requests:

↓

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$

$m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





LFU competitive ratio is unbounded

- Consider the sequence of requests:


↓



$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$
 $m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$



LFU competitive ratio is unbounded

- Consider the sequence of requests:


 $1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$
 $m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$




LFU competitive ratio is unbounded

- Consider the sequence of requests:


↓

$1, 1, \dots, 1, 2, 2, \dots, 2, 3, 3, \dots, 3, \dots, k-1, k-1, \dots, k-1, k, k+1, k, k+1, \dots, k, k+1$

$m \times 1's \quad m \times 2's \quad m \times 3's \quad m \times k-1's \quad m \times (k, k+1)'s$





$$LFU = (k-1) + 2m$$




LFU competitive ratio is unbounded

- Consider the sequence of requests:





$$\text{LFU} = (k-1) + 2m$$




LFU competitive ratio is unbounded

- Consider the sequence of requests:





$$\text{LFU} = (k-1) + 2m$$




$$\text{OPT} = k + 1$$

LFU competitive ratio is unbounded

- Consider the sequence of requests:



$$\text{LFU} = (k-1) + 2m$$



$$\text{OPT} = k + 1$$

When m is large enough, $\frac{\text{LFU}}{\text{OPT}} \approx O\left(\frac{m}{k}\right)$

The ratio grows with the input \Rightarrow **unbounded** \square

What Happened

- By a special requests sequence, we can force LFU to incur page faults frequently while the optimal assignment is still efficient
- The competitive ratio of LFU grows with the input size — **unbounded**

LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:

Once a page fault is incurred, evict the one that was used the least recently

LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:

Once a page fault is incurred, evict the one that was used the least recently




Cache



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:

Once a page fault is incurred, evict the one that was used the least recently





Cache



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:



Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:



Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:


Once a page fault is incurred, evict the one that was used the least recently



LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:

Once a page fault is incurred, evict the one that was used the least recently



1, 3, 3, 5, 4, 3, 2, 5, 2, 1

Cache

5


3

2

LRU (Least-Recently-Used)

LRU (Least-Recently-Used) algorithm:

Once a page fault is incurred, evict the one that was used the least recently



LRU is k -competitive

LRU is k -competitive

<Proof idea>

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase


- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)




1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)



1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1


Phase 1

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)



1, 3, 3, 5

Phase 1

4, 3, 2

Phase 2


5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)



1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1



Phase 1 Phase 2 Phase 3

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase


- Phase 0 is empty
- Phase i is the maximal sequence following phase $i - 1$ that contains at most k distinct page requests (that is, phase $i + 1$ begins on the request that is the $(k + 1)$ -th distinct page)



LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase




1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1

LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults



1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1


LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .



1, 3, 3, 5, 4, 3, 2, 5, 2, 1, 1, 3, 2, 3, 1, 3, 3, 5, 3, 5, 2, 1


LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .




LRU is k -competitive

<Proof idea>

Phase partitioning: partition the request sequence into phases and bound the cost of LRU and OPT in each phase

- Claim (a): In phase i , **LRU** only incurs at most k page faults

<Proof> Since **LRU** evicts the page that was used the longest time ago, it never evicts a page that was requested earlier in the same phase. Hence, **LRU** incurs at most k page faults in a phase as there are at most k distinct pages in each phase i .



At the moment when the j -th distinct page in phase i is requested, there are $j - 1$ pages accessed in phase i .

\Rightarrow There are $k - (j - 1)$ pages in the cache that haven't been accessed recently. Hence, LRU will evict one of them.

LRU is k -competitive

<Proof idea>


- Claim (b): In phase i , **OPT** incurs at least 1 page fault

LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.




LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.




LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.




LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.




LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.




LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.



LRU is k -competitive

<Proof idea>

- Claim (b): In phase i , **OPT** incurs at least 1 page fault

<Proof> Consider the cache just before phase i . At this moment, there are k pages in the cache. Since the first request in phase i is different from any of the pages in phase $i - 1$, any feasible algorithm has to evict one page to accommodate this request, and so does **OPT**.

Let LRU_i and OPT_i denote the page fault incurred by **LRU** and **OPT** in phase i , respectively. By Claim (a) and Claim (b),

$$\frac{\text{LRU}(I)}{\text{OPT}(I)} = \frac{\sum_i \text{LRU}_i}{\sum_i \text{OPT}_i} \leq \frac{k}{1} = k$$

□

What Happened

- **Phase partitioning:** partition the request sequence into phases such that each phase has k distinct pages
- By arguing that an algorithm incurs at most k page faults and OPT incurs at least 1 page fault in any phase, we can conclude that the algorithm is at most $O(\frac{n}{k})$ -competitive
- Arguing that **an algorithm incurs at most k page faults** is the key!

Paging Problem Lower Bound

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k$

1 2 3 ... k

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$.


1 2 3 k

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$.


1 2 3 $k+1$... k



Paging Problem Lower Bound

<Proof idea>


Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i .



Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i . The adversary repeatedly requests the page evicted by **ALG** for $n - 1$ rounds.



Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i . The adversary repeatedly requests the page evicted by **ALG** for $n - 1$ rounds.

In this instance, each request incurs a page fault for ALG. Therefore, **ALG** costs $k + n$.

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i . The adversary repeatedly requests the page evicted by **ALG** for $n - 1$ rounds.

In this instance, each request incurs a page fault for **ALG**. Therefore, **ALG** costs $k + n$.

Because there are only $k + 1$ pages involved, **OPT** incurs at most 1 page fault per k pages.

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i . The adversary repeatedly requests the page evicted by **ALG** for $n - 1$ rounds.

In this instance, each request incurs a page fault for **ALG**. Therefore, **ALG** costs $k + n$.

Because there are only $k + 1$ pages involved, **OPT** incurs at most 1 page fault per k pages.

$$\text{Therefore, } \frac{\text{ALG}(I)}{\text{OPT}(I)} \geq \frac{k + n}{k + n/k} \approx \Omega(k)$$

Even when every page requests change dramatically, the optimal solution can keep the k pages that will be used in the most recent future and evict the one that will be used later.

Paging Problem Lower Bound

<Proof idea>

Assume that the cache size is k . Consider any algorithm **ALG** and design the adversary as follows: First request pages $1, 2, 3, \dots, k, k + 1$. At this moment, **ALG** evicts a page $i \in [1, k]$. Then, the adversary requests page i . The adversary repeatedly requests the page evicted by **ALG** for $n - 1$ rounds.

In this instance, each request incurs a page fault for **ALG**. Therefore, **ALG** costs $k + n$.

Because there are only $k + 1$ pages involved, **OPT** incurs at most 1 page fault per k pages.

$$\text{Therefore, } \frac{\text{ALG}(I)}{\text{OPT}(I)} \geq \frac{k + n}{k + n/k} \approx \Omega(k)$$



Research cycle of online algorithms

