

# Match and Recursive Types

CS 151: Introduction to Computer Science I

# Pattern Matching

Syntax match:

```
(match exp0  
  [pat1 exp1]  
  [pat2 exp2]  
  ...  
  [patk expk])
```

- ▶ Similar to cond evaluation
- ▶ `exp0` is evaluated to a value we'll call `v`
- ▶ `v` is compared against each pattern in turn, in the order given: `pat1`, then `pat2`, and so on, up to `patk`

## Pattern Matching

A new expression, match:

```
(match (+ 1 1)
  [1 "one plus one is one"]
  [2 "one plus one is two"]
  [3 "one plus one is three"])
```

Used like this, match looks and behaves very similar to cond:

```
(: is-it-5 : Integer -> String)
(define (is-it-5 n)
  (match n
    [5 "It's 5!!!"]
    [_ "Not 5..."])))
```

...but swap else for the wildcard pattern `_`

# Pattern Matching

```
(match (+ 2 3)
  [0 0]
  [n (* n 2)])
```

First line is called a *constant pattern*

Second line is called a *variable pattern*, and it always succeeds

```
(: x : Integer)
(define x 100)
(match (* x 2)
  [150 "very good"]
  [_ (error "2x must be 150")])
```

Difference between variable and wildcard: using a variable creates a new variable

## Aside: Variable Scope

The *scope* of a variable is the region of code in which its value is accessible.

For normal variables, their scope is the entire program:

```
(: my-variable : String)
(define my-variable "CS is awesome")
```

For function arguments, their scope is the function body:

```
(: square : Real -> Real)
(define (square x)
  (* x x))
```

For pattern matches, their scope is a single case:

```
(match (+ 2 3)
  [n (* n 2)])
```

## Aside: Variable Scope

To *bind* a variable means to assign it a value

When you use a variable, the value comes from the innermost binding of that variable:

```
(: x : String)
(define x "I live outside")

(: func : String -> String)
(define (func x)
  (append x " and thank you"))
```

```
(func "please")  $\implies$  "please and thank you"
```

## Matching Structures

```
(define-struct Point
  ([x : Real]
   [y : Real]))
(: my-point : Point)
(define my-point (Point -3 2))
```

We can use `match` to “pull out” the parts of the structure:

```
(match my-point
  [(Point a b) (Point (+ a 1) (+ b 1))])
```

Equivalent to using the selector notation:

```
(Point (+ (Point-x my-point) 1)
       (+ (Point-y my-point) 1))
```

## Match on Union Types

```
(define-struct Circle
  ([radius : Real]
   [center : Point]
   [color : Color]))
(define-struct Square
  ([side-length : Real]
   [center : Point]
   [color : Color]))
(define-type Shape (U Circle Square))
```

```
(: area : Shape -> Real)
(define (area shape)
  (match shape
    [(Circle r _ _) (* pi r r)]
    [(Square s _ _) (* s s)]))
```



# Recursive Types: Russian Dolls



A type for Russian dolls:

```
(define-struct Doll
  ([inches-tall : Exact-Rational]
   [color : (U 'blue 'red 'yellow)]
   [inside : (U 'nothing Doll)]))
```

# Recursive Types: Russian Dolls

Some things we might want to do with Dolls:

```
(: count-dolls : Doll -> Integer)
(: doll=?      : Doll Doll -> Boolean)
```

```
(: count-dolls : Doll -> Integer)
(define (count-dolls doll)
  (match (Doll-inside doll)
    ['nothing 1]
    [(Doll _) (+
               1
               (count-dolls (Doll-inside doll)))]))
```

# Will it Run?

Add some new definitions for Russian dolls:

```
(define-type Color (U 'blue 'red 'yellow))  
(define-type Inside (U 'nothing Doll))  
  
(define-struct Doll  
  ([inches-tall : Integer]  
   [color : Color]  
   [inside : Inside]))
```

# Will it Run?

```
(: func : Integer -> Integer)
(define (func x)
  (cond
    [(= 0 x) 1]
    [else (tion (- x 1))]))
```

```
(: tion : Integer -> Integer)
(define (tion y)
  (cond
    [(= 0 y) 0]
    [else (+
            2
            (func y))]))
```

## Recursive Types: Person

```
(define-struct Person
  ([name : String]
   [year-of-birth : Integer]
   [children : (Listof Person)]))
```

```
(: ivanka : Person)
(: eric : Person)
(: donald : Person)
(define ivanka (Person "Ivanka Trump" 1981 empty))
(define eric (Person "Eric Trump" 1984 empty))
(define donald (Person "Donald Trump" 1946
  (list ivanka eric)))
```

# Find Descendant

The characters in *Game of Thrones* can get pretty complicated... you just want to know, who is an ancestor of Jon Snow?

```
(: ancestor? : Person -> Boolean)
(: any-ancestor? : (Listof Person) -> Boolean)
```

# Find Descendant

```
(: any-ancestor? : (Listof Person) -> Boolean)
(define (any-ancestor? character-list)
  (cond
    [(empty? character-list) #f]
    [else (or
            (ancestor? (first character-list))
            (any-ancestor? (rest
                           character-list))))]))

(: ancestor? : Person -> Boolean)
(define (ancestor? character)
  (match character
    [(Person "Jon Snow" _ _) #t]
    [(Person _ _ children) (any-ancestor?
                                   children)]))
```

# Natural Numbers

The natural numbers are  $0, 1, 2, 3, 4, \dots$

There is a Racket type for these, `Natural`...but rarely used

```
(define-struct Succ  
  ([nat : Nat]))  
(define-type Nat (U 'zero Succ))
```

How to represent 0:

```
'zero
```

How to represent 1:

```
(Succ 'zero)
```

How to represent 2:

```
(Succ (Succ 'zero))
```



# Natural Numbers

This is **our very own** definition the type `Natural`

```
(: zero? : Nat -> Boolean)
(: add : Nat Nat -> Nat)
(: pred : Nat -> Nat)
(: sub : Nat Nat -> Nat)
```

```
(: zero? : Nat -> Boolean)
(define (zero? nat)
  (match nat
    ['zero #t]
    [_ #f]))
```

# Natural Numbers

```
(:  pred :  Nat -> Nat)
(define (pred nat)
  (match nat
    ['zero (error "pred:  input is zero")]
    [(Succ m) m]))
```

```
(:  sub :  Nat Nat -> Nat)
(define (sub nat-left nat-right)
  (match nat-right
    ['zero nat-left]
    [(Succ m) (sub (pred nat-left) m)]))
```

# Integers

Can use our Nat to make our own definition of Integer:

```
(define-struct Int
  ([value : Nat]
   [sign : (U 'positive 'negative)]))
```

Implementing (`add-int : Int Int -> Int`) is painful...

## Rationals and Reals

Can also use to define Exact-Rational:

```
(define-struct Rat
  ([numerator : Nat]
   [denominator : Nat]
   [sign : (U 'positive 'negative)]))
```

And even Real:

```
(define-type Digit (U '0 '1 '2 '3 '4 '5 '6 '7 '8
'9))
(define-type Infinite-Decimal (Nat -> Digit))
(define-struct Real
  ([whole-number : Int]
   [decimal : Infinite-Decimal]))
```

# What to know

- ▶ Pattern matching
- ▶ Variable scope
- ▶ Recursive structs, mutual recursion
- ▶ Recursive definition of Natural

