CSCI-GA 2110

Programming Languages

Course Notes

Fall 2026

Instructor: Prof. Joseph Tassarotti
Recitation leaders: Seong-Heon Jung and Vishnu Satish
Notes by You Li

Acknowledgements

These notes follow the Fall 2026 offering of CSCI-GA 2110 (Programming Languages) at the Courant Institute, taught by Prof. Joseph Tassarotti, with recitations led by Seong-Heon Jung and Vishnu Satish. The course studies programming languages by *implementing* them: each new language feature is added to an interpreter written in Racket, following Krishnamurthi's *Programming Languages: Application and Interpretation* [1].

Each chapter covers one week: first the lecture, split into one section per topic, then that week's recitation. The code is the code shown in lecture and the recitation handouts; recitation solutions are the ones posted by the teaching assistants.

Notation. Code is Racket (`#lang racket`) in Chapters 1 and 2 and `#lang plai-typed` from Chapter 3 on. Interactions at the REPL are shown with a `>` prompt; in `plai-typed` the line starting with `-` is the type the checker reports, and the line after it is the value. A trace such as

```
(fact 2)
---> (* 2 (fact 1))
```

shows one evaluation step per line. In the interpreter chapters, e ranges over expressions of the language being implemented, $e[v/x]$ is e with v substituted for the free occurrences of x, and $\mathrm{FV}(e)$ is the set of free variables of e. Type names such as ArithE are set in sans serif in prose.

Contents

1 Week 1: Course Introduction and Racket Basics **6**

1.1 Studying Programming Languages . . . 7
1.1.1 Classification Is Not Understanding . . . 7
1.1.2 Studying by Implementing . . . 7
1.1.3 Course Logistics . . . 8
1.2 Expressions, Functions, and Recursion . . . 9
1.2.1 Racket Is an Expression Language . . . 9
1.2.2 Defining Functions . . . 9
1.2.3 Conditionals . . . 9
1.2.4 Recursion . . . 9
1.2.5 Tail Recursion . . . 10
1.3 Pairs and Lists . . . 11
1.3.1 Pairs . . . 11
1.3.2 Lists Are Nested Pairs . . . 11
1.3.3 Reversing a List . . . 12
1.4 Recitation 1: Functional Programming in Racket . . . 13
1.4.1 Expressions and Functions . . . 13
1.4.2 Specifications . . . 14
1.4.3 Recursion: Scrolling Through Lights . . . 14
1.4.4 Lists and Higher-Order Programming . . . 15

2 Week 2: Higher-Order Functions, Scope, and State **18**

2.1 Lists and Accumulators . . . 19
2.1.1 `snoc`: Adding to the End . . . 19
2.1.2 Reversing, Correctly and Incorrectly . . . 19
2.1.3 Aggregating a List . . . 20
2.1.4 Named `let`: Hiding the Helper . . . 21
2.2 Structs and Trees . . . 22
2.2.1 `struct` . . . 22
2.2.2 Binary Trees . . . 22
2.2.3 `match` . . . 23
2.3 Higher-Order Functions . . . 24
2.3.1 Functions Are Values . . . 24
2.3.2 `map` and `filter` . . . 24
2.3.3 Folds . . . 25
2.4 Scope and State . . . 27
2.4.1 `let` and `let*` . . . 27

2.4.2 Lexical Scope . . . 27
2.4.3 Pure Code and Side Effects . . . 28
2.4.4 Boxes: State You Can See . . . 29
2.5 Recitation 2: Boolean Expressions . . . 30
2.5.1 The Language and Its Representation . . . 30
2.5.2 An Interpreter for bexp . . . 31
2.5.3 An Optimization Pass: De Morgan . . . 31
2.5.4 Testing the Optimizer Two Ways . . . 33

3 Week 3: Types and a First Interpreter 35
3.1 Types in plai-typed . . . 36
3.1.1 Every Value Has a Type . . . 36
3.1.2 Type Inference and Annotations . . . 36
3.1.3 Function Types . . . 37
3.1.4 Lists Are Homogeneous . . . 38
3.1.5 Pairs . . . 38
3.1.6 Polymorphic Types . . . 38
3.1.7 Why Insist on Homogeneous Lists? . . . 39
3.2 `define-type` and `type-case` . . . 40
3.2.1 Defining a Type with Variants . . . 40
3.2.2 `struct` vs. `define-type` . . . 40
3.2.3 `type-case`: Taking a Value Apart . . . 41
3.2.4 Exhaustiveness . . . 41
3.3 S-Expressions and the Calculator . . . 43
3.3.1 Quote and Symbols . . . 43
3.3.2 S-Expressions . . . 43
3.3.3 Concrete and Abstract Syntax . . . 43
3.3.4 The Calculator . . . 44
3.3.5 What Malformed Input Does . . . 45
3.4 Recitation 3: Typed Boolean Expressions and Pattern Matching . . . 47
3.4.1 Part A: Boolean Expressions, Typed . . . 47
3.4.2 Part B: Pattern Matching with `match` . . . 49
3.4.3 `match` vs. `type-case` . . . 51

4 Week 4: Names and Functions 52
4.1 Names: `let` and Substitution . . . 53
4.1.1 The Plan . . . 53
4.1.2 Two New Variants . . . 53
4.1.3 Eager Substitution . . . 54
4.1.4 Shadowing . . . 54
4.1.5 `eval-eager` . . . 55
4.2 Lazy Substitution and Variable Capture . . . 56
4.2.1 Lazy Substitution . . . 56
4.2.2 Is Lazy More Efficient? . . . 56
4.2.3 Where Eager and Lazy Differ . . . 57
4.2.4 Variable Capture . . . 57
4.3 Capture-Avoiding Substitution . . . 58
4.3.1 Rename, Then Substitute . . . 58

4.3.2 `gensym`: Fresh Names . . . 58
4.3.3 `subst-lazy-v2` . . . 59
4.4 Functions: `lambda` and Application . . . 60
4.4.1 Syntax . . . 60
4.4.2 `lambda` in Substitution . . . 61
4.4.3 A New Result Type . . . 61
4.4.4 Eager Application . . . 62
4.4.5 Lazy Application: `eval-lazy-v2` . . . 63
4.4.6 Capture, Again . . . 64
4.5 Recitation 4: Pattern Matching in the Interpreter . . . 65
4.5.1 The New Form . . . 65
4.5.2 Types . . . 65
4.5.3 Parsing . . . 66
4.5.4 Substitution . . . 67
4.5.5 Evaluation . . . 67

5 Week 5: From Substitution to Environments 69
5.1 Substitution Revisited . . . 70
5.1.1 The Starting Point . . . 70
5.1.2 `let` Is Function Application . . . 70
5.1.3 Capture, Once More . . . 70
5.1.4 The Lambda Calculus . . . 71
5.1.5 α-Equivalence . . . 71
5.2 Environments . . . 73
5.2.1 The Plan . . . 73
5.2.2 The Data Structure . . . 73
5.2.3 The Interpreter . . . 74
5.2.4 Traces . . . 75
5.2.5 A Default Environment . . . 76
5.2.6 Checking Against Substitution . . . 76
5.3 Lazy `let` and Dynamic Scope . . . 77
5.3.1 Attempt 1: Store the Expression . . . 77
5.3.2 Dynamic vs. Lexical Scope . . . 78
5.3.3 Attempt 2: Store the Environment Too . . . 78
5.4 Functions with Environments: Closures . . . 80
5.4.1 Attempt 1: A Function Is Its Parameter and Body . . . 80
5.4.2 Attempt 2: Closures . . . 81
5.4.3 The Five Files Side by Side . . . 83
5.5 Recitation 5: Environments as Functions, Scope, and Macros . . . 84
5.5.1 The Language . . . 84
5.5.2 Environments as Functions . . . 84
5.5.3 One Interpreter, Two Scopes . . . 87
5.5.4 Predict, Then Check . . . 88
5.5.5 Scope with Assignment . . . 91
5.5.6 Scope and Macros . . . 92
5.5.7 A Look at Lean . . . 95

6 Week 6: Mutable State **96**
6.1 State and Boxes . . . 97
6.1.1 Four New Constructs . . . 97
6.1.2 The Examples . . . 97
6.1.3 Attempt 1: A Box Holds Its Value . . . 98
6.2 Store-Passing Style . . . 100
6.2.1 Locations and the Store . . . 100
6.2.2 Results Carry the Store . . . 100
6.2.3 Fresh Locations . . . 101
6.2.4 Threading the Store Through Arithmetic . . . 102
6.2.5 `let` Is Application, Again . . . 103
6.2.6 Application . . . 103
6.3 Boxes in the Store-Passing Interpreter . . . 105
6.3.1 The Box Clauses . . . 105
6.3.2 Running the Examples . . . 105
6.3.3 Tracing `ex4` . . . 106
6.3.4 Tracing `ex5`: Two Tables, Two Paths . . . 106
6.3.5 The Store Only Grows . . . 107
6.4 The Meta-Circular Interpreter . . . 108
6.4.1 Boxes Implemented by Boxes . . . 108
6.4.2 Side by Side . . . 109
6.4.3 What Each Version Explains . . . 109

Chapter 1

Week 1: Course Introduction and Racket Basics

Lecture 1: September 8, 2026. Recitation 1: September 11, 2026.

Supplementary reading:

- [1] Chapter 1 (Introduction).
- [4] Chapters 2 (Racket Essentials) and 3.8–3.9 (Pairs and Lists).
- [2] Part I, especially the design recipe (Section 3).
- [3] Sections 1.1 and 1.2.1 (the substitution model; linear recursion and iteration).

The first week explains how this course approaches programming languages, by building interpreters for small languages, and teaches enough Racket to start. This chapter covers:

- Section 1.1: why study programming languages, why classifying them by paradigm is the wrong place to start, and why the course implements interpreters;
- Section 1.2: Racket as an expression language, `define`, `cond`, recursion, and tail recursion with an accumulator;
- Section 1.3: pairs, lists, and the two-case shape of list functions;
- Section 1.4: Recitation 1, practicing function composition, specifications, recursion, and list functions on a traffic-light example.

1.1 Studying Programming Languages

1.1.1 Classification Is Not Understanding

The obvious way to organize the subject is by classification. Languages are sorted by *paradigm* (functional, imperative, object-oriented), by *abstraction* (high-level or low-level), by *representation* (text or graphical), and so on. A common course design follows from it: survey the categories, pick three or four languages from different ones, learn their basics, and write programs that highlight each one's features. That is not a bad idea, and you would learn a lot, but it is not the approach of this course.

The lecture makes the point with biological taxonomy. "Ape" sounds like a natural category: large, tailless primates such as the orangutan, the gorilla, and the chimpanzee. But when species are grouped by common descent, the group that contains all three also contains humans, and chimpanzees are closer to humans than to orangutans (Figure 1.1). A classification by surface features does not match the underlying structure. Sensible classification has to come *after* understanding the principles.




Figure 1.1: Grouping by common descent. Humans sit inside the great apes, not beside them (after slide 7).

The course's claim is that the same *building blocks* appear in many programming languages: functions, names and scope, data structures, state, types, control. It is better to understand these building blocks directly than to memorize which languages have which features.

Key Point 1 (Two false dichotomies)

- *"Functional" vs. "imperative" languages.* There is no dichotomy. A single language can have functional features, such as first-class functions, and imperative ones, such as mutable state. Racket, OCaml, Python, and JavaScript all have both.
- *"Interpreted" vs. "compiled" languages.* Interpreting and compiling describe an *implementation*, not a language. Any language can have both interpreters and compilers, so neither is a property of the language.

1.1.2 Studying by Implementing

To study the building blocks, we want to be precise and formal. One way is mathematical: give a theory of what programs mean and how they behave (formal semantics). This course takes a second way: it *implements* programming languages. To implement a feature you must decide exactly what it does in every case, so writing the implementation forces the precision that a mathematical definition would.

There are two strategies for implementing a language (Figure 1.2):

- A *compiler* translates a program in one language into another language that can be executed.

- An *interpreter* is a program that takes a program as input and directly executes it.

This course builds interpreters. Compilers are the subject of Compiler Construction (CSCI-GA 2130).




Figure 1.2: The two implementation strategies. This course writes interpreters.

1.1.3 Course Logistics

- **Staff.** Instructor: Joseph Tassarotti. Recitation leaders: Seong-Heon Jung and Vishnu Satish.
- **Textbook.** Krishnamurthi, *Programming Languages: Application and Interpretation*, 2nd edition [1], free online and linked from the syllabus.
- **Language.** The interpreters are written in Racket, for two reasons: Racket has many of the core features we want to study, so writing it is practice in them; and Racket was designed for implementing programming languages.
- **Grading.** Final exam 50%, homework 50%.
- **Homework.** Five assignments of two to three weeks each, done individually. Assignment 1 is a Racket warm-up, pure programming, auto-graded. Assignments 2–5 combine programming with conceptual questions. Up to 72 hours of lateness are allowed in total across all assignments; see the syllabus for details.

1.2 Expressions, Functions, and Recursion

1.2.1 Racket Is an Expression Language

A Racket program is not a list of steps to perform; it is an expression, and running it means simplifying that expression until only a value is left. Every construct below, including conditionals and function bodies, is an expression that produces a value.

Every call is written the same way: the function first, then its arguments, all inside parentheses. So addition is `(+ 3 x)`, not `3 + x`, and calling `foo` on 4 is `(foo 4)`.

1.2.2 Defining Functions

`(define (name argument ...) body)` gives a name to a function.

```
(define (foo x)
  (+ 3 x))
```

There is no `return` keyword, because there is nothing to return *from*: the body is a single expression, and its value is the answer. `(foo 4)` evaluates to `7`.

1.2.3 Conditionals

`cond` chooses between answers. It takes clauses written `[test result]`, tries the tests top to bottom, and returns the result of the first test that is true. `else` is the catch-all at the bottom.

```
(define (my-abs x)
  (cond
    [(> x 0) x]
    [(< x 0) (- x)]
    [else 0]))
```

`cond` is an *expression*, not a statement. It produces a value, which is why it can be the entire body of `my-abs`: there is no assignment and nothing to return, and the value of the `cond` is the value of the function. With one argument, `(- x)` is negation. Only the chosen branch is evaluated, so a branch that would divide by zero is harmless as long as its test is false.

1.2.4 Recursion

Recursion is how repetition is done. A recursive function needs two things:

- a *base case* that answers directly, without recurring, and
- a *recursive case* that makes the problem smaller, in a way that eventually reaches the base case, and trusts the function itself with the rest.

```
(define (fact x)
  (cond
    [(= x 0) 1]
    [else (* x (fact (- x 1)))]))
```

The way to check a recursive function by hand is to rewrite the expression one step at a time:

```
(fact 3)
---> (* 3 (fact 2))
---> (* 3 (* 2 (fact 1)))
---> (* 3 (* 2 (* 1 (fact 0))))
---> (* 3 (* 2 (* 1 1)))
---> 6
```

The `*` sits *outside* the recursive call, so no multiplication can happen on the way down. Each level waits for the one below it, and every level stays on the stack until the recursion bottoms out. The trace grows a tower of pending multiplications.

1.2.5 Tail Recursion

The work can be rearranged so that the multiplying happens on the way *down*. Pass the answer-so-far along as an extra argument, an *accumulator*:

```
(define (fact-helper x acc)
  (cond
    [(= x 0) acc]
    [else (fact-helper (- x 1) (* acc x))]))

(define (fact-tail x)
  (fact-helper x 1))
```

The accumulator starts at 1, the value that leaves a product unchanged; a sum would start at 0.

Definition 2 (Tail call)

A call is a *tail call* if it is the last thing the calling function does: its result is returned unchanged, with no work left pending. Racket guarantees that a tail call reuses the caller's stack frame instead of pushing a new one.

The recursive call in `fact-helper` is a tail call, so the function runs in constant stack space, like a loop:

```
(fact-helper 3 1)
---> (fact-helper 2 3)
---> (fact-helper 1 6)
---> (fact-helper 0 6)
---> 6
```

Nothing is ever pending, because `acc` is a finished number at every step. Since `fact-helper` takes two arguments and `fact` one, the wrapper `fact-tail` keeps the interface the same. Hiding the helper is a recurring theme; Section 2.1 does it with a named `let`.

1.3 Pairs and Lists

1.3.1 Pairs

`cons` glues any two values into a *pair*, and `car` and `cdr` take the pair apart:

```
> (cons 3 4)
'(3 . 4)
> (car (cons 1 2))
1
> (cdr (cons 1 2))
2
```

The names `car` and `cdr` are historical, from the registers of the IBM 704 on which Lisp was first implemented. `first` and `rest` are the same operations on lists, with readable names (the names [2] uses). Both work; pick one style and stay with it.

1.3.2 Lists Are Nested Pairs

A list is not a separate kind of thing. It is a chain of pairs in which the right component is always another list, ending in `empty` (also written `'()`):

Definition 3 (List)

A list is either `empty`, or `(cons x l)` where `x` is any value and `l` is a list.

```
(define l (cons 1 (cons 2 (cons 3 (cons 4 empty)))))
(define l-short (list 1 2 3 4))
```

`l` and `l-short` are the same value; `list` is shorthand for the chain of `cons`es (Figure 1.3). Both print as `'(1 2 3 4)`. Then `(first l)` is `1` and `(rest l)` is `'(2 3 4)`.




Figure 1.3: Box-and-pointer diagrams. Top: `'(1 2 3 4)`, four pairs whose `cdr`s chain to `empty` (drawn as a slash). Bottom: a bare pair.

Pitfall 4 (The dot)

The dot in `'(3 . 4)` means the right side of that pair is not a list, so the chain does not end in `empty`. Whenever a dot appears in output where you expected a list, you built a bare pair somewhere.

The two-case definition is why list functions keep having two `cond` clauses: one for `empty`, one for a `cons`.

1.3.3 Reversing a List

Key Point 5 (The shape of the function follows the shape of the data)

A list is empty or a `cons`, so a function on lists has those two cases. In the `cons` case, the recursive call is on the `rest`, the part of the data that is itself a list.

The empty list reversed is the empty list. Otherwise, reverse everything after the first element, then put the first element at the end:

```
(define (my-reverse l)
  (cond
    [(empty? l) empty]
    [else (append (my-reverse (rest l)) (list (first l)))]))
```

`append` joins two lists, so both arguments must be lists. That is why the first element is wrapped as `(list (first l))`, the one-element list. Rewriting by hand:

```
(my-reverse '(1 2 3))
---> (append (my-reverse '(2 3)) '(1))
---> (append (append (my-reverse '(3)) '(2)) '(1))
---> (append (append '(3) '(2)) '(1))
---> (append '(3 2) '(1))
---> '(3 2 1)
```

This works, but `append` itself walks its whole left argument, and it is called once per element, so `my-reverse` takes $O(n^2)$ time. Racket's built-in `reverse` uses an accumulator instead, the same trick as `fact-tail`; Recitation 1 writes that version (Section 1.4).

1.4 Recitation 1: Functional Programming in Racket

The recitation practices the basics of the lecture in DrRacket, on a running example about traffic lights. The handout is itself a program: it is written in `#lang scribble/lp2`, a literate-programming language in which code sits in named `@chunk` blocks inside the prose. "Scribble HTML/PDF" renders the document; "Run" runs every chunk listed in the top-level `<*>` chunk. Tests are written with `check-expect` from `test-engine/racket-tests`, and the final `(test)` reports the results.

1.4.1 Expressions and Functions

```
(define (is-even x)
  (= 0 (modulo x 2)))
```

Exercise 6 (Predict at the REPL)

What do `is-even`, `(is-even)`, `(is-even 2)`, `(is-even 3)`, `(is-even #t)`, and `(is-even 'four)` evaluate to?

Solution. `is-even` alone is the function value, printed `#<procedure:is-even>`; a function is a value like any other. `(is-even)` is an *arity mismatch*: the function expects one argument. `(is-even 2)` is `#t` and `(is-even 3)` is `#f`. `(is-even #t)` and `(is-even 'four)` are *contract violations* raised inside `modulo`, which expects integers. Racket checks this only when the call runs: nothing stops you from writing the call.

Building programs by composition. In functional style, programs are built by composing functions. A traffic light is one of `'red`, `'yellow`, `'green`. Two functions are given:

- `can-go` EXPECTS a traffic light and PRODUCES a boolean: `#t` when a vehicle approaching the light may safely enter the intersection.
- `next-light` EXPECTS a traffic light and PRODUCES the light that comes after it.

```
(define (can-go l) (equal? l 'green))

(define (next-light l)
  (match l
    ['red    'green]
    ['yellow 'red]
    ['green  'yellow]))
```

`match` compares `l` against each pattern in turn; a quoted symbol pattern matches that symbol. (Section 3.4 looks at `match` in detail.)

Exercise 7 (Pedal to the metal)

Write `can-floor-it`: it EXPECTS a traffic light and PRODUCES `#t` when a vehicle can safely enter the intersection at either the current light or the next one.

Solution. Compose the two given functions:

```
(define (can-floor-it l)
  (or (can-go l) (can-go (next-light l))))
(check-expect (can-floor-it 'green) #t)
(check-expect (can-floor-it 'red) #t)
(check-expect (can-floor-it 'yellow) #f)
```

Red is safe because the next light is green; yellow is not, because the next light is red.

1.4.2 Specifications

Before writing a function, state which inputs are valid and what output to expect. The handout's format is a list of EXPECTS and PRODUCES lines plus one sentence of meaning. For `next-light-iter`:

- EXPECTS a non-negative integer `n` and a traffic light `l`;
- PRODUCES a traffic light: the color of `l` after it changes `n` times.

The specification answers the two questions the code needs. When `n` is zero, the light has not changed, so the answer is `l`. When `n` is positive, the answer is the light after changing $n - 1$ times starting from `(next-light l)`.

```
(define (next-light-iter n l)
  (if (eq? n 0)
      l
      (next-light-iter (- n 1) (next-light l))))

(check-expect (next-light-iter 0 'green) 'green)
(check-expect (next-light-iter 1 'green) 'yellow)
(check-expect (next-light-iter 2 'yellow) 'green)
```

The tests come straight from the specification: one for the base case, one for a single step, and one that wraps around the cycle (yellow, red, green). The recursive call is a tail call, with the light itself playing the role of an accumulator.

1.4.3 Recursion: Scrolling Through Lights

A vehicle is one of `'sports-car`, `'suv`, `'prius`. `speed` gives its speed in meters per second and `time-to-change` gives how many seconds a light stays on:

```
(define (speed v)
  (match v
    ['sports-car 136]
    ['suv        48]
    ['prius      27]))

(define (time-to-change l)
  (match l
    ['red    10]
    ['yellow 2]
    ['green  23]))
```

Exercise 8 (Scroll)

`safe-to-scroll` EXPECTS a vehicle `v`, a non-negative distance `d` in meters, and a light `l` that has just turned on. It PRODUCES `#t` if the vehicle, driving at constant speed, enters the intersection without a violation. Hint: write a helper that decides whether the vehicle enters before the light changes.

Solution. If the vehicle reaches the intersection before the light changes, the answer is whether *this* light allows entry. Otherwise the problem shrinks: the vehicle has driven for one full light, so it is closer, and the light is now the next one.

```
(define (will-enter v d l)
  (<= d (* (time-to-change l) (speed v))))

(define (safe-to-scroll v d l)
  (if (will-enter v d l)
      (can-go l)
      (safe-to-scroll
       v
       (- d (* (time-to-change l) (speed v)))
       (next-light l))))

(check-expect (safe-to-scroll 'sports-car 137 'green) #t)
```

Two traces show both outcomes. A Prius covers $23 \times 27 = 621$ m during a green light:

```
(safe-to-scroll 'prius 1000 'green)    ; 1000 > 23*27 = 621
---> (safe-to-scroll 'prius 379 'yellow)  ; 379 > 2*27 = 54
---> (safe-to-scroll 'prius 325 'red)     ; 325 > 10*27 = 270
---> (safe-to-scroll 'prius 55 'green)    ; 55 <= 621: enters on green
---> #t

(safe-to-scroll 'suv 1200 'green)      ; 1200 > 23*48 = 1104
---> (safe-to-scroll 'suv 96 'yellow)     ; 96 <= 2*48 = 96: enters on yellow
---> #f
```

The recursion terminates because every recursive call has a strictly smaller `d`: each light lasts a positive time and every vehicle has positive speed.

Remark 9. The handout's prose writes the call as `(safe-to-scroll v l d)`, while the posted code takes `(v d l)`. The code and its test are consistent, so the order is `(v d l)`. This is the kind of mismatch a specification is meant to catch.

1.4.4 Lists and Higher-Order Programming

Warm-up: `cons` vs. `append`.

expression	result
`(cons 3 4)`	`'(3 . 4)`, a bare pair
`(cons 3 '(4))`	`'(3 4)`
`(cons '(4) 3)`	`'((4) . 3)`: a pair whose `car` is a list
`(append 3 4)`	error: `append: contract violation`
`(append 3 '(4))`	error: the first argument must be a list
`(append '(3) 4)`	`'(3 . 4)`: the last argument is not checked

`cons` puts one element in front of a list; `append` joins lists. Neither complains about every misuse, so watch for dots in the output.

Exercise 10 (All even)

Write `all-even-rec`: it EXPECTS a list of integers and PRODUCES `#t` when every number in it is even.

Solution. The TA solution uses `match` with a `cons` pattern, which tests for a non-empty list and names its two parts in one step:

```
(define (all-even-rec l)
  (match l
    ['()              #t]
    [(cons head tail) (and (is-even head) (all-even-rec tail))]))
(check-expect (all-even-rec '()) #t)
(check-expect (all-even-rec '(2 4 6)) #t)
(check-expect (all-even-rec '(2 4 6 7)) #f)
```

The empty list is all even (there is no counterexample), which is also what makes `#t` the right base value for `and`.

Exercise 11 (Map)

Given `all`, which checks that a list of booleans is all `#t`, write `all-even-map` without explicit recursion.

```
(define (all l) (andmap identity l))
```

Solution. The intended answer is `(all (map is-even l))`: `map` turns the numbers into booleans and `all` combines them. The TA solution skips the intermediate list and passes `is-even` to `andmap` directly:

```
(define (all-even-map l) (andmap is-even l))
```

`(andmap f l)` is `#t` when `f` returns true on every element. It stops at the first element that fails, whereas `map` would first compute all the booleans.

Exercise 12 (Reverse, and reverse with a tail call)

Write a function that reverses a list. Then write a version that uses tail-call optimization.

Solution. The direct version is `my-reverse` from Section 1.3, written with `match`:

```
(define (reverse-list l)
  (match l
    ['() '()]
    [(cons head tail) (append (reverse-list tail) (list head))]))
```

Its calls pile up pending append:

```
(reverse-list '(1 2 3 4 5 6 7))
---> (append (reverse-list '(2 3 4 5 6 7)) (list 1))
---> (append (append (reverse-list '(3 4 5 6 7)) (list 2)) (list 1))
---> ...
```

On a list with millions of elements, that is a call stack millions deep. The tail-recursive version carries the reversed-so-far list in an accumulator. Moving elements one at a time from the front of `l` to the front of `acc` reverses their order, and cons is the right tool, since it adds to the front:

```
(define (reverse-helper l acc)
  (match l
    ['() acc]
    [(cons head tail) (reverse-helper tail (cons head acc))]))

(define (reverse-list-tail l)
  (reverse-helper l '()))
```

```
(reverse-helper '(1 2 3) '())
---> (reverse-helper '(2 3) '(1))
---> (reverse-helper '(3) '(2 1))
---> (reverse-helper '() '(3 2 1))
---> '(3 2 1)
```

This is also faster: $O(n)$ instead of $O(n^2)$, since there is no append.

Remark 13 (Tail-call *elimination*)**.** When a language *guarantees* the optimization, it is often called tail-call elimination. Racket guarantees it; many languages, including Rust and Java, do not.

Chapter 2

Week 2: Higher-Order Functions, Scope, and State

Lecture 2: September 15, 2026. Recitation 2: September 18, 2026.

Supplementary reading:

- [4] Sections 4.4–4.6 (functions, local binding), 4.8 (sequencing), 5 (programmer-defined datatypes), and 12 (pattern matching).
- [2] Part II (self-referential data) and Part III (abstraction: `map`, `filter`, folds).
- [3] Sections 1.3 (higher-order procedures) and 3.1 (assignment and local state).

Lecture 2 finishes the tour of Racket: more list recursion and accumulators, structs for tree-shaped data, functions as values, scope, and finally state. Recitation 2 then writes the first interpreter of the course, for Boolean expressions, together with an optimization pass. This chapter covers:

- Section 2.1: adding to the end of a list, a quadratic `reverse` and a broken one, and accumulators packaged as named `let`;
- Section 2.2: `struct`, binary trees, and `match`;
- Section 2.3: `lambda`, closures, `map`, `filter`, and the two folds;
- Section 2.4: `let` and `let*`, lexical scope, pure code and side effects, and boxes;
- Section 2.5: Recitation 2, an interpreter and a De Morgan optimizer for Boolean expressions, and how to test an optimization.

2.1 Lists and Accumulators

Throughout this chapter we use the names `empty?`, `first`, and `rest` rather than `null?`, `car`, and `cdr`. They mean the same thing.

2.1.1 snoc: Adding to the End

`(cons x l)` makes one new pair whose head is `x` and whose tail is the old list `l`. Nothing is copied, so adding to the *front* costs $O(1)$ however long the list is.

Adding to the *back* is different. The old list ends in `'()`, and that `'()` cannot be replaced without rebuilding every pair on the way to it. So a back-insert walks the whole list, in $O(n)$. Racket does not provide one; we write it and call it `snoc`, "cons" backwards:

```
(define (snoc l x)
  (cond
    [(empty? l) (list x)]
    [else (cons (first l) (snoc (rest l) x))]))
```

Two shapes of input, two branches: the skeleton of almost every list function in this course. The empty case answers "the list containing just `x`"; the other keeps the first element in place and hands the rest of the problem to `snoc`. So `(snoc '() 'x)` is `'(x)` and `(snoc '(1 2) 'x)` is `'(1 2 x)`.

2.1.2 Reversing, Correctly and Incorrectly

To reverse a list, reverse everything after the first element, then put the first element at the very end, which is exactly `snoc`:

```
(define (rev l)
  (cond
    [(empty? l) '()]
    [else (snoc (rev (rest l)) (first l))]))
```

```
(rev '(1 2 3))
---> (snoc (rev '(2 3)) 1)
---> (snoc (snoc (rev '(3)) 2) 1)
---> (snoc (snoc '(3) 2) 1)
---> (snoc '(3 2) 1)
---> '(3 2 1)
```

This is correct but slow: one `snoc` per element, each $O(n)$, so $O(n^2)$ in total. It also needs $O(n)$ stack, because the `snoc` is wrapped *around* the recursive call, which therefore is not a tail call.

Here is a tempting rewrite with `cons` instead of `snoc`:

```
(define (rev-alt l)
  (cond
    [(empty? l) '()]
    [else (cons (rev-alt (rest l)) (first l))]))
```

```
> (rev-alt '(1 2 3))
'((() . 3) . 2) . 1)
```

Pitfall 14 (cons is not symmetric)

`cons` expects an element on the left and a list on the right. `rev-alt` passes them the other way round, so it builds a nest of pairs, not a list (Figure 2.1). There is no error, because a pair may hold any two values: the wrong argument order is a *silent* bug, and the dots in the output are the only sign. Swapping the arguments does not rescue this approach: `cons` can only ever add to the front, and reversing needs to add to the back.




Figure 2.1: What `rev-alt` builds: every pair has a non-list on its right, hence the dots.

2.1.3 Aggregating a List

Summing a list follows the same skeleton:

```
(define (sum-list l)
  (cond
    [(empty? l) 0]
    [else (+ (first l) (sum-list (rest l)))]))
```

The `+` sits *outside* the recursive call. It cannot happen until the recursion returns, so every level must be remembered, and a long enough list runs out of stack.

As with `fact` in Section 1.2, the fix is to carry the running total as an extra argument, making the recursive call a tail call:

```
(define (sum-list-helper l acc)
  (cond
    [(empty? l) acc]
    [else (sum-list-helper (rest l) (+ (first l) acc))]))

(define (sum-list-acc l)
  (sum-list-helper l 0))
```

```
(sum-list-helper '(1 2 3) 0)
---> (sum-list-helper '(2 3) 1)
---> (sum-list-helper '(3) 3)
---> (sum-list-helper '() 6)
---> 6
```

2.1.4 Named `let`: Hiding the Helper

A top-level helper with an extra argument is noise. A *named* `let` packages the same thing as a loop: the name after `let` becomes a local function, and the bindings give its parameters and their starting values.

```
(define (sum-list-loop l)
  (let loop ([l l]
             [acc 0])
    (cond
      [(empty? l) acc]
      [else (loop (rest l) (+ (first l) acc))])))
```

This is the idiomatic way to write a loop in Racket; it runs exactly like the helper version.

2.2 Structs and Trees

2.2.1 `struct`

`struct` defines a new kind of compound value. One line

```
(struct bt (label left right) #:transparent)
```

generates five functions:

- `bt`, the constructor: `(bt 1 empty empty)`;
- `bt?`, a predicate that answers `#t` for these values;
- `bt-label`, `bt-left`, `bt-right`, the accessors for the three fields.

Pitfall 15 (Forgetting `#:transparent`)

Without `#:transparent`, a struct value prints as `#<bt>` with its contents hidden, and `equal?` is true only when the two values are the very same object. Two trees that look identical then compare as different, and every test that compares trees fails. With the flag, values print readably and `equal?` compares field by field.

`struct` does *not* check the types of its fields. `(bt 1 2 3)` is accepted, even though 2 and 3 are not trees. Nothing goes wrong until some traversal calls `bt-label` on the number 2, possibly far from the line that built the bad value. Section 3.2 returns to this point: `define-type` in `plai-typed` rejects such a value where it is built.

2.2.2 Binary Trees


The empty tree is represented by `'()`, so a binary tree is either `empty` or a `bt` with a label and two subtrees.

```
(define tree
  (bt 1
      (bt 2 empty empty)
      (bt 3 empty empty)))
```

The definition of a tree mentions trees in *two* places, left and right, so a function over trees has two recursive calls. Lists mentioned themselves once, and list functions had one. The shape of the code follows the shape of the data (Figure 2.2).

```
(define (sum-bt t)
  (cond
    [(empty? t) 0]
    [(bt? t) (+ (bt-label t)
                (sum-bt (bt-left t))
                (sum-bt (bt-right t)))]
    [else (error 'sum-bt "not a tree: ~a" t)]))
```

Tree recursion is usually not made tail-recursive: with two recursive calls, at most one of them can be the last thing the function does, and the other has to be remembered.



(sum-bt tree)
$= 1 +$ (sum-bt (bt 2 ...)) $+$ (sum-bt (bt 3 ...))
$= 1 + (2 + 0 + 0) + (3 + 0 + 0)$
$= 6$

Figure 2.2: The value `tree`. Each `bt` node causes two recursive calls, one per subtree.

2.2.3 `match`

`match` checks the shape and extracts the fields in one step, which reads better once all the fields are needed anyway:

```
(define (sum-bt/match t)
  (match t
    ['() 0]
    [(bt label left right)
     (+ label (sum-bt/match left) (sum-bt/match right))]))
```

The pattern `(bt label left right)` matches only `bt` values and binds the three names to the fields in order.

2.3 Higher-Order Functions

2.3.1 Functions Are Values

A function does not need a name. `lambda` builds one on the spot, and it can be called immediately: `((lambda (x) (* x x)) 4)` is `16`. So `define` for functions is shorthand, and these two definitions are the same:

```
(define (square x)
  (* x x))

(define square-alt
  (lambda (x) (* x x)))
```

Use the short form. Do not nest one form inside the other: `(define (f x) (lambda ...))` defines a function that *returns* a function, which is a different thing.

Since functions are values, a function can return one:

```
(define (make-adder x)
  (lambda (y) (+ x y)))

(define add2 (make-adder 2))
```

Definition 16 (Closure)

A *closure* is a function value together with the bindings of the variables it refers to from the surrounding code.

`(make-adder 2)` returns a function that has not been called yet but already remembers that `x` is 2. Then `(add2 5)` is 7, and `((make-adder 3) 4)` is 7 as well.

2.3.2 `map` and `filter`

Once functions can be arguments, the two most common list patterns become ordinary functions. `map` applies a function to every element; the result has the same length as the input.

```
(define (my-map f l)
  (cond
    [(empty? l) '()]
    [else (cons (f (first l)) (my-map f (rest l)))]))
```

So

```
(map f (list a b c))                    ; = (list (f a) (f b) (f c))
(map (lambda (x) (+ 1 x)) (list 1 2 3))    ; = '(2 3 4)
```

`filter` keeps the elements that pass a test; the contents are unchanged, only the length shrinks. To drop an element, return the filtered rest without `cons`ing it back on:

```
(define (my-filter f l)
  (cond
    [(empty? l) '()]
    [else (if (f (first l))
              (cons (first l) (my-filter f (rest l)))
              (my-filter f (rest l)))]))
```

`(filter odd? (list 1 2 3 4 5))` is `'(1 3 5)`.

Key Point 17 (Three shapes of list code)


`map`: list to list, same length. `filter`: list to list, shorter. `fold`: list to a single value. Most list code is a combination of these three.

2.3.3 Folds


`map` and `filter` each fix what happens at every step. A *fold* takes the step as an argument: a two-argument `combine`, a `base` value for the empty list, and the list. It walks the list once and collapses it into one value. There are two folds, and they differ in which way the parentheses group (Figure 2.3):

$$\texttt{(my-foldl - 0 '(1 2 3))} = ((0-1)-2)-3 = -6,$$
$$\texttt{(my-foldr - 0 '(1 2 3))} = 1-(2-(3-0)) = 2.$$

With an associative and commutative `combine` such as `+`, `*`, or `max`, the two agree, which is why the difference is easy to miss until it bites.



`foldl`: $((0-1)-2)-3$



`foldr`: $1-(2-(3-0))$

Figure 2.3: The two folds of `-` over `'(1 2 3)` with base 0 (green). `foldl` leans left, starting from the base; `foldr` leans right, ending at the base.

`foldl` combines on the way down. In `my-foldl`, `base` doubles as the running accumulator. Each step folds one more element into it and calls itself, and that call is a tail call, so this is a loop in constant stack space:

```
(define (my-foldl combine base l)
  (cond
    [(empty? l) base]
    [else (my-foldl combine (combine base (first l)) (rest l))]))
```

```
(my-foldl + 0 '(1 2 3 4 5))
---> (my-foldl + 1 '(2 3 4 5))
---> (my-foldl + (+ 1 2) '(3 4 5))
---> (my-foldl + (+ 3 3) '(4 5))
---> (my-foldl + (+ 6 4) '(5))
---> (my-foldl + 15 empty)
---> 15
```

Nothing is pending; at every step the accumulator is a value and the list is shorter.

`foldr` combines on the way back up. In `my-foldr`, `combine` wraps the recursive call. No arithmetic can happen until the recursion reaches `'()` and the base value comes back:

```
(define (my-foldr combine base l)
  (cond
    [(empty? l) base]
    [else (combine (first l) (my-foldr combine base (rest l)))]))
```

```
(my-foldr + 0 '(1 2 3 4 5))
---> (+ 1 (my-foldr + 0 '(2 3 4 5)))
---> (+ 1 (+ 2 (my-foldr + 0 '(3 4 5))))
---> (+ 1 (+ 2 (+ 3 (+ 4 (+ 5 (my-foldr + 0 empty))))))
---> (+ 1 (+ 2 (+ 3 (+ 4 (+ 5 0)))))
---> 15
```

That growing pile of pending additions *is* the stack: it is the concrete reason `foldr` uses $O(n)$ space and `foldl` $O(1)$.

Key Point 18 (`foldr` rebuilds structure)

`(my-foldr cons '() l)` copies `l`, because `foldr` replaces each `cons` of the list by `combine` and the final `'()` by `base`. Hence `map` and `filter` are both folds in disguise:

```
(define (map-as-fold f l)
  (my-foldr (lambda (x acc) (cons (f x) acc)) '() l))

(define (filter-as-fold f l)
  (my-foldr (lambda (x acc) (if (f x) (cons x acc) acc)) '() l))
```

Pitfall 19 (Racket's `foldl` argument order)

The `combine` of `my-foldl` takes `(acc elem)`. Racket's built-in `foldl` calls `(combine elem acc)`, element first, the opposite order. So `(foldl - 0 '(1 2 3))` in Racket is $3 - (2 - (1 - 0)) = 2$, not -6. Check the order before reusing a `combine`.

2.4 Scope and State

2.4.1 `let` and `let*`

`let` binds names to values for the extent of its body. The clauses go in one pair of brackets; square and round brackets are interchangeable in Racket, so both of these are the same form:

```
(let ([x (+ 1 2)])
  (+ x x))            ; 6

(let [(x (+ 1 2))
      (y (+ 4 5))]
  (+ x y))            ; 12
```

The catch is *when* each name starts to exist. `let` evaluates all of its right-hand sides first, in the scope *outside* the `let`, and only then binds the names. So a later clause cannot use an earlier one:

```
(let ([x (+ 1 2)]
      [y (+ 1 x)])     ; x is not bound here
  (+ x y))
;; x: undefined; cannot reference an identifier before its definition
```

Read the message as "that name is not in scope here".

`let*` binds the clauses one at a time, each in the scope of the previous ones, so this version works and gives 7:

```
(define let-example
  (let* ([x (+ 1 2)]
         [y (+ 1 x)])
    (+ x y)))
```

There is no magic in `let*`; it is nested `let`s:

`(let* ([x a] [y b]) body)` means `(let ([x a]) (let ([y b]) body))`.

Use `let` by default, since it tells the reader the bindings are independent, and `let*` only when a clause really needs the one above it. Neither lets a clause refer to *itself*: a local recursive function needs `letrec`, or the named `let` of Section 2.1.

2.4.2 Lexical Scope

A `let` is an expression, so it can appear anywhere a value can, including in another `let`'s right-hand side:

```
(define nested-let-example
  (let ([x (let ([y 3]) (+ y y))])
    (+ x x)))          ; x = 6, so 12
```

But `y` exists only inside the inner `let`. Writing `(+ x y)` in the outer body is the same undefined-identifier error, even though `y` was "used" a moment earlier (Figure 2.4).




Figure 2.4: Scopes nest like the text. The body of the outer `let` is outside the inner `let`, so `y` is unbound there.

Definition 20 (Lexical scope)

Under *lexical* (static) scope, which binding a use of a name refers to is determined by where the binding is *written* in the program text, not by what happened to run before.

This is the same rule that makes the closure in `make-adder` work: the `x` in `(lambda (y) (+ x y))` refers to the `x` of the enclosing `define`, wherever the returned function is later called.

2.4.3 Pure Code and Side Effects

Everything so far is *pure*: a call depends only on its arguments and does nothing but return a value. Run the same expression twice and you get the same answer, so an expression can always be replaced by its value without changing the program. That is what makes the step-by-step traces of `rev` and the folds valid reasoning, not just illustration.

A *side effect* is anything else a call does: printing, mutating a variable, reading input, raising an error. In a language built on statements, `i++` is exactly this. Running it twice is not the same as running it once, so it cannot be replaced by its value.

- `"Hello World"` is a value. Evaluating it does nothing else.
- `(print "Hello World")` writes to the console and returns `(void)`. The output is the point; the return value is not.

Racket does not forbid effects; it makes them ordinary expressions, so staying pure is a choice made function by function.

Sequencing. A function body may hold several expressions. They run in order, the earlier ones only for their effects, and the value of the *last* one is returned:

```
(define (foo x)
  (print "Hello")
  (+ x 1))
```

`(foo 1)` returns 2 and prints along the way. The returned number is perfectly predictable; the printing is what makes `foo` impure. `begin` is the same sequencing as a single expression, for places where only one expression is allowed, such as a `cond` branch or an arm of `if`:

```
(begin
  (print "Hello")
  (print "World")
  (+ 1 2))          ; returns 3, after printing
```

Three ways to print. All return `(void)`; they differ only in what appears on the console. `(print "Hello")` shows `"Hello"`, the value as Racket would write it, quotes included. `(display "Hello")` shows `Hello`, the

human-readable form. `(printf "The number foo is: ~a !" (* 3 3))` shows `The number foo is: 9 !`: `~a` splices in the display form of the next argument.

2.4.4 Boxes: State You Can See

A *box* is a mutable container with exactly one slot, the smallest possible piece of state. It is a value like any other, so it can be passed to a function that changes it.

```
(define bar (box 3))

(define (increment-box b)
  (set-box! b (+ 1 (unbox b))))
```

`(box 3)` makes a box, `(unbox bar)` reads it, and `(set-box! bar 10)` overwrites it and returns `(void)`. `increment-box` is called for its effect and returns nothing useful, so the caller has to `unbox` afterwards to see the new contents:

```
(let ([b (box 3)])
  (increment-box b)
  (unbox b))          ; 4
```

The point of a box is that mutability is *visible*. A plain 3 can never change; a box holding 3 announces that someone may change it, so a reader can tell where the state lives. By convention, a name ending in `!` mutates something: a warning that calling it twice is not the same as calling it once.

2.5 Recitation 2: Boolean Expressions

This recitation builds the course's first interpreter and first program transformation, for a tiny language of Boolean expressions. Everything is in plain Racket, with structs and `match`.

2.5.1 The Language and Its Representation

The grammar of *bexp*:

$$\langle bexp \rangle \ ::= \ \langle boolean \rangle \ \mid \ \langle bexp \rangle \wedge \langle bexp \rangle \ \mid \ \langle bexp \rangle \vee \langle bexp \rangle \ \mid \ \neg \langle bexp \rangle$$

One struct per alternative of the grammar represents it in Racket:

```
(struct leaf-node (arg))
(struct or-node (left right))
(struct and-node (left right))
(struct not-node (arg))

(define bexp-bool-1 (and-node (leaf-node #t) (leaf-node #f)))
(define bexp-sym-1 (and-node (leaf-node 'x) (leaf-node 'y)))
```

A value built from these structs is an *abstract syntax tree*: the tree structure replaces parentheses and precedence. Note that the structs are *not* transparent and their fields are unchecked: `bexp-sym-1` has symbols, not booleans, at its leaves, and Racket accepts it.

Exercise 21 (Syntactic equality)

Write `syn-equal?`, which checks whether two bexps are the same tree.

Solution. Because the structs are opaque, `equal?` would compare them by identity (Section 2.2), so we write structural equality ourselves. `match*` matches several values at once, one pattern per value:

```
(define (syn-equal? b1 b2)
  (match* (b1 b2)
    [((and-node l1 r1) (and-node l2 r2)) (and (syn-equal? l1 l2) (syn-equal? r1 r2))]
    [((or-node l1 r1) (or-node l2 r2))   (and (syn-equal? l1 l2) (syn-equal? r1 r2))]
    [((not-node a1) (not-node a2))       (syn-equal? a1 a2)]
    [((leaf-node v1) (leaf-node v2))     (equal? v1 v2)]
    [(_ _) #f]))
```

One clause per variant where both sides agree, and a final catch-all for mismatched shapes.

Pitfall 22 (A missing variant hides behind a catch-all)

If the `not-node` clause were left out, two `not-nodes` would fall through to `[(_ _) #f]`, and `syn-equal?` would say a negation is not equal to itself. Nothing would complain, and every later test comparing expressions with a negation would fail even with a correct optimizer. With a catch-all clause present, check the list of variants, not just the clauses you were given.

2.5.2 An Interpreter for bexp

Exercise 23 (Interpreter)

Write `evaluate-bexp`, which computes the Boolean value an expression represents.

Solution. One clause per variant, and a recursive call wherever a variant contains a sub-expression:

```
(define (evaluate-bexp b)
  (match b
    [(leaf-node v)    v]
    [(or-node b1 b2)  (or (evaluate-bexp b1) (evaluate-bexp b2))]
    [(and-node b1 b2) (and (evaluate-bexp b1) (evaluate-bexp b2))]
    [(not-node b1)    (not (evaluate-bexp b1))]))

(check-expect (evaluate-bexp (leaf-node #t)) #t)
(check-expect (evaluate-bexp (and-node (leaf-node #t) (leaf-node #f))) #f)
(check-expect (evaluate-bexp (and-node (leaf-node #f) (leaf-node #t))) #f)
```

The third test swaps the arguments of the second; testing both orders is cheap and catches an implementation that looks at only one side.

This is the pattern of every interpreter in the course: our language's $\wedge$ is implemented by Racket's `and`, its $\vee$ by `or`, its $\neg$ by `not`. The *meaning* of each construct is given by the clause that handles it.

Missing cases. What happens with an incomplete `match`?

```
(define (evaluate-bexp-m b)
  (match b
    [(leaf-node v) v]))
```

Nothing complains when it is defined. The error appears only when it is called on a value that no clause matches: `(evaluate-bexp-m bexp-bool-1)` raises `match: no matching clause`. Racket checks patterns at run time, so a missing case is found only if some test happens to reach it. Section 3.4 redoes this in `plai-typed`, where the same mistake is rejected before the program runs.

2.5.3 An Optimization Pass: De Morgan

De Morgan's laws and double-negation elimination state the equivalences

$$\neg(P \wedge Q) = \neg P \vee \neg Q, \qquad \neg(P \vee Q) = \neg P \wedge \neg Q, \qquad \neg\neg P = P.$$

Using them left to right, an optimizer can eliminate redundant negations and push every remaining negation down to the leaves. The examples use symbolic leaves:

name	before	after
`bexp-1`	$\neg(\neg P \vee Q)$	$P \wedge \neg Q$
`bexp-2`	$\neg\neg P \vee \neg Q$	$P \vee \neg Q$
`bexp-3`	$P \vee \neg Q$	$P \vee \neg Q$ (already optimal)

```
(define bexp-1 (not-node (or-node (not-node (leaf-node 'P)) (leaf-node 'Q))))
(define bexp-2 (or-node (not-node (not-node (leaf-node 'P))) (not-node (leaf-node 'Q))))
(define bexp-3 (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))

(define bexp-1-opt (and-node (leaf-node 'P) (not-node (leaf-node 'Q))))
(define bexp-2-opt (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))
(define bexp-3-opt (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))
```

What does it mean for an optimization to be correct?. Before writing the optimizer, decide how to check it. An optimization is correct when it does two things:

1. it *preserves semantics*: the output evaluates to the same value as the input;
2. it actually *optimizes*: the output has the promised shape, here every negation sitting directly on a leaf.

Both become executable checks:

```
(define (preserves-sem? unopt)
  (equal? (evaluate-bexp unopt) (evaluate-bexp (demorgan-opt unopt))))

(define (is-optimizing? opt)
  (define (only-not-at-leaves? bexp)
    (match bexp
      [(leaf-node v) #t]
      [(or-node b1 b2) (and (only-not-at-leaves? b1) (only-not-at-leaves? b2))]
      [(and-node b1 b2) (and (only-not-at-leaves? b1) (only-not-at-leaves? b2))]
      [(not-node (leaf-node v)) #t]
      [(not-node _) #f]))
  (only-not-at-leaves? opt))


(define (is-correct? unopt)
  (and (preserves-sem? unopt) (is-optimizing? (demorgan-opt unopt))))
```

`is-optimizing?` relies on `match` trying clauses in order: `(not-node (leaf-node v))` is tried first, so the catch-all `(not-node _)` sees only negations of compound expressions, which mean the pass left work undone. Note also that `preserves-sem?` takes only the input and calls `demorgan-opt` itself, so it tests the optimizer rather than a hand-written answer.

The optimizer. What to do with a negation depends entirely on what is *inside* it, so a single `(not-node b1)` clause cannot work. Nested patterns split it into the four shapes the argument can have, one per variant. This is what the handout means by "you will need more cases than in `evaluate-bexp`":

```
(define (demorgan-opt b)
  (match b
    ; Standard Stuff
    [(leaf-node v)    (leaf-node v)]
    [(or-node b1 b2)  (or-node (demorgan-opt b1) (demorgan-opt b2))]
    [(and-node b1 b2) (and-node (demorgan-opt b1) (demorgan-opt b2))]
    [(not-node (leaf-node l)) (not-node (leaf-node l))]
    ; De-Morgan Stuff
    [(not-node (and-node b1 b2))
     (or-node (demorgan-opt (not-node b1)) (demorgan-opt (not-node b2)))]
    [(not-node (or-node b1 b2))
     (and-node (demorgan-opt (not-node b1)) (demorgan-opt (not-node b2)))]
    [(not-node (not-node b1)) (demorgan-opt b1)]))
```

- **A negated leaf** is already as far down as a negation can go; keep it.
- **De Morgan.** After rewriting $\neg(b_1 \wedge b_2)$ to $\neg b_1 \vee \neg b_2$, the new negations may themselves sit on top of an `and`, an `or`, or a `not`, so they are optimized again: the recursive calls are on `(not-node b1)`, not on `b1`. Calling `(demorgan-opt b1)` would drop the negation and change the meaning.
- **Double negation.** The two negations cancel, and the result is `(demorgan-opt b1)`, not just `b1`, because `b1` may still contain negations to push down.



$\neg(\neg P \vee Q)$ $P \wedge \neg Q$

Figure 2.5: `bexp-1` before and after the pass. Negations (yellow) end up only directly above leaves.

For `bexp-1` (Figure 2.5):

```
(demorgan-opt (not (or (not P) Q)))
---> (and-node (demorgan-opt (not (not P))) (demorgan-opt (not Q)))   ; not over or
---> (and-node (demorgan-opt P) (not Q))                              ; not-not cancels
---> (and-node P (not Q))
```

Why it terminates. Every recursive call is on a smaller tree. In the De Morgan cases the argument `(not-node b1)` is new, but it is smaller than the input `(not-node (and-node b1 b2))`, which has one more node and all of `b2` besides.

2.5.4 Testing the Optimizer Two Ways

The syntactic tests compare against the exact trees written by hand:

```
(check-expect (syn-equal? (demorgan-opt bexp-1) bexp-1-opt) #t)
(check-expect (syn-equal? (demorgan-opt bexp-2) bexp-2-opt) #t)
(check-expect (syn-equal? (demorgan-opt bexp-3) bexp-3-opt) #t)
```

The semantic tests check the two correctness properties without writing the expected tree at all:

```
(define bexp-4 (not-node (or-node (not-node (leaf-node #t)) (leaf-node #f))))
(define bexp-5 (or-node (not-node (not-node (leaf-node #t))) (not-node (leaf-node #f))))
(define bexp-6 (or-node (leaf-node #t) (not-node (leaf-node #t))))
(check-expect (is-correct? bexp-4) #t)
(check-expect (is-correct? bexp-5) #t)
(check-expect (is-correct? bexp-6) #t)
```

Remark 24 (Why booleans at the leaves)**.** `bexp-4` to `bexp-6` are `bexp-1` to `bexp-3` with `#t` and `#f` in place of `'P` and `'Q`. With symbols at the leaves, `evaluate-bexp` is meaningless: `(not 'P)` is `#f` and `(or 'P #f)` is `'P`, because Racket treats every value except `#f` as true. So a semantic check only means something on Boolean leaves.

Remark 25 (The handout's table)**.** An earlier version of the handout listed $\neg(\neg P \wedge Q) \mapsto P \wedge Q$ as the first example. That contradicts both the code (`bexp-1` is built with `or-node`) and De Morgan's law; the posted solution corrects the row to $\neg(\neg P \vee Q) \mapsto P \wedge \neg Q$. Trust the definitions over the prose, and check the prose by working one example by hand.

Chapter 3

Week 3: Types and a First Interpreter

Lecture 3: September 22, 2026. Recitation 3: September 25, 2026.

Supplementary reading:

- [1] Chapters 2 (Everything (We Will Say) About Parsing) and 3 (A First Look at Interpretation).
- [1] Chapter 15 (Checking Program Invariants Statically: Types), first sections, and the `plai-typed` documentation.
- [5] Chapter 1 (what type systems are for), optional.

From this week on, code is written in `#lang plai-typed`, the language of the textbook: Racket with a type checker that reads the whole program before anything runs. Lecture 3 introduces its types, defines new types with `define-type`, and uses them to write the first interpreter of the course, a calculator. Recitation 3 redoes Recitation 2 with types and then studies Racket's `match` in more depth. This chapter covers:

- Section 3.1: types, type inference and annotations, function types, homogeneous lists, pairs, and polymorphism;
- Section 3.2: `define-type`, `type-case`, and exhaustiveness checking;
- Section 3.3: quote and s-expressions, concrete vs. abstract syntax, and the calculator's parser and interpreter;
- Section 3.4: Recitation 3, typed Boolean expressions and pattern matching with `match`.

3.1 Types in plai-typed

`plai-typed` is installed with `raco pkg install plai-typed`, and a file starts with `#lang plai-typed`. It looks like Racket, but a type checker reads the whole program first, and a program that fails the check does not run at all.

3.1.1 Every Value Has a Type

At the REPL, every answer comes with two lines: the type the checker worked out, starting with `-`, and then the value.

```
> 3
- number
3
> (+ 3 4)
- number
7
> "hello"
- string
"hello"
> (+ 3 "hello")
typecheck failed: number vs. string
```

This is the idea of the lecture in miniature: the type is known *before* the value is computed. The checker does not run `(+ 3 4)` to find out it is a number; it knows because `+` takes numbers and returns a number.

3.1.2 Type Inference and Annotations

No types need to be written. Here the checker sees `(+ 3 x)`, concludes that `x` must be a number, and that the result is one too:

```
(define (add3 x)
  (+ 3 x))
```

Definition 26 (Type inference)

Type inference is the checker working out the types that the programmer did not write down.

Types can also be written, as many or as few as we like. An argument becomes `(x : number)`, and the return type goes after the argument list. Whatever is left out is inferred:

```
(define (add3-v2 (x : number))            ; return type inferred
  (+ 3 x))

(define (add3-v3 (x : number)) : number   ; both annotated
  (+ 3 x))
```

Pitfall 27 (Spaces around the colon)

`(x: number)` is read as one identifier named `x:`, followed by `number`, and is rejected with `expected either <id> or '[<id> : <type>]'`. Write `(x : number)`.

An annotation is a claim the checker verifies, not a hint it trusts. This one is wrong, since `(+ 3 x)` is a number, so the definition is rejected:

```
(define (add3-v4 (x : number)) : string
  (+ 3 x))
;; typecheck failed: number vs. string
```

Either way the program is checked before it runs: a call like `(add3-v3 "hello")` never gets the chance to fail at run time, because the whole file is rejected.

If the checker can infer the types, why write them? Two reasons from lecture:

- **Documentation.** The reader sees what the function takes and returns without reading its body.
- **Mental model.** Writing the type first makes you decide what the function is supposed to do before you write how it does it.

3.1.3 Function Types

Functions are values, so they have types. Read the arrow as "takes . . . and returns . . . ":

```
> add3
- (number -> number)
```

With two arguments, both go to the left of the arrow. Annotations can be mixed: in `myadd-v2`, `y` is unannotated but added to a number, so it is inferred to be one, and the two functions have the same type.

```
(define (myadd x y)
  (+ x y))
(define (myadd-v2 (x : number) y) : number
  (+ x y))
```

```
> myadd
- (number number -> number)
> myadd-v2
- (number number -> number)
```

A function that returns a function, `make-adder` from Section 2.3, now has a type that says so:

```
(define (myadd-v3 (x : number))
  (lambda (y) (+ x y)))
```

```
> myadd-v3
- (number -> (number -> number))
> (myadd-v3 2)
- (number -> number)
> ((myadd-v3 2) 5)
- number
7
```

Compare the two types. `myadd` takes two numbers at once. `myadd-v3` takes *one* number and returns a function that waits for the second, so `(myadd-v3 2)` is not a number yet but a function.

3.1.4 Lists Are Homogeneous

A list type says what its elements are, and every element must have that type:

```
> (list 1 2 3 4)
- (listof number)
'(1 2 3 4)
> (cons 3 (cons 4 empty))
- (listof number)
'(3 4)
> (list 1 "hello")
typecheck failed: number vs. string
> (cons 3 4)
typecheck failed: (listof number) vs. number
```

Plain Racket accepts both of the last two. In `plai-typed` the second argument of `cons` must be a list, so bare pairs (Section 1.3) are impossible. In exchange, list operations have precise types: the checker knows `(first (list 1 2 3 4))` is a `number` and `(rest (list 1 2 3 4))` a `(listof number)`, and likewise for `second` and `third`, without running anything.

3.1.5 Pairs

When two values of different types belong together, use a *pair* (a tuple). Its type is written with `*`:

```
> (pair 1 "hello")
- (number * string)
'#(1 "hello")
> (fst (pair 1 2))
- number
1
> (snd (pair 1 2))
- number
2
> (car (pair 1 2))
car: unbound identifier
```

A list has any length but one element type; a pair has exactly two slots, each with its own type. A pair is not a cons cell, and `plai-typed` provides no `car` or `cdr` at all: use `fst`/`snd` for pairs and `first`/`rest` for lists.

3.1.6 Polymorphic Types

Asking for the type of `first` shows something new:

```
> first
- ((listof 'a) -> 'a)
> rest
- ((listof 'a) -> (listof 'a))
> cons
- ('a (listof 'a) -> (listof 'a))
> fst
- (('a * 'b) -> 'a)
> map
- (('a -> 'b) (listof 'a) -> (listof 'b))
```

Definition 28 (Type variable, parametric polymorphism)

`'a` (read "alpha") is a *type variable*: any type may stand in its place, but every `'a` in one type must stand for the *same* type. A single definition that works uniformly at every type in this way is *parametrically polymorphic*; other languages call it generics.

So `first` takes a `(listof number)` to a `number` and a `(listof string)` to a `string`, but can never take a list of numbers to a string. Different letters allow different types: `fst` takes a pair of an `'a` and a `'b` and returns the `'a`. And the type of `map` alone says most of what `map` does: given a function from `'a` to `'b` and a list of `'a`, it produces a list of `'b`.

3.1.7 Why Insist on Homogeneous Lists?

Suppose `(list 1 "hello")` were allowed; call it `l`. What is the type of `(first l)`? It depends on which element happens to come first, and the checker cannot know that before the program runs. Then

- every use of `first` would need a check at run time, which is exactly what a type checker is supposed to spare us, and
- `(map f l)` is only safe if `f` accepts *both* numbers and strings, which `('a -> 'b)` cannot express.

One could design a type that lists every position, something like `(listof number string number)` for `(list 1 "hello" 2)`, but then every list function (`map`, `filter`, the folds) would need a far more complicated type. The simpler fix keeps lists homogeneous and instead makes *one* type that covers all the kinds of things to be mixed. That is what `define-type` is for.

3.2 define-type and type-case

3.2.1 Defining a Type with Variants

A shape is either a circle or a rectangle:

```
(define-type Shape
  [circle (radius : number)]                       ; variant 1
  [rectangle (width : number) (height : number)])  ; variant 2
```

This defines one new type, Shape, with two *variants*. Each variant has a constructor and typed fields:

```
> (circle 3)
- Shape
(circle 3)
```

Now `(list (circle 1) (rectangle 2 3))` is fine: the elements are different kinds of shapes, but they have one type, so the list is a `(listof Shape)`.

Like `struct`, `define-type` also generates

- predicates `circle?` and `rectangle?`, of type `(Shape -> boolean)`, and
- accessors `circle-radius`, `rectangle-width`, and `rectangle-height`, of type `(Shape -> number)`.

The predicates accept only shapes. In plain Racket `(circle? 5)` would return `#f`; here it never runs:

```
> (circle? 5)
typecheck failed: Shape vs. number
```

A recursive type. A type may mention itself. The binary tree of Section 2.2, now with types:

```
(define-type Tree
  [emp]
  [node (n : number) (lt : Tree) (rt : Tree)])
```

A variant with no fields is still a constructor, so the empty tree is `(emp)`, with parentheses. `(node 3 (emp) (emp))` has type Tree.

3.2.2 struct vs. define-type

Both make compound values, but they promise different things:

`struct` (`#lang racket`)	`define-type` (`plai-typed`)
one kind of value: a `bt` is always a `bt`	one *type* with several variants: `circle` or `rectangle`
fields unchecked: `(bt 1 2 3)` is accepted, and fails later	every field typed: `(node 3 5 (emp))` is rejected before the program runs, at the line that is wrong
different structs cannot share a homogeneous list type	all variants fit in one `(listof Shape)`

Why only one `circle?`. No other type in the program may also have a variant named `circle`. The immediate reason is that `circle`, `circle?`, and `circle-radius` are ordinary definitions, so a second `define-type` would define them again (`identifier already defined`). The deeper reason is inference: when the checker sees

(circle 3), the constructor's name is all it has to go on. If two types both had a circle variant, (circle 3) could belong to either, and inference would be stuck.

3.2.3 type-case: Taking a Value Apart

A define-type value is built with a constructor; type-case takes it apart again. There is one clause per variant, and the names in parentheses are bound to that variant's fields, in order (the names need not match those in define-type; only the order matters):

```
(define (area s)
  (type-case Shape s
    [circle (r) (* 3.14159 (* r r))]
    [rectangle (w h) (* w h)]))
```

```
> (area (circle 3))
- number
28.27431
> area
- (Shape -> number)
```

The same function can be written with the generated predicates and accessors:

```
(define (area-v2 s)
  (cond
    [(circle? s) (* 3.14159 (* (circle-radius s) (circle-radius s)))]
    [(rectangle? s) (* (rectangle-width s) (rectangle-height s))]))
```

It works, but type-case is shorter, names the fields, and lines the code up with the type: one clause per variant, just as list functions had one cond branch per kind of list.

3.2.4 Exhaustiveness

The real difference shows when a case is forgotten. type-case knows every variant of Shape, so leaving one out is rejected before the program runs:

```
(define (area-v3 s)
  (type-case Shape s
    [circle (r) (* 3.14159 (* r r))]))
;; type-case: syntax error; probable cause: you did not include a case
;; for the rectangle variant, or no else-branch was present
```

cond knows nothing about Shape; it tries its tests in order. The same mistake with cond is accepted, works on circles, and fails only at run time when it meets a rectangle:

```
(define (area-v4 s)
  (cond
    [(circle? s) (* 3.14159 (* (circle-radius s) (circle-radius s)))]))
```

```
> (area-v4 (circle 1))
- number
3.14159
> (area-v4 (rectangle 2 3))
cond: no matching clause
```

Key Point 29 (What `type-case` buys)

`type-case` checks before the program runs that every variant is handled, and it gives each clause the variant's fields with their types. A missing case is a static error, not a bug waiting for the right input.

3.3 S-Expressions and the Calculator

3.3.1 Quote and Symbols

The apostrophe `'`, read "quote", means "do not evaluate this; keep it as data". Without it, `x` is a variable to look up. With it, `'x` is the name itself, a *symbol*:

```
> x
x: free variable while typechecking in: x
> 'x
- symbol
'x
```

Quoting a parenthesized expression keeps the whole thing as data, without doing the addition:

```
> '(1 (+ 2 3) 4)
- s-expression
'(1 (+ 2 3) 4)
```

3.3.2 S-Expressions

Look at what `'(+ 2 3)` contains: a symbol and two numbers. That is exactly the kind of mixed list that Section 3.1 ruled out. So `plai-typed` gives all quoted data one type, `s-expression`, and provides functions to ask what a piece is and to convert it back out:

```
> (s-exp->list '(+ 2 3))
- (listof s-expression)
'(+ 2 3)
> (first (s-exp->list '(+ 2 3)))
- s-expression
'+
> (s-exp->symbol (first (s-exp->list '(+ 2 3))))
- symbol
'+
> (s-exp->number (second (s-exp->list '(+ 2 3))))
- number
2
```

Key Point 30 (Ask, then convert)

Ask with `s-exp-number?`, `s-exp-symbol?`, or `s-exp-list?`, then convert with the matching `s-exp->number`, `s-exp->symbol`, or `s-exp->list`. A conversion fails at run time if the guess was wrong.

Pitfall 31 (A lone quoted symbol is not an s-expression)

`'x` has type `symbol`, not `s-expression`, so `(parse 'x)` is a type error. To get an s-expression for one symbol, write `` `x `` (backquote) or `(symbol->s-exp 'x)`.

3.3.3 Concrete and Abstract Syntax

The first interpreter is a calculator:

```
'(+ 2 3)                    ===> 5
'(* 3 4)                    ===> 12
'(* (+ 2 3) (* 5 (+ 6 7)))  ===> 325
```

Following [1, Chapters 2–3], the work is split into separate steps (Figure 3.1):

- **Concrete syntax** is what the programmer types, the text `(+ 2 3)`. Racket's *reader* already turns text into an s-expression, so we get that step for free; quote is how we hand an s-expression over directly.
- **Abstract syntax** is a tree that keeps only the meaning. `parse` turns an s-expression into this tree, rejecting anything that is not a valid program.
- The **interpreter** walks the tree and computes the answer. [1] calls it `interp`; in lecture it is `eval`.




Figure 3.1: The interpreter pipeline. Racket's reader provides the first step.

3.3.4 The Calculator

Abstract syntax. One variant per kind of expression:

```
(define-type ArithE
  [numC (n : number)]
  [plusC (e1 : ArithE) (e2 : ArithE)]
  [timesC (e1 : ArithE) (e2 : ArithE)])
```

The operands of `plusC` are ArithE, not `number`. That is what allows `'(* (+ 2 3) 4)`: the left operand of the multiplication is itself an addition, the same trick as Tree having subtrees (Figure 3.2).




Figure 3.2: The abstract syntax of `'(* (+ 2 3) (* 5 (+ 6 7)))`. Parentheses are gone; the nesting is the tree.

The interpreter. One clause per variant:

```
(define (eval (e : ArithE)) : number
  (type-case ArithE e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval e1) (eval e2))]
    [timesC (e1 e2) (* (eval e1) (eval e2))]))
```

Three variants, three clauses, and a recursive call wherever the type mentions ArithE. `eval` never checks whether its input makes sense, and it does not have to: a value of type ArithE can only be built from the three constructors, so every tree it receives is well formed.

The parser. That guarantee has to come from somewhere, and it comes from `parse`. The version written in lecture:

```
(define (parse (s : s-expression)) : ArithE
  (cond
    [(s-exp-number? s) (numC (s-exp->number s))]
    [(s-exp-list? s)
     (let [(l (s-exp->list s))]
       (case (s-exp->symbol (first l))
         [(+) (plusC (parse (second l)) (parse (third l)))]
         [(*) (timesC (parse (second l)) (parse (third l)))]))]))
```

A number becomes a `numC`. A list is dispatched on its first element with `case`, which compares a symbol against literal symbols, and each operand is parsed recursively. Putting the steps together, `(eval (parse '(* (+ 2 3) (* 5 (+ 6 7)))))` is 325.

3.3.5 What Malformed Input Does

The lecture parser is right on well-formed input, but on bad input it either crashes with a message about something else, or quietly builds a wrong tree:

input	result
`(parse '(- 1 2))`	`case: no matching clause`
`(parse '(+ 1))`	`third: list contains too few elements`
`(parse '(+ 1 2 3))`	`(plusC (numC 1) (numC 2))`: the 3 is silently dropped

The last one is the worst kind of bug: no error, just a program that means something other than what was written. A more careful parser checks the shape of each form and reports what was expected. This version is not from lecture, but every check in it addresses one row of the table:

```
(define (parse (s : s-expression)) : ArithE
  (cond
    [(s-exp-number? s) (numC (s-exp->number s))]
    [(s-exp-list? s)
     (let [(l (s-exp->list s))]
       (if (and (= (length l) 3) (s-exp-symbol? (first l)))
           (case (s-exp->symbol (first l))
             [(+) (plusC (parse (second l)) (parse (third l)))]
             [(*) (timesC (parse (second l)) (parse (third l)))]
             [else (error 'parse "unknown operator")])
           (error 'parse "expected (op e1 e2)")))]
    [else (error 'parse "expected a number or a list")]))
```

- The length check rejects `'(+ 1)` and `'(+ 1 2 3)`.
- `s-exp-symbol?` rejects `'(1 2 3)`, whose head is not an operator at all.
- The `else` of `case` rejects operators the language does not have, such as `-`.

- The final `else` rejects anything that is neither a number nor a list, such as a lone symbol.

3.4 Recitation 3: Typed Boolean Expressions and Pattern Matching

Recitation 3 has two halves. Part A (handout 3a) redoes Recitation 2's interpreter and De Morgan optimizer in `plai-typed`, to see what the type checker buys. Part B (handout 3b) returns to plain Racket and studies `match`: literal patterns, wildcards, and taking lists apart.

3.4.1 Part A: Boolean Expressions, Typed

From four structs to one type. In Section 2.5, a Boolean expression was built from four unrelated structs; "a bexp" existed only in our heads, and no field had a type. With `define-type`, the four become variants of *one* type, and every field says what it holds:

```
(define-type bexp-b
  [leaf-node-b (b : boolean)]
  [and-node-b (b1 : bexp-b) (b2 : bexp-b)]
  [or-node-b (b1 : bexp-b) (b2 : bexp-b)]
  [not-node-b (b : bexp-b)])
```

Exercise 32 (Typed evaluator)

Implement `evaluate-bexp-b` with `type-case`.

Solution. `type-case` plays the role `match` played last week:

```
(define (evaluate-bexp-b [b : bexp-b]) : boolean
  (type-case bexp-b b
    [leaf-node-b (v) v]
    [and-node-b (b1 b2) (and (evaluate-bexp-b b1) (evaluate-bexp-b b2))]
    [or-node-b (b1 b2) (or (evaluate-bexp-b b1) (evaluate-bexp-b b2))]
    [not-node-b (b1) (not (evaluate-bexp-b b1))]))

(test (evaluate-bexp-b (leaf-node-b #t)) #t)
(test (evaluate-bexp-b (and-node-b (leaf-node-b #t) (leaf-node-b #f))) #f)
(test (evaluate-bexp-b (not-node-b (or-node-b (leaf-node-b #f) (leaf-node-b #f)))) #t)
```

`test` is `plai-typed`'s `check-expect`, and `(print-only-errors true)` at the top of the file makes passing tests silent. This is the same shape as `eval` for ArithE in Section 3.3.

What do the types buy us?.

(a) **Bad leaves are rejected before anything runs.** Last week's `bexp-sym-1` was

```
(and-node (leaf-node 'x) (leaf-node 'y))
```

and `evaluate-bexp` happily returned `'y`: Racket treats every value except `#f` as true, so `(and 'x 'y)` is `'y`. No error, just an answer of the wrong kind. The typed version

```
(evaluate-bexp-b (and-node-b (leaf-node-b 'x) (leaf-node-b 'y)))
```

is rejected (`typecheck failed: boolean vs. symbol`) before anything runs, and the error points at the leaf that is wrong, not at some later function that trips over it.

(b) **Missing cases are rejected too.** Last week's `evaluate-bexp-m` handled only leaves; it was accepted and failed only when called on something else. The typed version

```
(define (evaluate-bexp-b-m [b : bexp-b]) : boolean
  (type-case bexp-b b
    [leaf-node-b (v) v]))
```

stops the program from starting: `you did not include a case for the and-node-b variant`. This is the `area-v3`/`area-v4` contrast of Section 3.2 again.

De Morgan, typed. Now the leaves are variables:

```
(define-type bexp
  [leaf-node (s : symbol)]
  [and-node (b1 : bexp) (b2 : bexp)]
  [or-node (b1 : bexp) (b2 : bexp)]
  [not-node (b1 : bexp)])
```

Exercise 33 (Port `demorgan-opt` to `plai-typed`)

Rewrite the optimizer of Section 2.5 for the type bexp.

Solution. Last week's `match` could name a nested pattern directly, such as `(not-node (and-node b1 b2))`. A `type-case` clause only takes apart the *outermost* constructor, so the `not-node` clause needs a second `type-case`, on the thing being negated:

```
(define (demorgan-opt [b : bexp]) : bexp
  (type-case bexp b
    [leaf-node (v) (leaf-node v)]
    [and-node (b1 b2) (and-node (demorgan-opt b1) (demorgan-opt b2))]
    [or-node (b1 b2) (or-node (demorgan-opt b1) (demorgan-opt b2))]
    [not-node (b1)
      (type-case bexp b1
        [leaf-node (v) (not-node (leaf-node v))]
        [and-node (b2 b3) (or-node (demorgan-opt (not-node b2))
                                   (demorgan-opt (not-node b3)))]
        [or-node (b2 b3) (and-node (demorgan-opt (not-node b2))
                                   (demorgan-opt (not-node b3)))]
        [not-node (b2) (demorgan-opt b2)])]))
```

The inner clauses are the four nested patterns of last week, one per variant of the negated expression: a negated leaf stays; $\neg(b_2 \wedge b_3)$ becomes $\neg b_2 \vee \neg b_3$ with both new negations optimized again; $\neg(b_2 \vee b_3)$ symmetrically; and $\neg\neg b_2$ becomes the optimized b_2. Both `type-case`s are checked for exhaustiveness, so a forgotten shape of negation is now a static error.

The tests no longer need `syn-equal?`: `test` compares `define-type` values structurally.

```
(define bexp-1 (not-node (or-node (not-node (leaf-node 'P)) (leaf-node 'Q))))
(define bexp-2 (or-node (not-node (not-node (leaf-node 'P))) (not-node (leaf-node 'Q))))
(define bexp-3 (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))

(test (demorgan-opt bexp-1) (and-node (leaf-node 'P) (not-node (leaf-node 'Q))))
(test (demorgan-opt bexp-2) (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))
(test (demorgan-opt bexp-3) (or-node (leaf-node 'P) (not-node (leaf-node 'Q))))
```

3.4.2 Part B: Pattern Matching with `match`

So far `match` has only taken structs apart. It can also match literal values, ignore parts of the input with wildcards, and take lists apart.

Matching on values. A pattern can be a literal, which makes `match` a compact conditional:

```
(define (factorial x)
  (match x
    [0 1]
    [_ (* x (factorial (- x 1)))]))

(define (factorial-if x)
  (if (= x 0)
      1
      (* x (factorial-if (- x 1)))))
```

_ is the *wildcard*: it matches anything and binds nothing. Clauses are tried top to bottom, so _ goes last as the catch-all. With two cases `match` and `if` are about the same size; with more, nested `if`s pile up:

```
(define (fibonacci-if x)
  (if (= x 0)
      0
      (if (= x 1)
          1
          (+ (fibonacci-if (- x 1)) (fibonacci-if (- x 2))))))
```

Exercise 34 (Fibonacci with `match`)

Rewrite `fibonacci-if` using `match`.

Solution. One line per case, and the structure stays flat:

```
(define (fibonacci x)
  (match x
    [0 0]
    [1 1]
    [_ (+ (fibonacci (- x 1)) (fibonacci (- x 2)))]))

(check-expect (fibonacci 1) 1)
(check-expect (fibonacci 10) 55)
(check-expect (fibonacci 10) (fibonacci-if 10))
```

Exercise 35 (What is `else`?)

`[else ...]` often appears as the last clause of a `match`. Predict `(match 5 [else else])`.

Solution. It is `5`. Inside `match`, `else` is not a keyword but a *pattern variable*, like `x`: it matches anything and is bound to what it matched. So here `else` is bound to 5 and the clause returns it. That is why `[else ...]` happens to work as a catch-all; but it is an accident, and it quietly binds a variable named `else` in the body. Use _ instead.

Destructuring lists. Two attempts at "the third element of a list":

```
(define (my-third x)
  (match x
    [(list a b c d) c]
    [_ x]))

(define (other-third lst)
  (match lst
    [(cons _ (cons _ (cons third _))) third]
    [_ (error "List too short")]))
```

Exercise 36 (Predict)

On which inputs do the two functions behave differently, and why?

Solution. `(list a b c d)` matches a list of *exactly* four elements. `(cons _ (cons _ (cons third _)))` matches any list of *at least* three: the last _ matches whatever rest is left, including `'()`.

input	`my-third`	`other-third`
`(list 2 3)`	`'(2 3)`	error `"List too short"`
`0`	`0`	error
`(list '(2 3) 2 4 5 6 7)`	the whole list	`4`
`(list 1 2 3 4)`	`3`	`3`

```
(check-expect (my-third (list 2 3)) (list 2 3))
(check-expect (my-third 0) 0)
(check-expect (my-third (list '(2 3) 2 4 5 6 7)) (list '(2 3) 2 4 5 6 7))
(check-expect (my-third (list 1 2 3 4)) 3)

(check-error (other-third (list 2 3)) "List too short")
(check-error (other-third 0) "List too short")
(check-expect (other-third (list '(2 3) 2 4 5 6 7)) 4)
(check-expect (other-third (list 1 2 3 4)) 3)
```

`my-third` is right only on four-element lists, and when it is wrong it does not fail: the fallback `[_ x]` hands back its input, so the caller gets a list or a number where it expected the third element. That is the same kind of silent wrong answer as the calculator parser turning `'(+ 1 2 3)` into $1 + 2$ (Section 3.3). Raising an error, as `other-third` does, is better.

Exercise 37 (Fix `my-third`)

Make `my-third` return the third element of any list with at least three elements and raise an error otherwise, using a `list` pattern. Hint: `_ ...` matches zero or more elements.

Solution.

```
(define (my-third-fixed x)
  (match x
    [(list _ _ c _ ...) c]
    [_ (error "List too short")]))

(check-error (my-third-fixed (list 2 3)) "List too short")
(check-expect (my-third-fixed (list 1 2 3)) 3)
(check-expect (my-third-fixed (list '(2 3) 2 4 5 6 7)) 4)
```

This is equivalent to `other-third`'s nested `cons` pattern, and easier to read.

3.4.3 `match` vs. `type-case`

The two halves used two tools for taking values apart. Each is strong where the other is weak:

	`match`	`type-case`
language	`racket`	`plai-typed`
nested patterns	yes: `(not-node (and-node b1 b2))`	no: one level; nest another `type-case`
literals, wildcards, lists	yes	no
missing case	run-time error, only if reached	rejected before the program runs

`match` is more expressive. `type-case` is more limited, and in exchange it can check, before anything runs, that every variant is handled. Recitation 4 (Section 4.5) implements a small `match` in our own interpreter.

Chapter 4

Week 4: Names and Functions

Lecture 4: September 29, 2026. Recitation 4: October 2, 2026.

Supplementary reading:

- [1] Chapter 5 (Adding Functions to the Language), which implements functions by substitution as this week does, and Chapter 6 (From Substitution to Environments) for where the course goes next.
- [5] Sections 5.2–5.3 (the untyped lambda calculus: free variables, substitution, and α-conversion), optional.

Lecture 4 gives the calculator *names* and then *functions*. Both are implemented by substitution, and the lecture's real subject is how subtle substitution is: when to evaluate the thing being substituted, how inner bindings shadow outer ones, and how a careless substitution can *capture* a variable and change a program's meaning. Recitation 4 adds a `match` form to the same interpreter. This chapter covers:

- Section 4.1: `idC` and `letC`, eager substitution, and shadowing;
- Section 4.2: lazy substitution, its costs and benefits, and the variable-capture bug;
- Section 4.3: capture-avoiding substitution with fresh names from `gensym`;
- Section 4.4: `lambda` and application, a new `Value` type, eager and lazy application, and capture again, now also under eager evaluation;
- Section 4.5: Recitation 4, pattern matching in the interpreter.

4.1 Names: `let` and Substitution

4.1.1 The Plan

At the end of Chapter 3 the calculator had `numC`, `plusC`, and `timesC`. The first new form is `(let x e1 e2)`: compute `e1`, replace every `x` in `e2` with that value, then compute `e2`.

```
(let x 5 (+ x x))
---> (+ 5 5)                 replace every x in the body with 5
---> 10

(let x (+ 1 5) (+ x x))
---> (let x 6 (+ x x))       e1 is evaluated first
---> (+ 6 6)
---> 12
```

4.1.2 Two New Variants

```
(define-type ArithE
  [numC (n : number)]
  [idC (x : symbol)]
  [plusC (e1 : ArithE) (e2 : ArithE)]
  [timesC (e1 : ArithE) (e2 : ArithE)]
  [letC (x : symbol) (e1 : ArithE) (e2 : ArithE)])
```

(Section 4.4 adds two more variants for functions; from then on every function on ArithE has a case for them.)

What is `idC` for?. An `idC` is a *use* of a name, such as the `x` in `(+ x 1)`. The operands of `plusC` must be ArithEs, so a bare symbol `'x` cannot go there; `idC` wraps the symbol so a name can sit in the tree until substitution replaces it. It does for symbols what `numC` does for numbers.

A name appears in two roles, and only one of them is an `idC`:

```
;; (let x 5 (+ x 1))
(letC 'x (numC 5) (plusC (idC 'x) (numC 1)))
;;    ^ binding: a plain symbol    ^ use: an idC
```

The name right after `let` is being *bound*. It is a plain symbol field of `letC`, because it is never evaluated or replaced; it only tells substitution which name to look for. Symbols like `+` and `let` never become `idC`s either: `parse` consumes them to decide which variant to build. Writing `(plusC 'x (numC 1))` is a type error, since `'x` is a symbol and not an ArithE.

Parsing. A lone symbol becomes an `idC`. In `(let x e1 e2)` the `x` is taken as a plain symbol, while `e1` and `e2` are parsed recursively:

```
(define (parse (s : s-expression)) : ArithE
  (cond
    [(s-exp-number? s) (numC (s-exp->number s))]
    [(s-exp-symbol? s) (idC (s-exp->symbol s))]
    [(s-exp-list? s)
     (let [(l (s-exp->list s))]
       (case (s-exp->symbol (first l))
         [(+) (plusC (parse (second l)) (parse (third l)))]
         [(*) (timesC (parse (second l)) (parse (third l)))]
         [(let) (letC (s-exp->symbol (second l)) (parse (third l)) (parse (fourth l)))]))]))
```

As in lecture 3, there is no error checking: `(parse '(let x 1))` fails inside `fourth` with `list contains too few elements`.

4.1.3 Eager Substitution

`(subst-eager v x e)` replaces every `x` in `e` with the number `v`. Most variants just recurse into their children; the interesting cases are the ones that mention names.

```
(define (subst-eager (v : number) (x : symbol) (e : ArithE)) : ArithE
  (type-case ArithE e
    [numC (n) (numC n)]
    [idC (y) (if (equal? x y) (numC v) (idC y))]
    [plusC (e1 e2) (plusC (subst-eager v x e1) (subst-eager v x e2))]
    [timesC (e1 e2) (timesC (subst-eager v x e1) (subst-eager v x e2))]
    [letC (y e1 e2)
          (letC y
                (subst-eager v x e1)
                (if (equal? x y) e2 (subst-eager v x e2)))]))
```

Why `(numC v)` and `(idC y)`?. `subst-eager` returns an ArithE tree, but `v` is a number, so it is wrapped as `(numC v)` to go back into the tree. An `idC` for a different name is left alone: `(idC y)` rebuilds the same node, which is equivalent to returning `e`.

```
(subst-eager 5 'x (plusC (idC 'x) (idC 'y)))   ; = (plusC (numC 5) (idC 'y))
```

4.1.4 Shadowing

What is `(let x 5 (let x 6 (+ x x)))`: 12 or 10? The answer is 12. The inner `let` binds its own `x`, so inside its body `x` means 6: the inner `x` *shadows* the outer one (Figure 4.1).




Figure 4.1: Each use of a name refers to the nearest enclosing binder of that name.

That is the `(equal? x y)` check in the `letC` case: when an inner `let` binds the same name we are substituting for, substitution stops at its body.

```
(let x 5 (let x 6 (+ x x)))
---> (let x 6 (+ x x))       the outer subst leaves the inner body alone
---> (+ 6 6)
---> 12
```

Substituting blindly would give `(let x 6 (+ 5 5))`, which is 10. The inner `e1` is still substituted, because it sits *outside* the inner binding; the inner `x` exists only in the inner body:

```
(let x 1 (let x (+ x 1) x))
---> (let x (+ 1 1) x)       the x in e1 is the outer x
---> 2
```

4.1.5 `eval-eager`

```
(define (eval-eager (e : ArithE)) : number
  (type-case ArithE e
    [numC (n) n]
    [idC (x) (error 'eval "unbound variable")]
    [plusC (e1 e2) (+ (eval-eager e1) (eval-eager e2))]
    [timesC (e1 e2) (* (eval-eager e1) (eval-eager e2))]
    [letC (y e1 e2) (eval-eager (subst-eager (eval-eager e1) y e2))]))
```

The `letC` line is the plan written out: evaluate `e1`, substitute the resulting number for `y` in `e2`, and evaluate the result. `eval-eager` never meets an `idC` that some `let` bound, because the enclosing `letC` has already substituted it away. An `idC` that survives was never bound, as in `(+ x 1)`, so it is an error.

```
(let x 5 (let y (+ x 1) (* x y)))
letC x: eval e1 = 5, subst 5 for x in the body
---> (let y (+ 5 1) (* 5 y))
letC y: eval e1 = 6, subst 6 for y in the body
---> (* 5 6)
---> 30
```

Each `let` removes the `idC`s for its own name; once every `let` has been processed, none is left.

4.2 Lazy Substitution and Variable Capture

4.2.1 Lazy Substitution

An alternative: do not evaluate `e1` first. Substitute the unevaluated tree into the body, where it is evaluated each time the body uses it.

```
(let x (+ 1 1) (+ x 2))
eager:  ---> (let x 2 (+ x 2))  ---> (+ 2 2)  ---> 4
lazy:   ---> (+ (+ 1 1) 2)                    ---> 4
```

`subst-lazy` is `subst-eager` with `v` an ArithE, the unevaluated `e1`, which goes into the tree as is, with no `numC` wrapping:

```
(define (subst-lazy (v : ArithE) (x : symbol) (e : ArithE)) : ArithE
  (type-case ArithE e
    [numC (n) e]
    [idC (y) (if (equal? x y) v e)]
    [plusC (e1 e2) (plusC (subst-lazy v x e1) (subst-lazy v x e2))]
    [timesC (e1 e2) (timesC (subst-lazy v x e1) (subst-lazy v x e2))]
    [letC (y e1 e2)
          (letC y
                (subst-lazy v x e1)
                (if (equal? x y) e2 (subst-lazy v x e2)))]))

(define (eval-lazy (e : ArithE)) : number
  (type-case ArithE e
    [numC (n) n]
    [idC (x) (error 'eval "unbound variable")]
    [plusC (e1 e2) (+ (eval-lazy e1) (eval-lazy e2))]
    [timesC (e1 e2) (* (eval-lazy e1) (eval-lazy e2))]
    [letC (y e1 e2) (eval-lazy (subst-lazy e1 y e2))]))
```

Pitfall 38 (Mixing evaluators)

Every recursive call in `eval-lazy` must be to `eval-lazy`. If one called `eval-eager`, the type checker would not complain, since both return a number, but inner `lets` would silently become eager.

4.2.2 Is Lazy More Efficient?

When `x` is unused, yes: `e1` is never evaluated.

```
(let x (+ 5 6) 10)
eager:  (let x 11 10) ---> 10      (+ 5 6) computed once, for nothing
lazy:   10                         (+ 5 6) never computed
```

So `(let x (/ 5 0) 10)` would not be an error in the lazy version (if the language had `/`), and neither is an unbound name in `e1`: `(let x (+ y y) 10)` is an error eagerly but 10 lazily.

When `x` is used more than once, lazy is *less* efficient, since `e1` is recomputed at every use:

```
(let x (+ 5 6) (+ (+ x x) x))
eager:  (+ 5 6) once     ---> (+ (+ 11 11) 11)
lazy:   (+ 5 6) 3 times  ---> (+ (+ (+ 5 6) (+ 5 6)) (+ 5 6))
```

4.2.3 Where Eager and Lazy Differ

program	eager	lazy
`(let x (+ y y) 10)`	`unbound variable`	`10`
`(let y x (let x 2 y))`	`unbound variable`	`2`

The first difference is harmless: `x` is unused, so lazy never evaluates `e1` and never notices the unbound `y`. The second is a real bug.

4.2.4 Variable Capture

```
(let x y (let y 2 (+ x y)))
lazy:
---> (let y 2 (+ y y))        the free y is captured by the inner let
---> (+ 2 2)
---> 4
```

The outer `y` is free: nothing binds it, so the correct answer is an error. Racket agrees; the same program in `#lang racket` is rejected with `y: unbound identifier` before it runs. But lazy substitution moved that free `y` underneath `(let y 2 ...)`, where it now refers to the inner `y` (Figure 4.2).




Figure 4.2: Capture. The substituted `y` (red arrow) ends up bound by an inner `let` it had nothing to do with.

Now rename the inner `y` to `z`:

```
(let x y (let z 2 (+ x z)))
lazy:
---> (let z 2 (+ y z))
---> (+ y 2)
---> eval: unbound variable
```

Key Point 39 (Names of bound variables should not matter)

The two programs differ only in renaming the inner `y` to `z`, so they must mean the same thing. Yet lazy substitution gives 4 for one and an error for the other. This bug is called *variable capture*, and a substitution that can cause it is *capturing*.

`eval-eager` does not have this problem: it only ever substitutes numbers, and a number contains no names to capture. Lazy substitution substitutes whole expressions, which can contain free variables. (Once values can be functions, eager evaluation substitutes code too, and capture returns; see Section 4.4.4.)

4.3 Capture-Avoiding Substitution

4.3.1 Rename, Then Substitute

The fix is *capture-avoiding substitution*: before substituting into the body of an inner `let`, rename its bound variable to a fresh name that appears nowhere else. Renaming a bound variable never changes what a program means (that was the point of the y/z example), so we are free to do it whenever it helps.

```
(let x y (let y 2 (+ x y)))
---> (let x y (let g3189 2 (+ x g3189)))    rename the inner y first
---> (let g3189 2 (+ y g3189))              the free y is no longer captured
---> (+ y 2)
---> eval: unbound variable                 same answer as the z version
```

The only question is where the fresh name comes from.

4.3.2 `gensym`: Fresh Names

`gensym` ("generate symbol") is a Racket function that returns a brand-new symbol every time it is called:

```
> (gensym)
'g3189
> (gensym)
'g3190
> (equal? (gensym) (gensym))
#f
```

A name chosen by hand, such as `'tmp`, does not work: the program might already use `tmp`, and then the renaming would create exactly the capture it was meant to avoid.

Definition 40 (Uninterned symbol)

An ordinary symbol is *interned*: `'y` is the same symbol wherever it is written, so `(equal? 'y 'y)` is `#t`. The symbol returned by `gensym` is *uninterned*: it is different from every other symbol, including one spelled the same way.

Even if a program literally contained the name `g3189`, it would not be `equal?` to the `g3189` that `gensym` returned:

```
(define g (gensym))                              ; prints as 'g3189
(equal? g (string->symbol (symbol->string g)))   ; #f
```

So a gensym can never be captured by, or capture, any name the user wrote.

Importing it into `plai-typed`. `plai-typed` does not provide `gensym`, and it cannot check a plain Racket import without knowing its type. `typed-in` imports a function from a Racket module and declares its type at the same time:

```
(require (typed-in racket/base [gensym : (-> symbol)]))
```

`(-> symbol)` means "takes no arguments and returns a symbol". The checker trusts this declaration; it does not check Racket's code.

4.3.3 `subst-lazy-v2`

Only the binding case changes. If the inner `let` binds the same name as the one being replaced, stop, as before. Otherwise:

1. let `z` be `(gensym)`, a name that appears nowhere else;
2. rename `y` to `z` in the body: `(subst-lazy (idC z) y e2)`. This cannot cause capture, because no `let` inside `e2` binds the fresh `z`;
3. substitute `v` for `x` in the renamed body.

```
(define (subst-lazy-v2 (v : ArithE) (x : symbol) (e : ArithE)) : ArithE
  (type-case ArithE e
    [numC (n) e]
    [idC (y) (if (equal? x y) v e)]
    [plusC (e1 e2) (plusC (subst-lazy-v2 v x e1) (subst-lazy-v2 v x e2))]
    [timesC (e1 e2) (timesC (subst-lazy-v2 v x e1) (subst-lazy-v2 v x e2))]
    [letC (y e1 e2)
          (if (equal? x y)
              (letC y (subst-lazy-v2 v x e1) e2)
              (let [(z (gensym))]
                (letC z
                      (subst-lazy-v2 v x e1)
                      (subst-lazy-v2 v x (subst-lazy (idC z) y e2)))))]))
```

```
(subst-lazy-v2 (idC 'y) 'x (parse '(let y 2 (+ x y))))
;; = (letC 'g3445 (numC 2) (plusC (idC 'y) (idC 'g3445)))
```

The inner `y` became `g3445`, and the `y` that came from outside is still free, so evaluation reports it as unbound. Now the `y` and `z` versions of the program agree.

The lecture's version (`lec4a.rkt`) splits the `letC` case three ways: `x` equals `y`; `y` is `possibly-free?` in `v`, so rename; otherwise substitute without renaming. Its `possibly-free?` is a stub that always returns `#t`, so it behaves exactly like the two-way code above. Implementing `possibly-free?` properly, so that renaming happens only when needed, is left as an exercise (see the free-variable definition in Section 4.1).

Remark 41. Step 2 uses the old `subst-lazy`, which may capture in general. It is safe here because the expression being substituted, `(idC z)`, contains only the fresh name `z`, which nothing in `e2` can bind.

4.4 Functions: `lambda` and Application

4.4.1 Syntax

The last part of the lecture adds functions:

syntax	meaning	abstract syntax
`(lambda x e)`	a function with parameter `x` and body `e`	`lambdaC`
`(e1 e2)`	call the function `e1` on the argument `e2`	`appC`

```
(define-type ArithE
  [numC (n : number)]
  [idC (x : symbol)]
  [plusC (e1 : ArithE) (e2 : ArithE)]
  [timesC (e1 : ArithE) (e2 : ArithE)]
  [letC (x : symbol) (e1 : ArithE) (e2 : ArithE)]
  [lambdaC (x : symbol) (e : ArithE)]
  [appC (e1 : ArithE) (e2 : ArithE)])
```

`lambdaC` *defines* a function and `appC` *uses* one, much as `letC` introduces a name and `idC` uses it. Functions take one argument; several arguments can be simulated by currying (Section 2.3).

Parsing. Any list whose head is not `+`, `*`, `let`, or `lambda` is an application:

```
(define (parse (s : s-expression)) : ArithE
  (cond
    [(s-exp-number? s) (numC (s-exp->number s))]
    [(s-exp-symbol? s) (idC (s-exp->symbol s))]
    [(s-exp-list? s)
     (let [(l (s-exp->list s))]
       (if (s-exp-symbol? (first l))
           (case (s-exp->symbol (first l))
             [(+) (plusC (parse (second l)) (parse (third l)))]
             [(*) (timesC (parse (second l)) (parse (third l)))]
             [(let) (letC (s-exp->symbol (second l)) (parse (third l)) (parse (fourth l)))]
             [(lambda) (lambdaC (s-exp->symbol (second l)) (parse (third l)))]
             [else (appC (parse (first l)) (parse (second l)))])
           ;; head is not a symbol, e.g. ((lambda x (+ x 1)) 5)
           (appC (parse (first l)) (parse (second l))))))]))
```

```
(parse '((lambda x (+ x 1)) 5))
;; = (appC (lambdaC 'x (plusC (idC 'x) (numC 1))) (numC 5))
(parse '(f 5))
;; = (appC (idC 'f) (numC 5))
```

The outer `if` matters for calls whose head is itself a list, like `((lambda x (+ x 1)) 5)`: calling `s-exp->symbol` on it would fail with `s-exp->symbol: not a symbol`.

Remark 42. With an application fallback, `'(- 1 2)` no longer fails to parse. The `else` branch reads it as a call of a function named `-`, giving `(appC (idC '-) (numC 1))` and silently dropping the `2`. Before `lambda` was added, it was `case: no matching clause`.

4.4.2 `lambda` in Substitution

A `lambda` binds its parameter in its body, exactly as `let` binds `x` in `e2`. So the `lambdaC` case of each substitution function is its `letC` case without an `e1`: stop at shadowing, and in `subst-lazy-v2` rename with `gensym` first. The application case just recurses.

```
;; in subst-eager (subst-lazy is the same with subst-lazy)
[lambdaC (y e)
         (if (equal? x y) (lambdaC y e) (lambdaC y (subst-eager v x e)))]
[appC (e1 e2) (appC (subst-eager v x e1) (subst-eager v x e2))]

;; in subst-lazy-v2
[lambdaC (y e)
         (if (equal? x y)
             (lambdaC y e)
             (let [(z (gensym))]
               (lambdaC z (subst-lazy-v2 v x (subst-lazy (idC z) y e)))))]
[appC (e1 e2) (appC (subst-lazy-v2 v x e1) (subst-lazy-v2 v x e2))]
```

Pitfall 43 (The pattern variable shadows the argument)

In `[lambdaC (y e) ...]`, the pattern variable `e` (the body) shadows `subst`'s own argument `e` (the whole `lambda`). So the shadowing branch must rebuild `(lambdaC y e)`; returning plain `e` would drop the `lambda` and return only its body. Shadowing bites the interpreter's author too.

4.4.3 A New Result Type

A program can now produce a function, for example `(lambda x (+ x 1))` or `(let f (lambda x x) f)`, and a function is not a number. So evaluation returns a Value, which is either:

```
(define-type Value
  [numV (n : number)]
  [funV (x : symbol) (e : ArithE)])
```

`+` and `*` only make sense on numbers, so they unwrap `numV` first and complain about anything else:

```
(define (num+ (v1 : Value) (v2 : Value)) : Value
  (if (and (numV? v1) (numV? v2))
      (numV (+ (numV-n v1) (numV-n v2)))
      (error 'eval "not a number")))

(define (num* (v1 : Value) (v2 : Value)) : Value
  (if (and (numV? v1) (numV? v2))
      (numV (* (numV-n v1) (numV-n v2)))
      (error 'eval "not a number")))
```

This is the first *dynamic* type error in our language: whether `(+ e1 e2)` is meaningful depends on what `e1` and `e2` evaluate to, which the interpreter only learns at run time.

4.4.4 Eager Application

The lecture first adds functions to the *eager* interpreter (`lec4b.rkt`, `lec4c.rkt`). Application is *call-by-value*: evaluate the function, evaluate the argument, then substitute the argument's *value* into the body. `let` works the same way.

`subst-eager` substitutes only numbers, but a value may now be a function. So the value is turned back into an expression, and substituted with the expression-substituting `subst-lazy` or `subst-lazy-v2`. The expression they receive is already evaluated, so nothing is lazy about it:

```
(define (value->expr (v : Value)) : ArithE
  (type-case Value v
    [numV (n) (numC n)]
    [funV (x e) (lambdaC x e)]))

(define (eval-eager-v2 (e : ArithE)) : Value
  (type-case ArithE e
    [numC (n) (numV n)]
    [idC (x) (error 'eval "unbound variable")]
    [plusC (e1 e2) (num+ (eval-eager-v2 e1) (eval-eager-v2 e2))]
    [timesC (e1 e2) (num* (eval-eager-v2 e1) (eval-eager-v2 e2))]
    [letC (y e1 e2)
          (eval-eager-v2 (subst-lazy (value->expr (eval-eager-v2 e1)) y e2))]
    [lambdaC (x e) (funV x e)]
    [appC (e1 e2)
          (type-case Value (eval-eager-v2 e1)
            [funV (x e)
                  (eval-eager-v2 (subst-lazy (value->expr (eval-eager-v2 e2)) x e))]
            [numV (n) (error 'eval "not a function")])]))
```

The lecture's `lec4b.rkt` writes this with `Expr` for ArithE and `lambdaV` for `funV`, and gives `subst` a Value that it converts at the `idC` case; the effect is the same. Functions can now be passed around:

```
(let do-twice (lambda f (f (f 1)))
  (let double (lambda x (* 2 x))
    (do-twice double)))
---> (do-twice double)  with both substituted
---> (double (double 1))
---> 4
```

Eager capture. Section 4.2 said that eager substitution cannot capture because a number has no names in it. A function value does have names, and its body may contain free variables:

```
(let f (lambda x (+ x y))         y is free in f's body
  (let y 6
    (f 1)))
---> (let y 6 ((lambda x (+ x y)) 1))   substitute f's value: y is captured
---> ((lambda x (+ x 6)) 1)
---> 7
```

The right answer is an error: the `y` in `f` refers to no binding, and Racket rejects the same program with `y: unbound identifier`. `eval-eager-v2` returns 7 because `subst-lazy` carried the free `y` under `(let y 6 ...)`. Eager evaluation is not a defense against capture once values can contain code.

The fix (`lec4c.rkt`) is the one from Section 4.3: `eval-eager-v3` is `eval-eager-v2` with both calls to

subst-lazy replaced by subst-lazy-v2. Now the program above raises unbound variable, and returning f instead of calling it shows the renaming:

```
> (eval-eager-v3 (parse '(let f (lambda x (+ x y)) (let y 6 f))))
(funV 'g3507 (plusC (idC 'g3507) (idC 'y)))
```

Substituting f into the body of (let y 6 ...) renamed f's parameter to a fresh name, as the lambdaC case of subst-lazy-v2 always does; the free y stays free.

4.4.5 Lazy Application: eval-lazy-v2

The last version (lec4d.rkt) makes application lazy, like let in Section 4.2: the argument is substituted unevaluated.

```
(define (eval-lazy-v2 (e : ArithE)) : Value
  (type-case ArithE e
    [numC (n) (numV n)]
    [idC (x) (error 'eval "unbound variable")]
    [plusC (e1 e2) (num+ (eval-lazy-v2 e1) (eval-lazy-v2 e2))]
    [timesC (e1 e2) (num* (eval-lazy-v2 e1) (eval-lazy-v2 e2))]
    [letC (y e1 e2) (eval-lazy-v2 (subst-lazy-v2 e1 y e2))]
    [lambdaC (x e) (funV x e)]
    [appC (e1 e2)
          (type-case Value (eval-lazy-v2 e1)
            [funV (x e) (eval-lazy-v2 (subst-lazy-v2 e2 x e))]
            [numV (n) (error 'eval "not a function")])]))
```

- **lambdaC**: a lambda is already a value. There is nothing to compute until it is called.
- **appC**: evaluate e1; it must be a function (funV x e). Then call it the way let works: substitute the argument e2 for x in the body e, and evaluate the result. e2 is substituted unevaluated, because this is the lazy version.

```
((lambda x (+ x 1)) 5)
---> (+ 5 1)             subst 5 for x in the body
---> 6
```

Key Point 44 (let is application)

((lambda x e) e2) means the same as (let x e2 e). What lambda adds is that the function is a *value*: it can be named with let, passed as an argument, and returned as a result.

program	result
(let f (lambda x (* x 2)) (f 5))	(numV 10)
((lambda f (f 3)) (lambda x (+ x 1)))	(numV 4): a function as argument
(((lambda x (lambda y (+ x y))) 1) 2)	(numV 3): a function as result
((lambda x 5) y)	(numV 5): the unused argument is never evaluated
the do-twice example of Section 4.4.4	(numV 4)
(5 3)	not a function
(+ (lambda x x) 1)	not a number

4.4.6 Capture, Again

With functions, capture-avoiding substitution matters even more. A function can return a function, so a free name can end up under another `lambda`:

```
(((lambda x (lambda y (+ x y))) y) 2)
subst-lazy:     (lambda y (+ y y)),  then 2 ---> 4          captured!
subst-lazy-v2:  (lambda g (+ y g)),  then 2 ---> (+ y 2) ---> unbound variable
```

`eval-eager` and `eval-lazy` still return a `number`, and `subst-eager` can substitute only numbers, so their `lambdaC` and `appC` cases remain errors (`"TODO: lambda"`); `eval-eager-v2`/`v3` and `eval-lazy-v2` are the versions with functions.

program	`eval-eager-v3` (call-by-value)	`eval-lazy-v2` (call-by-name)
`((lambda x 5) y)`	`unbound variable`	`(numV 5)`
`(let x (+ y y) 10)`	`unbound variable`	`(numV 10)`
the `f`/`y` example of Section 4.4.4	`unbound variable`	`unbound variable`

With capture-avoiding substitution, the two strategies differ only where an argument is never used, as for `let` in Section 4.2. Racket, like most languages, is call-by-value.

4.5 Recitation 4: Pattern Matching in the Interpreter

In Section 3.4 we *used* Racket's `match` to write `factorial` and `fibonacci`. This recitation *implements* a small version of it: the calculator with `let` gets a `match` form, and each part of the interpreter is extended in turn: the types, `parse`, `subst`, and `eval`. The file starts with the `gensym` import of Section 4.3, since its `let` uses capture-avoiding lazy substitution.

4.5.1 The New Form

A pattern-matching expression looks like

```
(match e (n1 e1) (n2 e2) ... (_ en))
```

where each `ni` is a number literal and _ is the wildcard. To evaluate it:

1. evaluate `e` to a number, once;
2. try the clauses top to bottom: `ni` matches if it equals that number, and _ matches anything;
3. the *first* matching clause wins, and only its expression is evaluated;
4. if no clause matches, it is an error.

This is Racket's `match` restricted to literals and _, just enough for `factorial`- and `fibonacci`-style definitions. There are no pattern variables, so a clause never binds a name; that matters for substitution.

4.5.2 Types

A clause pairs a pattern with an expression. The two kinds of clause carry different data (a number pattern has a number, the wildcard nothing), so each gets its own variant:

```
(define-type PatternE
  [numP (n : number) (e : ArithE)]
  [anyP (e : ArithE)])

(define-type ArithE
  [numC (n : number)]
  [plusC (e1 : ArithE) (e2 : ArithE)]
  [timesC (e1 : ArithE) (e2 : ArithE)]
  [letC (x : symbol) (e1 : ArithE) (e2 : ArithE)]
  [idC (x : symbol)]
  [patternC (e : ArithE) (patterns : (listof PatternE))])
```

`patternC` holds the expression being matched, the *scrutinee*, and the clauses in order. The two types are *mutually recursive*: an ArithE can contain PatternEs, and each PatternE contains an ArithE. `define-type` allows that, in either order.

Examples. The handout's four examples, in ML-like notation:

	program	expected
1	`match 5 with | 5 -> 0 | 6 -> 1`	0
2	`match (1 + 2) with | 3 -> 1 | _ -> x`	1
3	`match x with | 0 -> z | _ -> (match y with | 0 -> x | 1 -> y)`	unbound variable
4	`let x = 1 in let y = 1 in` (the `match` of 3, last clause `y + 1`)	2

```
(define example-2 : ArithE
  (patternC (plusC (numC 1) (numC 2))
            (list (numP 3 (numC 1))
                  (anyP (idC 'x)))))

(define example-4 : ArithE
  (letC 'x (numC 1)
        (letC 'y (numC 1)
              (patternC (idC 'x)
                        (list (numP 0 (idC 'z))
                              (anyP (patternC (idC 'y)
                                              (list (numP 0 (idC 'x))
                                                    (numP 1 (plusC (numC 1) (idC 'y))))))))))))
```

Examples 2 and 4 both contain a name that nothing binds (`x` and `z`), yet neither is an error, because that clause is never chosen. In example 3 the error comes from the scrutinee `x`, which is always evaluated.

4.5.3 Parsing

The concrete syntax is `(match e clause ...)`, so after the `match` keyword, `(second l)` is the scrutinee and `(rest (rest l))` is the list of clauses. A helper turns that list of s-expressions into a list of PatternEs. Each clause is a two-element list `(pattern expr)`, and the pattern decides which variant to build:

```
(define (parse-patterns (s-pats : (listof s-expression))) : (listof PatternE)
  (cond
    [(empty? s-pats) empty]
    [else
     (let [(s-pat (s-exp->list (first s-pats)))]
       (cond
         [(s-exp-number? (first s-pat))
          (cons (numP (s-exp->number (first s-pat)) (parse (second s-pat)))
                (parse-patterns (rest s-pats)))]
         [(equal? (s-exp->symbol (first s-pat)) '_)
          (list (anyP (parse (second s-pat))))]))]))

(define (parse (s : s-expression)) : ArithE
  (cond
    [(s-exp-number? s) (numC (s-exp->number s))]
    [(s-exp-symbol? s) (idC (s-exp->symbol s))]
    [(s-exp-list? s)
     (let [(l (s-exp->list s))]
       (case (s-exp->symbol (first l))
         [(+) (plusC (parse (second l)) (parse (third l)))]
         [(*) (timesC (parse (second l)) (parse (third l)))]
         [(let) (letC (s-exp->symbol (second l)) (parse (third l)) (parse (fourth l)))]
         [(match) (patternC (parse (second l)) (parse-patterns (rest (rest l))))]))]))
```

Three details of the TA solution:

- A number clause is consed onto the rest, but a `_` clause returns `(list (anyP ...))`: parsing *stops* at the first wildcard. Any clause after it could never be reached, so dropping it does not change what the program means: `(parse '(match 1 (_ 0) (2 3)))` has one clause.

- The pattern is *not* parsed as an expression; it must be a number literal or `_`. Anything else is an error, though not one this function raises itself: `(match 3 ((+ 1 2) 0))` fails in `s-exp->symbol` (`not a symbol`), and `(match 3 (n 0))` falls off the end of the inner `cond` (`no matching clause`).
- `parse-patterns` and `parse` call each other, just as the two types refer to each other. `match` is a symbol in *our* language, matched by `case` like `+` and `let`.

4.5.4 Substitution

Exercise 45 (Why substitute into `match`?)

Why do we need to define substitution for pattern-matching expressions?

Solution. Because `let` is implemented by substitution, and the body of a `let` can contain a `match`. In example 4, the `x` and `y` bound by the `let`s are used in the scrutinees and in the clause bodies. If `subst` stopped at a `patternC`, those `idC`s would never be replaced and `eval` would report them as unbound. (In `plai-typed` the question does not really arise: `type-case` rejects a `subst` that has no `patternC` case.)

Substituting into a clause means substituting into its expression; the pattern itself is a number or `_`, with no names in it:

```
(define (subst-pattern (erep : ArithE) (x : symbol)) : (PatternE -> PatternE)
  (lambda (p)
    (type-case PatternE p
      [numP (n e) (numP n (subst erep x e))]
      [anyP (e) (anyP (subst erep x e))])))
```

`subst-pattern` is *curried*: it takes `erep` and `x` and returns a function from one clause to one clause. That is exactly the shape `map` wants, so the `patternC` case is one line:

```
(define (subst (erep : ArithE) (x : symbol) (e : ArithE)) : ArithE
  (type-case ArithE e
    [idC (y) (if (equal? x y) erep (idC y))]
    [numC (n) (numC n)]
    [plusC (e1 e2) (plusC (subst erep x e1) (subst erep x e2))]
    [timesC (e1 e2) (timesC (subst erep x e1) (subst erep x e2))]
    [patternC (e pats) (patternC (subst erep x e) (map (subst-pattern erep x) pats))]
    [letC (y e1 e2)
          (cond
            [(equal? x y) (letC y (subst erep x e1) e2)]
            [else
             (let [(z (gensym))]
               (letC z (subst erep x e1) (subst erep x (subst (idC z) y e2))))])]))
```

The `letC` case is lecture 4's capture-avoiding `subst-lazy-v2`. Note what the `patternC` case does *not* need: no shadowing check and no renaming. Those exist for `letC` because a `let` binds a name; our patterns bind nothing, so a clause body sees exactly the same names as the `match` around it, like the children of `plusC`.

4.5.5 Evaluation

The helper `get-pat-expr` takes the number the scrutinee evaluated to and the clauses, and returns the *expression* of the first clause that matches:

```
(define (get-pat-expr (num : number) (pats : (listof PatternE))) : ArithE
  (cond
    [(empty? pats) (error 'get-pat-expr "unmatched expression")]
    [else (type-case PatternE (first pats)
            [numP (n e) (cond [(equal? num n) e] [else (get-pat-expr num (rest pats))])]
            [anyP (e) e])]))

(define (eval (e : ArithE)) : number
  (type-case ArithE e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval e1) (eval e2))]
    [timesC (e1 e2) (* (eval e1) (eval e2))]
    [patternC (e pats) (eval (get-pat-expr (eval e) pats))]
    [letC (x e1 e2) (eval (subst e1 x e2))]
    [idC (x) (error 'eval "unbound variable!")]))
```

`eval` evaluates the scrutinee once, picks the clause, and evaluates only that clause's expression.

Why return the expression, not its value?. `get-pat-expr` could evaluate every clause and return numbers. That would be wrong, not just slow: example 4 has a clause `(0 z)`, and evaluating it would raise "unbound variable" even though the scrutinee is 1 and the clause is never chosen. Returning the unevaluated ArithE means only the chosen clause is evaluated, just as only one branch of an `if` is.

Tracing example 4. `g1` stands for whatever name `gensym` returns.

```
(let x 1 (let y 1 (match x (0 z) (_ (match y (0 x) (1 (+ 1 y)))))))
letC x:  subst (numC 1) for x in the body.
         The inner let binds y, not x, so y is renamed to g1 first.
---> (let g1 1 (match 1 (0 z) (_ (match g1 (0 1) (1 (+ 1 g1))))))
letC g1: subst (numC 1) for g1 in the body
---> (match 1 (0 z) (_ (match 1 (0 1) (1 (+ 1 1)))))
patternC: scrutinee = 1; (0 z) fails; _ matches
---> (match 1 (0 1) (1 (+ 1 1)))
patternC: scrutinee = 1; (0 1) fails; (1 ...) matches
---> (+ 1 1)
---> 2
```

The clause `(0 z)` is skipped without being evaluated, which is why the free `z` is harmless. Example 3 fails at its first step: the scrutinee is `(idC 'x)`, no `let` has replaced it, and `eval` reports it as unbound.

Clause order. Because `get-pat-expr` walks the list from the front and stops at the first match, order matters, and a clause after _ is dead code:

```
(test (eval (parse '(match 5 (_ 0) (5 1)))) 0)
(test (eval (parse '(match 5 (5 1) (_ 0)))) 1)
(test (eval (parse '(match 5 (5 1) (5 2)))) 1)
(test (eval (parse '(match (* 2 3) (5 0) (6 1) (_ 2)))) 1)
(test/exn (eval (parse '(match 7 (5 0) (6 1)))) "unmatched expression")
```

The last test is the run-time "no matching clause" error of Section 3.4, now in our own language. Nothing can check for it ahead of time: whether a clause matches depends on a number known only when the program runs.

Chapter 5

Week 5: From Substitution to Environments

Lecture 5: October 6, 2026. Recitation 5: October 9, 2026.

Supplementary reading:

- [1] Chapter 6 (From Substitution to Environments) and Chapter 7 (Functions Anywhere), which make exactly this week's move and hit the same dynamic-scope bug on the way.
- [3] Section 3.2 (The Environment Model of Evaluation), for the same idea drawn as frames and pointers.
- [7] Chapter 3 (Names, Scopes, and Bindings), for static and dynamic scope with assignment and for macros, which Recitation 5 draws on.
- [5] Sections 5.1–5.3 (the untyped lambda calculus), optional.

Week 4 implemented names and functions by *substitution*: rewrite the program, replacing a name by its value, before running it. Lecture 5 first finishes that story, then keeps the language and changes the implementation. An *environment* interpreter never rewrites the program; it carries a table from names to values and looks a name up when it reaches it. The lecture builds it in five small files, `lecture5a.rkt` to `lecture5e.rkt`, and twice the first attempt gets scope wrong in the same way. Recitation 5 revisits environments and scope, and carries the scope question over to assignment and macros. This chapter covers:

- Section 5.1: `let` as function application, capture once more, the lambda calculus, and α-equivalence;
- Section 5.2: an environment interpreter for `let`, checked against substitution (`lecture5a.rkt`);
- Section 5.3: lazy `let` with environments, dynamic scope, and the fix (`lecture5b.rkt`, `lecture5c.rkt`);
- Section 5.4: functions with environments, and closures (`lecture5d.rkt`, `lecture5e.rkt`);
- Section 5.5: Recitation 5, environments as functions, one interpreter for both scopes, scope with assignment, and hygienic macros.

5.1 Substitution Revisited

5.1.1 The Starting Point

The lecture opened where week 4 ended: the eager interpreter with functions, `eval-eager-v3` of Section 4.4.4. A call evaluates the function and the argument, then substitutes the argument's value into the body with the capture-avoiding `subst-lazy-v2` of Section 4.3; function values are written `(lambdaV x e)` in lecture, `funV` in week 4. On the board the two binding forms were

```
[letC (y e1 e2)
      (eval (subst e1 y e2))]
[appC (e1 e2)
      (let ([v1 (eval e1)]
            [v2 (eval e2)])
        (eval (subst (val->expr v2) (lambdaV-x v1) (lambdaV-e v1))))]
```

where `val->expr` turns a value back into an expression, as `value->expr` did in week 4.

Remark 46. The `letC` line above is a *lazy* `let` next to an *eager* application. The substitution interpreter kept for comparison in `lecture5a.rkt` (Section 5.2.6) evaluates `e1` first, and the rest of this chapter takes `let` to be eager whenever application is. Mixing the two strategies would break the equation of the next subsection.

5.1.2 `let` Is Function Application

Key Point 47 (`let` desugars to `lambda`)

`(let x e1 e2)` means `((lambda x e2) e1)`.

"Call `e1` by the name `x` while computing `e2`" is the same as "make the function with parameter `x` and body `e2`, and call it on `e1`".

Both sides evaluate `e1`, substitute it for `x` in `e2`, and evaluate the result:

```
(let x 5 (+ x x))          ((lambda x (+ x x)) 5)
---> (+ 5 5)               ---> (+ 5 5)
---> 10                    ---> 10
```

So `letC` is not needed in the core language: `parse` could turn every `let` into an `appC` of a `lambdaC`, and `eval` and `subst` would lose a case each. This is *desugaring*. The equation holds only if `let` and application use the same strategy, both eager or both lazy. With a lazy `let` and an eager call, `(let x (+ y y) 10)` is 10 but `((lambda x 10) (+ y y))` is an unbound-variable error.

5.1.3 Capture, Once More

The lecture's capture example, written on the board:

```
(let x (+ 1 y) (let y 2 (+ x y)))
```

Nothing binds the first `y`, so the right answer is an unbound-variable error (Figure 5.1). With a lazy `let`, `(+ 1 y)` is substituted unevaluated for `x`, and the question is what happens to its `y` when it lands inside `(let y 2 ...)`:

```
without renaming (subst-lazy):
---> (let y 2 (+ (+ 1 y) y))      the free y is captured
---> (+ (+ 1 2) 2)
---> 5                            wrong

with renaming (subst-lazy-v2):
---> (let z 2 (+ (+ 1 y) z))      inner y renamed to a fresh z first
---> (+ (+ 1 y) 2)
---> unbound variable             right
```

The second trace is the line `(let z 2 (+ (+ 1 y) z))` from the board. It is the week 4 example `(let x y (let y 2 (+ x y)))` with `y` replaced by `(+ 1 y)`: any substituted expression that has a free variable can be captured, however complicated it is. An eager `let` reports the error even earlier, while evaluating `(+ 1 y)` before any substitution.




Figure 5.1: Lexical binding structure of the board example. The `y` inside `(+ 1 y)` is free; a correct substitution must keep it free after moving it under `(let y 2 ...)`.

5.1.4 The Lambda Calculus

Delete `numC`, `plusC`, `timesC`, and `letC` from the expression type. What remains is Church's *lambda calculus* (1936), usually written with λ:

lambda calculus	our syntax	abstract syntax
x	`x`	`idC`
$\lambda x.\, e$	`(lambda x e)`	`lambdaC`
$e_1\ e_2$	`(e1 e2)`	`appC`

It has a single computation rule, *β-reduction*:

$$(\lambda x.\, e)\ e_2 \longrightarrow e[e_2/x],$$

which is the `appC` case of the lazy interpreter: substitute the argument for the parameter. Despite having nothing but functions, the lambda calculus can express every computation: numbers, Booleans, pairs, and recursion can all be encoded as functions. The `let` desugaring above is the first such encoding: a `let` is a β-redex.

5.1.5 α-Equivalence

Definition 48 (α-equivalence)

Two expressions are *α-equivalent* if they differ only in the names of bound variables, renamed consistently together with their uses. Free variables must stay as they are.

`(lambda x (+ x 1))`	`(lambda y (+ y 1))`	α-equivalent
`(let y 2 (+ x y))`	`(let z 2 (+ x z))`	α-equivalent
`(lambda x (+ x y))`	`(lambda x (+ x z))`	*not*: `y` and `z` are free
`(lambda x (lambda y x))`	`(lambda y (lambda y y))`	*not*: renaming `x` to `y` caused capture

Key Point 49 (Why α-equivalence matters for the interpreter)

α-equivalent programs must give the same answer: the names of bound variables are the programmer's choice and carry no meaning. This principle does two jobs in week 4:

- It *detects* the capture bug. `(let x y (let y 2 (+ x y)))` and `(let x y (let z 2 (+ x z)))` are α-equivalent, yet capturing substitution gives 4 for one and an error for the other.
- It *licenses* the fix. Renaming a bound `y` to a fresh `gensym` produces an α-equivalent program, so `subst` may rename whenever it likes.

The same test will expose the bug in Section 5.3: renaming the inner `x` to `z` in `(let x 1 (let y x (let x 2 (+ y y))))` changes the answer of the first lazy environment interpreter, so that interpreter is wrong.

5.2 Environments

5.2.1 The Plan

Every interpreter since Section 4.1 has had to answer one question: in

```
(let x 5 (+ x x))
```

when `eval` reaches the `x` in `(+ x x)`, where does the 5 come from? There are two answers (Figure 5.2).

- **Substitution** (week 4). Before evaluating the body, rewrite it: replace every `x` by the value. The body becomes `(+ 5 5)`, which contains no names at all, so evaluating it never has to ask about `x`.
- **Environments** (this week). Leave the body exactly as written. Evaluate it together with a table, the *environment*, that says `x = 5`. When evaluation reaches `x`, look it up in the table.

Both give 10. `lecture5a.rkt` goes back to the simplest language with names, numbers and eager `let`, and implements it the second way. The rest of the week is about making the second answer agree with the first in *every* program, not just this one.




Figure 5.2: Two implementations of the same `let`. Substitution changes the program; an environment changes only what `eval` carries along.

The lecture files call the expression type `Expr` rather than `ArithE`; the variants are the same. `lecture5a.rkt` drops `lambdaC` and `appC` again, so its only values are numbers and `eval` returns a `number`:

```
(define-type Expr
  [numC (n : number)]
  [plusC (e1 : Expr) (e2 : Expr)]
  [timesC (e1 : Expr) (e2 : Expr)]
  [letC (x : symbol) (e1 : Expr) (e2 : Expr)]
  [idC (x : symbol)])
```

5.2.2 The Data Structure

Definition 50 (Environment)

An *environment* is a mapping from names to values. Here it is a list of *bindings*, newest first; looking a name up returns the value of the *first* binding with that name.

```
(define-type Binding
  [bind (name : symbol) (val : number)])

(define-type-alias Env (listof Binding))
(define empty-env empty)
(define extend-env cons)

(define (lookup (x : symbol) (env : Env)) : number
  (cond
    [(cons? env)
     (if (equal? (bind-name (first env)) x)
         (bind-val (first env))
         (lookup x (rest env)))]
    [else (error 'lookup "No binding found")]))
```

Three small pieces of `plai-typed` appear here:

- `define-type-alias` gives a type a second name. `Env` *is* `(listof Binding)`; writing `Env` only documents intent.
- `(define extend-env cons)` names an existing function. Adding a binding is consing it onto the front: `(extend-env (bind 'x 5) env)`.
- `lookup` is ordinary list recursion, the shape of `my-reverse` in Section 1.3: an empty case (no binding, an error) and a `cons` case (check the first binding, else recur on the rest).

5.2.3 The Interpreter

`eval-env` takes the environment as an extra argument, and `eval` starts it with the empty one:

```
(define (eval-env (env : Env) (e : Expr)) : number
  (type-case Expr e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval-env env e1) (eval-env env e2))]
    [timesC (e1 e2) (* (eval-env env e1) (eval-env env e2))]
    [idC (x) (lookup x env)]
    [letC (x e1 e2)
          (let ([v1 (eval-env env e1)])
            (eval-env (extend-env (bind x v1) env) e2))]))

(define (eval (e : Expr)) : number
  (eval-env empty-env e))
```

Compare it with `eval-eager` of Section 4.1 clause by clause:

case	substitution	environment
`letC`	evaluate `e1`, *rewrite* `e2` with `subst`, evaluate the new tree	evaluate `e1`, *extend the env* with `x=v1`, evaluate the unchanged `e2`
`idC`	never reached for a bound name, so it is an error	`lookup`
others	recurse	recurse, passing `env` along unchanged

The `idC` row is the heart of the change. In the substitution interpreter, reaching a name means it was never bound. In `eval-env`, reaching a name is the normal case, and the table answers it.

5.2.4 Traces

Write the environment next to each step. `eval` starts with `[]`:

```
(let x 5 (+ x x))                  env = []
  evaluate 5                       ---> 5
  evaluate (+ x x)                 env = [x=5]
    x ---> 5,  x ---> 5
---> 10
```

Shadowing comes for free. The new binding goes on the front, and `lookup` returns the first match, so an inner binding hides an outer one of the same name (Figure 5.3). This is the comment `(+ x x) -- '((bind x 6) (bind x 5))` from lecture:

```
(let x 5 (let x 6 (+ x x)))        env = []
  evaluate 5                       ---> 5
  (let x 6 (+ x x))                env = [x=5]
    evaluate 6                     ---> 6
    (+ x x)                        env = [x=6, x=5]
      x ---> 6 (first match),  x ---> 6
---> 12
```

Substitution needed the `(equal? x y)` test in `subst-eager` to get this right (Section 4.1); here there is no special case at all.




Figure 5.3: The environment while evaluating `(let x 5 (let x 6 (+ x x)))`. Each `let` pushes a binding on the front; `lookup` scans from the front, so the newest `x` wins.

Scope comes from passing the env down. `eval-env` passes the extended environment only *into* the body of the `let`; it never returns it. So a binding is visible exactly inside its own body. The lecture's example is `(+ (let x 5 (+ 3 x)) e2)`:

```
(+ (let x 5 (+ 3 x)) x)            env = []
  left:  (let x 5 (+ 3 x))         env = []
           (+ 3 x)                 env = [x=5]   ---> 8
  right: x                         env = []      ---> lookup: No binding found
```

The `x=5` binding existed only during the left operand. When the right operand is evaluated, `plusC` uses its own `env`, which never contained `x`. This matches lexical scope: the second `x` is not inside the `let`.

5.2.5 A Default Environment

Starting from a non-empty environment gives the language predefined names for free:

```
(define default-env : Env
  (extend-env (bind 'pi 3.14159) (extend-env (bind 'e 2.71828) empty-env)))

(define (eval-default-env (e : Expr)) : number
  (eval-env default-env e))
```

```
> (eval-default-env (parse '(let r 10 (* pi (* r r)))))
- number
314.159
```

A program may still shadow them: `(let pi 3 pi)` is 3. The substitution interpreter has no natural place for such names; it would have to wrap every program in `(let pi 3.14159 ...)`. Real languages work like `default-env`: Racket's `+`, `map`, and `first` are bindings in the initial environment.

5.2.6 Checking Against Substitution

`lecture5a.rkt` ends with "our old substitution evaluator for comparison", the eager interpreter of Section 4.1 under new names:

```
(define (eval-subst (e : Expr)) : number
  (type-case Expr e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval-subst e1) (eval-subst e2))]
    [timesC (e1 e2) (* (eval-subst e1) (eval-subst e2))]
    [letC (x e1 e2)
          (let ([v1 (eval-subst e1)])
            (eval-subst (subst v1 x e2)))]
    [idC (x) (error 'eval-subst "unbound variable!")]))
```

where `subst` is `subst-eager`. Both interpreters are run on the same four programs:

program	`eval-subst`	`eval`
`(+ 27 (let x 5 (+ x x)))`	37	37
`(let x 5 (let y 6 (+ x y)))`	11	11
`(let x 5 (let x 6 (+ x x)))`	12	12
`(let x 5 (let x (* x 2) (+ x x)))`	20	20

The last program checks that `e1` is evaluated in the *outer* environment: `(* x 2)` sees `x=5`, and only then is `x=10` pushed for the body.

Key Point 51 (Environment vs. substitution, for `let`)

For this language the two interpreters always agree: each binding in `env` is a substitution that has been *postponed* until the name is actually reached. Instead of copying 5 into every `x` of the body up front, `eval-env` remembers `x=5` and fills it in on demand. Substitution is the reference: whenever a later environment interpreter disagrees with it, the environment interpreter has a scope bug. That is how the lecture finds both bugs of Sections 5.3 and 5.4.

5.3 Lazy `let` and Dynamic Scope

`lecture5b.rkt` and `lecture5c.rkt` make the environment interpreter *lazy*, as Section 4.2 did for substitution: `let` does not evaluate `e1`, but stores it and evaluates it only when `x` is used. The language is still that of `lecture5a.rkt`, numbers and `let`. The first attempt gets scope wrong; the second fixes it.

5.3.1 Attempt 1: Store the Expression

A binding now holds an unevaluated expression, and `lookup` returns it:

```
(define-type Binding
  [bind (name : symbol) (defn : Expr)])

(define (lookup (x : symbol) (env : Env)) : Expr
  ...)   ; as in lecture5a, returning (bind-defn (first env))

(define (eval-env1 (env : Env) (e : Expr)) : number
  (type-case Expr e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval-env1 env e1) (eval-env1 env e2))]
    [timesC (e1 e2) (* (eval-env1 env e1) (eval-env1 env e2))]
    [idC (x) (eval-env1 env (lookup x env))]
    [letC (x e1 e2) (eval-env1 (extend-env (bind x e1) env) e2)]))

(define (eval1 (e : Expr)) : number
  (eval-env1 empty-env e))
```

`letC` stores `e1` as is. `idC` looks up the stored expression and evaluates it, in `env`, the environment *at the use*. The first examples work ("So far so good", says the file):

```
> (eval1 (parse '(+ 27 (let x 5 (+ x x)))))
37
> (eval1 (parse '(let x 5 (let y 6 (+ x y)))))
11
> (eval1 (parse '(let x 5 (let x 6 (+ x x)))))
12
```

Then the lecture tries a program where the stored expression mentions a name that is rebound before the use:

```
(let x 1 (let y x (let x 2 (+ y y))))   env = []
  store x=1                             env = [x=1]
  store y=x            (the expression x, not a value)
                                        env = [y=x, x=1]
  store x=2                             env = [x=2, y=x, x=1]
  (+ y y)
    y ---> its expression is x; evaluate x in the CURRENT env
         ---> lookup x finds x=2 ---> 2
---> 4
```

"We get 4, but under our substitution semantics this would give us 2": when `y` was defined, the only `x` in scope was `x=1`, so `y` means 1 (Figure 5.4). There is a quicker way to see that 4 is wrong. Rename the inner `x` to `z`; the program is α-equivalent (Section 5.1), so the answer must not change:

```
> (eval1 (parse '(let x 1 (let y x (let x 2 (+ y y))))))
4
> (eval1 (parse '(let x 1 (let y x (let z 2 (+ y y))))))
2
```

It does change, so `eval-env1` is wrong. The file's last example is the counterpart of capture in Section 4.2:

```
> (eval1 (parse '(let x y (let y 2 (+ x x)))))
4
```

The `y` in `(let x y ...)` is free, so this should be an error, but by the time `x` is used, the environment happens to contain `y=2`.




Figure 5.4: What the `x` stored in `y` refers to. Lexically (dashed blue) it is the outer `x`, giving 2; `eval-env1` evaluates it after the inner `let x 2` and finds that one instead (red), giving 4.

5.3.2 Dynamic vs. Lexical Scope

Definition 52 (Lexical and dynamic scope)

Under *lexical* (static) scope, the binding a name refers to is determined by the program text: the nearest enclosing binder of that name, which can be found without running the program. Under *dynamic* scope, it is determined by the execution history: the most recent binding of that name that is still active when the name is evaluated.

The file adds that this is "slightly informal, we could give a more precise definition"; the binding arrows of Figure 5.4 are the informal picture.

Substitution always gives lexical scope: it replaces names inside the binder's body at the moment the binder is processed, so a name can only ever be replaced by its own binder. `eval-env1` gives dynamic scope, because it evaluates the stored expression in whatever environment exists when the name is used, and by then other bindings may have been added.

Pitfall 53 (Dynamic scope breaks α-equivalence)

Under dynamic scope, renaming a local variable can change what *other* code means, here the definition of `y`. A function's meaning depends on every caller's local names. This is why dynamic scope is considered a design mistake for ordinary variables, and why the test "rename a bound variable and compare" is such a useful bug detector.

5.3.3 Attempt 2: Store the Environment Too

`lecture5c.rkt` "corrects the issue by saving the environment *at the time of the let* inside of a binding", and evaluates the stored expression in that environment:

```
(define-type Binding
  [bind (name : symbol) (env : Env) (defn : Expr)])

(define (lookup (x : symbol) (env : Env)) : Binding
  ...)   ; returns the whole binding, (first env)

(define (eval-env2 (env : Env) (e : Expr)) : number
  (type-case Expr e
    [numC (n) n]
    [plusC (e1 e2) (+ (eval-env2 env e1) (eval-env2 env e2))]
    [timesC (e1 e2) (* (eval-env2 env e1) (eval-env2 env e2))]
    [idC (x) (let ([res (lookup x env)])
               (eval-env2 (bind-env res) (bind-defn res)))]
    [letC (x e1 e2) (eval-env2 (extend-env (bind x env e1) env) e2)]))

(define (eval2 (e : Expr)) : number
  (eval-env2 empty-env e))
```

Two lines changed. `letC` stores `env`, the environment of the `let`, alongside `e1`. `idC` evaluates the stored expression in the stored environment, not the current one. A binding refers to an earlier environment, so the types are mutually recursive: a Binding contains an Env, which is a list of Bindings.

```
(let x 1 (let y x (let x 2 (+ y y))))   env = []
  store x=(1 in [])                     env = [x]
  store y=(x in [x=1])                  env = [y, x]
  store x=(2 in [y, x=1])               env = [x, y, x]
  (+ y y)
    y ---> evaluate x in y's saved env [x=1] ---> 1
---> 2
```

"Now these examples have behaviors like what our substitution semantics produced":

```
> (eval2 (parse '(let x 1 (let y x (let x 2 (+ y y))))))
2
> (eval2 (parse '(let x 1 (let y x (let z 2 (+ y y))))))
2
> (eval2 (parse '(let x y (let y 2 (+ x x)))))
lookup: No binding found
```

In the last one, x's expression y is evaluated in x's saved environment, which is empty. The interpreter is still lazy: `(let x (+ y y) 10)` is 10, since x is never used.

Key Point 54 (The fix, in one sentence)

Run stored code in the environment where it was *written*, not where it is *used*. The pair (expression, environment) is the general tool for this; Section 5.4 needs it again for functions.

5.4 Functions with Environments: Closures

`lecture5d.rkt` and `lecture5e.rkt` add `lambda` to the environment interpreter, back with an eager `let`. As the file puts it, "once again we'll first do something that behaves 'incorrectly' (or at least counter-intuitively) and then we'll switch to a fixed version": the first attempt has dynamic scope, and the fix is the one of Section 5.3.

5.4.1 Attempt 1: A Function Is Its Parameter and Body

Expr gets `lambdaC` and `appC` back, `parse` is the week 4 one (a list whose head is not a keyword is an application), and the result type is the Value of week 4, with function values written `lambdaV`. A binding holds a Value:

```
(define-type Value
  [numV (n : number)]
  [lambdaV (x : symbol) (e : Expr)])

(define-type Binding
  [bind (name : symbol) (val : Value)])
;; Env, empty-env, extend-env, lookup: as in lecture5a, returning a Value

(define (eval-env (env : Env) (e : Expr)) : Value
  (type-case Expr e
    [numC (n) (numV n)]
    [lambdaC (x e) (lambdaV x e)]
    [plusC (e1 e2) (numV (+ (numV-n (eval-env env e1)) (numV-n (eval-env env e2))))]
    [timesC (e1 e2) (numV (* (numV-n (eval-env env e1)) (numV-n (eval-env env e2))))]
    [letC (x e1 e2)
          (let ([v1 (eval-env env e1)])
            (eval-env (extend-env (bind x v1) env) e2))]
    [appC (e1 e2)
          (let [(v1 (eval-env env e1))
                (v2 (eval-env env e2))]
            (eval-env (extend-env (bind (lambdaV-x v1) v2) env) (lambdaV-e v1)))]
    [idC (x) (lookup x env)]))

(define (eval (e : Expr))
  (eval-env empty-env e))
```

`+` and `*` unwrap their operands with `numV-n` directly, and `appC` takes the function apart with `lambdaV-x` and `lambdaV-e`, so adding a function or applying a number fails inside an accessor rather than with a custom message. A call evaluates the function and the argument (eager), then evaluates the body in `env` extended with `x=v2`: it is the `letC` clause with the body taken from the function value. The four `let` programs of Section 5.2.6 still give 37, 11, 12, 20, now as `numV`s, and simple functions work:

```
> (eval (parse '((lambda x (+ 2 x)) 1)))
(numV 3)
> (eval (parse '(let x 2 (let addx (lambda y (+ y x)) (addx 3)))))
(numV 5)
```

"But now..." `env` in the `appC` clause is the environment of the *call*. If the caller has rebound a name that the body uses freely, the body sees the caller's binding:

```
(let x 2
  (let addx (lambda y (+ y x))
    (let x 5
      (addx 3))))
  env at the call:   [x=5, addx=(lambdaV y (+ y x)), x=2]
  body (+ y x) in    [y=3, x=5, addx=..., x=2]
    y ---> 3,  x ---> 5   (the caller's x)
---> 8
```

Lexically, the x in addx's body is the x=2 around the lambda, so the answer should be 5 (Figure 5.5). "Oops, we have the same problem of dynamic scope!" And for the same reason as eval-env1: the function body is stored code, and it is run in the environment where it is used.




Figure 5.5: The free x in addx's body. Without closures, the body is evaluated in the caller's environment and finds the inner x.

This is also the week 4 eager-capture bug in a new form. In Section 4.4.4, (let f (lambda x (+ x y)) (let y 6 (f 1))) gave 7 under capturing substitution, because the free y of f met the y=6 at the call. lecture5d's eval gives 7 for it too. Capture in a substitution interpreter and dynamic scope in an environment interpreter are the same mistake.

5.4.2 Attempt 2: Closures

The fix is the one of Section 5.3: save the environment where the code was written, here where the lambda was evaluated, together with the code.

Definition 55 (Closure)

A *closure* is a function value consisting of the parameter, the body, and the environment in which the lambda expression was evaluated. Calling it evaluates the body in that saved environment, extended with the parameter.

lecture5e.rkt replaces lambdaV by closV and changes two clauses of eval-env; everything else is lecture5d.rkt unchanged:

```
(define-type Value
  [numV (n : number)]
  [closV (env : Env) (x : symbol) (e : Expr)])

    [lambdaC (x e) (closV env x e)]
    ...
    [appC (e1 e2)
          (let [(v1 (eval-env env e1))
                (v2 (eval-env env e2))]
            ; run the body in the closure's saved env, not the current one
            (eval-env (extend-env (bind (closV-x v1) v2) (closV-env v1)) (closV-e v1)))]
```

`lambdaC` captures the current `env` in the closure. `appC` extends `(closV-env v1)`, the saved environment, instead of `env`, the caller's. Value and Env now refer to each other, as Binding and Env did in `lecture5c.rkt`. (`val->expr` is gone: nothing is substituted any more, so values never have to turn back into expressions.)

The file reruns the `addx` example with the inner `x` changed to 6 (dynamic scope would give 9):

```
(let x 2
  (let addx (lambda y (+ y x))
    (let x 6
      (addx 3))))
  evaluating the lambda in [x=2]  ---> addx = (closV [x=2] y (+ y x))
  env at the call:   [x=6, addx, x=2]          (not used for the body)
  body (+ y x) in    [y=3, x=2]                (the closure's env + y=3)
    y ---> 3,  x ---> 2
---> 5
```

"It gives 5, as we'd expect with lexical scope." The closure carries its own environment, shown in Figure 5.6. Whatever the caller binds, the body sees only the bindings that were in scope where the `lambda` was written, plus its parameter. The week 4 example `(let f (lambda x (+ x y)) (let y 6 (f 1)))` is now `No binding found`, as it should be.




Figure 5.6: The closure for `addx` and the environments of the call `(addx 3)`. The body is evaluated in the closure's environment extended with `y=3`; the caller's `x=6` is never consulted.

Key Point 56 (Closures)

A function value must remember the environment in which it was created. This is not an optimization or a detail of this interpreter: it is the definition of lexical scope for first-class functions, and it is why `make-adder` in Section 2.3 returns a function that still knows its `x` after `make-adder` has returned.

5.4.3 The Five Files Side by Side

Each file is a small change to the previous one, alternating between a first attempt that gets scope wrong and a fix:

file	what is added	what a binding stores	scope
`lecture5a`	environments, eager `let`, numbers only	a number	lexical
`lecture5b`	lazy `let`, attempt 1	an unevaluated expression	dynamic
`lecture5c`	lazy `let`, attempt 2	an expression *and its env*	lexical
`lecture5d`	`lambda`, attempt 1	a value; functions are `lambdaV`	dynamic
`lecture5e`	`lambda`, attempt 2	a value; functions are closures	lexical

The two red rows fail for the same reason and are fixed the same way: some code is run in the environment where it is used instead of the environment where it was written. On the programs of this chapter:

	substitution (week 4)	`eval1` (5b)	`eval2` (5c)	`eval` (5d)	`eval` (5e)
`(let x 5 (let x 6 (+ x x)))`	12	12	12	12	12
`(let x 1 (let y x (let x 2 (+ y y))))`	2	4	2	2	2
`(let x y (let y 2 (+ x x)))`	error	4	error	error	error
`(let x (+ y y) 10)`	error	10	10	error	error
addx example	5	—	—	8	5
`(let f (lambda x (+ x y)) (let y 6 (f 1)))`	error	—	—	7	error

The substitution column is the capture-avoiding eager interpreter `eval-eager-v3` (Section 4.4.4). Red entries disagree with it for scope reasons; "—" means the file has no `lambda`. The row `(let x (+ y y) 10)` is not a scope difference but the eager/lazy one of Section 4.2: lazy interpreters never evaluate an unused `e1`.

5.5 Recitation 5: Environments as Functions, Scope, and Macros

Lecture 5 built environment interpreters twice, and twice the first attempt had dynamic scope (Sections 5.3 and 5.4). This recitation comes back to the same material from four sides:

1. a second representation of environments, as *functions* instead of lists;
2. one interpreter with a flag `dynamic?` that runs any program under either scope;
3. small programs whose result depends on the scope, to predict and then check;
4. scope in languages with assignment, and scope in *macros*, where the static/dynamic question comes back as *hygiene*.

The handout files are `recitation5.rkt` (parts 1–4), `macro.rkt` with `unhygenic.c` (macros), and `bexp.lean` (a short look at Lean). No TA solutions have been posted yet. The code below is my completed handout, and every result in this section comes from running it.

5.5.1 The Language

The language is that of `lecture5e.rkt`: numbers, `+`, `*`, `let`, one-argument `lambda`, and application.

```
(define-type Expr
  [numC (n : number)]
  [plusC (e1 : Expr) (e2 : Expr)]
  [timesC (e1 : Expr) (e2 : Expr)]
  [letC (x : symbol) (e1 : Expr) (e2 : Expr)]
  [lambdaC (x : symbol) (e : Expr)]
  [appC (e1 : Expr) (e2 : Expr)]
  [idC (x : symbol)])

(define-type Value
  [numV (n : number)]
  [closV (env : Env) (x : symbol) (e : Expr)])
```

`parse` is the lecture's. A list whose head is not `+`, `*`, `lambda`, or `let` is an application, whether the head is some other symbol, as in `(f 0)`, or another list, as in `((lambda x x) 3)`. Since every function takes exactly one argument, a function that needs none takes a dummy argument `_` and is called with `0`.

5.5.2 Environments as Functions

In Section 5.2 an environment was a list of bindings, and `lookup` walked the list. But the only thing the interpreter ever does with an environment is ask "what is `x` bound to?" So an environment can simply *be* the function that answers that question:

```
(define-type-alias Env (symbol -> (optionof Value)))
```

Given a name, the environment returns `(some v)` if the name is bound to `v` and `(none)` if it is unbound. `optionof` is plai-typed's built-in "maybe" type, with the two variants `some` and `none`. `Env` and `Value` refer to each other (a closure holds an environment, an environment returns values), which `define-type` allows across definitions.

The three operations. The handout leaves three definitions to fill in.

Exercise 57 (The empty environment)

Define `empty-env : Env`, the environment in which nothing is bound.

Solution.

```
(define empty-env : Env
  (lambda (x) (none)))
```

It answers `none` for every name. It does not raise an error itself; it only says "not here", and `lookup` decides that this is an error.

Exercise 58 (`extend-env`)

Define `(extend-env x v env)`, which binds `x` to `v` on top of `env`. Hint: return a new function. When is it asked about `x`? What should it do otherwise?

Solution.

```
(define (extend-env (x : symbol) (v : Value) (env : Env)) : Env
  (lambda (y)
    (if (equal? x y)
        (some v)
        (env y))))
```

Asked about `x`, the name it binds, the new function answers `v`. Asked about any other name, it passes the question on to the environment it extends. The old `env` is captured in the closure that `lambda` builds, so this is a closure in Racket, the very thing `closV` implements in our language. Unlike the lecture's `extend-env`, which took a Binding, this one takes the name and value directly; there is no Binding type at all.

Exercise 59 (`lookup`)

Define `(lookup x env)`, which returns the value bound to `x` in `env` and signals an error if `x` is unbound, with the message `(string-append "unbound variable: " (symbol->string x))`. Hint: you can `type-case` on an `optionof`, just as on a type you defined.

Solution.

```
(define (lookup (x : symbol) (env : Env)) : Value
  (type-case (optionof Value) (env x)
    [some (v) v]
    [none () (error 'lookup (string-append "unbound variable: " (symbol->string x)))]))
```

`lookup` calls the environment on `x` and takes the answer apart: `some` carries the value, `none` means no layer recognized the name.

Pitfall 60 (type-case syntax: plai-typed is not plait)

My first version of `lookup` wrote the clauses as `[(some v) v]` and `[(none) ...]`, and the type as `(Optionof Value)`. The file then does not even compile:

```
type-case: expected an identifier from a define-type
  at: (some v)
```

That is the syntax of `#lang plait`, the successor of plai-typed used in newer PLAI courses. In `#lang plai-typed` a clause is the variant name followed by a parenthesized list of field names, `[some (v) ...]` and `[none () ...]`, exactly as in every `type-case` on Expr so far; the type is written in lower case, `optionof`.




Figure 5.7: `env-1` and `env-2` from the handout, as chains of closures. Each `extend-env` wraps the previous environment; a lookup enters at the left and moves right until some layer recognizes the name. `(lookup 'x env-2)` stops at the first box (3), and `env-1`, still reachable on its own, answers 1.

Tests. The handout builds two environments (Figure 5.7):

```
(define env-1 (extend-env 'x (numV 1) (extend-env 'y (numV 2) empty-env)))
(define env-2 (extend-env 'x (numV 3) env-1))

(test (lookup 'x env-1) (numV 1))
(test (lookup 'y env-1) (numV 2))
(test/exn (lookup 'z env-1) "unbound")
(test (lookup 'x env-2) (numV 3))   ; the newer binding shadows the older one
(test (lookup 'x env-1) (numV 1))   ; env-1 is unchanged
```

Shadowing works for the same reason as with lists: the newest binding is asked first. The last test is *persistence*: extending `env-1` built a new function around it and changed nothing, which is what lets a closure keep the environment of its `lambda` while the rest of the program goes on extending.

Exercise 61 (Lookup time)

How long does `lookup` take, compared to the list version?

Solution. The same: linear in the number of bindings. A lookup calls one closure per enclosing `extend-env` until one matches, just as the list version visits one `cons` cell per binding. The function representation hides the chain inside closures, but the chain is still there (Figure 5.7). Neither version does better than linear; a faster lookup needs another data structure (a hash table, or, in a compiler, a known position for each variable).

Exercise 62 (What lists can do)

What can you do with a list environment that you can't do with a function environment?

Solution. Anything other than asking about one name. A function is opaque: the only operation on it is calling it. With a list you can

- print it, which matters for debugging: a `closV` shows its environment as `#<procedure>`;
- enumerate it: list all bound names, count them, or find the free variables a closure actually uses;
- compare two environments for equality. Two `closV`s with function environments can never be compared structurally, so a `test` whose expected value is a closure cannot be written;
- remove a binding, or save it to a file.

In exchange, the function representation commits to nothing: any function of type `(symbol -> (optionof Value))` is an environment, for example one that computes bindings on demand.

5.5.3 One Interpreter, Two Scopes

The handout gives `lecture5e.rkt`'s interpreter on the new environments, with one extra argument `dynamic?`: `#f` for static scope (as in `lecture5e.rkt`), `#t` for dynamic scope (as in `lecture5d.rkt`). Every case except `appC` is written, and is the same for both scopes:

```
(define (eval-env (dynamic? : boolean) (env : Env) (e : Expr)) : Value
  (type-case Expr e
    [numC (n) (numV n)]
    [plusC (e1 e2) (numV (+ (numV-n (eval-env dynamic? env e1))
                            (numV-n (eval-env dynamic? env e2))))]
    [timesC (e1 e2) (numV (* (numV-n (eval-env dynamic? env e1))
                             (numV-n (eval-env dynamic? env e2))))]
    [letC (x e1 e2)
          (let ([v1 (eval-env dynamic? env e1)])
            (eval-env dynamic? (extend-env x v1 env) e2))]
    [idC (x) (lookup x env)]
    [lambdaC (x body) (closV env x body)]
    [appC (e1 e2) ...]))                    ; the exercise below

(define (eval-static (s : s-expression)) : Value
  (eval-env #f empty-env (parse s)))
(define (eval-dynamic (s : s-expression)) : Value
  (eval-env #t empty-env (parse s)))
```

Exercise 63 (The `appC` case)

Fill in `appC`. Which environment should the function body run in? Under static scope, the environment saved in the closure (where the `lambda` was written); under dynamic scope, the current environment (where the function is called).

Solution.

```
[appC (e1 e2)
      (let ([f (eval-env dynamic? env e1)]
            [arg (eval-env dynamic? env e2)])
        (type-case Value f
          [closV (cenv x body)
                 (eval-env dynamic?
                           (extend-env x arg (if dynamic? env cenv))
                           body)]
          [else (error 'eval-env "not a function")]))]
```

A call evaluates the function and the argument (eager), and then has to choose *which environment to extend* with the parameter:

scope	body runs in	which is
static (`dynamic? = #f`)	`cenv`, saved in the closure	where the `lambda` was written
dynamic (`dynamic? = #t`)	`env`, the current environment	where the function is called

That one `if` is the whole difference between `lecture5d.rkt` and `lecture5e.rkt`. In dynamic mode the closure still saves `cenv`, but nothing ever reads it, so a `closV` there is just the `lambdaV` of Section 5.4. The `else` clause catches a call of a number, such as `(1 2)`, which raises `eval-env: not a function` in both modes.

The example from the end of lecture (Figure 5.5) gives one answer per scope:

```
(define lecture-example
  '(let x 2
     (let addx (lambda y (+ y x))
       (let x 6
         (addx 3)))))

(test (eval-static lecture-example) (numV 5))   ; x from where addx was written
(test (eval-dynamic lecture-example) (numV 9))  ; x from where addx was called
```

All seven tests in the file pass.

5.5.4 Predict, Then Check

For each program, predict the result under static scope and under dynamic scope *before* running it; then check with `(eval-static ...)` and `(eval-dynamic ...)`. The result may be an error rather than a value, and then the question is which error and why. In our language every local variable becomes a `let`, and a function that needs no argument takes a dummy `_` and is called with `0`.

Exercise 64 (Predict, part a)

In C-like syntax:

```
int x = 14;
int h()  { return x; }
int f()  { int x = 13; return h(); }
int g()  { int x = 12; return h(); }
```

What do `f()` and `g()` return? In our language:

```
(define ex-a-f
  '(let x 14
     (let h (lambda _ x)
       (let f (lambda _ (let x 13 (h 0)))
         (let g (lambda _ (let x 12 (h 0)))
           (f 0))))))
;; ex-a-g: the same, ending in (g 0)
```

Solution. Static: both return `(numV 14)`. Dynamic: `f()` returns `(numV 13)` and `g()` returns `(numV 12)`. The body `x` is free in `h`. Statically it means the `x` visible where `h` is written, the global 14, whoever calls `h`. Dynamically it means the most recent `x` on the way to the call: `f`'s 13, or `g`'s 12. So under dynamic scope the same function returns different values depending on its caller, and renaming `f`'s local `x` to `z`, which should not matter, changes the result back to 14.

Exercise 65 (Predict, part b)

In C-like syntax:

```
const int b = 5;
int foo() { int a = b + 5; return a; }
int bar() { int b = 2; return foo(); }
```

What does `bar()` return? In our language:

```
(define ex-b
  '(let b 5
     (let foo (lambda _ (let a (+ b 5) a))
       (let bar (lambda _ (let b 2 (foo 0)))
         (bar 0)))))
```

Solution. Static: `(numV 10)`. Dynamic: `(numV 7)`. This is part a again with a twist: `b` is meant to be a constant, yet under dynamic scope `bar`'s local `b` replaces it inside `foo`, giving $2+5=7$ instead of $5+5=10$. A `const` declaration does not protect a name from being shadowed.

Exercise 66 (Predict, part c)

`f` uses a variable `y` that is not bound where `f` is written:

```
(define ex-c
  '(let f (lambda _ y)
     (let y 3
       (f 0))))
```

Solution. Static: `lookup: unbound variable: y`. Dynamic: `(numV 3)`. `f` is written where no `y` exists, so statically its body can never find one, and the call fails. Dynamically the call happens inside `(let y 3 ...)`, and the lookup finds that `y`. Dynamic scope "fixes" this program, but it is the kind of program a static checker would rightly reject, since whether `f` works depends on every caller.

Exercise 67 (Predict, part d)

A function that returns a function:

```
(define ex-d
  '(let make-adder (lambda n (lambda m (+ n m)))
     (let add5 (make-adder 5)
       (add5 1))))
```

Solution. Static: `(numV 6)`. Dynamic: `lookup: unbound variable: n`. This is the program that sinks dynamic scope. Under static scope, `(make-adder 5)` evaluates `(lambda m (+ n m))` in `make-adder`'s body, where `n` is 5, and the closure saves that environment. Under dynamic scope the saved environment is ignored, and `n` exists only while `make-adder` is running:

```
(add5 1), dynamic:
  env at the call = {add5 = <m-closure>, make-adder = <n-closure>}
  body (+ n m) runs in that env extended with m = 1
  lookup n  --->  unbound variable: n
```

The binding of `n` disappeared when `make-adder` returned, but the function that uses it did not. This is why closures save their environment: returning a function needs the environment of its definition.

Exercise 68 (Predict, part e)

Same as part d, but now some other `n` is around when `add5` is called:

```
(define ex-e
  '(let make-adder (lambda n (lambda m (+ n m)))
     (let add5 (make-adder 5)
       (let n 100
         (add5 1)))))
```

Solution. Static: `(numV 6)`. Dynamic: `(numV 101)`. With an unrelated `n` at the call site, dynamic scope no longer fails; it silently uses that `n`, so `add5` adds 100. That is worse than part d: a crash points at the bug, a wrong number does not. Figure 5.8 shows the two environments the body of `add5` runs in.




Figure 5.8: The environment in which the body `(+ n m)` of `add5` runs in `ex-e`. Statically it extends the environment saved when `(lambda m ...)` was evaluated inside `make-adder`, where `n` is 5. Dynamically it extends the caller's environment, where the nearest `n` is the unrelated 100. In `ex-d` the `n = 100` cell is missing, so the dynamic lookup reaches `empty` and fails.

Running all six confirms the predictions:

program	static	dynamic
`ex-a-f`	`(numV 14)`	`(numV 13)`
`ex-a-g`	`(numV 14)`	`(numV 12)`
`ex-b`	`(numV 10)`	`(numV 7)`
`ex-c`	`lookup: unbound variable: y`	`(numV 3)`
`ex-d`	`(numV 6)`	`lookup: unbound variable: n`
`ex-e`	`(numV 6)`	`(numV 101)`

Key Point 69

Under static scope, the meaning of a free variable in a function is fixed by the program text: you can read it off without knowing who calls the function. Under dynamic scope it depends on the chain of calls at run time, so local names are no longer private (a, b), renaming a local variable can change the result, and a function that outlives its defining call loses its free variables (d) or silently picks up someone else's (e).

5.5.5 Scope with Assignment

Our language has no assignment, but most languages do, and then a function can *change* the variable a free name refers to. The question is the same as before, which variable does the name denote, and these exercises are worked on paper: for each program, what does it print under static scope, and under dynamic scope?

Exercise 70 (Assignment, part a)

```
int x;
void h() { printf("%d\n", x); }
void f() { x = 13; h(); }
void g() { x = 12; h(); }
int main() { x = 14; f(); g(); }
```

Solution. Both scopes print `13` then `12`. Neither `f` nor `g` declares a local `x`, so there is only one `x`, the global one, and the assignments change it before `h` reads it. Compare Predict, part a, where `f` and `g` *declare* locals: static and dynamic scope can disagree only when there is more than one variable with the same name.

Exercise 71 (Assignment, part b)

This one is bash, which really is dynamically scoped, so you can run it in a terminal:

```
x=1
function g () { echo $x ; x=2 ; }
function f () { local x=3 ; g ; }
f
echo $x
```

Solution. Dynamic (what bash does): `3` then `1`. `g` is called from `f`, so its `x` is `f`'s `local x`: it prints 3, and `x=2` overwrites `f`*'s* local. When `f` returns, its local disappears and the global `x` is still 1. Static: `1` then `2`. `g`'s `x` would always be the global: it prints 1 and sets the global to 2, which the last line prints.

Exercise 72 (Assignment, part c)

From [7, Chapter 3]:

```
n : integer                 -- global
procedure first()
    n := 1
procedure second()
    n : integer             -- local
    first()
n := 2
if read_integer() > 0
    second()
else
    first()
write_integer(n)
```

Solution. Static: `1`, whatever is read. `first`'s `n` is the global one, and `first` runs on either branch. Dynamic: `2` for a positive input, `1` otherwise. Called from `second`, `first`'s `n` is `second`'s local, so `n := 1` changes that local and the global stays 2. Called from the main program, `first` sets the global. The output depends on the input through the scope rule, and nothing in the text of `first` shows it.

5.5.6 Scope and Macros

The rest of the recitation (`macro.rkt`) moves the same question to *macros*. A macro generates code from a shorthand before the program runs. The generated code mentions names, some written in the macro's definition and some supplied at the use, and each must be resolved somewhere.

Text macros in C. The C preprocessor replaces text. `unhygenic.c`:

```c
#include <stdio.h>
#define SWAP(a, b) do { \
  int temp = (a);       \
  (a) = (b);            \
  (b) = temp;           \
} while(0)

int main(void) {
  int x = 10;
  int y = 20;
  SWAP(x, y);
  printf("temp = %d, y = %d\n", x, y);
  return 0;
}
```

Exercise 73 (Running `unhygenic.c`)

Compile and run `unhygenic.c` as it is. What does it print?

Solution. `temp = 20, y = 10`: the swap works (the label `temp` in the format string is just text; the value printed is `x`). The `do { ... } while(0)` wrapper turns the macro body into one statement, so that `SWAP(x, y);` also works as the body of an `if` without braces.

Exercise 74 (A strange renaming)

In the body of `main`, rename `x` to `temp`. Don't compile it yet.

Solution. Every `x` in `main` becomes `temp`:

```c
int main(void) {
  int temp = 10;
  int y = 20;
  SWAP(temp, y);
  printf("temp = %d, y = %d\n", temp, y);
  return 0;
}
```

Exercise 75 (Predicting the behavior)

Discuss with your neighbor what you *think* the renamed program prints.

Solution. Renaming a local variable consistently should not change what a program does, so the natural prediction is the same output as before: `temp = 20, y = 10`.

Exercise 76 (Explaining the behavior)

Now compile and run the program. Did it do what you expected? Why did it do that?

Solution. No. It prints `temp = 10, y = 20`: nothing is swapped. `cc -E` shows the expanded code:

```
int temp = 10;
int y = 20;
do { int temp = (temp); (temp) = (y); (y) = temp; } while(0);
```

The argument `temp` is pasted inside the block that declares the macro's own `temp`, so every `temp` in the block refers to the inner variable: the user's `temp` has been *captured*. The inner `temp` is initialized from itself, an uninitialized read (undefined behavior), then set to `y`, and finally `y = temp` copies that value back into `y`. The outer `temp` is never touched. This is the variable capture of Section 4.2, produced by a text substitution that knows nothing about binding.

Definition 77 (Preserving α-equivalence)

Recall (Section 5.1) that programs p and q are α-equivalent, $p \equiv_\alpha q$, if renaming bound variables in p gives q. A program transformation T, a function from programs to programs, *preserves α-equivalence* if

$$p \equiv_\alpha q \implies T(p) \equiv_\alpha T(q).$$

(The handout writes "if $p \equiv_\alpha p$, then $T(p) \equiv_\alpha p$", a typo for this.)

Exercise 78 (Reasoning about α-equivalence)

Consider the C preprocessor as a program transformation: it takes C code and produces C code. Does it preserve α-equivalence?

Solution. No. The program with `x` and the program with `temp` are α-equivalent: one renames a local variable of the other. After preprocessing they are not even equivalent in behavior, let alone α-equivalent: one swaps and the other does not. A transformation that preserves α-equivalence lets the programmer choose names freely; with C macros, the names used inside every macro body are silently reserved.

Hygienic macros in Racket. The same macro in Racket:

```
(define-syntax-rule (swap a b)
  (let ([tmp a])
    (set! a b)
    (set! b tmp)))
```

`define-syntax-rule` defines `(swap a b)` as a pattern and its expansion as a template. Using the macro's own name for one of the variables does not break it:

```
> (define tmp 10)
> (define y 20)
> (swap tmp y)
> (list tmp y)
'(20 10)
```

Racket's expander is *hygienic*: the `tmp` introduced by the template and the `tmp` the user passed in are different variables, even though they print the same. Effectively the macro's `tmp` is renamed to a fresh name, as `subst` did with `gensym` in Section 4.3, so the expansion is

```
(let ([tmp1 tmp]) (set! tmp y) (set! y tmp1))
```

Key Point 79

Hygiene is static scope for macros. A name written in the macro's template refers to the binding visible where the *macro is defined*; a name passed in by the user refers to the binding visible where the *macro is used*. A text macro like C's resolves every name at the use site, after expansion, which is the macro analogue of dynamic scope, and it has the same symptom: renaming a variable changes what a program does.

5.5.7 A Look at Lean

The last file, `bexp.lean`, revisits the Boolean expressions of Section 2.5 in Lean, a functional language whose type checker can also check *proofs*:

```
inductive BExp where
  | leaf (b : Bool)
  | and (l : BExp) (r : BExp)
  | or (l : BExp) (r : BExp)
  | not (b : BExp)

def eval (b : BExp) : Bool :=
  match b with
  | BExp.leaf b => b
  | BExp.and l r => eval l ∧ eval r
  | BExp.or l r => eval l ∨ eval r
  | BExp.not b => ¬ (eval b)

def opt (b : BExp) : BExp := b

theorem opt_correct : ∀ (b : BExp), eval (opt b) = eval b := by
  intro b
  unfold opt
  exact Bool.le_antisymm (fun a => a) fun a => a
```

`inductive` is `define-type`, and `eval` is the interpreter of Recitation 2 written with `match`. The new part is the `theorem`. In Recitation 2 the optimizer was checked by *testing* that `(eval (opt b))` equals `(eval b)` on chosen examples. Here the same statement is written for *all* `b` as a type, and the proof after `by` is a program that Lean checks has that type. The handout's `opt` is still the identity, so after `unfold opt` the goal is `eval b = eval b`; the last line proves it from $\leq$ in both directions (`rfl` would also do). Replacing `opt` by the De Morgan optimizer of Section 2.5 would make the theorem say something; its proof would then need induction on `b`, one case per constructor.

The rest of the file hints at *dependent types*, types that mention values:

- `BExpProof` packages an expression, a result, and a `certificate : eval bexp = result`. A value of this type cannot be built unless the result really is the value of the expression.
- `crazy (xs : Array Int) : (if xs.size > 10 then String else Int)` has a return type that depends on the *length* of its argument. A caller can use the result only after finding out which branch holds, which is what `if h : xs.size > 10` in `crazier` does: `h` is a proof of the condition, available inside the branch.

The bodies are `sorry`, Lean's placeholder that type checks as anything; the file shows what can be *stated*, not how to prove it.

Chapter 6

Week 6: Mutable State

Lecture 6: October 13, 2026. Recitation 6 will be added after it meets.

Supplementary reading:

- [1] Chapter 8 (Mutation: Structures and Variables), Section 8.1 in particular, which adds boxes to the closure interpreter with a store as this lecture does.
- [3] Section 3.1 (Assignment and Local State), for what assignment costs: an expression can no longer be replaced by its value.
- [6], optional: the paper that names the problem of Section 6.4, an interpreter that silently inherits features of the language it is written in.

Every interpreter so far has been *pure*: evaluating an expression produced a value and nothing else, so the same expression in the same environment always gave the same answer. Lecture 6 adds the smallest piece of mutable state, the box of Section 2.4, to last week's closure interpreter (`lecture5e.rkt`, Section 5.4). The first attempt stores a box's contents directly in the value and cannot express `set-box!`. The fix is a second table next to the environment, the *store*, which maps locations to values and is passed into and out of every evaluation step. The lecture then writes the same interpreter a second time using Racket's own boxes, and compares the two. This chapter covers:

- Section 6.1: the four new constructs, the examples, and a first attempt that cannot mutate;
- Section 6.2: store-passing style, with locations, `fetch`, the Result type, and threading the store through arithmetic, `let`, and application;
- Section 6.3: the box clauses of the store-passing interpreter, with traces showing where the environment and where the store come from;
- Section 6.4: the meta-circular interpreter, which implements boxes with Racket boxes, and what each version explains.

6.1 State and Boxes

6.1.1 Four New Constructs

The starting file is "a starting point for today's exploration of mutable state". It takes the closure interpreter of `lecture5e.rkt` (Section 5.4) and adds four constructs to Expr: `boxC` creates a box, `unboxC` reads its contents, `setboxC` updates them, and `seqC` is Racket's `(begin e1 e2)`.

```
(define-type Expr
  [numC (n : number)]
  [plusC (e1 : Expr) (e2 : Expr)]
  [timesC (e1 : Expr) (e2 : Expr)]
  [letC (x : symbol) (e1 : Expr) (e2 : Expr)]
  [lambdaC (x : symbol) (e : Expr)]
  [appC (e1 : Expr) (e2 : Expr)]
  [idC (x : symbol)]
  [boxC (e : Expr)]
  [unboxC (e : Expr)]
  [setboxC (e1 : Expr) (e2 : Expr)]
  [seqC (e1 : Expr) (e2 : Expr)])
```

The parser gets one line per construct, in the `case` on the head symbol, with Racket's names as the concrete syntax:

```
[(begin) (seqC (parse (second l)) (parse (third l)))]
[(box) (boxC (parse (second l)))]
[(set-box!) (setboxC (parse (second l)) (parse (third l)))]
[(unbox) (unboxC (parse (second l)))]
```

concrete syntax	abstract syntax	meaning
`(box e)`	`boxC`	a new box whose contents is the value of `e`
`(unbox e)`	`unboxC`	the current contents of the box `e`
`(set-box! e1 e2)`	`setboxC`	make the value of `e2` the contents of the box `e1`
`(begin e1 e2)`	`seqC`	evaluate `e1`, then `e2`; the value is that of `e2`

`begin` takes exactly two expressions, so a longer sequence is written with nested `begin`s. That is all the starting file provides: Value is still `numV` and `closV`, and `eval-env` is the one of `lecture5e.rkt` with an `else` clause that reports the new variants as unimplemented. The rest of the lecture writes the four clauses, twice.

6.1.2 The Examples

The file ends with five test programs:

```
(define ex1 (parse '(begin (+ 1 1) (+ 2 2))))
(define ex2 (parse '(let b (box 0) (set-box! b 1))))
(define ex3 (parse '(let b (box 0) (unbox b))))
(define ex4 (parse '(let b (box 0) (begin (begin (set-box! b 1)
                                                 (set-box! b (+ 1 (unbox b))))
                                          (unbox b)))))

(define ex5
  (parse '(let a (box 1)
            (let f (lambda x (+ x (unbox a)))
              (begin
                (set-box! a 2)
                (f 10))))))
```

Read as Racket programs, they should give:

- `ex1`: 4. The value of `(+ 1 1)` is computed and thrown away.
- `ex2`: whatever `set-box!` returns. Racket's returns `(void)`; this language will return the box (Section 6.3).
- `ex3`: 0, the initial contents.
- `ex4`: 2. The box is set to 1, then to one more than its contents, and read.
- `ex5`: 12. This is the interesting one. The closure `f` is created while `a` holds 1, and called after `a` has been set to 2. The closure saved its environment (Section 5.4), yet `(unbox a)` in its body must see the *new* contents, so $10 + 2 = 12$. Racket itself gives 12 for the same program.

6.1.3 Attempt 1: A Box Holds Its Value

The obvious first try: a box value simply contains the value it holds.

```
(define-type Value
  [numV (n : number)]
  [closV (env : Env) (x : symbol) (e : Expr)]
  [boxV (v : Value)])

    [boxC (e) (boxV (eval-env env e))]
    [unboxC (e) (boxV-v (eval-env env e))]
    [setboxC (e1 e2)
             (let ([v (eval-env env e1)])
               (boxV (eval-env env e2)))]
    [seqC (e1 e2)
          (let ([v (eval-env env e1)])
            (eval-env env e2))]
```

`boxC` and `unboxC` are fine: wrap the value, unwrap it. The trouble is `setboxC`. It evaluates the box `e1` into `v`, and then there is nothing to do with `v`: a `boxV` is an immutable piece of data, so the only option is to build a *new* `boxV` holding the new value. `seqC` evaluates `e1`, ignores the result, and evaluates `e2`. On the examples:

	Attempt 1	expected
ex1	(numV 4)	4
ex2	(boxV (numV 1))	the box, now holding 1
ex3	(numV 0)	0
ex4	(numV 0)	2
ex5	(numV 11)	12

In ex4, each set-box! builds a new box that the enclosing begin throws away, while the environment still binds b to the original (boxV (numV 0)) (Figure 6.1). The final (unbox b) reads that box and gets 0. In ex5, f's saved environment binds a to (boxV (numV 1)) forever, so the call gives 11.




Figure 6.1: Attempt 1 on ex4. Nothing points to the boxes that set-box! builds; the name b still refers to the original, unchanged box. The second one holds 1 because (unbox b) still reads 0.

Pitfall 80 (ex2 looks right)

(eval ex2) is (boxV (numV 1)), exactly what a working set-box! would return, and (unbox (set-box! (box 0) 7)) gives (numV 7). The new contents are visible through the *return value* of set-box!, never through the name of the box. That is functional update, like cons building a new list, not mutation. A test of mutation has to read the box again through another path afterwards, as ex4 and ex5 do.

The same failure shows up whenever two parts of a program hold the same box. In (let a (box 0) (let b a (begin (set-box! b 3) (unbox a)))), a and b name one box, so the answer should be 3; Attempt 1 gives (numV 0). A binding in the environment holds a *copy* of a value, and values are immutable, so a box cannot be a value that contains its contents.

Key Point 81 (Mutation needs a level of indirection)

For a change made through one reference to be seen through another, both must refer to a shared place that holds the contents, rather than contain the contents themselves. The box value must say *where* its contents are, and the contents must be kept somewhere that every part of the evaluation can see and that can change over time.

6.2 Store-Passing Style

6.2.1 Locations and the Store

The indirection is a second table. A box value no longer contains its contents; it contains a *location*, a number that names a cell in a table called the *store*.

Definition 82 (Location, store)

A *location* is an address, here a number. The *store* maps locations to values. A box value is a location; its contents are whatever the store currently maps that location to.

So a name now goes through up to two tables: the environment maps the name to a value, and if that value is a box, the store maps the box's location to its contents. The code for the store copies the code for the environment (Section 5.2) line for line:

```
(define-type-alias Location number)

(define-type Storage
  [cell (l : Location) (val : Value)])

(define-type-alias Store (listof Storage))
(define empty-store empty)
(define override-store cons)

(define (fetch (l : Location) (sto : Store)) : Value
  (cond
    [(cons? sto)
     (if (equal? (cell-l (first sto)) l)
         (cell-val (first sto))
         (fetch l (rest sto)))]
    [else (error 'fetch "No location found")]))
```

	environment	store
maps	names (`symbol`) to values	locations (`number`) to values
entry	`(bind name val)`	`(cell l val)`
add an entry	`extend-env` = `cons`	`override-store` = `cons`
look up	`lookup`, newest first	`fetch`, newest first

`fetch` is `lookup` with the names changed. Writing to a location does not remove its old cell: `override-store` puts a new cell for the same location on the front, and `fetch` stops at the first match. The latest write wins in the same way that the innermost binding wins in `lookup` (Figure 5.3), with shadowing in time instead of shadowing in the program text.

6.2.2 Results Carry the Store

A box value is now a location:

```
(define-type Value
  [numV (n : number)]
  [closV (env : Env) (x : symbol) (e : Expr)]
  [boxV (l : Location)])
```

Evaluating an expression may now change the store, and whoever evaluates next must see the change. So `eval-env` takes the current store as an argument and returns, together with the value, the store as it is *after* the evaluation:

```
(define-type Result
  [res (v : Value) (sto : Store)])

(define (eval-env (env : Env) (sto : Store) (e : Expr)) : Result
  (type-case Expr e
    [numC (n) (res (numV n) sto)]
    [lambdaC (x e) (res (closV env x e) sto)]
    [idC (x) (res (lookup x env) sto)]
    ...))

(define (eval (e : Expr))
  (eval-env empty-env empty-store e))
```

Numbers, `lambda`, and names do not touch the store, so they return the store they were given.

Key Point 83 (Store-passing style)

Every evaluation takes the store as input and returns the updated store as output. An effect is no longer something that *happens*; it is a difference between the store that went in and the store that came out. The interpreter itself stays pure: no Racket mutation is needed to explain the language's mutation (with one exception, `new-loc` below).

6.2.3 Fresh Locations

`(box e)` needs a location that no existing box uses. The lecture first wrote `new-loc` like this, and then commented it out:

```
#|
(define new-loc
  (let ([b (box 0)])
    (let ([l (unbox b)])
      (begin
        (set-box! b (+ 1 l))
        l))))
|#
```

There is no `lambda`, so the right-hand side is evaluated once, when the `define` runs: it creates the box, reads 0, sets the box to 1, and returns 0. `new-loc` is just the number 0, and the box is never seen again. Asking for `new-loc` twice gives 0 both times, and `(new-loc)` does not even type check:

```
> new-loc
- number
0
> (new-loc)
typecheck failed: call of a non-function
```

The fix wraps the body in `(lambda () ...)` inside the `let`:

```
(define new-loc
  (let ([b (box 0)])
    (lambda ()
      (let ([l (unbox b)])
        (begin
          (set-box! b (+ 1 l))
          l)))))
```

Now the `let` runs once and creates one box, and `new-loc` is a closure over it; the body runs at every call. This is the counter pattern: `make-adder` of Section 2.3 with a box in place of a number, so the closure's private state can change.

```
> (new-loc)
- number
0
> (new-loc)
- number
1
> (new-loc)
- number
2
```

Remark 84. `new-loc` implements the language's mutation using Racket's: `set-box!` on a Racket box. It is the one place where the store-passing interpreter is not pure. Only freshness matters, so the effect is harmless, but the counter is global: it is never reset between programs. Evaluating `ex2` twice in one session gives `(res (boxV 0) ...)` the first time and `(res (boxV 1) ...)` the second, with the same contents. The traces in this chapter are each run in a fresh session, so locations start at 0.

6.2.4 Threading the Store Through Arithmetic

`plusC` has two subexpressions, either of which may change the store. The clause evaluates `e1` in the incoming store `sto`, giving `sto1`; evaluates `e2` in `sto1`, giving `sto2`; and returns `sto2`:

```
    [plusC (e1 e2)
           (let ([r1 (eval-env env sto e1)])
             (type-case Result r1
               [res (v1 sto1)
                    (let ([r2 (eval-env env sto1 e2)])
                      (type-case Result r2
                        [res (v2 sto2)
                             (res (numV (+ (numV-n v1) (numV-n v2))) sto2)])))]))]
```

`type-case Result` is used here only to take a `res` apart into its two fields. `timesC` is the same with `*`. The store is *threaded*: each evaluation's output store is the next one's input (Figure 6.2), while `env` is passed unchanged to both operands, as before.




Figure 6.2: Threading the store through `(+ e1 e2)`. The store flows through the operands in sequence; the environment is handed to both unchanged.

Pitfall 85 (Passing the wrong store)

Every store has type Store, so the type checker accepts any of `sto`, `sto1`, `sto2` in any position. Two plausible slips in `plusC` are evaluating `e2` in `sto`, and returning `sto1`. Each is caught by a program that writes to a box inside one operand (these variants are not lecture code):

```
(let b (box 0) (+ (begin (set-box! b 5) 0) (unbox b)))   ; P1
(let b (box 0) (begin (+ 0 (begin (set-box! b 5) 0)) (unbox b)))   ; P2
```

program	lecture `plusC`	`e2` gets `sto`	returns `sto1`
P1	`(numV 5)`	`(numV 0)`	`(numV 5)`
P2	`(numV 5)`	`(numV 5)`	`(numV 0)`

Evaluating `e2` in `sto` makes `e2` blind to `e1`'s writes; returning `sto1` forgets `e2`'s writes once the addition is over. Each store must be used exactly once, by the next step.

6.2.5 `let` Is Application, Again

`letC` would need the same threading: evaluate `e1` in `sto`, then the body in the resulting store. The lecture avoids writing it by turning `let` into application, the equation of Section 5.1:

```
[letC (x e1 e2) (eval-env env sto (appC (lambdaC x e2) e1))]
```

The rewriting happens in `eval-env` rather than in `parse`, but the effect is the same: the store is threaded through `let` by the code for `appC`, written once. The equation is valid here because both `let` and application are eager.

6.2.6 Application

`appC` evaluates the function in `sto` and the argument in `sto1`, as `plusC` did, and then runs the body:

```
[appC (e1 e2)
      (type-case Result (eval-env env sto e1)
        [res (v1 sto1)
             (type-case Result (eval-env env sto1 e2)
               [res (v2 sto2)
                    (eval-env (extend-env (bind (closV-x v1) v2) (closV-env v1))
                              sto2
                              (closV-e v1))])])]
```

The body gets its environment and its store from different places. The environment is the closure's, `(closV-env v1)`, extended with the parameter: lexical scope, unchanged from `lecture5e.rkt`, whose comment the clause keeps ("we're going to use and extend the saved environment from the closure, instead of the current environment"). The store is `sto2`, the *current* one. A closure saves an environment but no store, and `closV` has no field for one.

Key Point 86 (Environment vs. store)

The environment follows the program text: it is saved in closures and restored when they are called, so a name means what it meant where it was written. The store follows time: it is passed from each step to the next in execution order and is never saved or restored, so a box's contents are whatever was last written, wherever the reading code was written.

If closures saved the store too, `f` in `ex5` would read `a` in the store of the moment `f` was created, where it holds 1, and `ex5` would give 11, the wrong answer of Attempt 1. Section 6.3 traces `ex5` and draws both tables.

6.3 Boxes in the Store-Passing Interpreter

6.3.1 The Box Clauses

With the store in place, the four new clauses are short. `boxC` evaluates the initial contents, takes a fresh location, and adds a cell for it; `unboxC` evaluates the box and fetches its location:

```
[boxC (e)
      (type-case Result (eval-env env sto e)
        [res (v sto1)
             (let ([l (new-loc)])
               (res (boxV l) (override-store (cell l v) sto1)))])]
[unboxC (e)
        (type-case Result (eval-env env sto e)
          [res (v1 sto1)
               (let ([v2 (fetch (boxV-l v1) sto1)])
                 (res v2 sto1))])]
```

Note that `unboxC` fetches from `sto1`, the store *after* evaluating `e`, in case evaluating the box expression itself wrote to it. `setboxC` evaluates the box and then the new contents, threading the store as `plusC` does, and adds a cell for the box's location on top of `sto2`:

```
[setboxC (e1 e2)
         (type-case Result (eval-env env sto e1)
           [res (v1 sto1)
                (type-case Result (eval-env env sto1 e2)
                  [res (v2 sto2)
                       (res v1 (override-store (cell (boxV-l v1) v2) sto2))])])]
[seqC (e1 e2)
      (type-case Result (eval-env env sto e1)
        [res (v1 sto1)
             (eval-env env sto1 e2)])]
```

Two details:

- `setboxC` returns `v1`, the box itself, not the new contents and not a void value (the language has none). This is a design choice; Racket's `set-box!` returns `(void)`.
- `seqC` discards `v1` but *not* `sto1`: `e2` runs in the store that `e1` left behind. In Attempt 1 the `seqC` clause looked the same, but there was no store to pass on, so `e1` could only be evaluated and forgotten. Here sequencing finally has a purpose: `e1` is run for its effect on the store.

6.3.2 Running the Examples

Each in a fresh session, so that `new-loc` starts at 0:

```
> (eval ex1)
- Result
(res (numV 4) '())
> (eval ex2)
- Result
(res (boxV 0) (list (cell 0 (numV 1)) (cell 0 (numV 0))))
```

```
> (eval ex3)
- Result
(res (numV 0) (list (cell 0 (numV 0))))
> (eval ex4)
- Result
(res (numV 2) (list (cell 0 (numV 2)) (cell 0 (numV 1)) (cell 0 (numV 0))))
> (eval ex5)
- Result
(res (numV 12) (list (cell 0 (numV 2)) (cell 0 (numV 1))))
```

All five are now right. `ex1` allocates nothing, so its final store is empty. `ex2` is the result shown in lecture: the value is the box, location 0, and the store holds two cells for location 0, the write of 1 in front of the initial 0.

6.3.3 Tracing `ex4`

Write the store newest first, with `l:v` for `(cell l v)`. The outer `let` becomes an application of `(lambda b ...)` to `(box 0)`:

```
(let b (box 0) (begin (begin (set-box! b 1)
                             (set-box! b (+ 1 (unbox b))))
                      (unbox b)))
  (lambda b ...)                          ---> closure, sto = []
  (box 0)       new location 0            sto = [0:0]
  body in env [b=(boxV 0)]
    (set-box! b 1)                        sto = [0:1, 0:0]
    (set-box! b (+ 1 (unbox b)))
      (unbox b): fetch 0 ---> 1
      (+ 1 1) ---> 2                      sto = [0:2, 0:1, 0:0]
    (unbox b): fetch 0 ---> 2
---> (numV 2) with sto = [0:2, 0:1, 0:0]
```

The environment never changes after the `let`: `b` is bound to `(boxV 0)` throughout. Every change happens in the store, and each `begin` hands the store from its first part to its second.

6.3.4 Tracing `ex5`: Two Tables, Two Paths

```
(let a (box 1)
  (let f (lambda x (+ x (unbox a)))
    (begin (set-box! a 2) (f 10))))
  (box 1)       new location 0            sto = [0:1]
  env [a=(boxV 0)]
  (lambda x ...) ---> f = (closV [a=(boxV 0)] x (+ x (unbox a)))
  env [f=closure, a=(boxV 0)]
  (set-box! a 2)                          sto = [0:2, 0:1]
  (f 10)
    body env:   the closure's [a=(boxV 0)] + x=10
    body store: the current one,          sto = [0:2, 0:1]
    (unbox a): fetch 0 ---> 2
    (+ 10 2) ---> 12
---> (numV 12) with sto = [0:2, 0:1]
```

The closure saved the binding `a=(boxV 0)`: a location, not a number. The location has not changed since the closure was created, but the store has, and the call reads the current store (Figure 6.3). This is how lexical

scope and mutation coexist: the closure fixes *which* box `a` is, and the store says what is in it *now*.




Figure 6.3: `ex5` while evaluating `(unbox a)` in `f`'s body. The environment (left) comes from the closure; the store (right) is the current one. The store at closure-creation time is still there as a suffix, but nothing reads it, since `fetch` stops at the newer cell.

Key Point 87 (Where the environment and the store come from)

	environment	store
to subexpressions	the same `env` to each	chained: `sto`, then `sto1`, ...
returned by `eval-env`	never	always, in the `res`
saved in a closure	yes	no
used for a function body	the closure's, extended	the current one, `sto2`
follows	the program text	the order of evaluation

6.3.5 The Store Only Grows

Nothing ever removes a cell. `set-box!` conses a new cell for an existing location, and the old one stays behind it, unreachable by `fetch`: after `ex4` the store holds three cells for location 0, of which only the first matters. Boxes that no part of the program can reach any more also keep their cells. A real implementation would overwrite a location in place and reclaim the memory of unreachable boxes with a garbage collector [1, Chapter 11]. For explaining what mutation *means*, a store that only grows is simpler: every past state is still visible in the trace, and the store after any step is the store before it with some cells added on the front.

6.4 The Meta-Circular Interpreter

6.4.1 Boxes Implemented by Boxes

The store-passing interpreter needed a new type, a new argument and result for `eval-env`, and a rewrite of every clause. The lecture's second file starts again from the starting file and takes a shortcut: the object language's boxes are implemented with Racket's boxes.

Definition 88 (Meta-circular interpreter)

An interpreter is *meta-circular* when it implements a feature of the language it interprets by the same feature of the language it is written in. SICP uses the word for an evaluator written in the language that it evaluates [3, Section 4.1]; here the word applies to one feature, boxes.

A box value holds a Racket box of values, `(boxof Value)`. `eval-env` goes back to the signature of `lecture5e.rkt`, `(env e) : Value`, with no store, and every old clause is unchanged:

```
(define-type Value
  [numV (n : number)]
  [closV (env : Env) (x : symbol) (e : Expr)]
  [boxV (b : (boxof Value))])

    [boxC (e)
          (boxV (box (eval-env env e)))]
    [unboxC (e)
            (unbox (boxV-b (eval-env env e)))]
    [setboxC (e1 e2)
             (let ([v1 (eval-env env e1)]
                   [v2 (eval-env env e2)])
               (begin
                 (set-box! (boxV-b v1) v2)
                 v1))]
    [seqC (e1 e2)
          (begin
            (eval-env env e1)
            (eval-env env e2))]
```

Each clause does in Racket what the construct does in the object language. `(box e)` makes a Racket box holding the value of `e` and wraps it in `boxV`. `unbox` unwraps and reads it. `set-box!` evaluates the box and the new contents and mutates the Racket box; like the store-passing version, it returns the box `v1`. `seqC` is Racket's `begin`.

Remark 89. Once all eleven variants have clauses, the starting file's `else` clause can never be reached, and `plai-typed` rejects the program: "the else branch of this type-case is unreachable". Deleting the `else` fixes it.

Compare this `setboxC` with Attempt 1's. There, `boxV` contained a `Value` directly, and `set-box!` could only build a new `boxV`. Here `boxV` contains a Racket box, a reference to a mutable cell. Copying the `boxV` into an environment or a closure copies the reference, not the cell, so every copy sees the same contents. This is the indirection of Section 6.1, supplied by Racket. The results agree with the store-passing interpreter on all five examples:

```
> (eval ex1)
- Value
(numV 4)
> (eval ex2)
- Value
(boxV (box (numV 1)))
> (eval ex3)
- Value
(numV 0)
> (eval ex4)
- Value
(numV 2)
> (eval ex5)
- Value
(numV 12)
```

In `ex5`, the closure for `f` saves an environment in which `a` is bound to a `boxV` holding a Racket box; `(set-box! a 2)` mutates that Racket box, and the call reads it.

6.4.2 Side by Side

	store-passing	meta-circular
box value	`(boxV l)`, a location	`(boxV b)`, a Racket box
contents live in	the store, an explicit list of cells	Racket's heap
`eval-env`	`(env sto e) : Result`	`(env e) : Value`
`set-box!`	adds a cell to the store it returns	Racket's `set-box!`
`begin`	passes `sto1` from `e1` to `e2`	Racket's `begin`
order of evaluation	forced by the store: `e2` needs `sto1`	whatever Racket does
Racket mutation used	only in `new-loc`	for every box operation
old clauses	all rewritten to thread the store	unchanged

6.4.3 What Each Version Explains

The meta-circular interpreter is much shorter, and it is correct, but it explains mutation *by* mutation. Someone who does not already know what `set-box!` does learns nothing from `[setboxC ... (set-box! (boxV-b v1) v2) ...]`. Two things in particular are inherited from Racket without appearing in the code:

- **The store.** Where the contents of a box live, and what happens to them over time, is Racket's business. The store-passing interpreter writes the store down as a value that can be printed, as in the `(res ...)` results above.
- **The order of evaluation.** In `setboxC`, `e1` is evaluated before `e2` only because Racket's `let` evaluates its right-hand sides left to right; in `plusC`, only because Racket evaluates the arguments of `+` left to right. In the store-passing interpreter the order is forced by data dependencies: `e2` cannot be evaluated until `sto1` exists, and `sto1` is produced by evaluating `e1`.

Once there is mutation, order matters. Consider (not a lecture example) the program

```
(let b (box 1) (+ (unbox b) (begin (set-box! b 10) (unbox b))))
```

Both interpreters give `(numV 11)`: the left operand reads 1 before the right operand writes 10. Evaluating the right operand first would give 20. Without mutation the two orders could never be told apart; with it, the order is part of the meaning of `+`, and the meta-circular interpreter specifies it only by reference to Racket.

Reynolds pointed out this kind of dependence: a definitional interpreter can silently inherit the evaluation order of the language it is written in [6].

Key Point 90 (What an interpreter explains)

An interpreter explains a feature only if it implements it with something simpler. Week 5 implemented environments with Racket lists and `plusC` with Racket's `+`; that was fine, because lists and addition were not what was being studied, and scope was implemented explicitly. This week the object of study is mutation, so implementing it with Racket's mutation is circular. The store-passing interpreter explains mutation with immutable lists and function arguments and results, and in doing so also makes evaluation order explicit.

There is one remaining circle in the store-passing interpreter: `new-loc` uses a Racket box. It is not essential: `new-loc` only has to produce a location not yet in the store, and a counter threaded alongside the store would do. It is the same kind of shortcut as `gensym` in week 4 (Section 4.3), a source of fresh names rather than the subject of the lecture.

Bibliography

[1] S. Krishnamurthi. *Programming Languages: Application and Interpretation*, 2nd edition. 2017. https://cs.brown.edu/~sk/Publications/Books/ProgLangs/

[2] M. Felleisen, R. B. Findler, M. Flatt, and S. Krishnamurthi. *How to Design Programs*, 2nd edition. MIT Press, 2018. https://htdp.org

[3] H. Abelson and G. J. Sussman. *Structure and Interpretation of Computer Programs*, 2nd edition. MIT Press, 1996.

[4] M. Flatt, R. B. Findler, and PLT. *The Racket Guide*. https://docs.racket-lang.org/guide/

[5] B. C. Pierce. *Types and Programming Languages*. MIT Press, 2002.

[6] J. C. Reynolds. Definitional interpreters for higher-order programming languages. In *Proceedings of the ACM Annual Conference*, 1972.

[7] M. L. Scott. *Programming Language Pragmatics*, 4th edition. Morgan Kaufmann, 2015.