pos_order_sale

Column	Type
md5key_order_sale 🔑	VARCHAR(32)
change_recieved	DECIMAL(5,2)
order_number	INT
tax_inclusive_amount	DECIMAL(2,1)
tax_amount	DECIMAL(5,4)
meal_location	TINYINT(1)
transaction_id	INT
store_id	INT
date	DATE

purchased_items

Column	Type
md5key_purchased_item	VARCHAR(32)
md5key_order_sale	VARCHAR(32)
category_desc	VARCHAR(50)
department_desc	VARCHAR(50)
description	VARCHAR(50)
store_id	INT
tax_inclusive_amount	DECIMAL(2,1)
tax_amount	DECIMAL(5,4)
adjusted_price	DECIMAL(3,2)
discount_amount	DECIMAL(4,2)
price	DECIMAL(4,2)
quantity	INT
PLU	VARCHAR(12)
menu_item_id	INT
date	DATE

store_restaurant

Column	Type
id 🔑	INT
address	VARCHAR(50)
region	VARCHAR(50)
state	VARCHAR(50)
city	VARCHAR(50)
zip_code	INT
type	VARCHAR(50)
loyalty_programme	CHAR(1)

menu_items

Column	Type
id 🔑	INT
menu_item_desc	VARCHAR(50)
PLU	VARCHAR(12)
recipe_id	INT

recipes

Column	Type
id 🔑	INT
description	VARCHAR(50)

recipe_sub_recipe_assignment

Column	Type
recipe_id	INT
sub_recipe_id	INT
factor	INT

sub_recipes

Column	Type
id 🔑	INT
sub_recipe_name	VARCHAR(50)
description	VARCHAR(50)

sub_recipe_ingr_assignments

Column	Type
sub_recipe_id	INT
ingredient_id	INT
quantity	INT

recipe_ingredient_assignment

Column	Type
recipe_id	INT
ingredient_id	INT
quantity	INT

ingredients

Column	Type
id 🔑	INT
ingredient_name	VARCHAR(50)
ingredient_short_desc	VARCHAR(50)
portion_uom_type_id	INT

portions_uom_types

Column	Type
id 🔑	INT
description	VARCHAR(15)

pos_order_sale

md5key_order_sale 🔑	VARCHAR(32)
change_recieved	DECIMAL(5,2)
order_number	INT
tax_inclusive_amount	DECIMAL(2,1)
tax_amount	DECIMAL(5,4)
meal_location	TINYINT(1)
transaction_id	INT
store_id	INT
date	DATE

purchased_items

md5key_purchased_item	VARCHAR(32)
md5key_order_sale	VARCHAR(32)
category_desc	VARCHAR(50)
department_desc	VARCHAR(50)
description	VARCHAR(50)
store_id	INT
tax_inclusive_amount	DECIMAL(2,1)
tax_amount	DECIMAL(5,4)
adjusted_price	DECIMAL(3,2)
discount_amount	DECIMAL(4,2)
price	DECIMAL(4,2)
quantity	INT
PLU	VARCHAR(12)
menu_item_id	INT
date	DATE

menu_items

id 🔑	INT
menu_item_desc	VARCHAR(50)
PLU	VARCHAR(12)
recipe_id	INT

recipes

id 🔑	INT
description	VARCHAR(50)

recipe_sub_recipe_assignment

recipe_id	INT
sub_recipe_id	INT
factor	INT

sub_recipes

id 🔑	INT
sub_recipe_name	VARCHAR(50)
description	VARCHAR(50)

sub_recipe_ingr_assignments

sub_recipe_id	INT
ingredient_id	INT
quantity	INT

recipe_ingredient_assignment

recipe_id	INT
ingredient_id	INT
quantity	INT

ingredients

id 🔑	INT
ingredient_name	VARCHAR(50)
ingredient_short_desc	VARCHAR(50)
portion_uom_type_id	INT

portions_uom_types

id 🔑	INT
description	VARCHAR(15)

store_restaurant

id 🔑	INT
address	VARCHAR(50)
region	VARCHAR(50)
state	VARCHAR(50)
city	VARCHAR(50)
zip_code	INT
type	VARCHAR(50)
loyalty_programme	CHAR(1)

dbdiagram.io