



Task: External Data Sources - Files

www.hyperiondev.com



Introduction

Welcome to the Input and Output Task!

The Java programs we have written so far store data in a variable and as soon as we end the program, the data is lost. In this task, you are going to be introduced to file input and output. A way in which we can write program data to an external storage medium(i.e your hard drive or usb flash drive).



**CONNECT WITH
YOUR MENTOR**

You don't have to take our courses alone! This course has been designed to be taken with an online mentor that marks your submitted code by hand and supports you to achieve your career goals on a daily basis.

To access this mentor support simply navigate to www.hyperiondev.com/support.

Reading a File

Files are useful for storing and retrieving data, and there are a number of ways to read from a file. One of the simplest ways is to use the `Scanner` class from the `java.util` package. The constructor of the `Scanner` class can take a `File` object as input. To read the contents of a text file at the path "C:\\test.txt", we would need to create a `File` object with the corresponding path and pass it to the `Scanner` object:

```
try {  
    File x = new File("C:\\test.txt");  
    Scanner sc = new Scanner(x);  
}  
catch (FileNotFoundException e) {  
  
}
```

Note: We surrounded the code with a `try/catch` block, because there's a chance that the file may not exist.

The `Scanner` class inherits from the `Iterator`, so it behaves like one. We can use the `Scanner` object's `next()` method to read the file's contents:

```
try {  
    File x = new File("C:\\test.txt");  
    Scanner sc = new Scanner(x);  
    while(sc.hasNext()) {  
        System.out.println(sc.next());  
    }  
    sc.close();  
} catch (FileNotFoundException e) {  
    System.out.println("Error");  
}
```

The file's contents are output word by word, because the `next()` method returns each word separately.

Note: It is always good practice to close a file when finished working with it. One way to do this is to use the `Scanner`'s `close()` method.

Creating Files

Formatter, another useful class in the `java.util` package, is used to create content and write it to files. Example:

```
import java.util.Formatter;

public class MyClass {
    public static void main(String[] args) {
        try {
            Formatter f = new Formatter("C:\\test.txt");
        } catch (Exception e) {
            System.out.println("Error");
        }
    }
}
```

This creates an empty file at the specified path. If the file already exists, this will overwrite it.

***Note:** Again, you need to surround the code with a try/catch block, as the operation can fail.*

Writing to Files

Once the file is created, you can write content to it using the same `Formatter` object's `format()` method. Example:

```
import java.util.Formatter;

public class MyClass {
    public static void main(String[] args) {
        try {
            Formatter f = new Formatter("C:\\test.txt");
            f.format("%s %s %s", "1", "John", "Smith \r\n");
            f.format("%s %s %s", "2", "Amy", "Brown");
            f.close();
        } catch (Exception e) {
            System.out.println("Error");
        }
    }
}
```

The `format()` method formats its parameters according to its first parameter. `%s` mean a string and gets replaced by the first parameter after the format. The second `%s` gets

replaced by the next one, and so on. So, the format `%s %s %s` denotes three strings that are separated with spaces.

Note: `\r\n` is the newline symbol in Windows.

The code above creates a file with the following content:

```
1 John Smith  
2 Amy Brown
```

Note: Don't forget to close the file once you're finished writing to it!

Compulsory Task 1

Follow these steps:

- Create a new java file called MyFile.java
- Write code to read the content of the text file input.txt. For each line in input.txt, write a new line in the new text file output.txt that computes the answer to some operation on a list of numbers.
- If the input.txt has the following:
Min: 1,2,3,5,6
Max: 1,2,3,5,6
Avg: 1,2,3,5,6

Your program should generate output.txt as follows:

The min of [1, 2, 3, 5, 6] is 1.

The max of [1, 2, 3, 5, 6] is 6.

The avg of [1, 2, 3, 5, 6] is 3.4.

- Assume that the only operations given in the input file are min, max and avg, and that the operation is always followed by a list of comma separated integers. You should define the functions min, max and avg that take in a list of integers and return the min, max or avg of the list.
- Your program should handle any combination of operations and any length of input numbers. You can assume that the list of input numbers are always valid integers and that the list is never empty.
- Compile, save and run your file.

Compulsory Task 2

Follow these steps:

- Modify your MyFile.java file to do the following:
- Change your program to additionally handle the operation "px" where x is a number from 10 to 90 and defines the x percentile of the list of numbers. E.g.:
Input.txt:
Min: 1,2,3,5,6

Max: 1,2,3,5,6
Avg: 1,2,3,5,6
P90: 1,2,3,4,5,6,7,8,9,10
Sum: 1,2,3,5,6
P70: 1,2,3

- Your output.txt should read:
The min of [1,2,3,5,6] is 1.
The max of [1,2,3,5,6] is 6.
The avg of [1,2,3,5,6] is 3.4.
The 90th percentile of [1,2,3,4,5,6,7,8,9,10] is 9.
The sum of [1,2,3,5,6] is 17.
The 70th percentile of [1,2,3] is 2.
- Compile, save and run your file.



SHARE YOUR
THOUGHTS WITH US

Hyperion strives to provide internationally-excellent course content that helps you achieve your learning outcomes. Think the content of this task, or this course as a whole, can be improved or think we've done a good job? [Click here](#) to share your thoughts anonymously.