BFP196WN

Low noise silicon bipolar RF transistor

Product description

- NPN silicon planar epitaxial transistor in 4-pin dual-emitter SOT343 package for low noise and low distortion wideband amplifiers. This RF transistor benefits from Infineon long-term experience in RF components and combines ease-of-use to stable volumes production, at benchmark quality and reliability.

Features

- For high voltage applications V_{CE} < 12 V
- Maximal power P_{tot} = 700 mW
- Transition frequency f_T = 7.5 GHz
- Noise figure NF_{min} = 1.3 dB at 900 MHz
- Easy to use Pb-free (RoHS compliant) and halogen-free industry standard SOT343 package with visible leads



Application

- GNSS active antenna
- Amplifiers in antenna and telecommunications systems
- CATV
- Power amplifier for DECT and PCN systems

Product validation

Qualified for industrial applications according to the relevant tests of JEDEC47/20/22

Device information

Attention: ***ESD (Electrostatic discharge) sensitive device, observe handling precautions***

Type / Ordering code	Package	Pin configuration				Marking	Related Links
BFP196WN / BFP196WNH6327XTSA1	SOT343	1=E	2=C	3=B	4=E	RLs	see ***SOT343 Package***

Table of contents

1 Absolute maximum ratings

Table 1 Absolute maximum ratings at T_A = 25 °C (unless otherwise specified)

Parameter	Symbol	Values		Unit	Note or Test condition
		Min.	Max.		
Collector emitter voltage	V_{CEO}	–	12	V	Base open
Collector emitter voltage	V_{CES}	–	20	V	Emitter / base short circuited
Collector base voltage	V_{CBO}	–	20	V	Emitter open
Emitter base voltage	V_{EBO}	–	2	V	Collector open
DC collector current	I_C	–	150	mA	–
DC base current	I_B	–	15	mA	–
Total power	P_{tot}	–	700	mW	–
Junction temperature	T_J	–	150	°C	–
Storage temperature	T_{Stg}	-55	150	°C	–

Attention*: *Stresses above the maximum values listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Maximum ratings are absolute ratings. Exceeding only one of these values may cause irreversible damage to the component.

2 Thermal characteristics

Table 2 Thermal resistance

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
Junction - soldering point	R_{thJS}	–	115	–	K/W	1)



Figure 1 Absolute maximum power dissipation P_{tot} vs. T_s

Note: *In the horizontal part of the above curve the junction temperature T_J is lower than $T_{J,max}$. In the declining slope it is $T_J = T_{J,max}$. P_{tot} has to be reduced according to the curve in order not to exceed $T_{J,max}$. It is $T_{J,max} = T_S + P_{tot} * R_{THJS}$.*

1 For the definition of R_{thJS} please refer to the application note AN077

3 Electrical performance in test fixture

3.1 DC parameter table

Table 3 DC characteristics at T_A = 25 °C

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
Collector emitter breakdown voltage	V_{CEO}	12	–	–	V	I_C = 1 mA, open base
Collector emitter leakage current	I_{CES}	–	–	100	µA	V_{CE} = 20 V, V_{BE} = 0 V Emitter / base short circuited
Collector base leakage current	I_{CBO}	–	–	100	nA	V_{CB} = 10 V, V_{BE} = 0 Open emitter
Emitter base leakage current	I_{EBO}	–	–	1	µA	V_{EB} = 1 V, I_C = 0 Open collector
DC current gain	h_{FE}	70	100	140		V_{CE} = 8 V, I_C = 50 mA Pulse measured

3.2 AC parameter tables

Table 4 General AC characteristics at T_A = 25 °C

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Transition frequency	f_T	5	7.5	–	GHz	V_{CE} = 8 V, I_C = 90 mA, f=500 MHz
Collector base capacitance	C_{CB}	–	0.9	–	pF	V_{CB} = 10 V, V_{BE} = 0 V, f = 1 MHz Emitter grounded
Collector emitter capacitance	C_{CE}	–	0.35	–	pF	V_{CE} = 10 V, V_{BE} = 0 V, f = 1 MHz Base grounded
Emitter base capacitance	C_{EB}	–	3.8	–	pF	V_{EB} = 0.5 V, V_{CB} = 0 V, f = 1 MHz Collector grounded

Electrical performance in test fixture

Measurement setup for the AC characteristics shown in the following tables is a test fixture with Bias T's in a 50 Ω system, T_A = 25 °C.



Figure 2 BFP196WN testing circuit

Table 5 AC characteristics, V_{CE} = 8 V, f = 0.45 GHz

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Power gain					dB	I_C = 50 mA
Maximum power gain	G_{ms}	–	23.5	–		$Z_s = Z_{Sopt}$, $Z_L = Z_{Lopt}$
Transducer gain	$\|S_{21}\|^2$	–	19.0	–		Z_S=Z_L=50 Ω
Minimum noise figure	NFmin	–	0.95	–	dB	I_C = 20 mA, $Z_S = Z_{Sopt}$
Linearity					dBm	I_C = 50 mA
1 dB compression point at output	OP1dB	–	19	–		Z_S=Z_L=50 Ω
3rd order intercept point at output	OIP3	–	32	–		

Table 6 AC characteristics, V_{CE} = 8 V, f = 0.9 GHz

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Power gain					dB	I_C = 50 mA
Maximum power gain	G_{ms}	–	17.0	–		$Z_s = Z_{Sopt}$, $Z_L = Z_{Lopt}$
Transducer gain	$\|S_{21}\|^2$	–	13.0	–		Z_S=Z_L=50 Ω
Minimum noise figure	NFmin	–	1.1	–	dB	I_C = 20 mA, $Z_S = Z_{Sopt}$
Linearity					dBm	I_C = 50 mA
1 dB compression point at output	OP1dB	–	19	–		Z_S=Z_L=50 Ω
3rd order intercept point at output	OIP3	–	32	–		

Electrical performance in test fixture

Table 7 AC characteristics, V_{CE} = 8 V, f = 1.5 GHz

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Power gain					dB	I_C = 50 mA
Maximum power gain	G_{ms}	–	12.5	–		$Z_s = Z_{Sopt}$, $Z_L = Z_{Lopt}$
Transducer gain	$\|S_{21}\|^2$	–	8.5	–		Z_S=Z_L=50 Ω
Minimum noise figure	NFmin	–	1.7	–	dB	I_C = 20 mA, $Z_S = Z_{Sopt}$
Linearity					dBm	I_C = 50 mA
1 dB compression point at output	OP1dB	–	19	–		Z_S=Z_L=50 Ω
3rd order intercept point at output	OIP3	–	32	–		

Table 8 AC characteristics, V_{CE} = 8 V, f =1.9 GHz

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Power gain					dB	I_C = 50 mA
Maximum power gain	G_{ms}	–	11	–		$Z_s = Z_{Sopt}$, $Z_L = Z_{Lopt}$
Transducer gain	$\|S_{21}\|^2$	–	6.5	–		Z_S=Z_L=50 Ω
Minimum noise figure	NFmin	–	2.1	–	dB	I_C = 20 mA, $Z_S = Z_{Sopt}$
Linearity					dBm	I_C = 50 mA
1 dB compression point at output	OP1dB	–	19	–		Z_S=Z_L=50 Ω
3rd order intercept point at output	OIP3	–	32	–		

Table 9 AC characteristics, V_{CE} = 5 V, f = 2.4 GHz

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Power gain					dB	
Maximum power gain	G_{ms}	–	9.7	–		I_C = 50 mA
Transducer gain	$\|S_{21}\|^2$	–	4.8	–		$Z_s = Z_{Sopt}$, $Z_L = Z_{Lopt}$
						Z_S=Z_L=50 Ω
Minimum noise figure	NFmin	–	2.5	–	dB	I_C = 20 mA, $Z_S = Z_{Sopt}$
Linearity					dBm	I_C = 50 mA
1 dB compression point at output	OP1dB	–	19	–		Z_S=Z_L=50 Ω
3rd order intercept point at output	OIP3	–	32	–		

3.3 Characteristic DC diagrams



Figure 3 Collector current $I_C = f(V_{CE})$, I_B = parameter



Figure 4 Current gain $h_{FE} = f(I_C)$, V_{CE} = 8 V

Electrical performance in test fixture



Figure 5 Collector current $I_C = f(V_{BE})$, V_{CE} = 8 V



Figure 6 Base current $I_B = f(V_{BE})$, V_{CE} = 8 V

Electrical performance in test fixture



Figure 7 Base/emitter leakage current $I_B = f(V_{EB})$, V_{CE} = 8 V

*Note: Regard absolute maximum ratings for I_C, V_{CE} and P_{tot} (see **Table 1**)*

3.4 Characteristic AC diagrams



Figure 8 Transition frequency $f_T = f(I_C)$, V_{CE} = parameter



Figure 9 Gain G_{ms}, G_{ma}, $|S_{21}|^2 = f(f)$, I_C = 50 mA, V_{CE} = 8 V

Electrical performance in test fixture



Figure 10 Maximum power gain $G_{max} = f(I_C)$, V_{CE} = 8 V, f = parameter



Figure 11 Maximum power gain $G_{max} = f(V_{CE})$, I_C = 50 mA, f = parameter

Electrical performance in test fixture



Figure 12 Output reflection coefficient S_{22} = f(f) at V_{CE} = 8 V, I_C = 20, 50 mA



Figure 13 Input reflection coefficient S_{11} = f(f) at V_{CE} = 8 V, I_C = 20, 50 mA

Electrical performance in test fixture



Figure 14 Source impedance for minimum noise figure Z_{Sopt} = f(f), V_{CE} = 8 V, I_C = 20, 50 mA



Figure 15 Noise figure N_{Fmin} = f(f), V_{CE} = 8 V, I_C = 20, 50mA, Z_S = Z_{Sopt}

Electrical performance in test fixture



Figure 16 Noise figure $NF_{min} = f(I_C)$, V_{CE} = 8 V, f = parameter, $Z_S = Z_{Sopt}$



Figure 17 Noise figure $NF_{50} = f(f)$, V_{CE} = 8 V, I_C = 20, 50 mA, Z_S = 50 Ω

Electrical performance in test fixture



Figure 18 Noise figure $NF_{50} = f(I_C)$, V_{CE} = 8 V, f = parameter, Z_S = 50 Ω

*Note: The curves shown in this chapter **Characteristic AC diagrams** have been generated using typical devices but shall not be understood as a guarantee that all devices have identical characteristic curves. T_A = 25 °C.*

4 SOT343 Package



Figure 19 SOT343 package outline (dimension in mm)



Figure 20 SOT343 footprint (dimension in mm)



Figure 21 SOT343 marking layout

Reel ø180 mm: 3.000 Pieces/Reel
Reels/Box: 1 x 3.000 = 3.000

Reel ø330 mm: 10.000 Pieces/Reel
Reels/Box: 1 x 10.000 = 10.000



Figure 22 SOT343 standard packing (dimension in mm)

Revision history

Major changes since previous revision

Reference	Description
Revision History: 2016-12-21, Revision 0.9	
rev 0.9	Preliminary datasheet

Edition 2017-01-20

Published by

Infineon Technologies AG

81726 Munich, Germany

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-kst1478698311373

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”) .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer’s compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer’s products and any use of the product of Infineon Technologies in customer’s applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer’s technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies’ products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Infineon:
BFP196WNH6327XTSA1