

University of Illinois at Urbana-Champaign
Dept. of Electrical and Computer Engineering

ECE 120: Introduction to Computing

Karnaugh Maps (K-Maps)

ECE 120: Introduction to Computing

© 2016-2017 Steven S. Lumetta. All rights reserved.

slide 1

To Simplify, Write Function as a Sum of Prime Implicants

One way to simplify a function F :

Choose a set of prime implicants that, when ORed together, give F .

But our approach for picking prime implicants is not so easy.

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 2

List All Implicants for One Variable A

Let's try a different approach.

Start with functions of one variable, A .

How many implicants are possible?

Remember:

- There are only four functions on A !
- We only consider products of literals.

$A \quad A' \quad 1$

(1 is the product of zero literals.)

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 3

The Domain of a Boolean Function is a Hypercube

We can

- **represent the domain**
- of a Boolean function F on N variables
- **as an N -dimensional hypercube.**

Each vertex in the hypercube corresponds to one combination of the N inputs.

The function F thus **has one value for each vertex** (each input combination).

ECE 120: Introduction to Computing


© 2016 Steven S. Lumetta. All rights reserved.

slide 4

Implicants for $N=1$ Correspond to Vertices and Edge

With $N = 1$ (one variable, A), a hypercube is just a line segment with two vertices.

The three possible **implicants correspond** to the **two vertices** and the **one edge** of the hypercube.



If we write the values of F by the vertices, we can see which implicants are covered with 1s.

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 5

We Draw Function $F(A)$ Using a 1-Variable K-Map


Instead of drawing a line segment, we can draw two boxes, as shown below.

We call this approach a **Karnaugh map (K-map)** on 1 variable.

The left box corresponds to $A = 0$, and the right corresponds to $A = 1$.

Each box represents

- an input combination of A ,
- a vertex of the hypercube, and
- an **implicant (a minterm)**.



ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 6


We Draw Function F Using a 1-Variable K-Map

We can mark implicants of F by **circling boxes that contain 1s**.

Here, we show a **loop** around the box corresponding to the **implicant A** .

To check whether an implicant is prime, we consider **growing the loop** to contain more boxes.

A circle that cannot grow is a prime implicant of F .



ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 7

We Draw Function F Using a 1-Variable K-Map


For the function F shown, we can grow the loop to contain both boxes.

The loop is now as big as possible (the full K-map!), so it cannot grow further.

The result (the **implicant 1**) is a **prime implicant of F** .

So $F(A) = 1$.

Feel excited?



ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 8

List All Implicants for Two Variables, A and B

Now consider two input variables, A and B.

How many implicants are possible?

Start with minterms...

AB AB' $A'B$ $A'B'$

And products of one literal...

A A' B B'

And, of course ...

1


ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 9

Minterms Correspond to Vertices

With $N = 2$ (inputs A and B), a hypercube is a square: four vertices, four edges, and a face.




ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 10

Single-Literal Implicants Correspond to Edges

Edges include both values of one variable.




ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 11

The Implicant 1 Corresponds to the Face/Square

The face includes both values of both variables.



ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 12

We Draw Function $G(A,B)$ Using a 2-Variable K-Map

We can draw a **K-map** on 2 variables for the function $G(A,B)$ as shown below.

Again, each box represents

- an input combination
- a vertex of the hypercube, and
- an **implicant** (a minterm).

		A	
		0	1
B	0	1	1
	1	0	1

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 13

Process for Finding $G(A,B)$ Using a K-Map

Now the problem is more interesting.

We want to **find the largest loops**

- with power-of-2 edge lengths (1 or 2)
- that together cover all 1s in G .

Why?

- A **loop that can't grow is a prime implicant** of G .
- If we cover all 1s, **the sum of the implicants gives the function G .**

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 14

To Find G , Start by Picking a 1 and Circling It

Start by picking a 1 and circling it.

The minterm $A'B'$ is an **implicant** of G .

But it's **not a prime implicant** of G .

We cannot grow the loop downward (cannot cover a 0—that would not be an implicant).

We can **grow the loop to the right...**

		A	
		0	1
B	0	1	1
	1	0	1

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 15

Grow the Loop Until We Get a Prime Implicant

Let's grow the loop.

The loop now represents

B' , which is a **prime implicant** of G .

But we didn't cover one of the 1s in G yet.

We **need a second loop**.

		A	
		0	1
B	0	1	1
	1	0	1

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 16


Start a Second Loop by Circling an Uncovered 1

The new loop represents the minterm **AB**,
which is an **implicant** of **G**.

But it's **not a prime**
implicant of **G**.

We cannot grow the
new loop to the left.

We can **grow the**
new loop upward...



ECE 120: Introduction to Computing

© 2016 Steven S. Lametta. All rights reserved.

slide 17

Again, Grow the Loop Until We Get a Prime Implicant

Let's grow the loop.


The loop now represents
A, which is a **prime**
implicant of **G**.

Together, these two loops
cover all 1s in **G(A,B)**.

So we can write

$$G(A,B) = B' + A$$

Now are you excited?



ECE 120: Introduction to Computing

© 2016 Steven S. Lametta. All rights reserved.

slide 18

List All Implicants for Variables A, B, and C

Guess what's next.

Three input variables: **A**, **B**, and **C**!

How many implicants are possible?

That's right: lots.

A 3D hypercube is a cube.

Let's count features instead.

A 3D Hypercube Has Vertices, Edges, Faces, and Cube

Now, let's count.


of vertices? 8

of edges? 12

of faces? 6

of cubes? 1

So the **total is 27**.



ECE 120: Introduction to Computing

© 2016 Steven S. Lametta. All rights reserved.

slide 19

ECE 120: Introduction to Computing

© 2016 Steven S. Lametta. All rights reserved.

slide 20

Notice a Pattern? 3^N Implicants on N Variables

$N = 1$ gives **3** implicants.

$N = 2$ gives **9** implicants.

$N = 3$ gives **27** implicants.

Maybe N gives 3^N implicants?

Why?

For each input variable, we have **three choices**:

- include the variable
- include the complemented variable, or
- leave the variable out.

How Can We Draw Boxes for the Cube?


Focus on the top half.

Each adjacent A,C pair shares an edge.

The last edge wraps around (from 10 to 00).

The **top face** is all four.

value of A,C 00 01 11 10



Loops Can be 1, 2, or 4 Boxes Wide

So we **use Gray code order** on the boxes (one bit changes at a time).

Loops can be

- 1 box wide (a vertex)
- 2 boxes wide (an edge)
- 4 boxes wide (the face)


Loops cannot be 3 boxes wide, because 3 boxes do not correspond to an implicant (implicants are hypercube features).

We Draw Function $H(A,B,C)$ Using a 3-Variable K-Map

Here is a **3-variable K-map**.

Let's find a way to express $H(A,B,C)$.

Start by circling a 1.



Some Minterms May Be Prime Implicants

The loop represents minterm $A'B'C$.

Is $A'B'C$ a prime implicant of H ?

Yes, since we cannot grow the loop left, right, nor downward.

		C			
		00	01	11	10
B	0	0	1	0	0
	1	1	0	1	1
		A			

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 25

Don't Forget to Check for Wrapping

Choose another 1 to cover and circle it.

The new loop is the minterm $A'BC'$.

Is $A'BC'$ prime for $H(A,B,C)$?

No, we can grow the loop to the left (wrap around).

		C			
		00	01	11	10
B	0	0	1	0	0
	1	1	0	1	1
		A			

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 26

We Have Found a Second Prime Implicant

Grow the loop.

The new loop is BC' .

Is BC' prime for $H(A,B,C)$?

Yes. A loop cannot have three 1s, and we cannot include the 0 in the row.

		C			
		00	01	11	10
B	0	0	1	0	0
	1	1	0	1	1
		A			

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 27

Keep Choosing Prime Implicants Until All 1s are Covered

We still have another 1 to cover. Circle it.

The new loop represents minterm ABC .

Is ABC a prime implicant of H ?

No, we can grow the loop to the right.

		C			
		00	01	11	10
B	0	0	1	0	0
	1	1	0	1	1
		A			

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 28

And We're Done: $H(A,B,C) = A'B'C + BC' + AB$


Grow the loop.

The new loop is **AB**.

Is **AB** prime for $H(A,B,C)$?

Yes.

So $H(A,B,C) = A'B'C + BC' + AB$



ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 29

K-Maps Extend Nicely to Four Variables

Now you're excited?

Ok, on to 4 variables!

It's hard to draw the hypercube.

But the K-map is not so bad.

Remember:

- **Gray code order** in both directions.
- **1, 2, or 4-box loops** (no 3-box loops!).

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 30

Goal: Minimal Number of Loops, Maximal Size per Loop

Your **goal** is to come up with

- a **minimal number of loops**
- of **maximal size** (all prime, of course).
- that together **cover all 1s** in the function.

If you do so, the **result will be optimal among SOP expressions* by our area heuristic** (for 4 or fewer variables).

*A POS expression might be better, as might an expression using XORs.

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 31

Considerations for Optimizing with K-Maps

Sometimes you end up with loops that aren't needed. If all of a loop's 1s are covered by other loops, you can remove the loop.

To make the process faster,

- try to **start by covering 1s for which you need make no choices**
- (1s for which all directions with adjacent 1s can be included in one big loop).

But you may have to make choices, and **there can be more than one optimal SOP form**.

ECE 120: Introduction to Computing

© 2016 Steven S. Lumetta. All rights reserved.

slide 32

Here's a 4-Variable K-Map

Here's how a **4-variable K-map** looks.

We won't solve this one now.

Want to try it in the online tool?

		C			
		00	01	11	10
D	00	0	0	0	1
	01	1	1	0	0
	11	1	1	1	1
	10	1	0	1	1
		A			
		B			