Model: ChatGpt, Claude

1. Chat.jsx line 217-245

   Prompt:

   請問要怎麼透過現有的code實現傳送圖片到聊天室的功能?

   Response:

```
import { ref, uploadBytes, getDownloadURL } from
"firebase/storage";

import { storage, db } from "./firebase"; //  依你的路徑

import { addDoc, collection, serverTimestamp } from
"firebase/firestore";


async function handleImageUpload(e) {
    const file = e.target.files[0];
    if (!file || !selectedRoom) return;


    try {
        //  建立  storage  路徑
        const storageRef = ref(
            storage,

`chatImages/${selectedRoom.id}/${Date.now()}_${file.name}`
        );
```

```
        // 上傳圖片
        await uploadBytes(storageRef, file);

        // 取得圖片 URL
        const url = await getDownloadURL(storageRef);

        // 存成訊息
        await addDoc(collection(db, "messages"), {
          roomId: selectedRoom.id,
          senderId: user.uid,
          type: "image",            // ⭐ 重點：標記是圖片
          imageUrl: url,            // ⭐ 圖片網址
          createdAt: serverTimestamp(),
        });

      } catch (err) {
        console.error("Upload error:", err);
      }
    }
```

Refinement:

2. Chat.jsx line 256-267,

請問要怎麼實現send emoji to message 的功能?

```
const [emojiPickerMsgId, setEmojiPickerMsgId] = useState(null);


// Add or remove emoji reaction
  async function toggleReaction(msgId, emoji) {
    const msgRef = doc(db, "rooms", room.id, "messages",
msgId);
    const msgSnap = await getDoc(msgRef);
    if (!msgSnap.exists()) return;
    const reactions = msgSnap.data().reactions || {};
    const users = reactions[emoji] || [];
    const hasReacted = users.includes(user.uid);
    await updateDoc(msgRef, {
      [`reactions.${emoji}`]: hasReacted ?
arrayRemove(user.uid) : arrayUnion(user.uid),
    });
    setEmojiPickerMsgId(null);
  }
```

3. Chat.jsx line 134-150, line41-93

> 但現在很奇怪的是，假如A block B，在A那一端看不到聊天室警告不能在聊天的UI，在B那邊只有剛開始登入的時候會看到剛剛被封的那個聊天室有警告(而且剛登入的時候，chatarea不應該有任何聊天室畫面才對，要user選了之後才出來)，但之後再點沁去那個聊天室就看不到警告了，那個警告ui應該一直都有才對

聊天室在判斷 block user 時，無法正確判斷是否是群聊還是私聊

Response:

```
// 把這段

const otherUserId = room?.members?.find((uid) => uid !==
user?.uid);

const isDMBlocked =
  !room?.isGroup &&
  otherUserId &&
  (blockedUsers.includes(otherUserId) ||
    blockedByUsers.includes(otherUserId));


// 改成這樣

const otherUserId = room?.members?.find((uid) => uid !==
user?.uid);

const isDMBlocked =
  !room?.isGroup &&
  (
    (otherUserId && blockedUsers.includes(otherUserId)) ||
    blockedByUsers.length > 0
  );
```

Refinement:

```
const otherUserId = room?.members?.find((uid) => uid !==
user?.uid);

const isDM = (room?.members?.length === 2);

const isDMBlocked =
  isDM &&
  (
    (otherUserId && blockedUsers.includes(otherUserId)) ||
    blockedByUsers.length > 0
  );

  console.log("DEBUG:", {
  isGroup: room?.isGroup,
  members: room?.members,
  otherUserId,
  blockedUsers,
  blockedByUsers,
  isDMBlocked,
});
```

並且在瀏覽器 console 執行這段，把所有 2-member room 的 isGroup 改成 false：

```
js
import { collection, getDocs, updateDoc, doc } from
"firebase/firestore";
import { db } from "./firebase";

const snap = await getDocs(collection(db, "rooms"));
for (const d of snap.docs) {
  const data = d.data();
```

```
    if (data.members?.length === 2 && data.isGroup === true) {
        await updateDoc(doc(db, "rooms", d.id), { isGroup: false });
        console.log("Fixed:", d.id);
    }
}
```