

Joshua Liang

010380383

Answers are highlighted in blue text

San Jose State University Department of Computer Science
Database Management Systems - I (CS 157A)

Homework #2 (5 pts)

Questions on Chapters (3 + 6): Please answer the following questions:

• **Q1 [1.5 pts]: For each of the following relation schemas and set of FD's:**

o **R(A,B,C,D) with FD's $AB \rightarrow C$, $C \rightarrow D$, and $D \rightarrow A$**

o **R(A,B,C,D) with FD's $B \rightarrow C$ and $B \rightarrow D$**

o **R(A,B,C,D) with FD's $AB \rightarrow C$, $BC \rightarrow D$, $CD \rightarrow A$ and $AD \rightarrow B$**

o **R(A,B,C,D) with FD's $A \rightarrow B$, $B \rightarrow C$, $C \rightarrow D$ and $D \rightarrow A$**

o **R(A,B,C,D,E) with FD's $AB \rightarrow C$, $DE \rightarrow C$, and $B \rightarrow D$**

o **R(A,B,C,D,E) with FD's $AB \rightarrow C$, $C \rightarrow D$, $D \rightarrow B$, and $D \rightarrow E$**

Do the following:

a) Indicate all the BCNF violations. Do not forget to consider FD's that are not in the given set, but follow from them. However, it is not necessary to give violations that have more than one attribute on the right side?

o **R(A,B,C,D) with FD's $AB \rightarrow C$, $C \rightarrow D$, and $D \rightarrow A$**

BCNF violations are $C \rightarrow D$, $D \rightarrow A$, $C \rightarrow A$

o **R(A,B,C,D) with FD's $B \rightarrow C$ and $B \rightarrow D$**

BCNF violations are $B \rightarrow C$, $B \rightarrow D$

o $R(A,B,C,D)$ with FD's $AB \rightarrow C$, $BC \rightarrow D$, $CD \rightarrow A$ and $AD \rightarrow B$

No BCNF violations

o $R(A,B,C,D)$ with FD's $A \rightarrow B$, $B \rightarrow C$, $C \rightarrow D$ and $D \rightarrow A$

No BCNF violations

o $R(A,B,C,D,E)$ with FD's $AB \rightarrow C$, $DE \rightarrow C$, and $B \rightarrow D$

BCNF violations are $AB \rightarrow C$, $DE \rightarrow C$, and $B \rightarrow D$

o $R(A,B,C,D,E)$ with FD's $AB \rightarrow C$, $C \rightarrow D$, $D \rightarrow B$, and $D \rightarrow E$

BCNF violations are $C \rightarrow D$, $D \rightarrow B$, and $D \rightarrow E$

b) Decompose the relations, as necessary, into collections of relations that are in BCNF?

o $R(A,B,C,D)$ with FD's $AB \rightarrow C$, $C \rightarrow D$, and $D \rightarrow A$

Schemas in BCNF are:

$\{A, B, C\}$, $\{C, D\}$, $\{D, A\}$, $\{C, B\}$

o $R(A,B,C,D)$ with FD's $B \rightarrow C$ and $B \rightarrow D$

Decomposing $R_1(B, C, D)$ and $R_2(B, A)$

Schemas in BCNF are:

(B, C, D) and (B, A)

o $R(A,B,C,D)$ with FD's $AB \rightarrow C$, $BC \rightarrow D$, $CD \rightarrow A$ and $AD \rightarrow B$

No need for decomposition

o $R(A,B,C,D)$ with FD's $A \rightarrow B$, $B \rightarrow C$, $C \rightarrow D$ and $D \rightarrow A$

No need for decomposition

o $R(A,B,C,D,E)$ with FD's $AB \rightarrow C$, $DE \rightarrow C$, and $B \rightarrow D$

Decomposing R into $R_1(A, B, C, D)$ and $R_2(A, B, E)$

Decomposing R_1 into $R_3(A, B, C)$ and $R_4(B, D)$

Schemas in BCNF are:

$\{A, B, C\}, \{B, D\}, \{A, B, E\}$

o $R(A, B, C, D, E)$ with FD's $AB \rightarrow C, C \rightarrow D, D \rightarrow B$, and $D \rightarrow E$

Decomposing R into $R_1(C, D, B, E)$ and $R_2(A, C)$

Decomposing R_1 into $R_3(D, B, E)$ and $R_4(C, D)$

Schemas in BCNF are:

$\{C, D\}, \{D, B, E\}, \{A, C\}$

• **Q2 [1 pt]: Let $R(A, B, C, D, E)$ be decomposed into relations with the following three sets of attributes: $\{A, B, C\}$, $\{B, C, D\}$, and $\{A, C, E\}$.**

For each of the following sets of FD's, use the chase test to tell whether the decomposition of R is lossless. For those that are not lossless, give an example of an instance of R that returns more than R when projected onto the decomposed relations and rejoined:

a) $B \rightarrow E$ and $CE \rightarrow A$

b) $AC \rightarrow E$ and $BC \rightarrow D$

c) $A \rightarrow D, D \rightarrow E$, and $B \rightarrow D$

d) $A \rightarrow D, CD \rightarrow E$, and $E \rightarrow D$.

a) This is the initial tableau:

A	B	C	D	E
a	b	c	d_1	e_1
a_1	b	c	d	e_1

a	b ₁	c	d ₁	e
---	----------------	---	----------------	---

After applying FD's $B \rightarrow E$ and $CE \rightarrow A$, this is the tableau:

A	B	C	D	E
a	b	c	d ₁	e ₁
a	b	c	d	e ₁
a	b ₁	c	d ₁	e

There is no unsubscripted row, so the decomposition is not lossless.

b) This is the initial tableau:

A	B	C	D	E
a	b	c	d ₁	e ₁
a ₁	b	c	d	e ₁
a	b ₁	c	d ₁	e

This is the final tableau after applying FD's $AC \rightarrow E$ and $BC \rightarrow D$:

A	B	C	D	E
a	b	c	d	e
a ₁	b	c	d	e ₁

a	b_1	c	d_1	e
---	-------	---	-------	---

There is an unsubscripted row, so the decomposition is lossless.

c) This is the initial tableau:

A	B	C	D	E
a	b	c	d_1	e_1
a_1	b	c	d	e_1
a	b_1	c	d_1	e

Table after applying FD's $A \rightarrow D$, $D \rightarrow E$, and $B \rightarrow D$:

A	B	C	D	E
a	b	c	d	e
a_1	b	c	d	e
a	b_1	c	d	e

There is an unsubscripted row, therefore decomposition for R is lossless for this set of FDs.

d) This is the initial tableau:

A	B	C	D	E
a	b	c	d ₁	e ₁
a ₁	b	c	d	e ₁
a	b ₁	c	d ₁	e

This is the final tableau after applying FDs $A \rightarrow D$, $CD \rightarrow E$ and $E \rightarrow D$

A	B	C	D	E
a	b	c	d	e
a ₁	b	c	d	e
a	b ₁	c	d	e

The first row is an unsubscripted row, so the decomposition for R is lossless

• Q3 [1.5 pts]: Write the following queries based on the following schema:

Movies(title, year, length, genre, studioName, producerC#)

StarsIn(movieTitle, movieYear, starName)

MovieStar(name, address, gender, birthdate)

MovieExec(name, address, cert#, netWorth)

Studio(name, address, presC#)

in SQL:

a) Find the address of MGM studios?

b) Find Sandra Bullock's birthdate?

c) Find all the stars that appeared either in a movie made in 1980 or a movie with "Love" in the title?

a) `SELECT address`

`FROM studio`

`WHERE name = 'MGM';`

b) `SELECT birthdate`

`FROM moviestar`

`WHERE name = 'Sandra Bullock';`

c) `SELECT starName`

`FROM StarsIn`

`WHERE movieYear = 1980 OR movieTitle LIKE '%Love%';`

• Q4 [1 pt]: Write the following queries based on the following schema:

Movies(title, year, length, genre, studioName, producerC#)

StarsIn(movieTitle, movieYear, starName)

MovieStar(name, address, gender, birthdate)

MovieExec(name, address, cert#, netWorth)

Studio(name, address, presC#)

Write the following queries in SQL:

- a) Who were the male stars in Titanic?**
- b) Which stars appeared in movies produced by MGM in 1995?**
- c) Who is the president of MGM studio?**
- d) Which movies are longer than “Gone With the Wind”?**

- a)

```
SELECT name
FROM MovieStar
WHERE gender = 'M'
and name IN (SELECT starName FROM StarsIn)
WHERE movieTitle = 'Titanic')
```
- b)

```
SELECT starName
FROM StarsIn
WHERE movieTitle in (
SELECT title
FROM Movies
WHERE studioName = 'MGM' and year = '1995');
```
- c)

```
SELECT presC#
FROM Studio
WHERE name = 'MGM';
```
- d)

```
SELECT M1.title
FROM Movie AS M1, Movie AS M2
WHERE M2.title = 'Gone With the Wind' AND
M1.length > M2.length;
```


