Cache Your Prompt When It's Green

Carbon-Aware Caching for Large Language Model Serving

Yuyang Tian, Desen Sun, Yi Ding, Sihang Liu
University of Waterloo Purdue University
SIGMETRICS 2026 PACM Meas. Anal. Comput. Syst.

Research meeting: 11 November 2026
Yu-Jui Liang Advisor: Hsiang-Yun Cheng
National Taiwan University / Academia Sinica

Source: GreenCache, title page

Discussion Index

Why Do We Need GreenCache?

A hit reloads reusable KV from SSD and avoids repeated prefill. The saved computation comes with a storage carbon cost.




Fig. 7. Carbon emissions per request (a) in the ES grid under different request rates, and (b) under different cache sizes and grids (based on grid average CI in Figure 2a).

Read Fig. 7(a), ES grid At low request rates, SSD embodied carbon per prompt outweighs the operational savings. At higher rates, caching saves more total carbon.

Storage cost Table 1 models up to 16 TB SSD at 480 $kgCO_2e$: **76.6%** of this server's embodied carbon, not a universal datacenter share. Serving is charged by allocation time, not 480 kg at each resize.

More KV caching is not always more carbon-efficient.

Source: GreenCache, p. 5, Table 1; p. 8, Fig. 7, Sec. 3.2.2

KV Reuse Table 1 Equations

Why Is a Fixed Cache Size Suboptimal?

Fixed 16 TB cache, 1.5 prompts/s. Carbon ratio = cache / no cache: **below 1** is a reduction; **Above 1** is an increase.




Fig. 8. Carbon emission savings from caching in 12 grids. A ratio < 1 indicates carbon emission reduction.

Across grids, Fig. 8(a) FR (CI 33): **16.5% more** carbon. MISO (CI 485): **7.5% less**. CI unit: gCO_2e/kWh.

Within a day, Fig. 8(b) CISO CI changes from 37 at 7 AM to 232 at 8 PM. The same cache has different carbon benefits.

Capacity evidence, Fig. 7(b) The previous slide compares 0–16 TB: more SSD adds embodied carbon, while avoided computation saves more carbon at high CI.

Capacity must account for load, carbon intensity, and latency constraints.

Source: GreenCache, pp. 8–9, Figs. 7(b), 8; Takeaway 5

Grid CI | Adapt Illustration

What Does GreenCache Optimize?

Choose allocated SSD capacity to minimize estimated serving carbon while meeting two latency requirements.

$$\min_{S \in \mathcal{S}} \quad C_{\text{operational}}(S) + C_{\text{embodied, allocated}}(S)$$

$$\text{subject to} \quad \text{TTFT attainment} \geq 90\%, \qquad \text{TPOT attainment} \geq 90\%.$$

Carbon accounting Operational carbon is energy $\times$ CI. Embodied carbon is amortized over allocation time, including allocated SSD and other server components.

Inputs and decision Predicted request rate and CI, plus profiled serving behavior, inform the choice of SSD capacity S from discrete candidates $\mathcal{S}$.

Replacement policy LCS ranks which KV entries to retain inside the chosen capacity.

TTFT: time to first token. TPOT: time per output token. Each attainment is a separate fraction of requests; neither is a guarantee for every request.

Source: GreenCache, Secs. 3.2, 5.4–5.5, Eq. (6)

Embodied Carbon | Carbon Model

How Does GreenCache Work?




Fig. 10. System overview of GreenCache. Components in green are newly designed by this work.

1. Profile Sweep SSD sizes and loads. Record TTFT, TPOT, and power.

2. Forecast Authors' SARIMA load model. CI from existing EnsembleCI.

3. Choose ILP selects the lowest-carbon discrete size that meets both attainments.

4. Apply Resize the cloud SSD allocation and evict with LCS.

Green boxes in Fig. 10 are the new control path. Requests still run on LMCache / vLLM. The decision is a cache size, not a new GPU kernel.

Source: GreenCache, Secs. 4–5.1, Fig. 10

Profiles ILP

How Is Cache Capacity Selected?

1. Profile candidate sizes Measure TTFT, TPOT, and power across cache sizes and request rates. These profiles describe the candidates available to the controller.

2. Forecast the next interval Predict request rate with SARIMA and carbon intensity with EnsembleCI. The live TTFT / TPOT monitor supplies feedback.

3. Solve the capacity ILP Use the profiles and forecasts to select the lowest-carbon candidate that meets both attainment constraints. Implementation: PuLP with the CBC solver.

4. Apply and repeat Resize hourly in 1 TB steps. Maximum capacity: 16 TB for Llama-3 70B and 8 TB for 8B. LCS evicts entries when capacity shrinks.

Scope of optimality: the best profiled candidate under the forecasts and constraints. Forecast and profile errors can change the chosen capacity.

Source: GreenCache, Secs. 5.2–5.5, 6.1, Eq. (6)

Full ILP SLO Numbers Predictors

What Does LCS Evict?

LRU keeps recently used entries. It ignores how many tokens a hit avoids, and how much SSD that entry occupies.

Least Carbon Savings score, Equation (7). Lowest score is evicted first.

$$\text{Score} = \frac{\#\text{Token} \times \#\text{Hit}}{\text{Size} \times \text{Age}}$$

This is a carbon-savings proxy. It is not a measured $kgCO_2e$ for that entry.

#Token

Reused token volume. More reused context avoids more prefill.

#Hit

How often the entry is reused.

Size

Entry footprint. Smaller entries cost less embodied carbon.

Age

Time in storage. Older entries are cheaper to drop.

Conversation and document QA use task-specific versions of the same idea, Equations (8)–(9).

Source: GreenCache, Sec. 5.5, Eq. (7)

Task Scores

Real Prototype, Traces, or a Simulator?

Actual hardware

GreenCache is built on LMCache, which uses vLLM and continuous batching. Llama-3 70B: 4× L40, INT8, up to 16 TB SSD. Llama-3 8B: 2× L40, BF16, up to 8 TB. The Table 1 platform has 512 GB DDR4.

Replayed workload

ShareGPT and TriviaQA supply text and reuse. Arrivals are Poisson, with rates taken from the Azure LLM trace and scaled to this machine. CI comes from CarbonCast for FR, FI, ES, and CISO.

Carbon model

CPU power from RAPL and GPU power from pyNVML, every 1 ms. SSD and DRAM power come from specifications. Embodied carbon is an ACT-style accounting model, amortized over allocation time.

No standalone GPU-serving simulator is reported. GreenCache extends LMCache/vLLM and evaluates measured serving behavior with realistic traces and carbon models.

Resizing allocates or releases cloud SSD capacity. It is not a measurement of physically installing or removing drives, and it is not a direct measurement of factory emissions at each resize.

Source: GreenCache, Secs. 5.2–5.4, 6.1

Measurement Notes

What Are the Evaluation Settings?

Models

Llama-3 70B (INT8, 4× L40) and Llama-3 8B (BF16, 2× L40). Different GPU counts and precisions, so the two models are not an apples-to-apples pair. Context window 8k tokens; longer context is truncated.

Workloads

ShareGPT multi-turn conversation. TriviaQA document comprehension at Zipf skewness $\alpha = 0.4$ and $\alpha = 0.7$. Hourly CI and hourly cache decisions.

Baselines

No Cache: vLLM, no context cache. **Full Cache:** the maximum configured capacity. **GreenCache:** adaptive capacity plus LCS. Full Cache and GreenCache share the same maximum.

Metrics

Total carbon per prompt. TTFT and TPOT SLO attainment, shown as P90 against the threshold. Cache capacity over the day. Token-level cache hit rate in the replacement study.


Target attainment is 90% for TTFT and, separately, 90% for TPOT. Threshold values and the trace-scaling procedure are in the backup.

Source: GreenCache, Sec. 6.1

SLO Thresholds

Q1: Does GreenCache Reduce Carbon?

Question: can adaptive capacity beat a fixed full cache on total carbon? Bars: No Cache, GreenCache, Full Cache. Blue labels are the GreenCache size in TB. Llama-3 70B.



(a) Carbon emissions of Llama-3 70B.

Fig. 12. Average carbon emissions of LLM tasks.

Versus **Full Cache**, averaged over FR, FI, ES, and CISO: multi-turn **12.6%**, document $\alpha = 0.4$ **9.4%**, document $\alpha = 0.7$ **5.6%**. These are not the FR-only 15.1%.


GreenCache lowers carbon by provisioning less cache when full capacity is unnecessary. No Cache is sometimes lower still, and the next slide shows why that is not an acceptable point.

Source: GreenCache, Sec. 6.2, Fig. 12a

Llama-3 8B

Q2: Does GreenCache Still Meet SLOs?

Question: is the carbon saving bought with unacceptable latency? P90 below the dashed threshold means at least 90% attainment. Llama-3 70B.



(a) Llama-3 70B.

Fig. 13. SLO attainment timelines of LLM tasks.

Thresholds

Multi-turn TTFT 2.5 s, TPOT 0.2 s. Document TTFT is 15 s. Fig. 13 keeps the 0.2 s TPOT line.

GreenCache

P90 sits slightly above Full Cache and stays under both lines in these plots.

No Cache

P90 crosses the lines often, so the lower-carbon point is not viable.


Lower carbon counts only when the serving constraints hold.

Source: GreenCache, Secs. 6.1–6.2, Fig. 13a

8B Timelines

Q3: Does Capacity Track Load and CI?

Llama-3 70B, multi-turn. Normalized CI and request rate, carbon per prompt, and the chosen cache size.



(a) Multi-turn conversation with Llama-3 70B.

Fig. 14. Timelines of carbon emissions under variable CI and rate.


On **FR, multi-turn, versus Full Cache**: average reduction **15.1%**, maximum **25.3%**. At 12 AM the paper reports 15 TB less SSD than Full Cache. High load still pushes capacity up. CISO, the higher-CI grid, keeps more cache.

Source: GreenCache, Sec. 6.2, Fig. 14a

Document Timeline

Q4: Does Adaptive Sizing Helps?

Ablation: LMCache's LRU plus GreenCache's adaptive capacity ("LRU + Optimal"), versus Full Cache. ES grid average CI, 124 gCO_2e/kWh. Llama-3 70B.



(a) Multi-turn conversation. (b) Document comp. (α=0.4). (c) Document comp. (α=0.7).

Fig. 15. Ablation study on adaptive caching (Llama-3 70B).

Capacity alone Without LCS, resizing still beats Full Cache: up to 10.3% on multi-turn, and 6.6–9.9% on document QA.

Load eats the margin The solver grows the cache to hold the SLO. "Optimal" means the profiled adaptive size, not a global-optimum proof.

Next Whether LCS improves token reuse is a separate measurement.

Source: GreenCache, Sec. 6.3.1, Fig. 15

Profiling Heatmaps

Q4: Does LCS Improve Token Reuse?

Hit rate = reused input tokens / total input tokens. Not the fraction of requests that hit. Llama-3 70B.

Size	ShareGPT			TriviaQA $\alpha = 0.4$			TriviaQA $\alpha = 0.7$		
(TB)	FIFO	LRU	LCS	FIFO	LRU	LCS	FIFO	LRU	LCS
1	0.05	0.05	0.08	0.05	0.05	0.06	0.10	0.11	0.19
2	0.11	0.12	0.17	0.08	0.08	0.09	0.16	0.19	0.25
4	0.19	0.21	0.28	0.12	0.12	0.14	0.23	**0.26**	**0.35**
8	0.34	0.40	0.47	0.19	0.20	0.22	0.37	0.38	0.44
16	0.52	0.69	0.71	0.31	0.32	0.33	0.47	0.52	0.52

Where LCS moves the rate At TriviaQA $\alpha = 0.7$ and 4 TB, LRU is 0.26 and LCS is 0.35: nine percentage points, on the token definition above.

Where it does not At 16 TB the policies converge, especially on the skewed document task. LCS matters more when the cache is tight.

Source: GreenCache, Sec. 6.3.2, Table 3

Score Formulas

Conclusion and Limitations

1. Problem

Context caching trades avoided prefill for provisioned SSD. Total carbon includes both terms.

2. Contribution

Profiling, load and CI forecasts, an ILP capacity choice, and LCS, under separate TTFT and TPOT attainments.

3. Evidence

Versus Full Cache, studied settings cut carbon while P90 stays inside the authors' thresholds. 15.1% / 25.3% is FR, Llama-3 70B, multi-turn.

4. Limitations

The public Azure trace covers about one week. Embodied carbon is amortized cloud allocation, not a factory measurement at each resize. Results move with reuse, CI, SSD assumptions, and SLOs. Experiments use dense Llama-3.

POSSIBLE EXTENSION / OUR INTERPRETATION

The same capacity question — how much fast storage is worth its embodied carbon under an SLO — can motivate later HBM/HBF hierarchy studies. GreenCache does not evaluate HBF hardware.

Source: GreenCache, Secs. 6–7, 9. Extension is ours, not an author result.

Limits and HBF

Discussion Index

Main answers the talk. This index opens the evidence behind a question.

Topic	What is here	Jump
A. Motivation	KV reuse, grids, latency, embodied carbon, Equations (1)–(5)	Open A
B. Method	Profiles, ILP, SLO numbers, predictors, LCS formulas	Open B
C. Evidence	Measurement boundary, 8B results, document timeline, solver time	Open C
D. Sensitivity	Forecast error, resize interval, SSD life, SSD carbon, limits	Open D

Is it a simulator? M08 Notes

Full ILP and SLOs Eq. 6 Thresholds

Main 15


8B and the other task Fig. 12 Fig. 14b

What we would not claim Limits

Discussion Index

Why Cache Repeated Context?

Multi-turn chats and document questions resend a shared context. A hit reloads KV instead of recomputing that prefill.



(a) Caching procedure. (b) Timeline of no cache and a cache hit.

Fig. 1. Illustration of caching for LLM serving.

What a hit saves Existing context is loaded from storage and stitched with the new tokens. Prefill of the repeated context is skipped.

What a hit does not save Autoregressive decode FLOPs remain. Decode latency can still fall because continuous batching waits less.

Source: GreenCache, Sec. 2.2, Fig. 1

ShareGPT, Llama-3 70B, 4× L40 Average prompt-processing TTFT is 1.7 s. Loading the previous context's KV averages 0.03 s.

How to read those two times They are not the same work item, and they are not an end-to-end speedup of one request.

Latency Detail
Context Length
Main 2
Discussion Index

Which Grids, and How Fast Does CI Move?




Fig. 2. (a) Average carbon intensity (CI) and energy sources of four grids in 2024 [18]. (b) CI variation due to energy sources of the CISO grid on July 6, 2022 [49].

2024 averages in Fig. 2a FR 33, FI 76, ES 124, and CISO 231 gCO_2e/kWh. The mix, not a single "green grid" label, sets operational carbon.

One CISO day Fig. 2b is 6 July 2022. Generation and CI move together. GreenCache's hourly decision uses this kind of variation, via CarbonCast and EnsembleCI.

Crop note The supplied Fig. 2 PNG has a few orphan pixels from a cut-off title. This slide drops the top 16 px. Axes, CI labels, and the legend are unchanged.

Source: GreenCache, Sec. 2.3, Fig. 2

Main 3 Next

Discussion Index

Where Does Caching Change Latency?




Fig. 3. (a) Latency and speedup from caching under different context lengths. (b) Latency breakdown.

Longer cached context, larger prefill speedup Fig. 3a. The prefill bar shrinks more than the decode bar as context grows.

Why decode moves at all Fig. 3b: caching does not remove decode computation. It shortens the wait in continuous batching.

Setup for this section Llama-3 70B, ShareGPT, the Table 1 server, LMCache on 16 TB, cache warmed with 200k prompts, 500 prompts recorded.

Source: GreenCache, Sec. 3.1.1, Fig. 3

KV Reuse

Next Discussion Index

How Long Is the Repeated Context?




Fig. 4. Distribution of context length in (a) ShareGPT [30] and (b) TriviaQA [32].

ShareGPT 77.2% of prompts carry more than 1000 tokens from earlier turns. Length, and therefore the value of a hit, varies inside the same task.

TriviaQA The reused context is the document. Average document length in the paper's discussion is 5880 tokens.

Design consequence Takeaway 1: longer contexts should be preferred when the cache cannot hold everything. LCS later puts token volume in the score.

Source: GreenCache, Sec. 3.1.1, Fig. 4

KV Reuse

Next Discussion Index

What Does Request Rate Change?




Fig. 5. (a) Latency of prefill and decode under different request rates, and the speedup from caching. (b) Fraction of prefill and decode latency.

Higher rate, more latency reduction Both prefill and decode improve more as the offered rate rises, because a shorter prefill also frees the batch.

Carbon follows the same direction Takeaway 2 and Fig. 7a: at low rate the SSD's embodied carbon can dominate; at high rate the avoided energy dominates.

SLO coupling A busy hour may need a large cache to keep attainment, even if that hour's CI is low.

Source: GreenCache, Sec. 3.1.2, Fig. 5

Main 2 Next

Discussion Index

Does a Bigger Cache Always Raise the Hit Rate?




Fig. 6. (a) Latency and speedup from caching under different cache sizes. (b) Cache hit rate.

Fixed load 1.5 prompts/s, cache from 1 to 16 TB, compared with no cache.

Diminishing hits Latency and speedup improve with size, then the hit-rate gain slows. Takeaway 3: larger is better for latency, not linearly, and not automatically for carbon.

Hand-off to carbon Fig. 7b then shows the embodied share rising with those same sizes.

Source: GreenCache, Sec. 3.1.3, Fig. 6

Main 3 Next

Discussion Index

Table 1: Embodied Carbon on This Server

Component	Type	Embodied carbon
CPU	AMD 7453	9.3 $kgCO_2e$
GPU	4× NVIDIA L40	106.4 $kgCO_2e$
Memory	512 GB DDR4	30.8 $kgCO_2e$
Storage	up to 16 TB SSD	up to 480 $kgCO_2e$

76.6% The paper states that SSD embodied carbon is 76.6% of this server's embodied carbon at the Table 1 configuration. $480/(9.3 + 106.4 + 30.8 + 480) = 76.6\%$.

Scope Prior studies are cited for SSDs exceeding 75% of datacenter-server embodied carbon. That citation is not a measurement of every server.

Accounting choice Only the allocated SSD capacity is charged, for the fraction of lifetime it is reserved. Default lifetime is 5 years unless a sensitivity slide says otherwise.

Source: GreenCache, Sec. 2.3, Table 1. Sum checked against the stated 76.6%.

Main 4 Main 2 Next Discussion Index

Carbon Accounting, Equations (1)–(5)

$$C = C_o + \frac{T}{\mathrm{LT}} C_e \qquad C_o = E \times \mathrm{CI}$$

$$C_e = C_{e,\mathrm{GPU}} + C_{e,\mathrm{CPU}} + C_{e,\mathrm{Mem}} + C_{e,\mathrm{SSD}}$$

$$C_{e,\mathrm{Cache}} = S_{\mathrm{Alloc}} \times \frac{T}{\mathrm{LT}} \times C_{e,\mathrm{SSD}}^{\mathrm{Unit}}$$

$$C = E \times \mathrm{CI} + \frac{T}{\mathrm{LT}} \left(C_{e,\mathrm{Cache}} + C_{e,\mathrm{Others}} \right)$$

Two different objects Per-prompt carbon in the plots is not the same number as the SSD-only embodied term, and neither is "GPU energy saved."

What caching changes It can lower E and T. It raises S_{Alloc}. Equation (5) is the tradeoff GreenCache searches.

Unit carbon Table 1's 480 $\mathrm{kgCO_2e}$ over 16 TB is 30 $\mathrm{kgCO_2e/TB}$. Fig. 20 then varies that assumption from 30 to 90.

Source: GreenCache, Secs. 2.3, 3.2.1, Eqs. (1)–(5)

Main 4 Main 2 Next

Discussion Index

Background Discussion index 24 / 40

Load and CI Push Capacity in Opposite Ways




Fig. 9. Adaptive caching.

Source: GreenCache, Sec. 4.1, Fig. 9

High load Fig. 9a grows the cache. The stated reason is SLO attainment, not carbon alone.

Low CI Fig. 9b shrinks the cache to avoid SSD embodied carbon. This is the forecast case, not a rule that low CI always means zero cache.

Why a forecast Growing the cache needs warm-up. Decisions look up to 24 hours ahead so the new capacity is warm when the load arrives.

Still an illustration The measured response is Fig. 14, not this cartoon.

Main 3 Next
Discussion Index

What Do the Profiles Actually Contain?




Fig. 11. Profiling results of TTFT and TPOT (lower is better), and carbon savings over no-cache (higher is better) when serving Llama-3 70B in the ES grid for (a) multi-turn conversation, using a ShareGPT dataset [30] and (b) document comprehension using a TriviaQA dataset [32] (with skewness of $\alpha = 0.4$).

Axes Llama-3 70B, ES grid. (a) ShareGPT multi-turn. (b) TriviaQA, $\alpha = 0.4$. Rows are cache size; columns are request rate.

Read the colors carefully TTFT and TPOT: lower is better. The carbon-savings panel is higher-better. The paper defines that ratio as no-cache over cached, so a value **above 1 is a benefit**. This is the opposite direction from Fig. 8, where a ratio below 1 is a reduction.

The pattern used by the solver Large caches help latency, especially at higher rate. At low rate a large cache can sit below 1 on the savings panel.

Source: GreenCache, Sec. 5.2, Fig. 11

Main 5 Main 13 Next

Discussion Index

Equation (6): Capacity ILP

$$\underset{S^{j_t}}{\operatorname{argmin}} \sum_{i=1}^{N} \Bigg(p_i^{j_t}\, \mathrm{TTFT}_i^{j_t}\, \mathrm{CI}_t + \frac{\mathrm{TTFT}_i^{j_t}}{\mathrm{LT}_{\mathrm{SSD}}}\, S_i^{j_t}\, C_{e,\mathrm{SSD}}^{\mathrm{Unit}} + \sum_{\mathrm{comp}\in\{\mathrm{GPU},\mathrm{CPU},\mathrm{Mem}\}} \frac{\mathrm{TTFT}_i^{j_t}}{\mathrm{LT}_{\mathrm{comp}}}\, C_{e,\mathrm{comp}} \Bigg)$$

$$\text{s.t.} \quad \sum_{i=1}^{N} z_{\mathrm{TTFT},i} \geq \rho N, \quad \sum_{i=1}^{N} z_{\mathrm{TPOT},i} \geq \rho N, \quad \rho = 0.9$$

Indices j_t is the predicted request rate at hour t, and CI_t is the predicted intensity. $z = 1$ when that request meets the corresponding latency limit.

Not one probability The two sums are separate constraints. A request can meet TTFT and miss TPOT.

Scope of the objective The carbon sum is written on prefill time. Cache size does not cut decode FLOPs; it changes decode delay through the batch. Solver: PuLP + CBC. Average decision time 7.03 s.

Source: GreenCache, Sec. 5.4, Table 2, Eq. (6), Sec. 6.4

Main 5 Main 6 Next

Discussion Index

SLO Thresholds and Decision Granularity

Task	Model	TTFT SLO	TPOT SLO
Multi-turn	Llama-3 70B	2.5 s	0.2 s
Multi-turn	Llama-3 8B	0.5 s	0.15 s
Document	Llama-3 70B	15 s	0.2 s line in Fig. 13
Document	Llama-3 8B	see note	0.15 s line in Fig. 13

Unresolved 8B document TTFT Section 6.1 says the document TTFT threshold is relaxed to 2.5 s for Llama-3 8B. The dashed line on that Fig. 13 panel is drawn at 4.0 s. Both are shown; this deck does not pick one.

How attainment is shown $\rho = 0.9$. A P90 curve under the threshold is the paper's picture of at least 90% attainment.

Search space Integer TB steps, CI treated as constant inside each hour, profiles taken after LCS warm-up. The paper proves NP-hardness by reduction to 0–1 Knapsack and then says the 1 TB grid makes the actual search small.

Source: GreenCache, Secs. 5.4, 6.1, Fig. 13

Main 6 Main 9 Next Discussion Index

Load Forecast and Carbon-Intensity Forecast

Load SARIMA, fit with pmdarima, including its parameter search. Hold-out uses the latest three days and predicts 24 hours. At runtime the model updates every hour. It runs on separate CPU cores.

Carbon intensity EnsembleCI, an existing predictor, trained on 18 months of CarbonCast and evaluated on 6 July 2022. GreenCache does not claim to have designed EnsembleCI.

Errors, Sec. 6.5 Load MAPE 4.3%. CI MAPE: FR 12.7%, FI 15.3%, ES 11.3%, CISO 6.8%. Median context-length gap versus the profile: 5.78% (multi-turn) and 1.13% (document).

Effect on the carbon result Relative to an ideal run with ground truth, CI error trims 0.0064% of the savings on average, adding load error trims 0.20%, and adding profiler mismatch trims 0.79%.

Source: GreenCache, Secs. 5.3, 6.1, 6.5

Main 6 Next Discussion Index

LCS Scores for the Two Tasks

Conversation reuses prior turns. Document QA reuses one document across questions. Size and Age stay as in Equation (7); the numerator is task-specific.

EQUATION (8): MULTI-TURN

$$\text{Score} = \frac{\text{CurTurn} \times \#\text{AccuToken}}{\text{Size} \times \text{Age}}$$

CurTurn keeps entries from deeper in the dialogue. #AccuToken is reused tokens across turns.

EQUATION (9): DOCUMENT QA

$$\text{Score} = \frac{\#\text{Hit} \times \text{AccuDocLen}}{\text{Size} \times \text{Age}}$$

#Hit counts questions on that document. AccuDocLen is reused document length.

Eviction Lowest score leaves first, until the allocated size is met. Enlarging allocates more cloud SSD; shrinking releases the freed capacity.

Still a proxy None of (7)–(9) multiplies by the current CI. CI affects the capacity decision. The score ranks entries inside the chosen capacity.

Source: GreenCache, Sec. 5.5, Eqs. (7)–(9)

Main 7 Main 14 Next

Discussion Index

What Is Measured, Replayed, and Modeled?

Serving path LMCache + vLLM + continuous batching, plus the authors' LCS policy. No paper statement says they built or modified a standalone GPU simulator.

Requests Profiling prompts and evaluation prompts are disjoint. ShareGPT cache warm-up: 200k prompts. TriviaQA: 50k. The profiler then runs 500 prompts. Zipf $\alpha = 0.4$: about 10% of documents get about 25% of prompts. $\alpha = 0.7$: about 10% get about 50%.


Time and grid Azure LLM inference trace, downscaled so the peak fits this server's sustainable throughput. Main carbon run uses variable CI on 6 July 2022. Ablations and SSD sensitivities use the ES average, 124 gCO_2e/kWh, and fixed rates of 1.5 prompts/s (multi-turn) or 0.2 (document) where Sec. 6.6 says so.

Power CPU: RAPL. GPU: pyNVML at 1 ms. SSD and DRAM: specification power, because those parts expose no direct measurement interface in the paper.

Source: GreenCache, Secs. 3, 5.2, 6.1, 6.6

Main 8 Next Discussion Index

Figure 12b: Llama-3 8B Carbon



(b) Carbon emissions of Llama-3 8B.

Fig. 12. Average carbon emissions of LLM tasks.

Same three workloads, smaller machine Versus Full Cache the paper reports 10.8%, 7.6%, and 9.7% lower carbon for multi-turn, $\alpha = 0.4$, and $\alpha = 0.7$.

Do not stack this on the 70B bars 8B uses 2× L40, BF16, and an 8 TB maximum. 70B uses 4× L40, INT8, and 16 TB.


Legend The strip above is the original Fig. 12 legend: gray No Cache, green GreenCache, tan Full Cache. Blue numbers are cache size in TB.

Source: GreenCache, Sec. 6.2, Fig. 12b. Legend viewport is the original top strip.

Main 10 Next

Discussion Index

Figure 13b: Llama-3 8B SLO Timelines



(b) Llama-3 8B.

Fig. 13. SLO attainment timelines of LLM tasks.

Multi-turn lines match the text TTFT threshold 0.5 s and TPOT threshold 0.15 s. GreenCache stays under them; No Cache crosses TTFT.

Document TTFT is unresolved The text sets 2.5 s. The dashed line in these document panels is at 4.0 s. TPOT in the figure is drawn at 0.15 s.


Reading P90 Staying under the dashed line is the paper's $\geq 90\%$ attainment test. The 70B half of this figure is on the main slide.

Source: GreenCache, Secs. 6.1–6.2, Fig. 13b

Main 11 Next

Discussion Index

Figure 14b: Document Timeline, $\alpha = 0.4$



(b) Document comprehension ($\alpha = 0.4$) with Llama-3 70B.

Fig. 14. Timelines of carbon emissions under variable CI and rate.

Larger footprints Document context keeps the cache near the top of the 16 TB range for much of the day. The paper's multi-turn range versus Full Cache is 6.9–20.4%; the document range is 3.2–16.2%.

Less room to shrink When the SLO already needs a large cache, embodied-carbon savings get smaller. That is why this task saves less than multi-turn at the same hours of high load.

Legend Red CI, dashed orange request rate, brown Full Cache CO_2, dashed green GreenCache CO_2, blue bars cache size in TB. The FR 15.1% / 25.3% numbers belong to multi-turn, Fig. 14a, not to this panel.

Source: GreenCache, Sec. 6.2, Fig. 14

Main 12 Next

Discussion Index

Solver Time per Resize




Fig. 16. Constraint solver execution time for every cache resize.

Cost of a decision Average 7.03 s to choose the next cache size, across the three tasks in Fig. 16.

Why that is acceptable in the paper The default resize interval is one hour, and the workloads are long-running. 7.03 s is overhead of the controller, not of the token path.


Not free in a faster loop Fig. 18 shows that resizing much faster than the hourly CI trace does not buy much carbon, while much slower resizing gives savings back.

Source: GreenCache, Sec. 6.4, Fig. 16

Main 6 Next

Discussion Index

Do Forecast and Profile Errors Spend the Savings?



(a) Multi-turn conversation. (b) Document comp. ($\alpha = 0.4$). (c) Document comp. ($\alpha = 0.7$).

Fig. 17. Impact of prediction and profile inaccuracies (Llama-3 70B).

What the bars add Left to right within the paper's comparison: CI error, then CI plus load error, then those plus profiler mismatch. The vertical axis is the loss of carbon savings versus an ideal ground-truth run, on a log scale so the small values are visible.

Magnitudes Averages reported in Sec. 6.5: 0.0064%, 0.20%, and 0.79%. Load error moves the chosen size, so it matters more than its MAPE suggests. Profiler error weighs more on FR and FI, where embodied carbon is a larger share.


Limit of the claim "Low impact" is this comparison on Llama-3 70B and these four grids. It is not a bound for every forecast model.

Source: GreenCache, Sec. 6.5, Fig. 17

Main 6 Next

Discussion Index

How Often Should the Cache Resize?



(a) Multi-turn conversation. (b) Document comp. ($\alpha = 0.4$). (c) Document comp. ($\alpha = 0.7$).

Fig. 18. Impact of variable cache resizing intervals (Llama-3 70B). A higher value indicates more savings.

Relative to the 1-hour default Fig. 18 plots carbon savings against that default. A higher value means more of the default saving remains. Intervals of 15 min, 30 min, 1 h, 2 h, 4 h, and 8 h are shown for all four grids.


Long intervals The solver must pick a size that protects the SLO for the whole interval, so it holds a larger cache and gives back savings. The drop is steepest for document QA at $\alpha = 0.4$, the case that already wants a large cache.

Shorter than one hour CarbonCast CI is hourly. Sub-hour decisions reuse that hour's CI. They stay close to the 1-hour result.

Source: GreenCache, Sec. 6.6.1, Fig. 18

Main 6 Next Discussion Index

SSD Lifetime Changes the Embodied Weight



(a) Multi-turn conversation. (b) Document comp. ($\alpha = 0.4$). (c) Document comp. ($\alpha = 0.7$).

Fig. 19. Variable SSD lifespan (Llama-3 70B, ES grid).

Setup Llama-3 70B, ES average CI, lifetimes 3, 5, and 7 years. Fixed rates: 1.5 prompts/s multi-turn, 0.2 prompts/s document. Default elsewhere in the paper is about 5 years.

Direction A 3-year life raises amortized SSD carbon, so shrinking the cache is worth more: the paper reports up to 11.9% savings in this study. A longer life makes the same resize less valuable.


Markers The figure includes No Cache and a Fail-SLO marker. A low bar that fails the SLO is not counted as the GreenCache result.

Source: GreenCache, Sec. 6.6.2, Fig. 19

Main 15 Next

Discussion Index

SSD Embodied Carbon Is an Assumption



(a) Multi-turn conversation. (b) Document comp. ($\alpha = 0.4$). (c) Document comp. ($\alpha = 0.7$).

Fig. 20. Variable SSD embodied carbon (Llama-3 70B, ES grid).

Range 30 to 90 $kgCO_2e/TB$, same rates and ES CI as the lifetime study. Table 1 corresponds to the 30 $kgCO_2e/TB$ end (480 kg / 16 TB).

Reported end point At 90 $kgCO_2e/TB$, GreenCache's saving versus the full cache reaches up to 25% in this sensitivity. Heavier SSD carbon makes the adaptive shrink more valuable.

What this does not measure The bars are the accounting model under a changed emission factor. They are not a second hardware campaign.

Source: GreenCache, Sec. 6.6.3, Fig. 20, Table 1

Main 15 Next

Discussion Index

Limits, and What We Would Not Claim

Trace Section 7: the public Azure LLM trace covers about one week. A stronger load model would need a longer trace. The authors treat the predictor as replaceable.

Embodied carbon The paper explicitly rejects treating unused hardware as sunk carbon. Unused cloud capacity is assumed to be used by someone else, so allocated SSD is charged for its time. That is an accounting assumption.

MoE, from the authors' discussion Mixture-of-experts models can cut activated compute while leaving KV storage in place, which would make the SSD term relatively larger. The experiments themselves are dense Llama-3, not MoE runs.

Possible extension / our interpretation A carbon-aware decision about how much fast memory to provision could inform HBM or HBF hierarchy design. Nothing in this paper measures HBM or HBF, and the 15.1% result does not transfer to that hardware.

Source: GreenCache, Sec. 7. The HBF sentence is our research note.

Main 15 Discussion Index