

Data Processing and Analysis in Python

Lecture 10

Classes



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

DR. ADAM LEE

Classes and Objects

- Programmers who use objects and classes know:
 - The interface that can be used with a class
 - The state of an object
 - How to **instantiate** a class to obtain an object
- Objects are **abstractions**
 - Package their state and methods in a single entity that can be referenced with a name
- Class definition is like a **blueprint** for each of the objects of that class and contains:
 - Definitions of all of the methods that its objects recognize
 - Descriptions of the data structures used to maintain the state of an object



UNIVERSITY OF
MARYLAND

Class Definitions

- Syntax of a simple class definition:
class <class name>(<parent class name>):
 <method definition-1>
 ...
 <method definition-*n*>
- Class name is a Python identifier
 - Typically capitalized
- Python classes are organized in a tree-like class **hierarchy**
 - At the top, or root, of this tree is the **Object** class
 - Some terminology: child/subclass **inherits** parent/base/superclass



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Method Definitions

- Method definitions are indented below class header
- Syntax of method definitions similar to functions

```
def method(self, ...):  
    ["""<doc-string>"""]  
    <method body>
```

 - Each method definition must include a first parameter named **self**
 - Can have required and/or default arguments, return values, create/use temporary variables
 - Returns None when no return statement is used
- Usage: `class.method(arguments)`



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

__init__(self, ...) Method

- Most classes include a special method named **__init__**
- This method is the class's **constructor**, because it is run automatically when a user instantiates the class
- The purpose of the constructor is to initialize an individual object's **attributes**



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

__str__(self) Method

- Returns a string representation of an object's state
- When the str function is called with an object, that object's __str__ method is automatically invoked to obtain the string that str returns
 - The function call str(s) is equivalent to the method call s.__str__()
 - The function call print(s) also automatically runs str(s)
- Perhaps the most important use of __str__ is in debugging, when you often need to observe the state of an object after running another method



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Operator Methods

Operator	Method Name
+	<code>__add__</code>
-	<code>__sub__</code>
*	<code>__mul__</code>
/	<code>__div__</code>
%	<code>__mod__</code>

Table 9-3 Built-in arithmetic operators and their corresponding methods

Operator	Meaning	Method
<code>==</code>	Equals	<code>__eq__</code>
<code>!=</code>	Not equals	<code>__ne__</code>
<code><</code>	Less than	<code>__lt__</code>
<code><=</code>	Less than or equal	<code>__le__</code>
<code>></code>	Greater than	<code>__gt__</code>
<code>>=</code>	Greater than or equal	<code>__ge__</code>

Table 9-5 The comparison operators and methods



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Example – Student

Student Method	What It Does
s = Student(name, number)	Returns a Student object with the given name and number of scores. Each score is initially 0
s.getName()	Returns the student's name
s.getScore(i)	Returns the student's i^{th} score, i must range from 1 through the number of scores
s.setScore(i, score)	Resets the student's i^{th} score to score, i must range from 1 through the number of scores
s.getAverage()	Returns the student's average score
s.getHighScore()	Returns the student's highest score
s.__str().__	Same as str(s). Returns a string representation of the student's information



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Example – Student

```
>>> from student import Student
>>> s = Student("Maria", 5)
>>> print(s)
Name: Maria
Scores: 0 0 0 0 0
>>> s.setScore(1, 100)
>>> print(s)
Name: Maria
Scores: 100 0 0 0 0
>>> s.getHighScore()
100
>>> s.getAverage()
20
>>> s.getScore(1)
100
```



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Rules of Thumb for Defining a Simple Class

- Before writing code, think about the **behavior and attributes** of the objects of the new class
 - What actions does an object perform?
 - How do these actions access or modify the object's state?
- Choose an appropriate **class name**, and develop a short list of the **methods** available to users
 - This interface should include appropriate **parameter names**
 - Brief descriptions of what the methods do
 - Avoid describing how the methods perform their tasks



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Rules of Thumb for Defining a Simple Class

- Write a short script that appears to use the new class in an appropriate way
 - The script should **instantiate** the class and **call** all of its methods
 - This helps to clarify the interface of your class and serve as an initial test bed for it
- Choose the appropriate data structures to represent the **attributes** of the class
- Fill in the class template with a constructor (an **__init__** method) and an **__str__** method
 - As soon as you have defined these two methods, you can test your class by instantiating it and printing the resulting object



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Rules of Thumb for Defining a Simple Class

- Complete and test the remaining methods incrementally
 - Work in a **bottom-up** manner
 - If one method depends on another, complete the second method first
- Remember to **document your code**
 - Include a **docstring** for the module, the class, and each method
 - Do not add docstrings as an afterthought
 - Write them as soon as you write a class header or a method header
 - Be sure to examine the results by running **help** with the class name



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS

Polymorphism

- **Polymorphism** is the condition of occurrence in different forms
- It refers to the use of a single type (operator, method, or object) to represent different types in different scenarios
 - Polymorphic + operator: $1 + 2$, $1.1 + 2.2$, `"one" + "two"`, etc.
 - Polymorphic `len()` function: `len("123")`, `len([1, 2, 3])`, etc.
- Python does not support **function overload**
 - To have multiple functions with the same name but with different signatures/implementations
 - The later one always overrides the prior



UNIVERSITY OF
MARYLAND

ROBERT H. SMITH
SCHOOL OF BUSINESS