## Database Management Systems Chapter 2: Modeling Data



DR. ADAM LEE

### **Objectives**

- Define terms.
- Understand importance of data modeling.
- Write good names and definitions for entities, relationships, and attributes.
- Distinguish unary, binary, and ternary relationships.
- Model different types of attributes, entities, relationships, and cardinalities.
- Draw ER diagrams for common business situations.
- Convert many-to-many relationships to associative entities.
- Model time-dependent data using time stamps.



#### A Good Data Name Is:

- Related to business, not technical, characteristics
- Meaningful and self-documenting
- Unique
- Readable
- Composed of words from an approved list
- Repeatable
- Written in standard syntax



#### **Data Definitions**

- Explanation of a term or fact:
  - **Term** word or phrase with specific meaning.
  - Fact association between two or more terms.
- Guidelines for good data definition:
  - A concise description of essential data meaning.
  - Gathered in conjunction with systems requirements.
  - Accompanied by diagrams.
  - Achieved by consensus, and iteratively refined.



#### **ER Model Constructs**

#### Entities:

- Entity instance person, place, object, event, concept (often corresponds to a row in a table).
- Entity Type collection of entities (often corresponds to a table).


#### Relationships:

- Relationship instance link between entities (corresponds to primary key-foreign key equivalencies in related tables).
- Relationship type category of relationship (link between entity) types).


#### Attributes:

 Properties or characteristics of an entity or relationship type (after corresponds to a field in a table).

### Figure 2-1: Sample ER Diagram



## Figure 2-2: Basic ER Notation



#### **Business Rules**

- Are statements that define or constrain some aspect of the business.
- Are derived from policies, procedures, events, functions.
- Assert business structure.
- Control/influence business behavior.
- Are expressed in terms familiar to end users.
- Are automated through DBMS software.



#### A Good Business Rule Is:

- Declarative what, not how
- Precise clear, agreed-upon meaning
- **Atomic** one statement
- Consistent internally and externally
- Expressible structured, natural language
- **Distinct** non-redundant
- Business-oriented understood by business people



#### **Entities**

- Entity a person, a place, an object, an event, or a concept in the user environment about which the organization wishes to maintain data
- Entity type a collection of entities that share common properties or characteristics
- Entity instance a single occurrence of an entity type



## Figure 2-3: Entity Type and Entity Instances

Attributes	Attribute Data Type	Example Instance	Example Instance
Employee Number	CHAR (10)	642-17-8360	534-10-1971
Name	CHAR (25)	Michelle Brady	David Johnson
Address	CHAR (30)	100 Pacific Avenue	450 Redwood Drive
City	CHAR (20)	San Francisco	Redwood City
State	CHAR (2)	CA	CA
Zip Code	CHAR (9)	98173	97142
Date Hired	DATE	03-21-1992	08-16-1994
Birth Date	DATE	06-19-1968	09-04-1975

FIGURE 2-3 Entity type EMPLOYEE with two instances



Lee-703-Ch2

10 ROBERT H. SMITH

## Strong/Weak Entities; Identifying Relationships

#### Strong entity:

- exists independently of other types of entities
- has its own unique identifier
- identifier underlined with single line

#### Weak entity:


- dependent on a strong entity (identifying owner) ... cannot exist on its own
- does not have a unique identifier (only a partial identifier)
- entity box and partial identifier have double lines

#### Identifying relationship:

links strong entities to weak entities



## Figure 2-5: Example of Weak Entity and Its Identifying Relationship



Strong entity

Weak entity



#### **Attributes**

- Attribute property or characteristic of an entity or relationship type
- Classifications of attributes:
  - Required versus Optional Attributes
  - Simple versus Composite Attribute
  - Single-Valued versus Multivalued Attribute
  - Stored versus Derived Attributes
  - Identifier Attributes



### Figure 2.6: Required versus Optional Attributes

Attributes	Attribute Data Type	Required or Optional	Example Instance	Example Instance
Student ID	CHAR (10)	Required	876-24-8217	822-24-4456
Student Name	CHAR (40)	Required	Michael Grant	Melissa Kraft
Home Address	CHAR (30)	Required	314 Baker St.	1422 Heft Ave
Home City	CHAR (20)	Required	Centerville	Miami
Home State	CHAR (2)	Required	ОН	FL
Home Zip Code	CHAR (9)	Required	45459	33321
Major	CHAR (3)	Optional	MIS	

**Required** – must have a value for every entity (or relationship) instance with which it is associated


**Optional** – may not have a value for every entity (or relationship) instance with which it is associated

Lee-703-Ch2

14 ROBERT H. SMITH

## Figure 2.7: Composite Attribute

Composite attribute – An attribute that has meaningful component parts (attributes)




Lee-703-Ch2 15 ROBERT H. SMITH

## Figure 2.8: Multi-Valued and Derived **Attributes**

**Multivalued** – may take on more than one value for a given entity (or relationship) instance

**Derived** – values can be calculated from related attribute values (not physically stored in the database)

**Multivalued** an employee can have more than one skill.



## **Identifiers** (Keys)

- Identifier (Key) an attribute (or combination of attributes) that uniquely identifies individual instances of an entity type.
- Simple versus Composite Identifier.
- Candidate Key— minimal combination of attributes ... satisfies the requirements for being an identifier.



Lee-703-Ch2

17 ROBERT H. SMITH

#### Criteria for Identifiers

- Choose Identifiers that:
  - Will not change in value.
  - Will not be null.
- Avoid intelligent identifiers (e.g., containing locations or people that might change).
- Substitute new, simple keys for long, composite keys.




Lee-703-Ch2

## Figure 2-9: Simple and Composite Identifier

**Attributes** 

(a) Simple identifier attribute

(b) Composite identifier attribute





Lee-703-Ch2

### Naming Attributes

- Name should be a singular noun or noun phrase.
- Name should be unique.
- Name should follow a standard format.
  - Common format = [Entity type name { [ Qualifier ] } ] Class
  - E.g. Employee Birth Date, Employee Annual Salary
- Similar attributes of different entity types should use the same qualifiers and classes.



Lee-703-Ch2 20 ROBERT H. SMITH

### **Defining Attributes**

- State what the attribute is and possibly why it is important.
- Make it clear what is and is not included in the attribute's value.
- Include aliases in documentation.
- State source of values.
- Specify required vs. optional.
- State min and max number of occurrences allowed.
- Indicate relationships with other attributes.



Lee-703-Ch2

## **Modeling Relationships**


- Relationship Type modeled as line between entity types.
- Relationship instance between specific entity instances.
- Relationships can have attributes.
  - These describe features pertaining to the association between the entities in the relationship.
- Two entities can have more than one type of relationship between them (multiple relationships).
- Associative Entity combination of relationship and entity.

Lee-703-Ch2

## Figure 2-10: Relationship Types and Instances

(a) Relationship type(e.g. Completes)

(b) Relationship instances




#### Degree of Relationships

- Degree of a relationship is the number of entity types that participate in it:
  - Unary Relationship
  - Binary Relationship
  - Ternary Relationship

•



## Figure 2-2: Degree of Relationships





## Cardinality of Unary/Binary Relationships

#### One-to-One:

Each entity in the relationship will have exactly one related entity.

#### One-to-Many:

 An entity on one side of the relationship can have many related entities, but an entity on the other side will have a maximum of one related entity.


#### Many-to-Many:

 Entities on both sides of the relationship can have many related entities on the other side.



Lee-703-Ch2 26 ROBERT H. SMITH


## Figure 2-12: Unary Relationships





Lee-703-Ch2 27 ROBERT H. SMITH

## Figure 2-12: Binary Relationships






Lee-703-Ch2

28 ROBERT H. SMITH

## Figure 2-12: Ternary Relationships



Note: a relationship can have attributes of its own.



Lee-703-Ch2


## **Cardinality Constraints**


- Cardinality Constraints the number of instances of one entity that can or must be associated with each instance of another entity.
- Minimum Cardinality:
  - If zero, then optional.
  - If one or more, then mandatory.
- Maximum Cardinality:
  - The maximum number of instances of one entity that may be associated with each instance of another entity.



Lee-703-Ch2 30 ROBERT H. SMITH

### Figure 2-17: Mandatory Cardinalities






A patient history is 'recorded for one and only one patient.


A patient must have recorded at least one history, and can have many.



## Figure 2-17: One Optional, One Mandatory

**Cardinalities** 






A project must be assigned to at least one employee, and may be assigned to many.


An employee can be assigned to any number of projects, or may not be assigned to any at all.



## Figure 2-17: Optional Cardinalities




A person is married to at most one other person, or may not be married at all.





Lee-703-Ch2


# Figure 2-21: Examples of Multiple Relationships





Lee-703-Ch2

# Figure 2-21: Examples of Multiple Relationships



Here, min cardinality constraint is 2. At least two professors must be qualified to teach each course.

Each professor must be qualified to teach at least one course.




#### **Associative Entities**

- Like an entity has name and attributes
- Is a relationship links entities together
- When should a relationship with attributes instead be an associative entity?
  - The associative entity could have meaning independent of the other entities.
  - The associative entity preferably has a unique identifier, and should also have other attribute(s).
  - Ternary (and higher degree) relationships should be converted to associative entities.



Lee-703-Ch2

## Figure 2-11: A Binary Relationship with an Attribute




Here, the date completed attribute pertains specifically to the employee's completion of a course...it is an attribute of the *relationship*.



Lee-703-Ch2 37 ROBERT H. SMITH

### Figure 2-11: An Associative Entity




Associative entity is like a relationship with an attribute, but it is also considered to be an entity in its own right.

Note: The many-to-many cardinality between entities in Figure 2-11 has been replaced by two one-to-many relationships with the associative entity.

Lee-703-Ch2 38 ROBERT H. SMITH

### Figure 2-13: An Associative Entity




This could just be a relationship with attributes ... it's a judgment call.



Lee-703-Ch2 39 ROBERT H. SMITH

# Figure 2-18: Cardinality Constraints in a Ternary Relationship






Lee-703-Ch2

40 ROBERT H. SMITH

### Figure 2-19: Simple Example of Time-Stamping




**Time stamp** – a time value that is associated with a data value, often indicating when some event occurred that affected the data value

The Price History attribute is both multivalued *and* composite.

Lee-703-Ch2

41 ROBERT H. SMITH

## Figure 2-20: ER Diagram with Associative Entity Over Time



Modeling time-dependent data has become more important due to regulations such as HIPAA and Sarbanes-Oxley.

The Assignment associative entity shows the date range of a product's assignment to a particular product line.