

# Reinforcement Learning

## Lecture 3a:

Policy Iteration

[SutBar] Sec. 4.3, [Put] Sec. 6.4-6.5,  
[SigBuf] Sec. 1.6.2.3, [RusNor] Sec. 17.3

# Policy Optimization

- Value iteration
  - Optimize value function
  - Extract induced policy
- Can we directly optimize the policy?
  - Yes, by **policy iteration**

# Policy Iteration

- Alternate between two steps

## 1. Policy evaluation

$$V^\pi(s) = R(s, \pi(s)) + \gamma \sum_{s'} \Pr(s'|s, \pi(s)) V^\pi(s') \quad \forall s$$

## 2. Policy improvement

$$\pi(s) \leftarrow \operatorname{argmax}_a R(s, a) + \gamma \sum_{s'} \Pr(s'|s, a) V^\pi(s') \quad \forall s$$

# Algorithm

## policyIteration(MDP)

Initialize  $\pi_0$  to any policy

$n \leftarrow 0$

Repeat

    Eval:  $V_n = R^{\pi_n} + \gamma T^{\pi_n} V_n$


    Improve:  $\pi_{n+1} \leftarrow \operatorname{argmax}_a R^a + \gamma T^a V_n$

$n \leftarrow n + 1$

Until  $\pi_{n+1} = \pi_n$

Return  $\pi_n$

# Example (Policy Iteration)



$n$	$V(PU)$	$\pi(PU)$	$V(PF)$	$\pi(PF)$	$V(RU)$	$\pi(RU)$	$V(RF)$	$\pi(RF)$
0	0	A	0	A	10	A	10	A
1	31.6	A	38.6	S	44.0	S	54.2	S
2	31.6	A	38.6	S	44.0	S	54.2	S

# Monotonic Improvement

- **Lemma 1:** Let  $V_n$  and  $V_{n+1}$  be successive value functions in policy iteration. Then  $V_{n+1} \geq V_n$ .
- Proof:
  - We know that  $H^*(V_n) \geq H^{\pi_n}(V_n) = V_n$
  - Let  $\pi_{n+1} = \operatorname{argmax}_a R^a + \gamma T^a V_n$
  - Then  $H^*(V_n) = R^{\pi_{n+1}} + \gamma T^{\pi_{n+1}} V_n \geq V_n$
  - Rearranging:  $R^{\pi_{n+1}} \geq (I - \gamma T^{\pi_{n+1}}) V_n$
  - Hence  $V_{n+1} = (I - \gamma T^{\pi_{n+1}})^{-1} R^{\pi_{n+1}} \geq V_n$

# Convergence

- **Theorem 2:** Policy iteration converges to  $\pi^*$  &  $V^*$  in finitely many iterations when  $S$  and  $A$  are finite.
- Proof:
  - We know that  $V_{n+1} \geq V_n \quad \forall n$  by Lemma 1.
  - Since  $A$  and  $S$  are finite, there are finitely many policies and therefore the algorithm terminates in finitely many iterations.
  - At termination,  $\pi_{n+1} = \pi_n$  and therefore  $V_n$  satisfies Bellman's equation:

$$V_n = V_{n+1} = \max_a R^a + \gamma T^a V_n$$

# Complexity

- Value Iteration:
  - Each iteration:  $O(|S|^2|A|)$
  - Many iterations: linear convergence
- Policy Iteration:
  - Each iteration:  $O(|S|^3 + |S|^2|A|)$
  - Few iterations: linear-quadratic convergence



# Modified Policy Iteration

- Alternate between two steps

## 1. **Partial** Policy evaluation

Repeat  $k$  times:

$$V^\pi \leftarrow R(s, \pi(s)) + \gamma \sum_{s'} \Pr(s'|s, \pi(s)) V^\pi(s') \quad \forall s$$

## 2. Policy improvement

$$\pi(s) \leftarrow \operatorname{argmax}_a R(s, a) + \gamma \sum_{s'} \Pr(s'|s, a) V^\pi(s') \quad \forall s$$

# Algorithm

## modifiedPolicyIteration(MDP)

Initialize  $\pi_0$  and  $V_0$  to anything

$n \leftarrow 0$

Repeat

    Eval: Repeat  $k$  times

$$V_n \leftarrow R^{\pi_n} + \gamma T^{\pi_n} V_n$$

    Improve:  $\pi_{n+1} \leftarrow \operatorname{argmax}_a R^a + \gamma T^a V_n$

$$V_{n+1} \leftarrow \max_a R^a + \gamma T^a V_n$$

$n \leftarrow n + 1$

Until  $\|V_n - V_{n-1}\|_{\infty} \leq \epsilon$

Return  $\pi_n$

# Convergence

- Same convergence guarantees as value iteration:

- Value function  $V_n$ :  $\|V_n - V^*\|_\infty \leq \frac{\epsilon}{1 - \gamma}$

- Value function  $V^{\pi_n}$  of policy  $\pi_n$ :

$$\|V^{\pi_n} - V^*\|_\infty \leq \frac{2\epsilon}{1 - \gamma}$$

- Proof: somewhat complicated (see Section 6.5 of Puterman's book)

# Complexity

- Value Iteration:
  - Each iteration:  $O(|S|^2|A|)$
  - Many iterations: linear convergence
- Policy Iteration:
  - Each iteration:  $O(|S|^3 + |S|^2|A|)$
  - Few iterations: linear-quadratic convergence
- Modified Policy Iteration:
  - Each iteration:  $O(k|S|^2 + |S|^2|A|)$
  - Few iterations: linear-quadratic convergence