

BG77xA-GL&BG95xA-GL& BG950S-GL FILE Application Note

LPWA Module Series

Version: 1.1

Date: 2024-07-16

Status: Released



At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local offices. For more information, please visit:

<http://www.quectel.com/support/sales.htm>.

For technical support, or to report documentation errors, please visit:

<http://www.quectel.com/support/technical.htm>.

Or email us at: support@quectel.com.

Legal Notices

We offer information as a service to you. The provided information is based on your requirements and we make every effort to ensure its quality. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an “as available” basis. We may revise or restate this document from time to time at our sole discretion without any prior notice to you.

Use and Disclosure Restrictions

License Agreements

Documents and information provided by us shall be kept confidential, unless specific permission is granted. They shall not be accessed or used for any purpose except as expressly provided herein.

Copyright

Our and third-party products hereunder may contain copyrighted material. Such copyrighted material shall not be copied, reproduced, distributed, merged, published, translated, or modified without prior written consent. We and the third party have exclusive rights over copyrighted material. No license shall be granted or conveyed under any patents, copyrights, trademarks, or service mark rights. To avoid ambiguities, purchasing in any form cannot be deemed as granting a license other than the normal non-exclusive, royalty-free license to use the material. We reserve the right to take legal action for noncompliance with abovementioned requirements, unauthorized use, or other illegal or malicious use of the material.

Trademarks

Except as otherwise set forth herein, nothing in this document shall be construed as conferring any rights to use any trademark, trade name or name, abbreviation, or counterfeit product thereof owned by Quectel or any third party in advertising, publicity, or other aspects.

Third-Party Rights

This document may refer to hardware, software and/or documentation owned by one or more third parties ("third-party materials"). Use of such third-party materials shall be governed by all restrictions and obligations applicable thereto.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing or usage of trade.

Privacy Policy

To implement module functionality, certain device data are uploaded to Quectel's or third-party's servers, including carriers, chipset suppliers or customer-designated servers. Quectel, strictly abiding by the relevant laws and regulations, shall retain, use, disclose or otherwise process relevant data for the purpose of performing the service only or as permitted by applicable laws. Before data interaction with third parties, please be informed of their privacy and data security policy.

Disclaimer

- a) We acknowledge no liability for any injury or damage arising from the reliance upon the information.
- b) We shall bear no liability resulting from any inaccuracies or omissions, or from the use of the information contained herein.
- c) While we have made every effort to ensure that the functions and features under development are free from errors, it is possible that they could contain errors, inaccuracies, and omissions. Unless otherwise provided by valid agreement, we make no warranties of any kind, either implied or express, and exclude all liability for any loss or damage suffered in connection with the use of features and functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage may have been foreseeable.
- d) We are not responsible for the accessibility, safety, accuracy, availability, legality, or completeness of information, advertising, commercial offers, products, services, and materials on third-party websites and third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2024. All rights reserved.

About the Document

Revision History

Version	Date	Author	Description
-	2021-02-04	Damir KLICKOVIC	Creation of the document
1.0	2022-05-05	Damir KLICKOVIC	First official release
1.1	2024-07-16	Nikola RADOSAVLJEVIC	1. Added applicable modules BG773A-GL, BG953A-GL, BG955A-GL and BG950S-GL 2. Added notes whenever AT commands not implemented for BG950S-GL.

Contents

About the Document.....	3
Contents	4
Table Index.....	5
1 Introduction	6
1.1. Using FILE AT Commands.....	6
1.2. Description of Data Mode	7
2 Description of FILE AT Commands	8
2.1. AT Command Introduction	8
2.1.1. Definitions.....	8
2.1.2. AT Command Syntax	8
2.2. Declaration of AT Command Examples	9
2.3. AT Command Description	9
2.3.1. AT+QFLDS Get Space Information of Storage Medium	9
2.3.2. AT+QFLST List File Information on Storage Medium	10
2.3.3. AT+QFDEL Delete File(s) on Storage Medium	12
2.3.4. AT+QFUPL Upload a File to Storage Medium	13
2.3.5. AT+QFDWL Download a File from Storage Medium	15
2.3.6. AT+QFOPEN Open a File	16
2.3.7. It AT+QFREAD Read a File.....	17
2.3.8. AT+QFWRITE Write to a File	18
2.3.9. AT+QFSEEK Set File Pointer to a Specified Position.....	19
2.3.10. AT+QFPOSITION Get Offset of File Pointer.....	20
2.3.11. AT+QFTUCAT Truncate File from File Pointer.....	20
2.3.12. AT+QFCLOSE Close a File.....	21
2.3.13. AT+QFCRC Calculate CRC of a Specified UFS File.....	22
2.3.14. AT+QFCPY Make a Copy of a UFS Specified File	22
3 Examples	24
3.1. Upload and Download a File.....	24
3.1.1. Upload a File	24
3.1.2. Download a File	25
3.2. Write to and Read a File	25
3.2.1. Write to and Read a UFS File	25
3.2.2. Write to and Read an EUFS File.....	25
4 Summary of Error Codes	27
5 Appendix Reference	29

Table Index

Table 1: Applicable Modules..... 6

Table 2: Types of AT Commands 8

Table 3: Summary of Error Codes..... 27

Table 4: Terms and Abbreviations 29

1 Introduction

The document is an application note introducing AT commands for the operation of files on different physical storage mediums, which are supported by Quectel BG77xA-GL, BG95xA-GL and BG950S-GL modules.

The storage mediums supported are:

- **UFS:** User File Storage directory (a special directory in the flash file system) on the modem side
- **EUFS:** Extended User File Storage on the application side

The file name indicates storage location. A file name with the prefix “UFS:” or without any prefix indicates that it is in the UFS, while one with the prefix “EUFS:” indicates that it is in the EUFS.

Table 1: Applicable Modules

Module Series	Model
BG77xA-GL	BG770A-GL
	BG773A-GL
BG95xA-GL	BG950A-GL
	BG951A-GL
	BG953A-GL
	BG955A-GL
-	BG950S-GL

1.1. Using FILE AT Commands

The general procedure for uploading/downloading, opening/creating, reading and writing to a file in the storage:

Step 1: Upload a file to the storage with **AT+QFUPL**. If necessary, download the file with **AT+QFDWL** to verify its content, data integrity, etc.

Step 2: Open the file with **AT+QFOPEN**. When the file is opened, you can write to it or read from it any time and from any location until the file is closed with **AT+QFCLOSE**.

When opening a file with **AT+QFOPEN**, you can, for example, set the file into overwrite mode or read-only mode with **<mode>** (see **Chapter 2.3.6** for details). After the file is opened, a **<filehandle>** is assigned to it so that various file operations can be carried out.

Step 3: After the file is opened, you can write to it with **AT+QFWRITE** or read the data content from the current file pointer position with **AT+QFREAD**.

- You can set the file pointer position with **AT+QFSEEK** or query the current position with **AT+QFPOSITION**.
- **AT+QFTUCAT** will truncate the file from the current position to the end of the file.

Step 4: Close the file with **AT+QFCLOSE**, after which the **<filehandle>** becomes invalid.

Commonly used commands to manage files in the storage:

- 1) **AT+QFLDS**: Get storage space information.
- 2) **AT+QFLST**: List the file information in the specified storage.
- 3) **AT+QFDEL**: Delete the file(s) in the specified storage.

1.2. Description of Data Mode

The COM port of the BG77xA-GL, BG95xA-GL and BG950S-GL modules has two working modes: AT command mode and data mode. Data inputted via the COM port in former mode are viewed as AT commands, whereas they are treated as data in latter mode.

● Enter Data Mode

Execute **AT+QFUPL**, **AT+QFDWL**, **AT+QFREAD** or **AT+QFWRITE** to enter the data mode. If you input **+++** or pull MAIN_DTR pin up to make the port exit the data mode, the execution of these commands will be interrupted before the response is returned. In such a case, the COM port cannot re-enter the data mode if you execute **ATO**.

● Exit Data Mode

Input **+++** or pull MAIN_DTR pin up to make the COM port exit the data mode. To prevent **+++** from being misinterpreted as data, the following rules should be followed:

- 1) Do not input any character for at least 1 second before and after inputting **+++**.
- 2) Input **+++** within 1 second, and wait until **OK** is returned. Once **OK** is returned, the COM port exits the data mode and switches to AT command mode.

If you are exiting the data mode by pulling MAIN_DTR pin up, make sure to set **AT&D1** first.

2 Description of FILE AT Commands

2.1. AT Command Introduction

2.1.1. Definitions

- **<CR>** Carriage return character.
- **<LF>** Line feed character.
- **<...>** Parameter name. Angle brackets do not appear on the command line.
- **[...]** Optional parameter of a command or an optional part of TA information response. Square brackets do not appear on the command line. When an optional parameter is not given in a command, the new value equals its previous value or the default settings, unless otherwise specified.
- **Underline** Default setting of a parameter.

2.1.2. AT Command Syntax

All command lines must start with **AT** or **at** and end with **<CR>**. Information responses and result codes always start and end with a carriage return character and a line feed character: **<CR><LF><response><CR><LF>**. In tables presenting commands and responses throughout this document, only the commands and responses are presented, and **<CR>** and **<LF>** are deliberately omitted.

Table 2: Types of AT Commands

Command Type	Syntax	Description
Test Command	AT+<cmd>=?	Test the existence of the corresponding command and return information about the type, value, or range of its parameter.
Read Command	AT+<cmd>?	Check the current parameter value of the corresponding command.
Write Command	AT+<cmd>=<p1>[,<p2>[,<p3>[...]]]	Set user-definable parameter value.
Execution Command	AT+<cmd>	Return a specific information parameter or perform a specific action.

2.2. Declaration of AT Command Examples

The AT command examples in this document are provided to help you learn about the use of the AT commands introduced herein. The examples, however, should not be taken as Quectel's recommendations or suggestions about how to design a program flow or what status to set the module into. Sometimes multiple examples may be provided for one AT command. However, this does not mean that there is a correlation among these examples, or that they should be executed in a given sequence.

2.3. AT Command Description

2.3.1. AT+QFLDS Get Space Information of Storage Medium

This command gets the space information of the specified storage medium.

AT+QFLDS Get Space Information of Storage Medium	
Test Command AT+QFLDS=?	Response OK
Write Command AT+QFLDS=<storage>	Response +QFLDS: <freesize>,<total_size> OK If there is an error related to the ME functionality: +CME ERROR: <err>
Execution Command AT+QFLDS	Response +QFLDS: <UFS_file_size>,<UFS_file_number> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<storage>	String type. Storage medium type. "UFS" UFS on modem side "EUFS" Extended UFS on application side
<freesize>	Integer type. Free space size of <storage> . Unit: byte.
<total_size>	Integer type. Total size of <storage> . Unit: byte.

<UFS_file_size>	Integer type. Size of all files in UFS. Unit: byte.
<UFS_file_number>	Integer type. Number of files in UFS.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

Example

```

AT+QFLDS="UFS" //Query the space information of UFS on modem side.
+QFLDS: 1249984,1562624

OK
AT+QFLST=""
+QFLST: "Test1.txt",10
+QFLST: "Test2.txt",16
+QFLST: "Test3.txt",150
+QFLST: "Test4.txt",2056
+QFLST: "Test5.txt",98

OK
AT+QFLDS //Query the size and number of all files in UFS.
+QFLDS: 2330,5

OK

```

NOTE

This AT command is in development for BG950S-GL.

2.3.2. AT+QFLST List File Information on Storage Medium

This command lists the information of a single file or all files on a specified storage medium.

AT+QFLST List File Information on Storage Medium

Test Command	Response
AT+QFLST=?	OK
Write Command	Response
AT+QFLST=<filename>	+QFLST: <file>,<file_size> [+QFLST: <file>,<file_size> [...]]
	OK
	If there is any error:

	+CME ERROR: <err>
Execution Command AT+QFLST	Response Return the information of UFS files: +QFLST: <file>,<file_size> [+QFLST: <file>,<file_size> [...]] OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. File(s) to be listed. Maximum length: 28 bytes.
"*"	All files in UFS
"UFS:*"	All files in UFS
"EUFS:*"	All files in the <i>ufs</i> directory of EUFS
"EUFS:/ufs/*"	All files in the <i>ufs</i> directory of EUFS
"EUFS:/datatx/*"	All files in the <i>datatx</i> directory of EUFS
"<file>"	A specified file <file> in UFS
"UFS:<file>"	A specified file <file> in UFS
"EUFS:<file>"	A specified file <file> in <i>ufs</i> directory of EUFS
"EUFS:/ufs/<file>"	A specified file <file> in <i>ufs</i> directory of EUFS
"EUFS:/datatx/<file>"	A specified file <file> in <i>datatx</i> directory of EUFS
<file>	String type. The exact name of a file.
<file_size>	Integer type. File size. Unit: byte.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

Example

```

AT+QFLST="*" //List all files in UFS.
+QFLST: "F_M12-1.bmp",562554
+QFLST: "F_M12-10.bmp",562554
+QFLST: "F_M12-11.bmp",562554

OK
AT+QFLST="Test1.txt" //List a specified file "Test1.txt" in UFS.
+QFLST: "Test1.txt",2

OK

```

```

AT+QFLST="EUFS:/ufs/*" //List all files in ufs directory of EUFS.
+QFLST: "EUFS:test.txt",10
+QFLST: "EUFS:test2.txt",20

OK

AT+QFLST="EUFS:test.txt" //List a specified file "test.txt" in ufs directory of EUFS.
+QFLST: "EUFS:test.txt",10

OK

```

2.3.3. AT+QFDEL Delete File(s) on Storage Medium

This command deletes a specified file or all files from a storage medium.

AT+QFDEL Delete File(s) on Storage Medium

Test Command AT+QFDEL=?	Response +QFDEL: <filename> OK
Write Command AT+QFDEL=<filename>	Response OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. File(s) to be deleted. Maximum length: 28 bytes.
""	Delete all files in UFS
"UFS:."	Delete all files in UFS
"EUFS:/ufs/*"	Delete all files in the <i>ufs</i> directory of EUFS (<i>ufs</i> directory remains)
"EUFS:/datatx/*"	Delete all files in the <i>datatx</i> directory of EUFS (<i>datatx</i> directory remains)
"EUFS:."	Delete all files in the <i>ufs</i> directory of EUFS (<i>ufs</i> directory remains)
"UFS:<file>"	Delete a specified file <file> in UFS
"EUFS:<file>"	Delete a specified file <file> in <i>ufs</i> directory of EUFS
"EUFS:/ufs/<file>"	Delete a specified file <file> in <i>ufs</i> directory of EUFS
"EUFS:/datatx/<file>"	Delete a specified file <file> in <i>datatx</i> directory of EUFS
<file>	String type. The exact name of a file.

<err> Integer type. Error code. See **Chapter 4** for possible **<err>** values.

Example

```
AT+QFDEL=""
OK

AT+QFDEL="Test1.txt"
OK
```

2.3.4. AT+QFUPL Upload a File to Storage Medium

This command uploads a file to a storage medium. If any file on the storage medium already contains a file with the same name as the file being uploaded, an error will be reported.

After the Write Command is executed and **CONNECT** is returned, the module will switch to the data mode. When the uploaded data reach **<file_size>**, or if no other data is inputted when **<timeout>** is reached, the module exits the data mode automatically. During data transmission, you can send **+++** or pull MAIN_DTR pin high to make the module exit the data mode. For more information, see **Chapter 1.2**.

AT+QFUPL Upload a File to Storage Medium

Test Command AT+QFUPL=?	Response +QFUPL: <filename>[(1-<freesize>)][(range of supported <timeout>s)][(list of supported <ackmode>s)] OK
Write Command AT+QFUPL=<filename>[,<file_size>[,<timeout>[,<ackmode>]]]	Response CONNECT TA switches to the data mode (transparent transmission mode), so the binary data of the file can be inputted. When the total size of the inputted data reaches <file_size> or TA receives +++ , TA will return to the command mode and report the following code: +QFUPL: <upload_size>,<checksum> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. Name of the file to be uploaded. Maximum length: 28 bytes.
"<file>"	Upload the file to UFS
"UFS:<file>"	Upload the file to UFS
"EUFS:<file>"	Upload the file to <i>ufs</i> directory of EUFS
"EUFS:/ufs/<file>"	Upload the file to <i>ufs</i> directory of EUFS
"EUFS:/datatx/<file>"	Upload the file to <i>datatx</i> directory of EUFS
<file>	String type. The exact name of a file.
<freesize>	Integer type. Free space size of <storage>. Unit: byte.
<file_size>	Integer type. File size expected to be uploaded. Default value: 10240. Unit: byte. Maximum length is not greater than <freesize>.
<timeout>	Integer type. Waiting time for inputting data to UART and USB. Range: 1–65535. Default value: 5. Unit: s.
<ackmode>	Integer type. Determines whether to use ACK mode. 0 Turn ACK mode off. 1 Turn ACK mode on.
<upload_size>	Integer type. Actual size of uploaded data. Unit: byte.
<checksum>	Integer type. Checksum of uploaded data.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

- It is strongly recommended to use DOS 8.3 file name format for <filename>.
- <checksum> is a 16-bit checksum calculated using bitwise XOR.
If the number of characters is odd, set the high 8 bits of the checksum as the value of the last characters, and set the low 8 bits to 0. Use an XOR operator to calculate the checksum. Inputting +++ sequence will end the data transmission and switch to the command mode. However, previously uploaded data will be preserved and stored in the file.
- When executing the command, the data must be entered after **CONNECT** is returned.
- The ACK mode safeguards against data loss when uploading a large file, if hardware flow control is not functioning properly. The ACK mode works as follows:
 - Run **AT+QFUPL=<filename>,<file_size>,<timeout>,1** to enable the ACK mode.
 - The module outputs **CONNECT**.
 - MCU sends 1 K bytes of data, to which the modules respond with an **A**.
 - MCU receives the **A** and then sends the next 1 K bytes of data.
 - Repeat Steps 3 and 4 till the end of data transfer.
 See **Chapter 3.1.1.2** for an example of ACK mode usage.
- Due to the physical limitations of the platform, i.e., write speed to the NOR flash memory, the upload feature has 2 operational modes to prevent any data loss in the process of writing a file. Two modes are: 1) without HW flow control activated, and 2) with HW flow control activated.
 - In former mode, the max file size is 200000 bytes. Sending files exceeding that will result in an error. Writing time can significantly vary upon file size, content, and area of the flash where the file is being written.
 - In latter mode, there is no file size limitation other than the available disk space, by executing

AT+IFC=2,2. To ensure safe file transfer in this mode, RTS and CTS on the client side must be switched on before file sending. Transmission time can be longer than mode 1.

6. This AT command is in development for BG950S-GL.

2.3.5. AT+QFDWL Download a File from Storage Medium

This command downloads a specified file from a storage medium.

AT+QFDWL Download a File from Storage Medium

Test Command AT+QFDWL=?	Response +QFDWL: <filename> OK
Write Command AT+QFDWL=<filename>	Response CONNECT TA switches to the data mode, so the binary data of the file can be outputted. When the content of the file is read or the TA receives +++ , the TA will return to the command mode and report the following code: +QFDWL: <download_size>,<checksum> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. Name of the file to be downloaded. Maximum length: 28 bytes.
"<file>"	Download the file from UFS
"UFS:<file>"	Download the file from UFS
"EUPS:<file>"	Download the file from the <i>ufs</i> directory of EUPS
"EUPS:/ufs/<file>"	Download the file from the <i>ufs</i> directory of EUPS
"EUPS:/datatx/<file>"	Download the file from the <i>datatx</i> directory of EUPS
<file>	String type. The exact name of a file.
<download_size>	Integer type. Size of downloaded data. Unit: byte.
<checksum>	Integer type. Checksum of downloaded data.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

1. Inputting **+++** will end the data transmission and switch to the command mode.
2. **<checksum>** is a 16-bit checksum calculated using bitwise XOR.

2.3.6. AT+QFOPEN Open a File

This command opens a file and gets the file handle to be used in commands such as **AT+QFREAD**, **AT+QFWRITE**, **AT+QFSEEK**, **AT+QFPOSITION**, **AT+QFTUCAT** and **AT+QFCLOSE**.

AT+QFOPEN Open a File

Test Command AT+QFOPEN=?	Response +QFOPEN: <filename>[, (range of supported <mode>s)] OK
Read Command AT+QFOPEN?	Response +QFOPEN: <filename>,<filehandle>,<mode> [+QFOPEN: <filename>,<filehandle>,<mode> [...]] OK
Write Command AT+QFOPEN=<filename>[,<mode>]	Response +QFOPEN: <filehandle> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. Name of the file to be opened. Maximum length: 28 bytes. "<file>" Open the file in UFS "UFS:<file>" Open the file in UFS "EUFS:<file>" Open the file of the <i>ufs</i> directory of EUFS. "EUFS:/ufs/<file>" Open the file of the <i>ufs</i> directory of EUFS "EUFS:/datatx/<file>" Open the file of the <i>datatx</i> directory of EUFS
<file>	String type. The exact name of a file.
<filehandle>	Integer type. Handle of the file to be used.
<mode>	Integer type. File opening mode.

- 0 If the file does not exist, it is created. If the file exists, it is opened directly. In both cases, the file can be read and written to.
- 1 If the file does not exist, it is created. If the file exists, it is overwritten. In both cases, the file can be read and written to.
- 2 If the file exists, it is opened directly as a read-only file. Otherwise, an error is returned.
- 3 If the file does not exist, it is created. If the file exists, data is appended at the end of the file. In both cases, the file can be read and written to.

<err>

Integer type. Error code. See **Chapter 4** for possible **<err>** values.

NOTE

- 1. **<filehandle>** starts from 0 in UFS, whereas it starts from 20000 in EUFS.
- 2. This AT command is in development for BG950S-GL.

2.3.7. It AT+QFREAD Read a File

This command reads the data of a file specified by the file handle. The data start from the current position of the file pointer that belongs to the file handle.

AT+QFREAD Read a File	
Test Command AT+QFREAD=?	Response +QFREAD: <filehandle>[,<data_length>] OK
Write Command AT+QFREAD=<filehandle>[,<data_length>]	Response CONNECT <read_length> TA switches to the data mode. When the total size of the data reaches <data_length> (unit: byte), the TA will go back to the command mode, display the result and report the following code: OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file to be read.
<data_length>	Integer type. Length of the file to be read. Default value: file length. Unit: byte.

<read_length>	Integer type. Actual read length. Unit: byte.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

2.3.8. AT+QFWRITE Write to a File

This command writes data into a file. The data is written starting from the current position of the file pointer associated with the file handle.

AT+QFWRITE Write to a File	
Test Command AT+QFWRITE=?	Response +QFWRITE: <filehandle>[<data_length>[,<timeout>]] OK
Write Command AT+QFWRITE=<filehandle>[<data_length>[,<timeout>]]	Response CONNECT TA switches to the data mode. When the total size of the written data reaches <data_length> (unit: byte) or the time reaches <timeout> , the TA will go back to the command mode and report the following code: +QFWRITE: <written_length>,<total_length> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file to be written to.
<data_length>	Integer type. Length of the file to be written to. Maximum value of this parameter is determined by <freesize> of AT+QFUPL . Default value: 10240. Unit: byte.
<timeout>	Integer type. Waiting time for inputting data to USB/UART. Range: 1–65535. Default value: 5. Unit: second.
<written_length>	Integer type. Actual written length. Unit: byte.
<total_length>	Integer type. Total file length. Unit: byte.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

1. Due to the physical limitations of the platform, i.e. write speed to the NOR flash memory, the upload feature has 2 operational modes to prevent any data loss in the process of writing a file. Two modes are: 1) without HW flow control activated, and 2) with HW flow control activated.
 - 1) In former mode, the max file size is 200000 bytes. Sending files exceeding that will result in an error. Writing time can significantly vary upon file size, content, and area of the flash where the file is being written.
 - 2) In latter mode, there is no file size limitation other than the available disk space, by executing **AT+IFC=2,2**. To ensure safe file transfer in this mode, RTS and CTS on the client side must be switched on before file sending. Transmission time can be longer than mode 1.
2. This AT command is in development for BG950S-GL.

2.3.9. AT+QFSEEK Set File Pointer to a Specified Position

This command sets a file pointer to a specified position. This will decide the starting position of commands such as **AT+QFREAD**, **AT+QFWRITE**, **AT+QFPOSITION** and **AT+QFTUCAT**.

AT+QFSEEK Set File Pointer to a Specified Position

Test Command AT+QFSEEK=?	Response +QFSEEK: <filehandle>,<offset>[,<position>] OK
Write Command AT+QFSEEK=<filehandle>,<offset>[,<position>]	Response OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file for which a pointer is set.
<offset>	Integer type. Number of bytes of the file pointer movement.
<position>	Integer type. Pointer movement mode. 0 Move forward from the beginning of the file. 1 Move forward from the current pointer position. 2 Move backward from the end of the file.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

1. If **<position>**=0/2 and **<offset>** exceeds file size, the command returns **ERROR**.
2. If **<position>**=1 and the total size of **<offset>** and the current pointer position exceed the file size, the command returns **ERROR**.

2.3.10. AT+QFPOSITION Get Offset of File Pointer

This command gets the offset of a file pointer from the beginning of the file.

AT+QFPOSITION Get Offset of File Pointer

Test Command AT+QFPOSITION=?	Response +QFPOSITION: <filehandle> OK
Write Command AT+QFPOSITION=<filehandle>	Response +QFPOSITION: <offset> OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file for which the offset of the file pointer is to be retrieved.
<offset>	Integer type. Offset from the beginning of the file.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

2.3.11. AT+QFTUCAT Truncate File from File Pointer

This command truncates the file from the current pointer position to the end of the file.

AT+QFTUCAT Truncate File from File Pointer

Test Command AT+QFTUCAT=?	Response +QFTUCAT: <filehandle> OK
Write Command AT+QFTUCAT=<filehandle>	Response OK

	If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file to be truncated.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

This AT command is in development for BG950S-GL.

2.3.12. AT+QFCLOSE Close a File

This command closes a file and ends all file operations. After that, the file handle is released and should not be used again, unless the file is re-opened with **AT+QFOPEN**.

AT+QFCLOSE Close a File

Test Command AT+QFCLOSE=?	Response +QFCLOSE: <filehandle> OK
Write Command AT+QFCLOSE=<filehandle>	Response OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filehandle>	Integer type. Handle of the file to be closed.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

2.3.13. AT+QFCRC Calculate CRC of a Specified UFS File

This command calculates the CRC16, CRC16_CCITT and CRC32 checksums of a specified UFS file.

AT+QFCRC Calculate CRC of a Specified UFS File

Test Command AT+QFCRC=?	Response +QFCRC: <filename> OK
Write Command AT+QFCRC=<filename>	Response When the specified file exists, the command returns 32-bit CRC, 16-bit CRC values and 16-bit CRC CCITT: +QFCRC: <crc32>,<crc16>,<crc16_ccitt> OK When the file exists but has no byte: +QFCRC: 0,0,0 If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<filename>	String type. Input format: "UFS:filename". "UFS:" can be omitted.
<crc32>	32-bit CRC value.
<crc16>	16-bit CRC value.
<crc16_ccitt>	16-bit CRC CCITT value.
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

This command applies to UFS files only.

2.3.14. AT+QFCPY Make a Copy of a UFS Specified File

This command copies the whole content of a source file to a destination file.

- If the destination file already exists, the command returns an **ERROR** unless **<enable>=1**.
- If the destination file has the same name as the source file, the command returns an **ERROR**.
- If the remaining space of the file system is smaller than the file size to be copied, the command also returns an **ERROR**.

AT+QFCPY Make a Copy of a Specified UFS File

Test Command AT+QFCPY=?	Response +QFCPY: <src_file>,<dest_file>[,<enable>] OK
Write Command AT+QFCPY=<src_file>,<dest_file>[,<enable>]	Response OK If there is any error: +CME ERROR: <err>
Characteristics	The command takes effect immediately; The configurations will not be saved.

Parameter

<src_file>	String type. Source file name. Input format: "UFS:filename". "UFS:" can be omitted.
<dest_file>	String type. Destination file name. Input format: "UFS:filename". "UFS:" can be omitted.
<enable>	Integer type. Determines whether to overwrite the existing file that has the same name as the destination file. <u>0</u> Disable 1 Enable
<err>	Integer type. Error code. See Chapter 4 for possible <err> values.

NOTE

This command applies to UFS files only.

3 Examples

3.1. Upload and Download a File

3.1.1. Upload a File

3.1.1.1. Non-ACK Mode

```

AT+QFUPL="test1.txt",10           //Upload the text file "test1.txt" to UFS.
CONNECT
<Input file bin data>
+QFUPL: 10,3938

OK
AT+QFUPL="EUFS:test.txt",4        //Upload the text file "test.txt" to ufs directory of EUFS.
CONNECT
<Input file bin data>
+QFUPL: 4,6a05s

OK

```

3.1.1.2. ACK Mode

The ACK mode makes data transmission more reliable. When transmitting a large file without hardware flow control, the ACK mode is recommended to prevent data loss. For more information about the ACK mode, see **AT+QFUPL**.

```

AT+QFUPL="test.txt",3000,5,1      //Upload the text file "test.txt" to UFS.
CONNECT
<input file bin data of 1024 bytes>
A                                //After receiving 1024 bytes of data, the module returns A.
                                Then the next 1024 bytes of data can be inputted.
<input file bin data of 1024 bytes>
A
<input the rest file bin data>

```

```
+QFUPL: 3000,B34A
```

```
OK
```

3.1.2. Download a File

```
AT+QFDWL="test.txt"
```

```
//Download the text file "test.txt" from UFS.
```

```
CONNECT
```

```
<Output Data>
```

```
+QFDWL: 10,613e
```

```
//Size and checksum value of the downloaded data is returned.
```

```
OK
```

3.2. Write to and Read a File

3.2.1. Write to and Read a UFS File

```
AT+QFOPEN="test",0
```

```
//Open the file to get the file handle.
```

```
+QFOPEN: 0
```

```
OK
```

```
AT+QFWRITE=0,10
```

```
//Write 10 bytes to the file.
```

```
CONNECT
```

```
<Write Data>
```

```
+QFWRITE: 10,10
```

```
//The actual written bytes and the size of the file are returned.
```

```
OK
```

```
AT+QFSEEK=0,0,0
```

```
//Set the file pointer to the beginning of the file.
```

```
OK
```

```
AT+QFREAD=0,10
```

```
//Read 10 bytes from the file.
```

```
CONNECT 10
```

```
<Read Data>
```

```
OK
```

```
AT+QFCLOSE=0
```

```
//Close the file.
```

```
OK
```

3.2.2. Write to and Read an EUFS File

```
AT+QFLDS="EUPS"
```

```
//Query the space information of EUPS.
```

```
+QFLDS: 1388544,2435072
```

```
OK
AT+QFOPEN="EUFS:test",0           //Open the file to get the file handle.
+QFOPEN: 20000

OK
AT+QFWRITE=20000,10               //Write 10 bytes to the file.
CONNECT
<Write Data>
+QFWRITE: 10,10                   //The actual written bytes and the size of the file are returned.

OK
AT+QFSEEK=20000,0,0               //Set the file pointer to the beginning of the file.
OK
AT+QFREAD=20000,10               //Read 10 bytes from the file.
CONNECT 10
<Read Data>

OK
AT+QFCLOSE=20000                  //Close the file.
OK
```

4 Summary of Error Codes

The error code **<err>** indicates an error related to mobile equipment. The detailed information about **<err>** is presented in the following table, which includes only the error codes related to the file operation of the module.

Table 3: Summary of Error Codes

<err>	Meaning
400	Invalid input value
401	File size exceeds the limit
402	Attempted to read zero byte
403	Drive is full
405	File not found
406	Invalid file name
407	File already exists
409	Failed to write to the file
410	Failed to open the file
411	Failed to read the file
413	Maximum number of open files reached
414	File is read-only
416	Invalid file descriptor
417	Failed to list the file
418	Failed to delete the file
419	Failed to get disk information
420	Insufficient space

421	Operation timed out
423	File too large
425	Invalid parameter
426	File is already open
427	Failed to allocate memory. If the file size is > 200 KB, IFC: 2,2 must be used
428	Maximum allowed number of files on the drive exceeded

5 Appendix Reference

Table 4: Terms and Abbreviations

Abbreviation	Description
ACK	Acknowledgement
COM	Communication Port
CRC	Cyclic Redundancy Check
DOS	Disk Operating System
EUFS	Extended User File Storage
MCU	Microprogrammed Control Unit
ME	Mobile Equipment
TA	Terminal Adapter
UART	Universal Asynchronous Receiver/Transmitter
UFS	User File Storage
USB	Universal Serial Bus
XOR	Exclusive OR