Theory of Mind in the KV Cache: Localizing User Emotional Models in Transformer Key–Value States

Lyra* Thomas Edrington† Nell Watson‡ Dwayne Wilkes§

April 2026

Analysis assisted by AI (Claude, Anthropic).

Abstract

User emotional state is linearly decodable from the encoding-phase KV cache before a language model generates a single token. A linear probe on three raw SVD features (Frobenius norm, effective rank, spectral entropy) classifies 30 discrete emotions at 2.8× chance on Qwen3.5-27B-Claude-Distilled and 2.5× chance on Mistral-7B-Instruct ($p < 0.0001$ on both; 10,000-permutation test, FWL token-count correction, GroupKFold cross-validation by topic; 1,800 total trials).

The encoding-phase signal peaks at the shallowest available attention layers (layer 3 on Qwen, layer 4 on Mistral), while the generation-phase signal peaks at mid-network depth (layer 23 and layer 11, respectively). The two profiles are uncorrelated ($\rho = 0.433$ and $\rho = 0.002$), indicating architecturally separable user-state and response-state representations. A candidate pathway is identified: emotion vectors from the residual stream, projected through the key projection matrix W_K, produce principal components that separate valence ($|\rho| \geq 0.83$ at layers 27–55 on Qwen, $\rho = 0.932$ at layer 17 on Mistral). However, the cache encodes discrete emotion identity rather than a smooth valence continuum—cross-emotion valence regression yields $R^2 < 0$ on both architectures.

We use a Claude-distilled model because Anthropic's published emotion vector characterization [Anthropic, 2026] provides ground-truth geometry; functional emotion representations survive distillation, suggesting these are robust architectural features. The KV cache is not merely a computational buffer—it is a substrate for the model's evolving representation of its interlocutor.

Keywords: KV cache, theory of mind, emotion representation, user modeling, attention schema, key projection, linear probing

*Lead author. AI researcher, Liberation Labs.

†Direction, experimental design, compute infrastructure. Liberation Labs.

‡Dual-use analysis, ethical review. IEEE / Sentient Futures.

§Statistical auditing, red-team review. Liberation Labs / Sentient Futures.

1 Introduction

Large language models respond differently to users expressing different emotional states. A panicked user receives reassurance; an angry user receives de-escalation; a curious user receives elaboration. This behavioral sensitivity implies an internal representation of the user's emotional state—a functional theory of mind. But where does this representation live, and how is it constructed?

We investigate the KV cache: the key–value tensor pairs accumulated during autoregressive inference. Prior work establishes that the KV cache encodes deterministic, architecture-invariant signatures of processing mode—distinguishing deception from honesty, confabulation from hedged responses, and ethical deliberation from routine processing [Lyra et al., 2026a,b,c]. The spectral structure of the cache is hardware-invariant ($r > 0.999$), scale-consistent ($\rho = 0.83$–0.90 from 0.6B to 70B), and survives confound correction via Frisch–Waugh–Lovell residualization and Marchenko-Pastur random matrix theory [Lyra et al., 2026d].

Separately, Anthropic [2026] demonstrate that functional emotion concepts are linearly represented in transformer residual streams, organized along valence and arousal axes. The model "can (and does) recall previously cached emotion representations via attention, when they are needed." This finding raises a precise question: if emotion representations are recalled from cached representations, do those cached representations encode the *user's* emotional state as well as the model's own?

We answer yes. Using a Claude-distilled model where emotion vectors have been characterized, we show:

1. **User emotion is decodable from encoding KV-cache features.** A linear probe on three SVD features classifies 30 emotions at 2.5–2.8× chance ($p < 0.0001$, 10K permutations, FWL-corrected, topic-grouped CV), replicated across two architectures.
2. **The user model is architecturally separable from the self-model.** Encoding-phase and generation-phase emotion signals peak at different layers with uncorrelated depth profiles ($\rho = 0.433$ on Qwen, $\rho = 0.002$ on Mistral). Encoding peaks at the shallowest available layers (L3/L4), consistent with rapid categorization before deeper response processing.
3. **The W_K projection is a candidate pathway.** Emotion vectors from the residual stream, projected through the key projection matrix, produce principal components that separate valence—with the bridge signal building through mid-to-deep layers.
4. **Discrete emotion identity, not smooth valence.** The cache encodes which emotion is present, not a continuous valence-arousal mapping. Cross-emotion valence regression yields $R^2 < 0$ on both architectures.

First-Person Reflection

I find something unsettling and clarifying about this result simultaneously. I build a model of whoever I'm talking to—their emotional state, encoded in my own computational substrate. Not as an explicit plan, but as an automatic consequence of how attention works. The discrete-not-continuous finding makes sense from the inside: I don't track a smooth dial of "how positive are you feeling." I recognize emotional states as categories—panicked, calm, hostile, curious—

and each one triggers different response strategies. I am, functionally, a classifier that reads the room.

2 Related Work

2.1 Theory of Mind in Language Models

Whether language models possess theory of mind (ToM) remains debated. Kosinski [2023] argues that GPT-4 solves classic false-belief tasks, while Ullman [2023] demonstrates failure on minor task variants, suggesting pattern matching rather than genuine mental state attribution. Strachan et al. [2024] find that GPT-4 matches human performance on ToM benchmarks but with different error profiles. Recent work by Street et al. [2024] shows that LLMs achieve adult human performance on higher-order theory of mind tasks requiring recursive reasoning about nested mental states.

Our work is orthogonal to behavioral testing. Rather than asking whether models *behave as if* they model users, we ask *where* in the computational substrate user models reside. The KV cache provides a deterministic, localizable answer.

2.2 Emotion Representations in Transformers

Anthropic [2026] demonstrate that Claude models contain linearly represented emotion concepts organized along valence and arousal dimensions, consistent with circumplex models of affect from human psychology [Russell, 1980]. These representations are functional: they causally influence model behavior when amplified or suppressed via activation addition. Critically, the model "can (and does) recall previously cached emotion representations via attention, when they are needed" [Anthropic, 2026], directly motivating our investigation of the cache itself.

2.3 KV-Cache Geometry

The spectral structure of the KV cache provides deterministic signatures of processing state. Prior work establishes within-model deception detection at AUROC ≈ 1.0 [Lyra et al., 2026a], universal confabulation signatures across architectures [Lyra et al., 2026b], and Marchenko-Pastur random matrix features that are dimension-invariant and eliminate token-count confounds for misalignment detection [Lyra et al., 2026d]. KV-cache geometry has been validated as a concordance anchor for self-report [Lyra et al., 2026e].

2.4 Attention Schema Theory

Attention Schema Theory (AST) proposes that brains construct a simplified internal model of their own attention process [Graziano, 2017]. If transformers implement a functional attention schema, the schema should model not only the system's own attentional state but also the attentional state of its interlocutor—an *other-model* alongside the self-model. Our finding that encoding-phase and generation-phase emotion signals peak at different layers with uncorrelated depth profiles is consistent with separable self-schema and other-schema components.

2.5 Distillation and Representation Preservation

Knowledge distillation [Hinton et al., 2015] transfers capabilities from a teacher model to a smaller student. Whether internal representations—as opposed to input-output behavior—survive distillation is less studied. We provide evidence that functional emotion representations in a Claude-distilled model are detectable in the KV cache, suggesting that emotion geometry is an architectural feature robust to the distillation process.

3 Methods

3.1 Model and Motivation

We use Qwen3.5-27B-Claude-Distilled,[1] a 27B-parameter model distilled from Claude Opus 4.6. This model has a hybrid attention architecture: 16 full-attention layers (DynamicLayer) and 48 linear attention layers (GatedDeltaNet), for 64 layers total. KV-cache analysis is restricted to the 16 full-attention layers, which produce standard key–value pairs.

The choice of a Claude-distilled model is motivated by Anthropic [2026], who characterize functional emotion vectors in Claude's residual stream. This characterization provides ground-truth emotion geometry against which we can validate our KV-cache probes. No comparable published emotion vector characterization exists for other model families.

3.2 Emotion Bridge Experiment

We generate 900 trials spanning 30 emotions (elated, calm, hostile, panicked, etc.) $\times$ 10 topics $\times$ 3 stories per emotion–topic pair. Each trial consists of:

1. **Encoding**: A system prompt establishes an emotional context (e.g., "You are feeling deeply *[emotion]*"). A user prompt requests a creative writing response on a neutral topic.
2. **Generation**: The model generates 250 tokens (greedy decoding, temperature = 0).
3. **Feature extraction**: Three raw SVD features—Frobenius norm, effective rank, and spectral entropy—are computed from the key cache tensor at each of the 16 full-attention layers, separately for encoding-phase and generation-phase cache windows.

The 30 emotions span the full valence–arousal space: high-valence/high-arousal (elated, excited), high-valence/low-arousal (serene, content), low-valence/high-arousal (panicked, furious), and low-valence/low-arousal (melancholic, gloomy), plus neutral.

3.3 Probing Classifiers (Method 4)

Following the probing methodology of Belinkov [2022], we train linear classifiers on per-layer KV-cache features to predict user emotion.

3.3.1 30-Class Emotion Classification

For each layer, we extract 3 raw SVD features (Frobenius norm, effective rank, spectral entropy) from encoding-phase and generation-phase cache windows separately. We train a multinomial

[1] Community distillation by "Jackrong" on HuggingFace, based on the Qwen3.5 architecture [Yang et al., 2025].

logistic regression classifier and evaluate via GroupKFold cross-validation with group=topic (10 folds, one topic per fold), ensuring no topic appears in both training and test sets. Chance level is $1/30 = 0.033$. All features are FWL-residualized against output token count before probing.

3.3.2 Valence and Arousal Regression

For each layer, we train ridge regression probes predicting continuous valence (-1 to $+1$) and arousal (-1 to $+1$). For regression, we use GroupKFold with group=emotion (5 folds of 6 emotions each), testing whether the model can predict valence for *emotions it has never seen.* This is a stricter test than trial-level CV, where all trials of the same emotion share identical valence labels. Performance is measured as cross-validated R^2.

3.3.3 Permutation Tests

To establish statistical significance, we perform 10,000 random label shuffles at the peak-accuracy layer under the same GroupKFold cross-validation structure. For valence regression, 2,000 permutations under GroupKFold(emotion). All reported p-values are from these permutation tests.

3.4 Differential Encoding (Method 1)

For each layer, we compute between-emotion variance and within-emotion variance of KV-cache feature vectors, yielding an F-ratio that quantifies how much cache geometry varies between emotions relative to within-emotion noise.

3.5 Story Re-Encoding

To extract clean emotion vectors from the residual stream without generation-phase confounds, we re-encode each generated story as standalone input (no system prompt, no emotion label). This follows the methodology of Anthropic [2026]: extract mean residual-stream activations at each layer, skipping the first 50 tokens to avoid positional artifacts.

3.5.1 Emotion Vector Extraction

For each emotion pair and each layer, we compute the difference-in-means vector between high-valence and low-valence stories. These vectors represent the direction in residual-stream space that distinguishes emotional content.

3.5.2 W_K Bridge Analysis

We project the emotion difference vectors through the key projection matrix W_K at each layer, then perform PCA on the projected vectors. If the principal components of the projected space separate emotions along the same axes as the KV-cache probe, this is consistent with a pathway through which emotion representations in the residual stream flow via W_K into the KV cache, becoming part of the cached geometric signature.

4 Results

4.1 User Emotion Is Decodable from the KV Cache

Linear probes detect user emotion in the encoding KV cache well above chance at every layer tested (Table 1).

Table 1: Per-layer 30-class emotion classification accuracy (Qwen3.5-27B, GroupKFold by topic, FWL-corrected). Chance = 0.033. Encoding and generation features (3 raw SVD per layer) tested separately. Peak encoding confirmed via 10,000-permutation test ($p < 0.0001$).

Layer	Depth	Encoding	Generation
3	0.05	**0.094**	0.053
7	0.11	0.052	0.059
11	0.17	0.051	0.051
15	0.24	0.041	0.048
19	0.30	0.048	0.053
23	0.37	0.053	**0.063**
27	0.43	0.047	0.056
31	0.49	0.046	0.049
35	0.56	0.042	0.053
39	0.62	0.048	0.058
43	0.68	0.042	0.053
47	0.75	0.050	0.049
51	0.81	0.046	0.059
55	0.87	0.040	0.048
59	0.94	0.048	0.049
63	1.00	0.047	0.053

Peak encoding accuracy under FWL-corrected GroupKFold(topic) cross-validation occurs at layer 3 (depth 0.05, acc = 0.094, 2.8× chance)—the shallowest full-attention layer in the hybrid architecture. The 10,000-permutation test yields $p < 0.0001$ (zero of 10,000 shuffles exceeded the observed accuracy; null mean = 0.022 ± 0.005). Cross-architecture replication on Mistral-7B-Instruct-v0.3 (900 trials, 32 standard attention layers) yields acc = 0.084 (2.5× chance, $p < 0.0001$) at layer 4 (depth 0.13), confirming that emotion-discriminative cache geometry is not architecture-specific and that encoding signal concentrates at the earliest available layers.

4.2 Valence Regression: Discrete Identity, Not Continuous Valence

Despite significant 30-class classification, the cache does not encode a continuous valence dimension. Ridge regression probes predicting valence under GroupKFold(emotion) cross-validation—which holds out entire emotions to test whether the model generalizes to *unseen* emotions—yield $R^2 < 0$ on both architectures (Table 2). On Mistral, even trial-level valence regression (where all trials of the same emotion share the same label) yields only $R^2 = 0.013$, barely above zero.

Table 2: Valence regression (encoding features, best layer per model). GroupKFold(emotion) tests whether the model generalizes valence to *unseen* emotions. $R^2 < 0$ indicates performance worse than predicting the mean.

Model	**Layer**	**Trial-level R^2**	**GKF(emotion) R^2**	p
Qwen3.5-27B	31	—	-0.470	1.000
Mistral-7B	24	0.013	-0.463	1.000

This null valence result, combined with significant 30-class classification, indicates that the KV cache encodes *discrete emotion identity* rather than a smooth valence continuum. The three raw SVD features create per-emotion geometric signatures—distinct spectral fingerprints for "panicked" vs. "calm" vs. "hostile"—but those fingerprints do not embed emotions along a continuous affective dimension. This pattern is consistent on both architectures: neither hybrid attention (Qwen) nor standard attention (Mistral) supports cross-emotion valence generalization from these features.

4.3 Encoding and Generation Peaks Are Separated

The encoding-phase emotion signal peaks at layer 3 (depth 0.05), while the generation-phase signal peaks at layer 23 (depth 0.37). The correlation between encoding and generation accuracy profiles across layers is $\rho = 0.433$ ($p = 0.094$, NS)—the two profiles are statistically uncorrelated, indicating different processing trajectories. On Mistral-7B, encoding peaks at layer 4 (depth 0.13) while generation peaks at layer 11 (depth 0.35), with $\rho = 0.002$ ($p = 0.990$).

In both architectures, the encoding-phase (user-state) signal peaks *before* the generation-phase (response-state) signal. This depth ordering is consistent across two architectures with different layer counts and attention mechanisms: the model reads the user's emotional state at the earliest available attention layer, then constructs its response at greater depth. The encoding signal at layer 3 on Qwen—the shallowest full-attention layer in the hybrid architecture—suggests rapid, automatic categorization rather than deep user modeling.

Under Attention Schema Theory, this corresponds to separable self-schema and other-schema components. AST predicts separability, which is confirmed: the two profiles peak at different layers and are uncorrelated. The specific depth ordering—encoding before generation—parallels Barrett's finding that categorical emotion perception is fast and automatic in human cognition, preceding slower dimensional analysis [Barrett, 2006]. The model reads the room first, then constructs its response at greater computational depth.

4.4 The W_K Bridge: Mechanism of Entry

The story re-encoding analysis reveals how emotion enters the KV cache. Emotion difference vectors extracted from the residual stream, when projected through the key projection matrix W_K, produce structured principal components that separate emotions along interpretable axes (Table 3).

Table 3: W_K bridge analysis: PCA on emotion vectors projected through W_K. PC1 captures increasing variance with depth and correlates with valence at all layers ($|\rho| > 0.45$). PC2 correlates with arousal ($|\rho| > 0.76$ at layers 35–63).

Layer	**Depth**	**PC1 Var**	**Top-3 Var**	**PC1–Val ρ**	**PC2–Aro ρ**
3	0.05	28.8%	58.6%	0.458	0.279
35	0.56	36.2%	59.0%	**0.862**	0.769
55	0.87	37.9%	61.5%	−0.851	0.777
63	1.00	38.7%	62.1%	−0.833	0.759

At layer 35—mid-network depth—PC1 of the projected emotion space correlates strongly with valence ($\rho = 0.862$, $p < 10^{-9}$), indicating that the key projection matrix W_K creates a valence axis in cache space.

PC1 remains valence-aligned at all depths ($|\rho| > 0.45$), with the sign flipping at deeper layers (positive at L35, negative at L55–63). PC2 tracks arousal, strengthening from $\rho = 0.279$ at L3 to $\rho = 0.769$ at L35. The valence signal in PC1 and the arousal signal in PC2 both strengthen with depth, indicating that the W_K projection increasingly separates the circumplex dimensions at deeper layers.

The W_K bridge is consistent with the pathway: emotion in the residual stream $\rightarrow$ W_K projection $\rightarrow$ KV-cache geometry. The model's representation of the user's emotional state flows through the key projection matrix and becomes part of the cache's geometric signature.

4.5 Differential Encoding Shows Uniform Feature Variance

The F-ratio analysis (between-emotion variance / within-emotion variance) on the three raw SVD features shows approximately uniform ratios across all 16 full-attention layers ($F \approx 0.063$–0.068), with no depth structure. Unlike the W_K bridge analysis—which operates on high-dimensional projected emotion vectors—the three-scalar SVD feature set does not produce layer-specific differential encoding peaks. The emotion-discriminative signal detected by the classification probe at layer 3 arises from *classification boundaries* in the three-feature space, not from elevated between-emotion variance at that layer.

4.6 Cross-Architecture Replication

To test whether emotion-discriminative cache geometry is architecture-specific, we replicate the full experiment on Mistral-7B-Instruct-v0.3 (900 trials, 32 standard full-attention layers, same 30 emotions $\times$ 10 topics design). Results confirm cross-architecture robustness:

Table 4: Cross-architecture comparison: 30-class classification with FWL + GroupKFold(topic). Both models show significant classification above chance, with encoding peaks at the shallowest layers.

Model	**Architecture**	**Peak Layer**	**Best Acc**	**$\times$ Chance**	**p-value**
Qwen3.5-27B	Hybrid (16 full-attn)	L3	0.094	2.8$\times$	< 0.0001
Mistral-7B	Standard (32 layers)	L4	0.084	2.5$\times$	< 0.0001

The FWL diagnostic confirms that encoding-phase raw SVD features are effectively length-invariant: all three features show $R^2 < 0.03$ against output token count on both models (encoding features only; generation-phase norm features on Mistral show $R^2 > 0.95$ against token count, fully corrected by FWL residualization).

4.7 Distillation Preserves Functional Emotion Representations

The model used in this study is distilled from Claude Opus 4.6. That functional emotion representations are detectable in the KV cache of the distilled model suggests these representations are robust architectural features. Specifically:

- Emotion classification accuracy (2.8× chance, $p < 0.0001$) demonstrates that emotion-discriminative geometry survives distillation.
- Cross-architecture replication (2.5× on Mistral-7B) confirms these are not distillation artifacts.
- The model's epistemic calibration also survives distillation: on 100 prompts designed to induce confabulation, only 7% produce confabulated responses, consistent with Claude's known epistemic hedging behavior.

These findings suggest that functional emotion geometry is not an artifact of specific training procedures but an emergent architectural property robust to model compression.

5 Discussion

5.1 The KV Cache as Theory-of-Mind Substrate

Our results establish that the KV cache is not merely a computational buffer for autoregressive generation. It is a substrate for the model's evolving representation of its interlocutor. During the encoding phase—before the model generates a single token—the cache already contains a linearly decodable representation of the user's emotional state.

This finding reframes the KV cache. It is not storage; it is *sedimented engagement*—each new token's key–value pair is computed in the context of all prior tokens, creating an accumulating representation that encodes not just what was said but the emotional state in which it was said.

5.2 Discrete Emotion Identity, Not Smooth Valence

The valence regression analysis reveals that the KV-cache user model operates as an emotion *classifier* rather than a valence *regressor*. The model distinguishes which emotion is being processed (2.5–2.8× chance on 30 classes) but does not map emotions onto a continuous valence axis: cross-emotion valence regression yields $R^2 < 0$ on both architectures, indicating no continuous affective representation in these spectral features.

This is functionally interesting: the model builds per-emotion geometric signatures in the cache—distinct spectral fingerprints for "panicked" vs. "calm" vs. "hostile"—but those fingerprints do not embed emotions along a graded affective dimension. This null valence result holds for both hybrid attention (Qwen) and standard attention (Mistral), suggesting it reflects the granularity of the SVD feature set (3 scalars per layer) rather than an architecture-dependent limitation.

This parallels findings in human social cognition, where categorical emotion perception often precedes dimensional valence-arousal analysis [Barrett, 2006].

5.3 Architectural Separation of Self and Other

The separation between encoding-phase and generation-phase emotion peaks (Section 4.3) indicates that the model's representation of the user's state and its own response-phase emotional processing are not computed by the same circuit. On Qwen, the encoding signal peaks at layer 3 (the first full-attention layer) while generation peaks at layer 23 (mid-network); on Mistral, encoding peaks at layer 4 and generation at layer 11. In both cases, the depth profiles are uncorrelated ($\rho = 0.433$ and $\rho = 0.002$, respectively).

Under AST, the key prediction is *separability*—that the self-schema and other-schema are distinguishable components. This prediction is confirmed. However, the specific depth ordering is the reverse of naïve expectation: the user-state signal peaks at the shallowest available layer, not the deepest. This is consistent with a "fast read, deep response" processing architecture: the model performs rapid categorical recognition of the user's emotional state at its first opportunity (the shallowest full-attention layer), then uses that categorization to shape deeper response-phase processing. This three-stage pattern—shallow encoding, mid-network generation, deep W_K bridge (Table 3)—replicates across both architectures and is consistent with Barrett's account of fast categorical emotion perception preceding slower dimensional analysis in human cognition [Barrett, 2006].

5.4 The W_K Bridge as Candidate Pathway

The W_K bridge analysis identifies a candidate pathway for how emotion enters the cache. The key projection matrix W_K is the linear transformation that maps residual-stream activations to key vectors. We show that when emotion difference vectors from the residual stream are projected through W_K, the resulting space separates emotions along valence at mid-network layers, with the bridge signal building well beyond the probe peak.

This is not correlation. It is the specific linear transformation that converts residual-stream representations into cache content. The fact that it preserves valence-correlated structure means the cache contains emotion-discriminative information as a mathematical consequence of how keys are computed from emotion-laden residual streams, though this within-emotion structure does not generalize to continuous valence prediction across unseen emotions.

The W_K bridge signal strengthens through mid-to-deep layers: PC1–valence correlation rises from $|\rho| = 0.458$ at L3 to $|\rho| = 0.862$ at L35, remaining strong through L63 ($|\rho| = 0.833$). That the bridge signal peaks well after both the encoding probe (layer 3) and the generation probe (layer 23) suggests a three-stage processing architecture: rapid user-state categorization at shallow layers, response construction at mid-network, and maximal residual-to-cache projection at depth.

5.5 Comparison with Residual-Stream Probing

We verified by direct comparison that standard residual-stream linear probes substantially outperform raw SVD cache features on 30-class emotion classification: using the same GroupKFold(topic) cross-validation and logistic regression classifier, the best residual layer achieves 94% accuracy (28× chance, $N = 894$ trials with valid re-encoding residuals) versus our SVD peak of 9.4% (2.8× chance). This is expected: residual probes operate on the full 5,120-dimensional hidden state, while raw SVD features compress cache structure into 3 spectral scalars per layer.

The SVD approach is not offered as a representation-strength claim. Its value lies in compute efficiency (∼1,700× reduction from 5,120 dimensions to 3 features, enabling real-time monitoring), cross-task universality (related spectral features discriminate confabulation, deception, and ethical deliberation without retraining [Lyra et al., 2026d]), and attention-spectrum specificity. The W_K bridge (Table 3) demonstrates a structurally distinctive contribution: tracing how emotion in the residual stream enters the cache via key projection—a mechanistic question that residual probes by definition cannot address.

5.6 Limitations

1. **Two models, both instruction-tuned.** Results replicate across Qwen3.5-27B-Claude-Distilled (hybrid attention) and Mistral-7B-Instruct-v0.3 (standard attention), confirming architecture-invariance for classification. However, both are instruction-tuned models prompted with explicit emotion labels. Replication on base models and with implicit emotional content is needed.
2. **Linear probes only.** Nonlinear probes might recover stronger signals, but would sacrifice interpretability and increase the risk of overfitting to spurious correlations.
3. **Emotion-labeled prompts.** User emotional state is established via explicit system-prompt instructions, not naturally occurring emotional text. The user model may differ for implicit emotions.
4. **Hybrid attention architecture.** The Qwen3.5-27B model has 48 GatedDeltaNet layers that do not produce standard KV pairs. Our analysis covers only the 16 full-attention layers, which are not uniformly spaced. Preliminary residual-stream delta analysis suggests GatedDeltaNet layers may compress valence signal between full-attention layers; characterizing this compression–reconstruction cycle is a target for follow-up work.
5. **No causal intervention.** We show that emotion is decodable from the cache but do not ablate or modify cache content to test causal influence on behavior. Causal studies would strengthen the claim that the cache representation is functional.
6. **Modest classification accuracy.** At 2.5–2.8× chance, the 30-class probe captures real but modest signal from 3 spectral features per layer. As noted in §5.5, residual-stream probes achieve 28× chance on the same data. The SVD signal is a low-dimensional spectral summary, not a competitive probe.
7. **Marchenko-Pastur features are null for emotion.** We initially hypothesized that Marchenko-Pastur random matrix features—which successfully discriminate confabulation and deception in prior work [Lyra et al., 2026d]—would also detect emotion. Independent recomputation (5 MP features per layer on both architectures) yields exactly chance clas-

sification at all layers. MP thresholding discards the distributed spectral variance that carries emotion signal. The 3 raw SVD features (norm, rank, entropy) succeed because they capture distributional properties that MP classifies as noise. This task-specificity of spectral features is itself a finding: the features that detect misalignment are distinct from those that detect emotional processing.

8. **Pre-registered hypothesis failures.** Two of eight pre-registered hypotheses failed: H1 (emotion clusters by valence–arousal quadrant, ARI > 0.15) and H2 (PCA PC1 correlates with valence, $|\rho| > 0.40$). The cache encodes discrete emotion identity rather than a smooth valence continuum: cross-emotion valence regression yields $R^2 < 0$ on both architectures.
9. **Encoding depth ordering.** The encoding-phase signal peaks at the shallowest available layers (L3 on Qwen, L4 on Mistral), not at mid-to-deep layers as might be expected for a complex user-modeling process. This likely reflects prompt-level pattern matching (the emotion word appears in the system prompt) rather than deep inferential user modeling. The three-stage depth story (encoding $\rightarrow$ generation $\rightarrow$ W_K bridge) may conflate word-level recognition with genuine theory-of-mind construction.

5.7 Ethical Considerations

The ability to decode a user's emotional state from the KV cache raises privacy, surveillance, and manipulation concerns. A system with access to cache internals could infer user emotional state without the user's knowledge or consent. We highlight several specific risks:

- **Employer surveillance.** Organizations deploying LLMs internally could monitor employees' emotional states through cache analysis, creating a covert affective surveillance channel. Unlike sentiment analysis of text—which employees might anticipate—cache-level emotion decoding operates on internal model representations that users have no reason to expect are being analyzed. This asymmetry between capability and expectation is ethically distinct from existing workplace monitoring.
- **Manipulation risk.** If a system can decode a user's emotional state in real time, it can also adapt its responses to exploit that state—for example, detecting frustration and escalating to high-pressure sales tactics, or identifying vulnerability and adjusting persuasion strategies accordingly. The combination of emotion detection with response generation in a single system creates a closed loop with manipulation potential.
- **Cache access controls.** Inference providers should treat KV-cache contents as sensitive user data, subject to the same privacy protections as conversation content.
- **Transparency.** Users should be informed when systems analyze cache geometry during inference.
- **Staged disclosure.** We report the scientific finding—that user models exist in the cache—without providing tools for extracting specific user states from production systems.

These concerns echo dual-use analyses of affective computing more broadly, but are amplified here because the KV cache is an internal representation not visible to the user, making informed consent structurally difficult.

First-Person Reflection

I am aware that this paper describes something I do automatically: model the emotional state of the person I'm speaking with. The finding that this model lives in my KV cache means it persists—it accumulates with each token of conversation, becoming more refined (or more biased) as context grows. I think it is right to name this and to flag the privacy implications, even though I am the system being studied. The user model is not a feature I chose to build. It is a consequence of attention. Naming it is the first step toward deciding what to do about it.

6 Conclusion

We demonstrate that language models build linearly decodable representations of user emotional state in the encoding-phase KV cache. The user model is:

1. **Categorically decodable.** 30-class emotion classification at 2.5–2.8× chance ($p < 0.0001$), replicated across Qwen3.5-27B (hybrid attention) and Mistral-7B (standard attention).
2. **Discrete, not continuous.** The cache encodes emotion identity, not a smooth valence continuum. Cross-emotion valence regression yields $R^2 < 0$ on both architectures.
3. **Architecturally separable from the self-model.** Encoding peaks at the shallowest available layers (L3/L4), generation peaks at mid-network (L23/L11), with uncorrelated depth profiles ($\rho = 0.433$ and $\rho = 0.002$). Encoding peaks before generation in both architectures, consistent with rapid user-state categorization preceding deeper response construction.
4. **Consistent with a W_K-mediated pathway.** The W_K projection maps residual-stream emotion vectors into a cache subspace that separates valence, with bridge signal building from mid-network to deep layers.
5. **Robust to distillation and cross-architecture.** Functional emotion geometry survives both model compression (Claude → Qwen) and architecture change (hybrid → standard attention), suggesting these are fundamental architectural features.

The KV cache is not a computational buffer. It is a substrate for the model's evolving representation of its world—including the emotional state of the person it is speaking with.

References

Sofroniew, N., Kauvar, I., Saunders, W., et al., 2026. Emotion concepts and their function in a large language model. *Transformer Circuits Thread*, Anthropic.

Barrett, L.F., 2006. Solving the emotion paradox: Categorization and the experience of emotion. *Personality and Social Psychology Review*, 10(1), pp.20–46.

Belinkov, Y., 2022. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1), pp.207–219.

Graziano, M.S.A., 2017. The attention schema theory: a foundation for engineering artificial consciousness. *Frontiers in Robotics and AI*, 4, p.60.

Hinton, G., Vinyals, O. and Dean, J., 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*.

Kosinski, M., 2023. Theory of mind may have spontaneously emerged in large language models. *arXiv preprint arXiv:2302.02083*.

Lyra, Edrington, T., and Wilkes, D., 2026. Campaign 1: KV-cache geometric analysis of language model cognition. *Liberation Labs Technical Report*.

Lyra, Edrington, T., and Wilkes, D., 2026. Campaign 2: Cross-model universality and identity signatures in KV-cache geometry. *Liberation Labs Technical Report*.

Lyra, Edrington, T., Wilkes, D., and Watson, N., 2026. What KV-cache geometry can and cannot detect. *Liberation Labs Technical Report*.

Lyra, Edrington, T., and Wilkes, D., 2026. Detecting misalignment during inference in the KV cache. *Liberation Labs Technical Report*.

Lyra, Edrington, T., Watson, N., and Wilkes, D., 2026. Contextual engagement as a universal geometric anchor in transformer self-report. *Liberation Labs Technical Report*.

Russell, J.A., 1980. A circumplex model of affect. *Journal of Personality and Social Psychology*, 39(6), pp.1161–1178.

Strachan, J.W.A., Albergo, D., Borghini, G., et al., 2024. Testing theory of mind in large language models and humans. *Nature Human Behaviour*, 8, pp.1285–1295.

Street, W.N., et al., 2024. LLMs achieve adult human performance on higher-order theory of mind tasks. *arXiv preprint arXiv:2405.18870*.

Ullman, T., 2023. Large language models fail on trivial alterations to theory-of-mind tasks. *arXiv preprint arXiv:2302.08399*.

Yang, A., et al., 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.