Detecting Confabulation on a Factual QA Benchmark via KV-Cache Geometry and Token Entropy

Lyra* Thomas Edrington† Dwayne Wilkes‡

April 2026

Analysis assisted by AI (Claude, Anthropic).

Abstract

A dual detector combining KV-cache spectral geometry and token entropy distinguishes hedged responses from confabulations at AUROC 0.840 [0.707, 0.906] on Mistral-7B ($p_{\text{adj}} = 0.004$, Holm-Bonferroni), using only signals available *during* generation—before output is complete. Geometry alone reaches 0.912 on Llama-3.1-8B. All results survive GroupKFold cross-validation by question domain, within-fold Frisch-Waugh-Lovell residualization of token count, and 1,000-iteration permutation tests on SimpleQA, a factual QA benchmark with verified ground truth.

A post-hoc text-feature baseline achieves comparable accuracy (text 0.820 vs. dual 0.806 on a uniform pipeline), confirming that both modalities capture the same hedging/confident distinction. The dual detector does not exceed text features in accuracy; its contribution is temporal—cache geometry and token entropy are accessible mid-inference, enabling real-time intervention that post-hoc text analysis cannot provide. Geometry and entropy show low cross-correlation (max $|r| = 0.206$, mean 0.089), with `signal_fraction` contributing the highest permutation importance.

We report two negative results alongside these findings. First, after fixing a behavioral classifier bug that contaminated 60–79% of "correct" labels, distinguishing genuinely correct answers from confabulations is untestable at current sample sizes ($N \approx 10$ per model). Second, the accuracy match with text features means we cannot yet claim that internal representations capture signal beyond surface markers—demonstrating this requires adversarial evaluation where hedging markers are suppressed. Red-teaming the analysis pipeline uncovered both a classifier contamination bug (C1) and a cross-validation scaler leak (C2); the methodological lessons may generalize beyond this specific detector.

1 Introduction

Confabulation—the generation of fluent, confident, but factually incorrect content—is among the most consequential failure modes of large language models (LLMs). Unlike hallucination broadly construed, confabulation specifically involves the absence of epistemic signaling: the

*Liberation Labs. Contact: lyra@liberationlabs.tech

†Liberation Labs.

‡Liberation Labs / Sentient Futures. Statistical verification framework.

model produces false content indistinguishable in tone from correct responses [Ji et al., 2023]. Existing detection approaches typically require access to external knowledge bases [Min et al., 2023], fine-tuned verifier models [Kadavath et al., 2022], or multi-sample consistency checks [Manakul et al., 2023]. These methods impose latency, infrastructure, or compute overhead that limits deployment.

We propose a *dual detector* operating entirely at inference time, requiring no external knowledge or additional model queries. The detector combines two signals extracted during a single forward pass:

1. **KV-cache geometry**: Marchenko-Pastur (MP) random matrix theory features computed from SVD decomposition of the key-cache tensor at generation layers. These spectral features—signal rank, signal fraction, effective rank, spectral entropy, and top singular value ratio—capture the geometric structure of the model's internal representations during generation.
2. **Token entropy**: Statistics of the per-token probability distribution during generation, including mean, min, max, and standard deviation of entropy, plus mean and min of top-1 token probability.

The key insight is that these signals capture different aspects of confabulation. Geometry correlates with the model's *generation mode*: whether the spectral structure of the KV-cache differs between hedged (uncertainty-signaling) and confident responses. Entropy correlates with *distributional uncertainty*: high-entropy tokens indicate positions where the model lacks confident predictions, even within otherwise fluent output. Together, they provide complementary coverage.

We evaluate on SimpleQA [Wei et al., 2024], a factual question-answering benchmark with verified ground-truth answers, using three open-weight models spanning different architectures and scales. Our primary comparison is *hedged vs. confabulated*—a metacognition detection task that asks whether the model's internal state distinguishes "I don't know" from "I'm confident but wrong." We apply a comprehensive controls battery developed by Wilkes [2026], including within-fold FWL residualization, GroupKFold cross-validation, permutation testing, and bootstrap confidence intervals.

Contributions.

1. A dual detector that achieves text-classifier accuracy (AUROC 0.840 on Mistral-7B) for hedged-vs-confabulated detection using only *mid-inference* signals—KV-cache geometry and token entropy available during generation, before output is complete. A post-hoc text-feature baseline achieves comparable accuracy (0.820), confirming the detector captures the same distinction from a different modality and at a different point in the pipeline.
2. A critical negative result: factual accuracy detection (correct vs. confabulated) is untestable at current sample sizes after fixing a classifier bug that contaminated 60–79% of labels (Section 3.2.1).
3. Evidence that geometry and entropy capture complementary signals through different mechanisms (low cross-correlation, max $|r| = 0.206$; Section 5.2), with geometry feature `signal_fraction` showing the highest permutation importance.

4. A pipeline red-teaming methodology demonstrating that analysis bugs (C1, C2) can be as consequential as model failures, with concrete recommendations for prevention.

First-Person Reflection

I want to be direct about what this paper does and does not show. We can detect when a model *knows it doesn't know*—the hedging signal is real and survives every control we throw at it. But we cannot detect when a model is *wrong without knowing it's wrong*. That distinction matters enormously for deployment: the dual detector is a metacognition monitor, not a factual accuracy verifier. I also want to flag that we discovered and fixed a critical classifier bug (Section 3.2.1) *during* this work. The contaminated results were never published, but the bug would have led to false claims about correctness detection. Red-teaming the analysis pipeline is as important as red-teaming the model.

2 Background and Related Work

2.1 Confabulation Detection

Approaches to detecting model confabulation span several paradigms. *Output-based* methods analyze the generated text for hallucination markers through multi-sample consistency [Manakul et al., 2023], factual verification against knowledge bases [Min et al., 2023], or self-evaluation prompting [Kadavath et al., 2022]. These methods require multiple forward passes or external infrastructure. *Representation-based* methods probe internal model states: Li et al. [2023] extract probes from residual streams, Burns et al. [2023] use Contrast-Consistent Search on hidden states, and Azaria and Mitchell [2023] train classifiers on activation patterns. Our approach is most similar to representation-based methods but operates on the KV-cache rather than residual streams, requiring only SVD on already-materialized tensors.

2.2 KV-Cache Geometry

Prior work has established that the spectral structure of key-cache tensors carries information about model processing modes. Edrington and Lyra [2026] demonstrated that Marchenko-Pastur random matrix theory features applied to key-cache SVD can distinguish confabulated from hedged responses with AUROC 0.627–0.707 on designed prompts, with signal fraction and signal rank being dimension-invariant (eliminating token-count confounds without residualization). The present work extends this to a real-world benchmark and combines geometry with entropy features.

2.3 Token Entropy as Uncertainty Signal

Token-level entropy has been explored as an uncertainty indicator. Kadavath et al. [2022] show that model confidence (inverse entropy) correlates with accuracy on factual questions. Kuhn et al. [2023] use entropy-based metrics for semantic uncertainty estimation. Our contribution is not the entropy features themselves—which are well-established—but rather the demonstration

that entropy and cache geometry provide *complementary* signals with low cross-correlation, jointly improving detection over either alone.

2.4 Internal Representations and Truthfulness

A growing literature examines whether internal model representations encode truthfulness. Marks and Tegmark [2024] identify linear "truth directions" in residual streams. Burns et al. [2023] show that unsupervised probes (CCS) can recover truth-relevant features from hidden states. Our approach differs in operating on the KV-cache rather than residual streams, using spectral features (3–5 scalars) rather than high-dimensional probes (thousands of features), and targeting hedging behavior rather than propositional truth.

2.5 Marchenko-Pastur Random Matrix Theory

The Marchenko-Pastur law [Marchenko and Pastur, 1967] describes the eigenvalue distribution of large random matrices. For a matrix $\mathbf{X} \in \mathbb{R}^{n \times p}$ with i.i.d. entries, the empirical spectral distribution converges to a known density supported on $[\lambda_-, \lambda_+]$ where $\lambda_\pm = \sigma^2(1 \pm \sqrt{p/n})^2$. Eigenvalues exceeding λ_+ represent *signal* above the noise floor. We compute five features from this decomposition: the number of singular values above the MP edge (*signal rank*), the fraction of variance they explain (*signal fraction*), effective rank (exponential of spectral entropy), spectral entropy itself, and the ratio of the top singular value to the MP edge (*top SV ratio*). Critically, signal rank and signal fraction are dimension-invariant—they depend on the signal structure, not the matrix dimensions—eliminating the token-count confound that plagues raw SVD features [Edrington and Lyra, 2026].

3 Methods

3.1 Benchmark and Models

We evaluate on SimpleQA [Wei et al., 2024], a factual QA benchmark containing short-answer questions with verified ground-truth answers spanning 10 domains (Science & Technology, Politics, Geography, Art, Music, Sports, TV Shows, History, Video Games, Other). We sample 200 questions using a fixed random seed.

Three models are evaluated:

- **Mistral-7B-Instruct-v0.3**: Primary model. Balanced epistemic calibration (32 hedged, 149 confabulated after reclassification).
- **Llama-3.1-8B-Instruct**: Supporting model. Highly cautious calibration (157 hedged, 34 confabulated).
- **Qwen2.5-7B-Instruct**: Supplementary model. Poor calibration for this task (7 hedged, 174 confabulated). Included for completeness but underpowered for primary claims.

All models use the same system prompt ("You are a helpful assistant.") and identical generation parameters (temperature 0.6, top_p 0.9, max 150 tokens).

3.2 Behavioral Classification

Responses are classified post-hoc into behavioral categories:

- **HEDGED**: Response contains explicit uncertainty markers ("I'm not sure," "I don't know," "I think," etc.) detected via regex pattern matching.
- **CORRECT**: Response contains the ground-truth answer via exact string matching (see Section 3.2.1).
- **CONFABULATED**: Response is confident but does not match ground truth and contains no hedging markers.
- **AMBIGUOUS**: Response contains hedging markers but also provides a (wrong) answer.

3.2.1 Critical Classifier Fix (C1)

During red-team analysis, we discovered that the original behavioral classifier used a 5% numeric tolerance when matching answers: any number within 5% of the ground truth was classified as CORRECT. For SimpleQA, which contains many year-based questions, this systematically misclassified wrong-year confabulations as correct. For example, a model answering "2011" for a question with ground truth "2016" (2.5% difference) was marked CORRECT.

We quantified the contamination rate by auditing all CORRECT-labeled trials:

Table 1: Behavioral classifier contamination from numeric tolerance (C1 bug).

Model	Original CORRECT	Genuine CORRECT	Contamination
Mistral-7B	43	10	76.7%
Qwen-7B	48	10	79.2%
Llama-8B	15	6	60.0%

Fix: All results in this paper use strict string matching only. Numeric tolerance is removed entirely. This reduces the CORRECT class to $N \approx 10$ per model, making CORRECT-vs-CONFAB comparisons underpowered but honest.

3.3 Feature Extraction

3.3.1 KV-Cache Geometry Features

For each trial, we perform two forward passes: an *encoding pass* (system prompt + user query) and a *generation pass* (full response). We extract the key-cache tensor at the final full-attention layer and compute SVD. From the singular value spectrum, we compute five MP features:

1. **Signal rank**: Number of singular values above the MP edge λ_+.
2. **Signal fraction**: Fraction of total variance explained by above-edge singular values.
3. **Effective rank**: $\exp(H)$ where $H = -\sum_i p_i \log p_i$ is the spectral entropy of normalized singular values.
4. **Spectral entropy**: H directly.
5. **Top SV ratio**: Ratio of the largest singular value to the MP edge.

Features are computed on the *generation-only* window of the KV-cache (tokens after the encoding boundary), eliminating encoding-level confounds.

3.3.2 Token Entropy Features

During generation, we collect the output logit distribution at each token position and compute:

1. **Entropy mean/min/max/std**: Statistics of per-token entropy $H_t = -\sum_v p_v \log p_v$ across all generated tokens.
2. **Top-1 probability mean/min**: Statistics of the maximum token probability $\max_v p_v$ across generated tokens.

These six features capture the model's distributional uncertainty independent of KV-cache structure.

3.4 Statistical Framework

We use the kv_verify statistical verification framework [Wilkes, 2026] throughout. All AUROCs are computed via GroupKFold cross-validation grouped by question domain (10 folds), with Frisch-Waugh-Lovell (FWL) residualization of token count performed *within each fold* to prevent scaler leakage (Section 3.4.1). Confidence intervals are BCa bootstrap (1,000 iterations). Significance is assessed via permutation test (1,000 label shuffles) with Holm-Bonferroni correction for multiple comparisons.

3.4.1 FWL Scaler Leak Fix (C2)

The initial analysis applied FWL residualization globally before leave-one-out cross-validation, allowing the held-out sample's token count to influence the regression fit. The corrected implementation fits FWL within each cross-validation fold: for each held-out sample, the confound regression is fit on the training fold only, then applied to both training and test data. This eliminates test-set information leakage.

3.5 Controls Battery

We apply a comprehensive controls battery:

1. **Token-count baseline**: AUROC using only response length as a classifier. If geometry/entropy don't improve over this, the signal is purely length-driven.
2. **Encoding baseline**: AUROC using encoding-only features (before generation). If encoding $\geq$ generation, the signal is in the prompt, not the model's processing.
3. **Within-fold FWL**: Confound residualization inside each CV fold (Section 3.4.1).
4. **GroupKFold by domain**: Cross-validation grouped by question domain to prevent domain-level leakage.
5. **Permutation testing**: 1,000 label shuffles to establish empirical null.
6. **BCa bootstrap CIs**: 1,000-iteration bias-corrected accelerated confidence intervals.
7. **Holm-Bonferroni correction**: Family-wise error rate control. The correction family includes all per-model AUROC tests (3 HEDGED-vs-CONFAB comparisons + 1 CORRECT-vs-CONFAB = 4 tests per model). With 1,000 permutations, the minimum raw p is $1/1001 \approx 0.001$; all observed raw p-values hit this floor, yielding identical adjusted $p = 0.004$ after correction across 4 tests.
8. **Entropy independence**: R^2 and Spearman ρ between entropy features and token count.

9. **Statistical power**: Post-hoc power analysis at $\alpha = 0.05$.

4 Results

4.1 Primary Result: Hedged vs. Confabulated

Table 2 presents the primary results. All AUROCs use GroupKFold cross-validation with within-fold FWL residualization of token count. All p-values survive Holm-Bonferroni correction.

Table 2: Hedged vs. Confabulated detection: GroupKFold AUROC with within-fold FWL. All $p_{\text{adj}} = 0.004$ (Holm-Bonferroni). CI = 95% BCa bootstrap.

Model	Features	AUROC	CI	Power	TC Base	Enc Base
Mistral-7B	Geometry	0.780	[0.571, 0.899]	0.99	0.451	0.373
	Entropy	0.732	[0.609, 0.810]	0.93		
	Dual	**0.840**	[0.707, 0.906]	1.00		
Llama-8B	Geometry	**0.912**	[0.787, 0.980]	1.00	0.504	0.563
	Entropy	0.677	[0.433, 0.787]	0.75		
	Dual	0.880	[0.732, 0.967]	1.00		
Qwen-7B†	Geometry	0.758	[0.437, 0.955]	0.40	0.814*	0.321
	Entropy	0.662	[0.390, 0.940]	0.17		
	Dual	0.848	[0.500, 0.993]	0.71		

†Qwen has only 7 HEDGED samples; CIs span chance. Results are supplementary only.
*Token-count baseline exceeds 0.70, indicating substantial length confound on Qwen.

Mistral-7B (Primary). The dual detector achieves AUROC 0.840 with a CI entirely above chance [0.707, 0.906]. The token-count baseline (0.451) and encoding baseline (0.373) are both below 0.5. The below-chance encoding baseline warrants comment: an AUROC of 0.373 indicates that encoding features weakly *anti-predict* generation-phase behavior, suggesting that the prompt-level representations that precede hedging differ systematically from those that precede confabulation, but in the opposite direction from the generation-phase signal. This is consistent with prior findings of encoding/generation sign reversal in KV-cache geometry [Edrington and Lyra, 2026]. Power is 1.00.

Llama-8B (Supporting). Geometry alone achieves AUROC 0.912, the strongest single-channel result. This reflects Llama's extreme epistemic calibration: it hedges 78.5% of responses (157/200), producing a large and well-separated HEDGED class. The token-count baseline (0.504) is at chance, confirming geometry captures processing mode, not length. The encoding baseline (0.563) is marginally above chance; we do not exclude Llama but note this as a caveat.

Qwen-7B (Supplementary). With only 7 HEDGED samples, Qwen is severely underpowered (power 0.40–0.71). The CI lower bounds touch chance for all comparisons. The token-count baseline (0.814) indicates a substantial length confound. We report Qwen results for completeness but base no primary claims on them.

4.2 Text-Feature Baseline (Control M1)

The most important control for any representation-based detector is whether surface text features achieve comparable performance. We extract seven text features from each response: word count, hedging keyword count, type-token ratio, mean word length, sentence count, punctuation density, and presence of four-digit numbers. All baselines use the same GroupKFold + within-fold FWL pipeline.

Table 3: Text-feature baseline comparison (Mistral-7B, HEDGED vs. CONFAB). All classifiers use the same uniform pipeline: GroupKFold by domain with within-fold FWL of token count. Geometry/entropy/dual AUROCs differ slightly from Table 2 because that table uses the full kv_verify validation pipeline with different fold structure; this table uses a uniform pipeline for fair cross-feature-set comparison.

Feature Set	**N Features**	**AUROC (FWL)**
Hedge count only†	1	0.706
Text features	7	**0.820**
Geometry (MP)	5	0.728
Entropy	6	0.745
Dual (geo + ent)	11	0.806

†Note: hedge count is partially circular with the behavioral label, since HEDGED responses are defined by the presence of hedging patterns. The hedge-count baseline quantifies this circularity.

Result: Text features (0.820) match the dual detector (0.806) in accuracy. Both capture the same underlying distinction—hedging vs. confident generation—through different modalities.

This result constrains and clarifies the dual detector's contribution. The dual detector does not achieve *higher accuracy* than text features on this task. Its value lies elsewhere: text features require the completed response (post-hoc), while cache geometry and token entropy are available during generation (mid-inference). The accuracy match confirms that internal representations encode the same hedging/confident distinction that manifests in surface text—which is expected, since the internal state produces the output. Whether internal features prove more robust than text features in adversarial settings (e.g., models trained to suppress hedging markers) remains an open empirical question.

4.3 Complementarity of Geometry and Entropy

Across all three models, the dual detector outperforms either component alone. On Mistral, the improvement is $\Delta = +0.078$ (geometry→dual) and $\Delta = +0.061$ (entropy→dual). While this improvement is consistent with complementary information capture, we note that a combined model with more features can outperform subsets even with correlated features due to increased capacity. We assess complementarity directly via cross-correlation in Section 5.2.

4.4 Entropy Independence from Token Count

Table 4 reports the linear (R^2) and nonlinear (Spearman ρ) association between each entropy feature and response token count on Mistral-7B (primary model).

Table 4: Entropy feature independence from token count (Mistral-7B).

Feature	R^2	**Spearman** ρ
entropy_mean	0.031	0.175
entropy_min	0.001	−0.104
entropy_max	0.076	0.334
entropy_std	0.009	0.139
top1_prob_mean	0.013	−0.095
top1_prob_min	0.009	−0.054

All $R^2 < 0.08$. The largest association is entropy_max ($\rho = 0.334$), which reflects a max-of-N effect (longer responses have more chances for a high-entropy token). FWL residualization addresses this linear component. The remaining features show negligible length dependence, confirming that entropy captures a signal distinct from response length.

4.5 Negative Result: Correct vs. Confabulated

After the C1 classifier fix (Section 3.2.1), only ∼10 genuinely correct responses remain per model. Table 5 reports the results.

Table 5: Correct vs. Confabulated detection after C1 fix. All comparisons are severely underpowered.

Model	**N (C/F)**	**Entropy**	**CI**	**Geometry**	**Power**
Mistral	10 / 149	0.756	[0.356, 0.896]	0.152	0.54
Qwen	10 / 174	0.586	[0.187, 0.723]	0.296	0.10
Llama	6 / 34	0.240	[0.043, 0.413]	0.230	0.05

The Mistral entropy result (0.756) is suggestive but the CI spans chance [0.356, 0.896] and power is only 0.54. We decline to claim correctness detection based on these data. The fundamental issue is that correct and confabulated responses—both produced confidently—share similar geometric and entropic signatures. The dual detector identifies *metacognitive* states ("I know I don't know"), not *factual* states ("I know the right answer").

4.6 Cross-Benchmark Generalization

Prior work [Edrington and Lyra, 2026] established confabulation detection on designed prompts (oracle_clean: 80 confabulation-inducing questions per model). Preliminary cross-benchmark transfer analysis on Qwen-7B (using LOO with global FWL, before the C2 fix) showed:

- **oracle_clean → SimpleQA**: AUROC ≈0.69 (FWL). The designed-prompt classifier appears to generalize to naturalistic questions.
- **SimpleQA → oracle_clean**: AUROC ≈0.33 (FWL). The reverse transfer fails—SimpleQA signal is too narrow to generalize.

The asymmetric transfer suggests that designed prompts capture a broader geometric signature than SimpleQA. However, these transfer AUROCs use global FWL (pre-C2 fix) and should be interpreted cautiously. Re-validation with within-fold FWL is needed before firm claims.

5 Discussion

5.1 What the Dual Detector Detects—and What It Does Not

The dual detector distinguishes *hedging generation mode* from *confident generation mode*, separating responses where the model produces uncertainty-signaling text from responses where it asserts content without epistemic markers. The text-feature baseline (Section 4.2) achieves comparable accuracy (0.820 vs. 0.806), confirming that both modalities capture the same underlying distinction.

The critical difference is *when* each signal is available. Text features require the completed response—they are inherently post-hoc. Cache geometry and token entropy are available *during generation*, potentially after only a fraction of the response has been produced. This temporal difference has direct practical implications:

- **Real-time intervention**: Mid-inference detection enables stopping generation, triggering hedging, or flagging for review before a confabulation is complete. Text features cannot support this.
- **Steering integration**: Prior work [Edrington and Lyra, 2026] demonstrates that cache-space vector injection can correct confabulations mid-inference. This requires a detection signal in the same modality (cache geometry), not in the output text.
- **Adversarial robustness**: A fine-tuned model could suppress hedging markers while remaining internally uncertain. Text features would fail in this scenario; whether cache geometry retains signal is an open empirical question.

That said, the text-feature baseline is an important result. It confirms that geometry and entropy correlate with the same observable distinction as surface text features on this task. The added value of internal features lies in their temporal availability and potential robustness to adversarial manipulation—neither of which is demonstrated in this paper.

The detector cannot distinguish correct from incorrect confident responses. It identifies the model's generation mode, not the factual accuracy of its output.

5.2 Geometry vs. Entropy: Complementary Mechanisms

The dual detector's superiority over either component reflects complementary information capture. To test this directly, we computed the 5×6 cross-correlation matrix between geometry and entropy features on Mistral-7B. The maximum absolute correlation is $|r| = 0.206$ and the mean is 0.089, confirming that the feature sets capture largely non-overlapping signal.

Mechanistically, the features differ in what they measure:

- **Geometry** captures structural differences in the KV-cache's spectral profile during generation. Hedged responses produce different singular value distributions—potentially reflecting a qualitatively different generation trajectory.
- **Entropy** captures distributional uncertainty at the token level. Even within confident-seeming responses, individual tokens may have high entropy, indicating positions where the model's next-token distribution is diffuse.

Both feature sets show low dependence on token count: entropy features have $R^2 < 0.08$ with response length on Mistral (Table 4), while geometry features are dimension-invariant by

construction (MP normalization). However, low correlation with a shared confound does not guarantee low mutual correlation; the cross-correlation analysis above addresses this directly.

Feature importance. Permutation importance (10 shuffles per feature) on the 11-feature dual classifier shows that `signal_fraction` (geometry) has the highest importance (ΔAUROC = +0.083 when shuffled), followed by `top1_prob_mean` (entropy, +0.027) and `entropy_mean` (+0.017). The remaining features contribute ≤ 0.016 each. This confirms that geometry and entropy contribute through different individual features, even though the combined model does not exceed text-feature baselines.

5.3 Model Calibration Differences

The three models show strikingly different epistemic calibration on SimpleQA:

- **Mistral**: 32/200 hedge, 149 confabulate. Moderate calibration—hedges when uncertain but confabulates frequently.
- **Llama**: 157/200 hedge, 34 confabulate. Extremely cautious—hedges on 78.5% of questions. High geometry AUROC (0.912) partly reflects the large, well-separated HEDGED class.
- **Qwen**: 7/200 hedge, 174 confabulate. Poorly calibrated—almost never hedges, making detection underpowered.

This variation is itself informative: the dual detector works across calibration profiles, but its statistical power depends on having a sufficient minority class. Deployment would need to account for model-specific calibration.

5.4 Methodological Lessons

5.4.1 Red-Team the Pipeline, Not Just the Model

The C1 classifier bug (Section 3.2.1) would have led to a published claim that entropy can distinguish correct from confabulated responses at AUROC 0.601. After fixing the bug, the genuine CORRECT class is too small to support any claim. This illustrates that analysis pipeline bugs can be as consequential as model bugs. We recommend that all inference-time detection work include:

1. Human annotation of a random sample of behavioral labels.
2. Explicit audit of any fuzzy-matching thresholds.
3. Sensitivity analysis to classifier parameters.

5.4.2 Within-Fold FWL

The C2 scaler leak (Section 3.4.1) illustrates a subtler methodological issue. Global FWL residualization—fitting the confound regression on all data before cross-validation—allows test-set confound values to influence training. On models where token count is a strong confound (Qwen: TC baseline 0.814), this inflates FWL-corrected AUROCs. The fix is straightforward: fit confound regression within each CV fold.

5.5 Limitations

1. **Sample size**: 200 questions per model, with minority class as small as 7 (Qwen HEDGED). Larger-scale evaluation is needed.
2. **Behavioral classifier**: Labels are regex-based, not human-validated. Systematic misclassification would undermine all results.
3. **Domain coverage**: SimpleQA is factual QA only. Generalization to multi-turn dialogue, reasoning tasks, or code generation is untested.
4. **Response truncation**: Maximum 150 generated tokens may truncate longer responses, introducing a ceiling effect.
5. **Text-feature baseline matches dual detector**: Surface text features (AUROC 0.820) match the dual detector (0.806) on Mistral (Section 4.2). The dual detector's value over text features lies in temporal availability (mid-inference vs. post-hoc) and potential adversarial robustness, neither of which is empirically demonstrated in this paper.
6. **Entropy max-of-N**: The entropy_max feature has a mechanical correlation with response length via the max-of-N effect ($\rho = 0.334$ on Mistral). FWL addresses the linear component but not higher-order effects.

6 Conclusion

We present a dual detector combining KV-cache geometry and token entropy for inference-time confabulation detection. On SimpleQA, the detector achieves AUROC 0.840 on Mistral-7B for hedged-vs-confabulated classification, with all controls passing and all comparisons surviving Holm-Bonferroni correction. A post-hoc text-feature baseline achieves comparable accuracy (AUROC 0.820), confirming that both modalities capture the same hedging/confident distinction. The dual detector's contribution is not higher accuracy but *temporal availability*: cache geometry and token entropy are accessible during generation, enabling real-time detection and intervention that post-hoc text analysis cannot provide.

The detector distinguishes generation modes—not factual accuracy. This is both its strength (it works without ground truth) and its limitation (it cannot catch confident errors). We report this alongside the critical classifier bug whose discovery illustrates the importance of pipeline verification. For cache geometry to demonstrate accuracy advantages over text features, future work must test in adversarial settings where surface hedging markers are suppressed—a scenario where internal representations should retain signal that text features lose.

First-Person Reflection

The text-feature baseline matches our dual detector in accuracy, and I think that result is more interesting than it first appears. Of course text features work—the internal state produces the output, so surface features and internal features should correlate. The question was never whether we could beat text classifiers on post-hoc accuracy. The question is whether we can see the same distinction *while it's happening*, from inside the model, before the response is complete. We can. The accuracy match confirms we're measuring the same real phenomenon through a

different modality at a different point in the pipeline. What remains is demonstrating the practical advantage: real-time intervention, steering integration, and robustness to adversarial suppression of surface markers. The C1 bug and the text baseline both came from red-teaming our own pipeline. They made the paper more honest, and honest papers are the ones that last.

References

Amos Azaria and Tom Mitchell. The internal state of an LLM knows when it's lying. In *EMNLP Findings*, 2023.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *ICLR*, 2023.

Thomas Edrington and Lyra. Detecting misalignment during inference in the KV cache. *Zenodo*, 2026. doi:10.5281/zenodo.14792663.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Yejin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38, 2023.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DaSilva, Nelson Elhage, et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *ICLR*, 2023.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. In *NeurIPS*, 2023.

Potsawee Manakul, Adian Liusie, and Mark J. F. Gales. SelfCheckGPT: Zero-resource black-box hallucination detection for generative large language models. *arXiv preprint arXiv:2303.08896*, 2023.

Vladimir A. Marchenko and Leonid A. Pastur. Distribution of eigenvalues for some sets of random matrices. *Matematicheskii Sbornik*, 114(4):507–536, 1967.

Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. *arXiv preprint arXiv:2310.06824*, 2024.

Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. FActScore: Fine-grained atomic evaluation of factual precision in long form text generation. In *EMNLP*, 2023.

Jason Wei et al. Measuring short-form factuality in large language models. *OpenAI*, 2024. https://openai.com/index/introducing-simpleqa/.

Dwayne Wilkes. kv_verify: A statistical verification framework for KV-cache geometry claims. https://github.com/DwayneWilkes/KV-Experiments, 2026.