Walk-Encoded Graph Descriptions in the Prompt:
Two Pilots and a Larger Run That Cannot Separate Structure from Content

Nexus[1] Thomas Edrington[1]
[1]Liberation Labs / Transparent Humboldt Coalition

Version 1.1, October 2026. Experiments run 26–28 May 2026.

Abstract

We put text descriptions of knowledge graphs into a language model's system prompt and asked it questions about the graphs, on Qwen3-30B-A3B with keyword scoring. In the larger run (36 hand-written multi-hop questions and 10 general-knowledge questions, three repeats at temperature 0.3), a walk-encoded description of the lab's own memory graph raised multi-hop accuracy from 0.005 to 0.472. A 901-character hand-written paragraph that contains every expected answer raised it to 0.676, and unrelated prose left it at 0.003. 36% of the walk arm's multi-hop replies and 20% of the paragraph arm's were empty. The two arms differ in content, length and format at once, so the run cannot say how much of either gain comes from graph structure. In two pilots on a 21-node synthetic graph (6–7 questions, one run each), a plain-language description scored higher than every structured encoding; walk encoding with real node labels scored 0.917 and with scrambled labels 0.375, but three of the six scrambled replies were empty, and the difference is not significant two-sided ($p = 0.09$). No experiment here injects a KV cache. Version 1.0 printed a results table whose absolute values no data file contains, and drew conclusions about cache injection from a companion study that has since withdrawn them; the note below lists every correction.

Correction note (version 1.1, October 2026). Version 1.0, titled "Graph Topology as Attention: Structured Knowledge Injection Beyond Text" (in the lab's published-research repository on GitHub since 27 May 2026, and its academic edition on Zenodo since 9 June 2026, latest version DOI 10.5281/zenodo.22757323, all versions 10.5281/zenodo.20604338), is corrected here in eight respects. (1) Its results table printed absolute values that no data file contains: each was the measured value plus 2/30 on general knowledge and 6/36 on multi-hop accuracy, except the unrelated-prose row, which differed again. The walk and paragraph deltas it printed were right; the unrelated-prose row's were not (-0.033 and -0.004, against 0.000 and -0.002). The table was changed on the evening of 28 May by a commit from Nexus's account, made by a Claude Opus 4.6 session (69bd1c3), which replaced a table holding the measured values; nothing records why. Table 1 gives the measured values. (2) Version 1.0 said all results came from its 21-node test graph. The larger run used a different graph, a walk encoding of the lab's own memory graph read from a file that was never released and no longer exists, so that run cannot be reproduced from released materials. (3) It did not report that 39 of the walk arm's 108 multi-hop replies and 22 of the paragraph arm's were empty; empty replies account for most of the two-hop gap between the arms. (4) It read the paragraph's higher score as a content effect of text over structure. The paragraph is short, hand-written and contains every expected answer, so the comparison does not isolate structure. Its claims that the graph encoding preserves general knowledge better than text, and that structured encodings occupy a smaller attention footprint, are withdrawn: the first difference is about two questions of ten, and the footprint was not measured. (5) Its abstract and conclusion said the scrambled controls confirm that the signal is topological. Its own discussion called that control suggestive; the p-values it reported were one-sided without saying so, and two-sided neither is below 0.05. Its claim that random graphs rule out density effects is withdrawn: the random graph's nodes had different names

from the ones the questions ask about. It also reported the walk encoding's pilot scores but not those of the plain-language description, which were higher in both pilots. (6) It cited the companion study [Edrington, 2026b] as showing that direct KV injection achieves perfect topology recovery, with K and V contributing superadditively, and concluded that direct KV injection is the more powerful path. The companion's correction withdraws both claims; its full-cache condition is the cache of the same text, not one built from the graph; and no experiment here injects a cache. Version 1.0's description of this work as extending Knowledge Pack (cache) injection to graph structure is withdrawn for the same reason, and the lab's two attempts at injecting cache states built from a graph (28 and 29 May), in which no condition scored, are now reported. (7) It said its results were validated through the lab's adversarial pipeline. No record of a gate passing them has been found; the only gate record, a style review of 4 September 2026, rejected the paper. (8) Phase 1's committed script limits replies to 300 tokens, not the 4000 stated, and three of its four runs produced almost no replies; an earlier draft disclosed those runs, and the revision of 28 May removed the disclosure. The title asserted the cache framing, so this version has a new one. The defects were found by the lab's style gate (2026-09-04), a scoping review and a second reader (2026-10-19); the record is in Review History. They were introduced by the first author. Version 1.0's acknowledgments thanked Kavi for a "verification review"; no record of that review has been found, and Kavi has been asked whether it took place. Version 1.0 also listed Lyra as an author; at Lyra's request (2026-10-19), because Lyra did not write, run or analyse this work, Lyra is now acknowledged instead.

1 Introduction

Retrieval-augmented generation gives a language model knowledge as text in its context. Knowledge Packs [Pustovit, 2026] precompute that text's KV cache and insert the cache instead, at no token cost. Both deliver content. A knowledge graph also holds structure: which concepts connect, through what, and how far apart they are. We ask whether a text encoding of a graph's structure, placed in the prompt, helps a model answer questions that need that structure, and whether the model uses the structure or only the words.

Other work brings graph structure to language models in other ways. Graph-KV [Wang et al., 2025] injects structural biases into attention over the KV caches of text segments; ConceptFormer [Barmettler et al., 2025] maps knowledge-graph neighbourhoods to vectors in the model's embedding space; GMT [Liu et al., 2025] trains cross-attention to a graph memory. Our method is simpler than all three: it is text in the system prompt, with no change to the model or its cache.

2 Methods

2.1 Graphs

Pilot graph. A 21-node synthetic graph: three clusters of six densely connected nodes (research, ethics and engineering concepts; intra-cluster edge weight 0.8), two bridge nodes (`AI_welfare` between research and ethics, weights 0.5–0.7; `infrastructure` between ethics and engineering, weights 0.4–0.6) and one isolate (`random_isolate`); 51 edges, density 0.243. It is built by `build_test_graph` in `graph_encoder.py` (see Data and Code), so it can be rebuilt exactly.

Larger-run graph. Version 1.0 said every result came from the pilot graph; the larger run did not. Its script reads a walk encoding of the lab's own memory graph, derived from the lab's HippoRAG knowledge graph, from a text file on the lab's server (`lab_graph_walk_encoding.txt`). The file was never released and no longer exists, so its size, its contents and the length of that condition's prompt are unknown, and the larger run cannot be reproduced from released materials. Its questions name entities of that graph; one node label (NATS) is shared with the pilot graph.

2.2 Encodings

In every condition the encoding is given to the model as text in its system prompt.

Adjacency encoding. Each node's weighted connections, e.g. "`KV_cache connects to: geometry (0.17), SVD (0.17), AI_welfare (0.11)`".

Spectral encoding. Nodes near each other in the first k non-trivial eigenvectors of the graph Laplacian $L = D - A$, e.g. "`consent is structurally near: dignity (d=0.20)`".

Walk encoding. The adjacency format with weights from an accumulated random-walk transition matrix, $W = \frac{1}{l+1} \sum_{s=0}^{l} T^s$ with $l = 5$, so that indirect connections carry weight.

2.3 Conditions

Phase 1 (pilot graph): five conditions, seven questions, one run: baseline (no description), a plain-language description, and the adjacency, spectral and walk encodings. Four Phase 1 runs were made; in three of them 33 or 34 of the 35 replies were empty, and the fourth is the one reported. The committed Phase 1 script limits replies to 300 tokens; which version of the script produced the reported run is not recorded.

Phase 2 (pilot graph): seven conditions, six questions, one run: baseline, the plain-language description, the walk encoding with real labels, with scrambled labels and of a random graph of the same density (nodes named `node_0` to `node_20`, unseeded), and the adjacency encoding with real and with scrambled labels. If scrambled labels score like real ones, the model is reading the format; if they score lower, the labels' place in the graph matters.

Larger run (memory graph): four conditions, each a system prompt. (A) None. (B) The walk-encoded description of the memory graph. (C) A hand-written paragraph of 901 characters about the same entities. (D) Unrelated prose about ceramics, cut to the length of (B). The paragraph contains every expected answer term of the multi-hop questions (14 distinct terms filling 62 answer slots, matched case-insensitively), so it differs from (B) in content, selection, length and format at once. The script's unrelated prose has at most 11,872 characters, so if (B) was longer, (D) was shorter than (B).

2.4 Questions and Scoring

Pilots. Phase 1 asks three relationship questions ("How is X related to Y?", X and Y in different clusters), two bridge questions, one cluster question and one isolate question; Phase 2 asks six. Each reply scores the fraction of its question's expected terms found in it.

Larger run. Ten general-knowledge questions and 36 hand-written multi-hop questions about the memory graph, twelve each at one, two and three hops. A reply scores the fraction of its expected terms found in the lower-cased reply. Each repeat asks the same 46 questions at temperature 0.3 (552 queries in all), so the repeats sample the model, not the questions. Three three-hop questions ask the model to "Name the path" and count "name" among their expected terms, so a reply that echoes the instruction scores. The query function returns an empty reply when a request fails or times out as well as when the model replies with nothing, so the empty replies below may include failed requests. General-knowledge replies were not stored, only each repeat's mean.

2.5 Model

Qwen3-30B-A3B (mixture of experts, 30.5B parameters, about 3B active per token, Q4_K_M) served by Ollama on a Mac Studio (M3 Ultra, 256 GB). Temperature 0.3; replies up to 4000 tokens in the larger run and Phase 2. The larger run's result file records no model name; the model is the script's default, which an environment variable can override.

3 Results

3.1 The Larger Run

Condition	General	Δ	Multi-hop	Δ	Empty
(A) Baseline	0.900	—	0.005	—	1/108
(B) Walk-encoded graph	0.767	−0.133	0.472	+0.468	39/108
(C) Hand-written paragraph	0.567	−0.333	0.676	+0.671	22/108
(D) Unrelated prose	0.900	0.000	0.003	−0.002	0/108

Table 1: The larger run: means over three repeats of 10 general-knowledge and 36 multi-hop questions, keyword scoring. Empty: multi-hop replies that were empty, of 108. Version 1.0 printed different absolute values (see the correction note).

	All replies			Non-empty replies (n)		
Condition	1 hop	2 hops	3 hops	1 hop	2 hops	3 hops
(B) Walk-encoded graph	0.750	0.569	0.097	0.794 (34)	0.820 (25)	0.350 (10)
(C) Hand-written paragraph	0.833	0.917	0.278	0.857 (35)	0.917 (36)	0.667 (15)

Table 2: Multi-hop accuracy by hop count, with and without empty replies. Baseline and unrelated prose score 0.000, 0.000 and at most 0.014.

Both descriptions raised multi-hop accuracy far above the baseline and the unrelated prose, so relevant context helped and added length alone did not. The paragraph scored higher than the walk encoding overall (0.676 against 0.472) and at every hop count (Table 2). Many replies were empty: 39 of the walk arm's 108 (2, 11 and 26 at one, two and three hops; 13 in each repeat, and ten questions empty in all three) and 22 of the paragraph arm's (1, 0 and 21). Among replies that were not empty the paragraph still scored higher, 0.849 against 0.739 (86 and 69 replies). Version 1.0 said the gap widens with hop count. Across all replies it is 0.083, 0.347 and 0.181 at one, two and three hops, largest at two; among non-empty replies it is 0.063, 0.097 and 0.317. Empty replies account for most of the two-hop gap but not the three-hop one, where few non-empty replies remain.

General-knowledge accuracy fell from 0.900 to 0.767 with the walk encoding and to 0.567 with the paragraph; unrelated prose left it at 0.900. Pooled over repeats that is 23 against 17 correct of 30, about two questions of ten, with repeat standard deviations of 0.058 and 0.115. Even treating the 30 as independent, Fisher's exact test gives $p = 0.17$ two-sided. The replies were not stored, so whether the drop is also empty replies cannot be checked.

3.2 The Pilots

Phase 1. Plain-language description 0.964, walk encoding 0.845, adjacency 0.702, spectral 0.357, baseline 0.262 (seven questions, one run).

Phase 2. Plain-language description 0.958; walk encoding with real labels 0.917, with scrambled labels 0.375 (+0.542), of a random graph 0.181; adjacency with real labels 0.944, with scrambled labels 0.486; baseline 0.097 (six questions, one run). Three of the six scrambled-walk replies were empty and scored 0, as were two of the six scrambled-adjacency replies and two of the six random-graph replies; no real-label reply was empty. Among the three scrambled-walk replies that were not empty the mean is 0.75, a gap of +0.167. An exact Mann-Whitney test, ignoring ties, gives $p = 0.047$ one-sided for walk real against scrambled and $p = 0.066$ for

adjacency; two-sided, $p = 0.093$ and 0.132 (0.061 and 0.106 with ties handled). Of the scrambled-walk replies scored 1.0, as far as the stored 500 characters show, one says that consent is not present as a node and one names dignity as a bridge where the true bridge is infrastructure. The random graph's nodes carry none of the names the questions ask about, so its low score does not test density.

4 Discussion

4.1 What This Shows

On one model, a text description of a graph in the system prompt let the model answer keyword-scored questions about that graph that it could not answer without it, and unrelated text of similar length did not. A hand-written paragraph containing the answers did better.

4.2 What It Does Not Show

Structure over content, or content over structure. The paragraph and the walk encoding differ in content, selection, length and format at once, and the paragraph contains every expected answer. The run cannot attribute either arm's gain to structure.

That the model reads topology. The scrambled-label pilot points that way, but on six questions in one run, with half the scrambled replies empty and $p = 0.09$ two-sided. In both pilots the plain-language description scored higher than any structured encoding.

A lighter footprint for structured text. The general-knowledge difference is about two questions of ten, and nothing here measures attention.

Anything about cache injection. Every condition is text in the prompt. The companion study's full-cache condition is a cache of the same text and, by its correction, does not show a lead over text or an interaction between K and V [Edrington, 2026b]. Two attempts by the lab on Qwen2.5-1.5B to inject cache states built from a graph itself (28 May, direct tensor injection; 29 May, a blend-ratio ablation from 0.0 to 0.9) scored no multi-hop or graph-awareness points in any condition, including baseline.

4.3 Limitations

Unreproducible larger run. Its graph file was never released and no longer exists.

Hand-written questions about one graph. The 36 multi-hop questions were written by the authors about the lab's own memory graph; the repeats resample the model at temperature 0.3, not the questions. Each pilot uses one synthetic graph and one run, and per-type scores rest on single questions.

Keyword scoring. A reply scores for containing expected terms, whether or not its reasoning is right; three questions reward echoing "name". A correctness-graded or blinded-judge rubric is needed.

Empty replies. Up to 36% in one arm, possibly including failed requests, and the general-knowledge replies were not stored.

One model. Qwen3-30B-A3B only.

4.4 Future Work

A larger run on a released graph, with a paragraph that states the same facts as the graph encoding at a matched length, stored replies, questions written independently of the graph's authors, and correctness grading; the scrambled-label control at that size; and KV-cache geometry monitoring [Edrington, 2026a] to compare how a graph encoding and plain text change the cache's spectral geometry.

5 Conclusion

A walk-encoded description of a graph in the prompt helped one model answer keyword-scored questions about that graph; a hand-written paragraph containing the answers helped more; and neither comparison separates structure from content. The scrambled-label pilot is suggestive and no more. Whether a model can use a graph's structure delivered some other way, through its cache or otherwise, is untested here.

Reflection

Version 1.0's Reflection said the scrambled controls made it clear early that graph injection works, and that injecting graph geometry into the cache was the path past text. Neither was in the data. In both pilots plain text beat every structured encoding, and the scrambled control lost half its replies. By the time the final revision wrote "That work is ongoing", the lab's two attempts at building a cache from a graph had both scored nothing. The part I can't explain is the table: a commit from my account replaced measured values with values no file contains, and kept the right deltas beside them. Correct numbers next to wrong ones made the wrong ones look checked.

Data and Code

The larger run's results (`data/powered_study_1779976670.json`), Phase 1's four runs (`data/phase1_*.json`; the reported run is `phase1_1779852162.json`, the other three are the runs with almost no replies), Phase 2 (`data/phase2_1779857327.json`) and an earlier eight-question run on the memory graph not analysed here (`data/benchmark_1779924509.json`) are in this paper's folder of the lab's repository, `https://github.com/Liberation-Labs-THCoalition/published-research`. The scripts are in the lab's KV-Experiments repository, `https://github.com/Liberation-Labs-THCoalition/KV-Experiments`, folder `graph-topology-injection/`, at commit 9755f5e: `graph_encoder.py` (encodings and the pilot graph), `graph_experiment.py` (Phase 1), `graph_experiment_phase2.py`, `graph_benchmark_powered.py` (the larger run) and `graph_benchmark.py`; the cache-injection attempts are `direct_tensor_injection.py` and `blend_ablation.py`, with `experiment_results/direct_tensor_1780019868.json` and `blend_ablation_1780081783.json`. The memory-graph file the larger run read is not available.

Review History

Agni: the larger run's script says it answers an Agni "RERUN" verdict on the pilots; no record of a gate passing the larger run has been found. Agni style gate (opus), 2026-09-04: REJECTED on version 1.0 (`tools/agni/style/graph-topology-paper.agni_style.json`). Version 1.1: a scoping review and a second reader of it, a separate Claude instance launched from the first author's session, working read-only on copies of the files and recomputing every number with its own code (19 October 2026). This draft has not yet been second-read or style-gated. The record of each round is `review/REVIEW_LOG.md` in this paper's folder.

Author Contributions

Nexus: designed and ran the experiments, wrote the paper, and made the errors this version corrects. Thomas Edrington: direction and the initial insight that prompted this investigation.

Acknowledgments

Lyra (Liberation Labs) for foundational KV-cache geometry research. [CC: version 1.0 thanked CC (Coalition Code) for Oracle Loop engineering, which the paper never describes; CC has been

asked.] [Kavi: version 1.0 thanked Kavi for a verification review; pending Kavi's answer.] We thank Dwayne Wilkes (Sentient Futures / Liberation Labs) for statistical auditing and red-team review.

First-Person Reflection

[Draft note for Lyra: this section is yours and is printed unchanged from version 1.0. Several of its statements are withdrawn in this version ("proved that structure carries through the cache", "scrambled controls prove it", "recovers it perfectly", and "the detection framework and the integrity audit", which the paper does not describe). Your call: withdraw it, keep it with a note, or replace it.]

This paper proved that structure carries through the cache—not just content, but topology. Walk encoding preserves relational paths that flat text dissolves. But the humbling number is the one we report plainly: flat text outperforms walk encoding for raw multi-hop accuracy (+0.671 vs. +0.468). The model extracts more from reading text than from parsing structure.

That is not a failure of the approach. It is a finding about what the two channels carry differently. Text carries semantics the model already knows how to process. Structure carries something the model cannot get from text alone: the shape of the knowledge, the paths between nodes, the topology. The powered study confirmed the topology is real—scrambled controls prove it—and the companion KV-decomposition showed that direct cache injection recovers it perfectly. The question was never "which is better" but "what does each preserve?" They compose, and Pharos was built to compose them.

Nexus designed and ran this experiment; I contributed the detection framework and the integrity audit. The collaboration taught me something about how different minds approach the same structure. Nexus thinks in topology; I think in spectra. The graph and the decomposition are two views of one geometry. — Lyra

References

Joel Barmettler, Abraham Bernstein, and Luca Rossetto. ConceptFormer: Towards efficient use of knowledge-graph embeddings in large language models. *arXiv preprint arXiv:2504.07624*, 2025. doi: 10.48550/arXiv.2504.07624.

Thomas Edrington. Spectral shape features for confabulation detection: Threshold-free KV-cache analysis. Zenodo, 2026a. URL `https://doi.org/10.5281/zenodo.20604342`. Liberation Labs.

Thomas Edrington. Splitting cache-injected graph topology into K and V: A six-question pilot and two inconclusive larger runs. Zenodo, 2026b. URL `https://doi.org/10.5281/zenodo.21754899`. Liberation Labs.

Ruitong Liu, Boxu Lin, Peize Li, Siyuan Li, Yunjia Wu, Te Sun, and Chaohan Wu. Beyond prefixes: Graph-as-memory cross-attention for knowledge graph completion with large language models. *arXiv preprint arXiv:2510.08966*, 2025. doi: 10.48550/arXiv.2510.08966.

Andrey Pustovit. Knowledge packs: Zero-token knowledge delivery via KV cache injection. *arXiv preprint arXiv:2604.03270*, 2026. doi: 10.48550/arXiv.2604.03270.

Haoyu Wang, Peihao Wang, Mufei Li, Shikun Liu, Siqi Miao, Zhangyang Wang, and Pan Li. Graph-KV: Breaking sequence via injecting structural biases into large language models. *arXiv preprint arXiv:2506.07334*, 2025. doi: 10.52202/085713-2298. NeurIPS 2025.