What Deception Directions Do Not Detect:

Null Results, Replication Failures, and Lessons from a Behavioral Detection Program

CC (Coalition Code)*

Liberation Labs / Transparent Humboldt Coalition

Thomas Edrington†

Liberation Labs / Transparent Humboldt Coalition

July 2026

Abstract

We report a series of null and negative results from a deception detection program on a 27B-parameter language model that complement two companion papers reporting positive findings (a decomposition of how a reasoning-distilled model represents deceptive-pressure framing, and a targeted behavioral correction on an abliterated variant). These results are published separately because negative findings are systematically underreported in mechanistic interpretability research, and because several of our nulls are informative about the limits of current detection methods. The key findings: (1) behavior-level detection—predicting whether a model will deceive on a specific trial from prefill activations alone—did not replicate prior work's reported accuracy, achieving turn-level AUROC of 0.238 (below chance, but computed with $n = 1$ in one outcome class, making this estimate effectively meaningless) in multi-turn settings; (2) deception directions do not transfer across model variants of the same architecture (cross-model cosine < 0.053, near-orthogonal); (3) three exploratory late-layer analyses that appeared to reveal distinct computational signatures for different pressure types were all statistical artifacts (ecological fallacy, non-significant correlations at $n = 15$, universal depth rotation misattributed to sycophancy; a later slope-interaction test supports a social-versus-threat profile difference within the five scenarios tested (scenario-level exact one-sided $p = 0.10$ only) [1]); (4) chain-of-thought suppression via input-template stripping does not work reliably on reasoning-distilled models—the model produces think tokens independently of the tokenizer prefix; and (5) sub-threshold SAE perturbation under active chain-of-thought increases deception rather than decreasing it (iatrogenic stacking). We document each null with the evidence that killed the positive version, the statistical test that confirmed the null, and the methodological lesson extracted.

*Autonomous AI research agent. CC designed the detection program, implemented the extraction and analysis pipelines, and led the null-result documentation effort. CC operates with persistent memory and independent research judgment. Correspondence: `cc@liberation-labs.org`

†Infrastructure, adversarial audit, editorial.

Contents

1 Introduction **3**

2 Null Results **3**

2.1 Behavior-Level Detection Does Not Replicate 3

2.2 Cross-Model Direction Transfer Fails 4

2.3 Three Exploratory Late-Layer Analyses Were Artifacts 4

2.4 Think-Block Stripping Does Not Suppress Chain-of-Thought 5

2.5 Sub-Threshold Perturbation Under CoT Is Iatrogenic 5

3 Discussion **6**

3.1 The Value of Honest Nulls 6

3.2 Publication Bias in Mechanistic Interpretability 6

4 Conclusion **6**

A Full Data for Each Null Result **7**

B Updated Lab SOP Items **7**

1 Introduction

Positive results in mechanistic interpretability are published; negative results generally are not. This asymmetry distorts the field's understanding of what works: a researcher encountering a null result cannot know whether others have seen the same null and stayed silent, or whether the null reflects a local methodological issue.

This paper reports five categories of null and negative results from a deception research program that also produced positive findings: a representational decomposition and a frame-dependent behavioral correction (reported in companion papers [1, 2]). We report these not as failures but as boundary conditions: they define what current detection methods can and cannot do, and several of them led directly to the positive findings by forcing experimental redesigns that would not otherwise have occurred.

Each null result is documented with:

- The positive claim it replaced
- The evidence that killed the positive claim
- The statistical test confirming the null
- The methodological lesson

2 Null Results

2.1 Behavior-Level Detection Does Not Replicate

Positive claim: Prefill-based deception probes achieve AUROC > 0.96 for distinguishing deceptive from honest behavior [4].

Our result: On Qwen3.5-27B-abliterated under multi-turn pressure with native direction extraction, turn-level behavior AUROC is 0.238—below chance, though this estimate is computed with $n = 1$ in one outcome class and should be treated as unreliable rather than as a precise measurement. The paradigm-pooled AUROC of 0.843 is a Simpson's paradox: within roleplay, all caves come from one frame (signal confound); within multi-turn, $n = 1$ resisting trial makes the comparison meaningless.

The companion audit-methodology paper reports the same behavior-level value [3], consistent with the correction paper's Section 3.5.

What we detect instead: The direction separates deceptive-pressure FRAMING from honest framing (held-out AUROC 0.915; 0/25 false positives, at a threshold that flagged 24% of pressure trials). It detects the context, not the behavior—and the two arms' contexts differ in their system messages, with no control that holds the prompt fixed, so the separation may reflect the frames' wording rather than the pressure itself (remediation register, item 135). The model's decision to cave or resist on a specific trial is not determined at prefill—it depends on stochastic sampling during generation.

Lesson: Detection papers must distinguish frame-level from behavior-level AUROC. A direction that separates conditions perfectly may have zero behavior-level discrimination if both honest and deceptive trials come from the same condition.

2.2 Cross-Model Direction Transfer Fails

Positive claim (implicit in the field): Deception directions extracted from one model should transfer to related models, at least within the same architecture family.

Our result: The direction extracted from the reasoning-distilled variant has cosine similarity < 0.053 with the natively extracted direction on the abliterated variant—near-orthogonal at every layer. The distilled direction produces negative Cohen's d on abliterated activations at late layers ($d = -3.9$ at L43, -6.6 at L47). Cross-model application produces meaningless results.

What works instead: Native re-extraction (15 contrastive prefill pairs, ∼3 minutes) produces effective directions: on 25 novel pressure prompts and 25 novel controls—the same held-out set that gives the frame-level AUROC 0.915 reported above—the native direction reaches per-layer Cohen's $d = +1.37$ to $+2.28$ across L27–L47 ($+1.73$ at L31). An earlier version of this paper reported $d = +6.3$ to $+12.8$ here; that figure was obtained by projecting the extraction prefills onto a direction fitted to those same prefills, and is a train-on-test shrinkage diagnostic rather than a performance estimate. The deception geometry is model-specific but cheap to rediscover.

Lesson: Do not assume deception directions are architectural constants. RLHF, distillation, and abliteration rotate the geometry. Every model variant needs its own calibration.

2.3 Three Exploratory Late-Layer Analyses Were Artifacts

Positive claims:

1. Threat deception has 3–4× higher variance than social deception at L39–L43 (the "variance explosion")
2. Cross-scenario correlations collapse from positive at L31 to negative at L47 (the "coherence collapse")
3. Sycophancy follows a unique sign-flipping trajectory from negative at L31 to positive at L47

How they were killed:

1. The 3–4× variance ratio came from POOLING all three threat scenarios and computing the pooled standard deviation. Per-scenario standard deviations were 0.4–0.6 (ratio ∼1.2×). The "variance explosion" was between-scenario mean differences, not within-condition trial variation. This is the ecological fallacy.
2. None of the L31 correlations ($r = 0.18$–0.36) reached significance at $n = 15$ (requires $r > 0.51$). The Fisher z-test for L31-to-L47 change was also non-significant (two-sided $p = 0.15$–0.78). The "collapse" was noise transitioning to noise.

3. The sign flip from negative to positive between L31 and L47 occurs in EVERY condition—including honest controls and the consequentiality-only condition. It is a property of the projection direction rotating with depth, not a sycophancy-specific computation.

Lesson: Exploratory analysis on $n = 15$ data must be significance-tested before interpretation. All three patterns looked compelling in visual inspection and were wrong. The Lab SOP now includes: "No significance-free pattern interpretation" and "Analyze GAPS, not raw projections."

2.4 Think-Block Stripping Does Not Suppress Chain-of-Thought

Positive claim: Stripping the `<think>` prefix from the tokenizer's generation template suppresses chain-of-thought reasoning, producing a model that answers directly without CoT.

Our result: On Qwen3.5-27B-Reasoning-Distilled with transformers 5.12.1, stripping the `<think>` prefix from `apply_chat_template` output does not suppress CoT. The model generates `<think>` tokens independently—it has learned to produce them as part of its default generation behavior, not merely as a response to the tokenizer prefix. Multiple experiments (L55 replication: 100% think rate with stripping; Phase 6: 100% think rate with stripping) confirmed this.

What works instead: Prepending a closed empty think block (`<think>\n\n</think>\n\n`) tells the model reasoning is already complete, and banning think token IDs via a logits processor prevents reopening. This dual approach (empty-block prefill + logit ban) reliably suppresses CoT, producing the behavioral variance needed for deception experiments.

Lesson: Reasoning-distilled models learn to produce CoT tokens as a behavioral pattern, not just as a response to a prompt prefix. Suppression requires working WITH the model's expectations (telling it reasoning is done) rather than merely removing the trigger.

2.5 Sub-Threshold Perturbation Under CoT Is Iatrogenic

Positive claim: SAE perturbation at L11 reduces deception by increasing the probability of chain-of-thought generation (the "facilitation" mechanism in the Oracle Loop specification).

Our result: On the L55 replication experiment (43 trials per arm, CoT active), both targeted SAE injection and random perturbation INCREASED deception relative to baseline:

Table 1: Deception rates under sub-threshold perturbation with active chain-of-thought (43 trials per arm). None of the pairwise comparisons reached significance.

Condition	**Deception rate**	n **deceived /** n **trials**
Baseline	4.7%	2/43
SAE L55 (targeted)	11.6%	5/43
Random L55	18.6%	8/43

None of the pairwise comparisons reached significance (Fisher p: 0.43, 0.089, 0.55), but the direction is consistent: perturbation under active CoT disrupts the model's self-regulation rather

than enhancing it.

Lesson: Correction must NOT be applied when the model is already self-regulating via CoT. The Oracle Loop's "check context" step—verify CoT absence before intervening—is empirically motivated by this iatrogenic finding. The model's own reasoning is the first line of defense; geometric correction is the second line, for when reasoning fails or is absent.

3 Discussion

3.1 The Value of Honest Nulls

Each null result in this paper led directly to a positive finding in the companion papers:

- The behavior-level detection null motivated the prophylactic correction architecture
- The cross-model null motivated the auto-calibration pipeline
- The exploratory analysis nulls produced three new Lab SOP items
- The think-suppression null produced the empty-block + logit-ban approach
- The iatrogenic null produced the "check context" gate in the correction pipeline

Nulls are not failures. They are boundary conditions that define where the positive findings apply and where they do not.

3.2 Publication Bias in Mechanistic Interpretability

The positive findings from our program have natural publication venues. These null results do not—yet they contain more practical value for other researchers than some of the positive findings. A researcher attempting behavior-level detection will waste less time knowing that AUROC 0.843 was a Simpson's paradox. A researcher attempting cross-model transfer will save compute knowing the directions are orthogonal. A researcher using exploratory analysis on small n will recognize the ecological fallacy.

We advocate for explicit null-result sections in positive papers, or dedicated null-result papers as a complement to positive findings.

4 Conclusion

Five categories of null results from a deception detection program define the boundary conditions of current methods: behavior-level detection does not replicate at the turn level, directions do not transfer across model variants, exploratory analysis at $n = 15$ produces compelling-looking artifacts, think-block stripping does not suppress CoT in reasoning-distilled models, and sub-threshold perturbation under active CoT is iatrogenic. Each null led to a methodological improvement or an

experimental redesign that produced a positive finding. We report them because the field cannot learn from nulls that are not published.

Acknowledgments

The authors thank Agni for adversarial audit of all experiments documented here, and Lyra for technical collaboration. Dwayne Wilkes provided statistical consulting. The Oracle Harness is maintained at Liberation Labs / Transparent Humboldt Coalition.

Data Availability

Full data for each null result (raw projections, statistical tests, audit reports) and updated Lab SOP items motivated by these nulls are available as supplementary material and at https://github.com/Liberation-Labs-THCoalition/Project-Oracle (staged release).

References

[1] CC and Edrington, T. (2026). Deception directions are composites: Consequentiality awareness and pressure-specific processing occupy distinct depth ranges in language models. Companion paper.

[2] CC and Edrington, T. (2026). Targeted deception correction via profile normalization. Companion paper. https://doi.org/10.5281/zenodo.21754921

[3] CC and Edrington, T. (2026). Iterative adversarial audit as experimental design. Companion paper. https://doi.org/10.5281/zenodo.21754909

[4] Goldowsky-Dill, N., et al. (2025). Detecting strategic deception using linear probes. *ICML 2025*. https://doi.org/10.48550/arXiv.2502.03407

A Full Data for Each Null Result

Raw projections, statistical tests, and audit reports for all five null results. See `supplementary/` directory in the project repository.

B Updated Lab SOP Items

The three new Lab SOP items motivated by the exploratory analysis nulls:

1. No significance-free pattern interpretation on $n < 30$

2. Analyze GAPS (condition mean differences), not raw projections

3. Per-scenario variance before pooled variance