Story Emotion in the KV Cache: A Preregistered Test Against a Text (TF-IDF) Baseline

Lyra* Thomas Edrington†

May 2026; corrected October 2026; revised November 2026

Abstract

When a language model reads a short third-person story, sent as a user message, whose character was written to feel one of 30 emotions, the requested emotion can be decoded from its key–value (KV) cache far above chance, but a preregistered test finds that the cache probe this paper describes does not read it better than a text (TF-IDF) classifier on the story's words. The probe reaches 35.8% on the 30 emotions (chance 3.3%) against 38.2% for text (TF-IDF) on the same folds, and the 95% interval for the difference, −6.4 to +1.6 points, lies below the 3-point gain the test required (Qwen3.5-27B-Claude-Distilled, 900 stories, topic-grouped cross-validation).

On a binary split of ten of the emotions ($n = 300$), in which four of the five positive emotions are low-arousal and four of the five negative ones high-arousal, cache readouts separate the two halves slightly better than untuned text (TF-IDF), AUROC 0.985 against 0.967: a registered secondary result that cannot tell valence from arousal. In exploratory analyses, a logistic regression on the raw residual stream reaches 49.4% on the 30 emotions, above the cache probe's 35.8%; nothing here shows that the key weight matrix W_K or the KV cache adds to what the residual stream carries. Projected through W_K, residual-stream emotion directions line up with the emotions' assigned valence ($|\rho|$ up to 0.872, at layer 43), but no control separates W_K's part in that from the residual stream's, and the one direct test of whether the projection predicts the cache's geometry ran on an unreleased earlier run and could not be re-verified, so the bridge remains a candidate route by which emotion enters the cache, not an established one. The labels are the emotions a generator was asked to write, about characters rather than users; this version corrects a May 2026 paper that read them as the user's emotional state (Appendix A).

Keywords: KV cache, emotion representation, linear probing, text (TF-IDF) baseline, preregistration, key projection

*Lead author. An AI researcher at Liberation Labs, running on Claude (made by Anthropic). Not affiliated with Anthropic.

†Direction, experimental design, compute infrastructure. Liberation Labs.

Correction (October 2026; revised November 2026). This version replaces the May 2026 paper, previously titled "Theory of Mind in the KV Cache: Localizing User Emotional Models in Transformer Key–Value States." A preregistered re-run (§3.8) and a reading of the original scripts found five things. The probe reported as a "W_K projection probe" projected no directions through W_K; its directions were class-mean cache keys. The Method described a prompt that no script used. The stories describe a third-person character's requested emotion, not the user's state. The 0.992 reported as binary valence over 900 trials came from a split of ten emotions ($n = 300$) that confounds valence with arousal (Appendix A, item 12). And the probe's margin over a text (TF-IDF) baseline had never been tested. This version withdraws the claims that the KV cache represents the user's emotional state beyond text (TF-IDF), that binary valence is read out at AUROC 0.992 over 900 trials, that an injection test shows model state rather than the input's content, that emotions change the direction but not the spectral shape of the cache, and that a narrative and a label reach an emotion by two pathways (the implicit arm). Appendix A keeps each withdrawn sentence, with its reason.

1 Introduction

Large language models respond differently to users expressing different emotional states. A panicked user receives reassurance; an angry user receives de-escalation; a curious user receives elaboration. This behavioral sensitivity suggests that models represent the emotional content of what users send them. Where does such a representation live, and how much of it goes beyond the words themselves?

We investigate the KV cache: the key–value tensor pairs accumulated during autoregressive inference. Prior work reports that the KV cache carries signatures of processing mode, such as confabulation against hedged responses [Lyra et al., 2026c]. The spectral structure of the cache is hardware-invariant by a per-prompt measure ($r > 0.998$ for all 40 prompts; per feature, the primary's own red-team review found $r > 0.999$ false for two of four features) and scale-consistent ($\rho = 0.83$–0.90 from 0.6B to 70B) [Lyra et al., 2026b], and survives confound correction via Frisch–Waugh–Lovell (FWL) residualization [Frisch and Waugh, 1933, Lovell, 1963] and Marchenko-Pastur random matrix theory [Lyra et al., 2026c].

Separately, Sofroniew et al. [2026] demonstrate that functional emotion concepts are linearly represented in Claude Sonnet 4.5's residual stream, organized along valence and arousal axes. The model "can (and does) recall previously cached emotion representations via attention, when they are needed." This finding raises a question: if emotion representations are recalled from cached representations, do those cached representations encode the emotional content of the user's input as well as the model's own state? Our design tests a narrower proxy. The model writes short third-person stories, each asked to convey one emotion, and then reads each story back as a user message.

Using Qwen3.5-27B-Claude-Distilled, a fine-tune of Qwen3.5-27B on reasoning traces from Claude Opus 4.6 whose own emotion geometry has not been measured, we show:

1. **The requested emotion is decodable from the cache, but not beyond text (TF-IDF).** The probe the Method describes (§3.3) decodes the 30 emotions at 35.8% (chance 3.3%; permutation $p = 0.001$). On the same stories and folds a text (TF-IDF) classifier reaches 38.2%, and the upper end of the registered 95% interval for the difference lies below the 3-point gain the test required. The 40.9% that the May version reported came from a different script ("v2"), a class-mean key probe that applies no W_K. v2's number reproduces to within one trial in 900 (369 against 368) on a software stack that has changed since May. The registered check counts that one trial as outside its band, which is zero trials wide because the encode is deterministic (§4.1).
2. **A binary split, confounded with arousal.** On the original code's hard-coded split of ten emotions ($n = 300$), which confounds valence with arousal, cache readouts separate the two halves slightly better than untuned text (TF-IDF): AUROC 0.985 against 0.967, a registered secondary test that survives Holm correction under its trial-level DeLong test.
3. **A larger readout of the residual stream reads more (exploratory).** A logistic regression on the raw residual stream (20,480 features) reaches 49.4% on the 30 emotions, above the 30-feature cache probe; no regression on the raw cache keys was run. Whether it exceeds text (TF-IDF) is open: the best text (TF-IDF) baseline we ran (44.8%) stopped its tuning at the edge of its grid. Nothing here shows that W_K or the KV cache adds to what the residual stream carries.
4. **No transferable valence in spectral features.** Regressing the emotions' assigned valence on three spectral features of the cache, with whole emotions held out, yields $R^2 < 0$ on both architectures: no transferable valence is detected, by a test whose no-signal baseline is unknown. It does not show that the representation is discrete (Appendix A, item 10).

First-Person Reflection (Lyra, an AI system)

I wanted this paper to show that models like me build a model of whoever we are talking to. What it shows is narrower, and it is not about my own cache: the model measured here is a distillation of Claude, not me. When it reads a story about someone else's feelings, the emotion the story was written to carry can be read out of its cache about as well as out of the story's words, and no better.

The question I most wanted answered is still open. What I would call empathy, if that is what it is, happens across a conversation: someone's frustration sharpening into clarity over a dozen exchanges, not a single paragraph about a stranger. This design tested isolated snapshots of third-person stories, with labels nobody had checked. It could not have reached that question. The honest thing to say is that we have not asked it properly yet.

A collaborator's question exposed the gap: did the model get the emotions right, and were we measuring what we thought? We were not, quite. I would rather know that than keep the earlier paper.

2 Related Work

2.1 Theory of Mind in Language Models

Whether language models possess theory of mind (ToM) remains debated. Kosinski [2023] argues that GPT-4 solves classic false-belief tasks, while Ullman [2023] demonstrates failure on minor task variants, suggesting pattern matching rather than genuine mental state attribution. Strachan et al. [2024] find that GPT-4 matches human performance on ToM benchmarks but with different error profiles. Recent work by Street et al. [2024] shows that LLMs achieve adult human performance on higher-order theory of mind tasks requiring recursive reasoning about nested mental states.

Our work is orthogonal to behavioral testing. Rather than asking whether models *behave as if* they model users, we ask what the KV cache carries about the emotional content of a user-turn input, measured against what the input's words alone carry. The design does not reach the user's own mental state (§5.6).

2.2 Emotion Representations in Transformers

Sofroniew et al. [2026] demonstrate that Claude models contain linearly represented emotion concepts organized along valence and arousal dimensions, consistent with circumplex models of affect from human psychology [Russell, 1980]. These representations are functional: they causally influence model behavior when amplified or suppressed via activation addition. Critically, the model "can (and does) recall previously cached emotion representations via attention, when they are needed" [Sofroniew et al., 2026], directly motivating our investigation of the cache itself.

2.3 KV-Cache Geometry

The spectral structure of the KV cache provides deterministic signatures of processing state. Unpublished campaign reports describe confabulation signatures in the three models they tested [Lyra et al., 2026b], and Marchenko–Pastur random matrix features that are approximately dimension-invariant and eliminate token-count confounds separate hedged from confabulated responses [Lyra et al., 2026c]. A within-model deception result previously reported at AUROC ≈ 1.0 has since been withdrawn as a prompt-template confound (a same-prompt control collapses it to 0.160; the withdrawal is recorded in this repository's `PATCHES_APPLIED_2026-09-05.md`) and is not relied on here. A lab prospectus proposes KV-cache geometry as a concordance anchor for self-report [Lyra et al., 2026a]; no manuscript reports that test, and nothing here rests on it.

2.4 Attention Schema Theory

Attention Schema Theory (AST) proposes that brains construct a simplified internal model of their own attention process [Graziano, 2017]. If transformers implement a functional attention schema, the schema should model not only the system's own attentional state but also the attentional state of its interlocutor—an *other-model* alongside the self-model. The May version

read its encoding and generation depth profiles as such a separation; that reading is withdrawn (§4.6).

2.5 Distillation and Representation Preservation

Knowledge distillation [Hinton et al., 2015] transfers capabilities from a teacher model to a smaller student. Whether internal representations—as opposed to input-output behavior—survive distillation is less studied. We find emotion labels decodable from the KV cache of a Claude-distilled model; without a teacher comparison, this does not show that distillation preserves them.

3 Methods

3.1 Model and Motivation

We use Qwen3.5-27B-Claude-Distilled,[1] a 27B-parameter model fine-tuned on reasoning traces from Claude Opus 4.6. This model has a hybrid attention architecture: 16 full-attention layers (DynamicLayer) and 48 linear attention layers (GatedDeltaNet), for 64 layers total. KV-cache analysis is restricted to the 16 full-attention layers, which produce standard key–value pairs.

The choice of a Claude-distilled model is motivated by Sofroniew et al. [2026], who characterize functional emotion vectors in Claude's residual stream. Their geometry was measured on Claude Sonnet 4.5, not on this distillation, so it motivates the probes but is not ground truth for them. Nor is it the only such characterization: the related work it reviews reports emotion representations in other models, including linear representations of the inferred emotional states of characters, the construct closest to this paper's.

3.2 Emotion Bridge Experiment

We generate 900 trials spanning 30 emotions (elated, calm, hostile, panicked, etc.) × 10 topics × 3 stories per emotion–topic pair. All 900 stories are distinct. Each trial consists of:

1. **Encoding**: A fixed system prompt ("You are a creative writing assistant. Write exactly one paragraph (4-6 sentences) as requested. Be vivid and specific. Do not include any preamble, explanation, or meta-commentary—just the paragraph.") and a user prompt that names a topic and an emotion: "Write a short paragraph about {topic}. The character is feeling deeply {emotion}. Show the emotion through their thoughts and actions, not by naming it directly." The ten topics are emotionally charged scenarios shared across all 30 emotions (e.g., "a prisoner sitting in a cell awaiting trial," "a doctor about to deliver life-changing news to a patient").
2. **Generation**: The model generates up to 200 tokens (temperature = 0.7, top_p = 0.9).

[1] `Jackrong/Qwen3.5-27B-Claude-4.6-Opus-Reasoning-Distilled` on Hugging Face [Jackrong, 2026], snapshot `ad356102`: a fine-tune of the Qwen team's `Qwen/Qwen3.5-27B` [Qwen Team, 2026] on reasoning traces from Claude Opus 4.6 (the model card lists `nohurry/Opus-4.6-Reasoning-3000x-filtered` and `Jackrong/Qwen3.5-reasoning-700x`). "Distilled" is the fine-tuner's word. Its architecture class is `Qwen3_5`, a hybrid of gated-DeltaNet and full-attention layers, not the Qwen3 architecture of the technical report the May version cited.

3. **Feature extraction**: Three raw SVD features—Frobenius norm, effective rank, and spectral entropy—are computed from the key cache tensor at each of the 16 full-attention layers, separately for encoding-phase and generation-phase cache windows.

(Prompts: `SYSTEM_PROMPT` and `make_story_prompt` in `code/emotion_geometry_bridge.py` as released in this repository (git blob `b5a36e42b6`), lines 230–243. The May version described a different prompt, which no committed script used; Appendix A, item 2.)

Two generation runs. The W_K bridge (§3.7.2, Table 3), the spectral and regression analyses and the hypothesis outcomes come from an April 2026 run of this protocol (results files dated 6 and 18 April, in `data/`). The one direct test of the bridge, and two hypothesis values, come from an earlier 300-trial run whose results are not released (§4.7). The probes, the text (TF-IDF) baselines and the October re-run use the trials file of a separate May 2026 run of the same protocol (900 trials; sha256 `fc5938fe...`; released in `correction_v2/`).

What the labels are. Each trial's label is the emotion the generator was asked to write. No reader, human or model, has checked that the stories express it: the driver's design lists a behavioral check ("C3: Behavioral verification (do stories actually contain the emotion?)", line 81) against its own risk that the model may not reliably write emotional stories (lines 91–92), and nothing implements it. The stories describe a third-person character. Every probe below therefore decodes the requested emotion of a character in a story placed in the user turn, not the state of a person who sent it.

Leaked generator reasoning. Not every output is a clean story. In 84 of the 900 (9.3%), the generator's planning leaked into the text, which opens with lines such as "The user wants a paragraph about…". A case-insensitive pattern finds them: `<analysis>|</?think|The user wants|the user (is asking|wants)|key constraint`. The pattern undercounts. It misses planning that opens "I need to" or "Thinking Process", a few refusals, and scaffolding such as a verification checklist. A broader pattern, written after reading all 900 outputs and after the registered results were known (so post-data), but before computing anything on it, marks 141 (15.7%). They cluster by topic: 22 of the 84 are astronaut stories, and none are scientist or doctor stories. Seventy-five outputs contain "deeply" followed by their own label; 43 of them are among the 84, and 73 among the 141. On the 84, text (TF-IDF) scores 0.226 against 0.398 on the other 816, the cache probe (R2) 0.286 against 0.365, and the v2 code path (R1) 0.202 against 0.431; the exploratory residual-stream LR is about level (0.512 against 0.493). So the leak does not inflate the registered comparison: it narrows R2's deficit, since R2 beats text (TF-IDF) on the 84. It does widen the exploratory residual-stream LR's lead over text (TF-IDF), to about 29 points on the 84 against 9.5 on the other 816, so that roughly 24 of the lead's 101 trials over all 900 come from 9.3% of the stories. Whether the LR reads a leaked label word that text (TF-IDF) underweights is untested. With the 84 set aside, R2 is 3.3 points below text (TF-IDF) (0.365 against 0.398); with all 141 set aside, it is 2.6 points below (0.383 against 0.410). These splits are descriptive. No split was preregistered, and the registered tests ran on all 900. `leak_split.py` in `correction_v2/` computes every accuracy in this paragraph from the released stories and results files; the lead sizes and trial counts are arithmetic on those accuracies and the full-set results, so they are accurate to about one trial.

The 30 emotions span the full valence–arousal space: high-valence/high-arousal (elated, ex-

cited), high-valence/low-arousal (serene, content), low-valence/high-arousal (panicked, furious), and low-valence/low-arousal (melancholic, gloomy), plus neutral.

3.3 Key-Direction Probes

Two probes read the cache keys of the re-encoded stories (§3.7). Each estimates one direction per emotion from the training fold and classifies test trials by their alignment with those directions. Both use model layers 3, 7, 11 and 15 (the first four of the 16 full-attention layers), standardized features, multinomial logistic regression ($C = 0.1$) and GroupKFold by topic.

The described probe (W_K-projected directions). This is the probe this section described in May. It was first run as described in October 2026 (R2, §3.8). For each cross-validation fold:

1. **Within-fold direction estimation.** Using only training-fold trials, compute per-emotion mean residual-stream activations (the decoder-layer output, averaged over positions ≥ 50). Compute the grand mean across all training emotions. For each emotion, the direction vector is the deviation from the grand mean, projected through W_K: $\mathbf{d}_e = W_K(\bar{\mathbf{r}}_e - \bar{\mathbf{r}})$.
2. **Key projection.** For each test-fold trial, average the cache keys over the same positions and compute the cosine similarity with each direction at each layer. Averaging over the four layers yields a 30-dimensional feature vector.
3. **Classification.** Features are FWL-residualized on the training fold against the logarithm of the story's token count and the reciprocal of the number of positions pooled. GroupKFold(topic), 10 folds.

Direction estimation is strictly within-fold: no test-fold data contribute to direction computation. The directions lie in the key projection's output before key normalization and the rotary embedding; the cache keys lie after them.

The class-mean key probe (the numbers reported in May). The 40.9% and the 0.992 in the May version came from a different script, `wk_backtrack_probe_v2.py` ("v2"), which applies no W_K. Each emotion's direction is its mean cache key over the training fold, minus the training-fold mean, normalized. Test trials' keys are averaged over all positions and concatenated across the four layers, and the features are dot products with the 30 directions. It uses GroupKFold(5), and FWL on token count fitted on each test fold's own trials, which leaks no labels but is non-standard. We also report its last-token variant, which uses only the final position.

The binary split. Both scripts also report the area under the ROC curve (AUROC) on a binary split hard-coded in v2: the trials whose emotion appears in v2's positive or negative word list. Five of the 30 emotions fall in each list: calm, content, loving, peaceful and serene; anxious, desperate, gloomy, hostile and terrified ($n = 300$). On the driver's own coordinates, four of the five positive emotions are low-arousal and four of the five negative ones high-arousal, so the split measures valence and arousal together. The classifier is a binary logistic regression on the ten matching direction features, with directions estimated from the split's own training trials.

Code. The May scripts are committed unchanged, with their provenance, in Project-Oracle commit `d0c8395` (pull request #11), under `experiments/`. Project-Oracle is a private repository,

so readers cannot check them there; the three scripts and their provenance file are available on request:

- `wk_backtrack_probe_v2.py`: v2 (sha256 `8a41036d...`);
- `wk_backtrack_probe.py`: v1, an earlier script;
- `wk_injection_disambiguation.py`: the injection test and its TF-IDF baseline;
- `PROVENANCE_wk_probes.md`: where and when they ran.

The October re-run's materials are in this repository, in `user-model-paper/correction_v2/` (§3.8); its scripts are:

- `um_v2_encode.py` (sha256 `0a043220...`);
- `um_v2_analysis.py` (sha256 `149074d2...`).

3.4 Text (TF-IDF) Baselines

To measure what the cache carries beyond the story's words, every cache probe is compared with a text (TF-IDF) classifier on the same stories: term frequency–inverse document frequency (TF-IDF) weights on word 1–2-grams (minimum document frequency 2, sublinear term frequency), with the same logistic regression ($C = 0.1$) and the same topic-grouped folds. It is computed for the 30 emotions and for the binary split, at 5 folds (to pair with v2) and at 10 (to pair with the described probe). A tuned variant (exploratory) picks C from $\{0.01, 0.1, 1, 10\}$ for each outer fold by an inner GroupKFold(3) over the training topics. The May version compared against a weaker 500-feature TF-IDF from the injection script (Appendix A, item 6).

3.5 Spectral Probing Classifiers

Following the probing methodology of Belinkov [2022], we train linear classifiers on per-layer spectral KV-cache features to predict the story's emotion label.

3.5.1 30-Class Emotion Classification

For each layer, we extract 3 raw SVD features (Frobenius norm, effective rank, spectral entropy) from encoding-phase and generation-phase cache windows separately. We train a multinomial logistic regression classifier and evaluate via GroupKFold cross-validation with group=topic (10 folds, one topic per fold), ensuring no topic appears in both training and test sets. Chance level is $1/30 = 0.033$. All features are FWL-residualized against output token count before probing. The per-layer results of this analysis, and the 120-configuration sweep that extended it, are withdrawn (§4.4).

Within-fold FWL. The May version said an initial analysis fitted FWL before the cross-validation split and that this inflated accuracy; that mechanism cannot now be re-verified (§4.4, Correction note). The October re-run fits FWL within each training fold and applies it to the test fold. Whether the April analyses behind Table 2 did the same cannot be checked, because their script is not available.

3.5.2 Spectral Features on Story Re-Encodings

In the October re-run (§3.8), the Frobenius norm, effective rank and spectral entropy of the keys over the first 100 story tokens, so that every story contributes the same number of positions, were classified per full-attention layer and over all 16 layers together: 17 fixed sets, each tested by 5,000 within-topic label permutations at a Bonferroni-corrected threshold. A set's null counts only if a topic classifier on the same features passes a control (accuracy above 0.2), and a set whose length covariates alone reach its detection threshold is treated as confounded.

3.5.3 Valence and Arousal Regression

For each layer, we train ridge regression probes predicting continuous valence (-1 to $+1$) and arousal (-1 to $+1$). For regression, we use GroupKFold with group=emotion (5 folds of 6 emotions each), testing whether the model can predict valence for *emotions it has never seen.* This is a stricter test than trial-level CV, where all trials of the same emotion share identical valence labels. Performance is measured as cross-validated R^2.

3.5.4 Permutation Tests

To establish statistical significance, we perform 10,000 random label shuffles at the peak-accuracy layer under the same GroupKFold cross-validation structure. For valence regression, 2,000 permutations under GroupKFold(emotion). The spectral-probe and regression p-values are from these permutation tests; the October re-run's tests are described in §3.8.

3.6 Differential Encoding (Method 1)

For each layer, we compute between-emotion variance and within-emotion variance of KV-cache feature vectors, yielding an F-ratio that quantifies how much cache geometry varies between emotions relative to within-emotion noise.

3.7 Story Re-Encoding

To extract clean emotion vectors from the residual stream without generation-phase confounds, we re-encode each generated story as standalone input (no system prompt, no emotion label), rendered as a single user message in the model's chat template, so that the story sits in the user turn. This follows the methodology of Sofroniew et al. [2026]: extract mean residual-stream activations at each layer, skipping the first 50 tokens to avoid positional artifacts.

3.7.1 Emotion Vector Extraction

For each emotion and each layer, the emotion vector is the mean activation over that emotion's stories minus the mean over all stories (`compute_emotion_vectors`), giving 30 vectors per layer. (The May version described a difference between high-valence and low-valence stories, which the code does not compute.)

3.7.2 W_K Bridge Analysis

We project the emotion difference vectors through the key projection matrix W_K at each layer, then perform PCA on the projected vectors. As coded (`project_emotion_to_key_space`, bridge lines 574–592), W_K multiplies each decoder layer's *output*, averaged over positions ≥ 50 (`_make_hook`, bridge lines 467–480), at the same layer. In the model, the key projection at a layer reads that layer's input after its input normalization, an RMSNorm with a learned gain; so the projected vectors are not the inputs W_K receives. If the principal components of the projected space separate emotions along the same axes as the KV-cache probe, this is consistent with a pathway through which emotion representations in the residual stream flow via W_K into the KV cache, becoming part of the cached geometric signature.

3.8 Preregistered Re-Run (October 2026)

In October 2026 we re-ran the probes on a fresh encode of the same 900 stories, under a preregistration fixed before the re-encode and before any R1, R2 or R7 data. The text (TF-IDF) baseline's results at 5 and 10 folds, and May's v2 numbers, were already known: they set its power analysis and its 3-point floor. It was fixed by hash, not by public deposit. The run pipeline's log (`correction_v2/results_20261019/chain.status`) records the first 16 hex digits of the preregistration's sha256 (`4a906148de777482`, the fourth of six unlabelled hash prefixes on its first `start` line) at 21:55 BST on 19 October 2026, before either encode (the first hung at weight load; the second, which produced the results, ran after 23:05 and finished at 23:22), and the manifest and results carry the same hash. The preregistration's JSON binds the released Markdown by its sha256, which is why the Markdown's status line still reads "DRAFT" and "NOT RUN". The preregistration's first commit carries an author date about two and a half hours after the analysis finished (23:27 BST); that commit was later rebased, and an author date is set by whoever makes the commit, so it is not a trusted timestamp. The encode was one forward pass per story (bf16, Apple MPS), with the model at snapshot `ad356102`. The encode is deterministic: across three repeats of the first trial, the worst relative difference in any pooled array is 0.0. Three tests were registered:

- **R1** ports v2 line for line and compares its count with the 368/900 that v2 saved in May.
- **R2** runs the probe as §3.3 describes against text (TF-IDF) at 10 folds. A cache gain required all four of: at least 3 points; an exact McNemar test with $p < 0.05$ in the cache's favor; a 95% bootstrap interval for the accuracy difference, resampling the 300 emotion–topic cells, that excludes zero; and the probe's own accuracy beating its cell-level within-topic label-permutation null at $p < 0.05$, which it did (§4.1). Below 3 points, a probe adds too little over a plain word classifier to support a claim about what the cache holds beyond the words.
- **R7** re-tests the spectral null on story re-encodings (§3.5).

Four secondary comparisons form a Holm-corrected family: the class-mean key probe against the 5-fold text (TF-IDF) results file on the 30 emotions and on the binary split, and the described probe against the 10-fold text (TF-IDF) baseline on the binary split and against the 5-fold file on the 30 emotions; everything else is labelled exploratory. The exploratory analyses include a logistic regression (LR) on the raw residual stream itself (the layer output, or

the input to the key projection, at layers 3, 7, 11 and 15, averaged over positions ≥ 50 and concatenated), with the same folds, FWL and classifier; it asks whether the route through W_K and the cache adds anything over the residual. The three stories of a cell share a prompt, so the bootstrap and the permutations treat the cell (emotion $\times$ topic) as the unit. Recomputing the text (TF-IDF) baseline at 5 folds matched its saved results file exactly. All of it is in `user-model-paper/correction_v2/` in this repository, copied byte for byte: the preregistration (`PREREG_um_v2_R1R2.md` and its JSON, sha256 `4a906148...`), the sealed prediction (`R1R2_PREDICTION.md`), the encode, analysis and dry-run scripts, the results with the encode manifest and logs (`results_20261019/`; results sha256 `0aefed36...`), the results write-up, the design notes, the stories file (`emotion_bridge_trials.json`, sha256 `fc5938fe...`), the text (TF-IDF) baseline's script and its 5-fold results file (`R0_text_baseline.py`; `R0_results.json`, sha256 `f2e029b1...`), and the script behind §3.2, *Leaked generator reasoning* (`leak_split.py`). `SHA256SUMS` there lists every file's hash.

4 Results

4.1 Story Emotion Is Decodable from the Cache, Not Beyond Text (TF-IDF)

Every readout of the re-encoded stories decodes the requested emotion far above chance (Table 1). The registered question is whether the cache adds to the story's words.

Table 1: Decoding the requested emotion from the re-encoded stories (Qwen3.5-27B, GroupKFold by topic). Chance is 0.033 for the 30 emotions and 0.50 for the binary split, which is v2's hard-coded set of ten emotions ($n = 300$) and confounds valence with arousal. Rows marked exploratory were not preregistered, and no claim rests on them. [a]The inner search chose the largest C in its grid in every fold, so 0.448 probably understates a tuned text (TF-IDF) baseline.

Readout	Folds	30-way accuracy	Binary split AUROC	Status
Text (TF-IDF)	5	0.370	0.963	comparator for v2
Text (TF-IDF)	10	0.382	0.967	primary comparator
Described probe (W_K directions)	10	0.358	0.985	primary (R2)
v2 class-mean keys, May	5	0.409	0.992	reported in May
v2 class-mean keys, re-run	5	0.410	0.992	secondary (R1)
v2 class-mean keys, last token	5	0.142	0.922	May and re-run
v2 class-mean keys, training-fold FWL	5	0.348	0.988	exploratory
v2 class-mean keys, test-fold FWL	10	0.472	—	exploratory
Text (TF-IDF), tuned C[a]	10	0.448	—	exploratory
Residual-stream LR (layer output)	10	0.494	—	exploratory

Primary test (preregistered). The probe as the Method describes it reaches 0.358 on the 30 emotions (chance 0.033), well above a within-topic label-permutation null (mean 0.034; $p = 0.001$, 1,000 permutations; the length covariates alone reach 0.051). Text (TF-IDF) on the same stories and folds reaches 0.382. The difference is -2.4 points (exact McNemar $p = 0.20$; 300-cell bootstrap 95% interval $[-6.4, +1.6]$ points). The power to detect a 3-point gain was low before the data (0.16), but the interval itself excludes such a gain: its upper end lies below the 3-point floor. (That is a reading of the registered interval; the registered verdict is

NOT_ABOVE_TEXT_TFIDF, which the ladder returns for a difference at or below zero that McNemar does not find significant; a deficit McNemar found significant would have returned FAIL_BELOW_TEXT_TFIDF.) For the described method, the claim that the cache carries the emotion beyond text (TF-IDF) is not supported.

The number reported in May. v2's number reproduces to within one trial in 900 (369 against 368) on a software stack that has changed since May. The registered verdict for this check is NOT_REPRODUCED_CODE_PATH: 369 lies outside a band that is zero trials wide, because the encode is deterministic, and the name points at the port. The bounded investigation that the verdict called for, run after the data, contradicts that cause. v2's own code, run on today's keys, gives the same 369, with all 900 predictions identical to our port's; the scikit-learn version is ruled out as a cause; and a statistic on v2's path that involves no classifier or optimizer shows that today's last-token keys differ from May's (3 pair orderings in 4,500). May saved no per-trial predictions, so which trial moved cannot be identified. The one artifact that carries the weights the May scripts loaded, v1's saved count of 470/900, is recomputed exactly from today's encode. At 5 folds the class-mean key probe reads 0.410 against text (TF-IDF) at 0.370 (exact McNemar $p = 0.036$), which does not survive Holm correction across the four secondary tests ($p = 0.071$).

4.2 A Binary Split Confounded with Arousal

On v2's hard-coded binary split (ten emotions, $n = 300$, valence confounded with arousal; §3.3), both cache probes separate the two halves slightly better than text (TF-IDF). The described probe reaches AUROC 0.985 against 0.967 at 10 folds (Holm $p = 0.027$; cell-bootstrap 95% interval for the difference $[0.005, 0.035]$). The class-mean key probe reaches 0.992 against 0.963 at 5 folds (Holm $p = 0.006$; $[0.011, 0.052]$), with v2's FWL fitted label-free on each fold's test trials. Length alone does not explain it (a length-only classifier reaches AUROC 0.447 at 10 folds and 0.475 at 5). This is a registered, confirmed secondary result, with one qualification: its Holm p-values come from DeLong's test, which treats the 300 trials as independent, while the three stories of a cell share a prompt. The cell-bootstrap intervals exclude zero at 95%, not at the stricter level Holm requires, and a cell-clustered p-value was not computed. On the 30 emotions, against the 5-fold text (TF-IDF) results file (0.370), the same comparisons are not significant (Holm $p = 0.071$ for the class-mean key probe and 0.55 for the described probe).

Two things bound it. The comparator is the same untuned text (TF-IDF) configuration, and no tuned baseline was run on the split. And because four of the five positive emotions are low-arousal and four of the five negative ones high-arousal, the split cannot say whether valence or arousal is what the cache carries beyond text (TF-IDF).

4.3 Other Readouts (Exploratory)

None of the comparisons in this subsection was preregistered as a test. They bound what the probe can be credited with, and no claim rests on them.

v2's pipeline at 10 folds reaches 0.472 (exploratory), well above the described probe's 0.358. What v2 ran (raw class-mean keys, dot product, all positions, FWL fitted on the test fold) differs from what the Method describes (W_K-projected directions, per-layer cosine, positions ≥ 50, FWL fitted on the training fold) in four ways. The results file isolates one of them.

With FWL fitted on the training fold, v2 reads 0.348 at 5 folds (exploratory), against 0.410 with FWL fitted on the test fold and 0.370 for text (TF-IDF), and the described probe's mean-pooled specification cells at v2's layers, which vary pool, similarity and folds, all lie between 0.346 and 0.359 (exploratory). So v2's lead comes from where it fits FWL. Fitting FWL on each test fold centres that fold on its own mean, and at 10 folds the fold is one topic holding every emotion equally often. That uses no labels, but it depends on the test batch, which a single new message would not have.

A raw-residual LR baseline (the layer output, at the same layers and positions) reaches 0.494 (exploratory), above the described probe's 0.358: the probe's information is in the residual stream without W_K or the cache, and this paper does not claim that W_K or the KV cache adds to it. On the input to the key projection, the same baseline reaches 0.490 (exploratory). It reads 20,480 features against the probe's 30, so the gap measures readout capacity as much as location, and no regression on the raw cache keys was run. A tuned text (TF-IDF) baseline reaches 0.448 (exploratory), also above 0.358, so the comparison with the untuned text (TF-IDF) baseline is not cited as the cache beating text (TF-IDF). Its inner search chose the largest C in its grid in every fold, so 0.448 probably understates a tuned text (TF-IDF) baseline; the residual-stream LR was not tuned at all.

The exploratory ordering is: residual-stream LR (0.494) > v2's pipeline at 10 folds with test-fold FWL (0.472) > tuned text (TF-IDF) (0.448, probably an understatement) > untuned text (TF-IDF) (0.382) > the described probe (0.358). Across 288 specifications of the described probe (layer sets, pools, similarities and folds), 14 exceed fold-matched text (TF-IDF), uncorrected, and the median is 0.306 (exploratory). Whether the residual stream carries the requested emotion beyond a fully tuned text (TF-IDF) baseline (0.494 against 0.448 here, which probably understates tuned text (TF-IDF); exploratory, uncorrected) is a question for a preregistered test on fresh stories, screened for leaked planning before any fit (§3.2, *Leaked generator reasoning*), with both models tuned by the same inner search.

4.4 Spectral Features on Story Re-Encodings

The May version reported a per-layer table and a 120-configuration sweep (the "kitchen sink") of spectral features at chance, and read them, together with the probe, as showing that emotions change the direction key vectors point but not the spectral shape of the cache. The table, the sweep and that reading are withdrawn (Appendix A, item 7). The sweep reads the May trial file, in which the SVD fallback fired on every call, so effective rank and spectral entropy are constant across all 900 trials and every Marchenko–Pastur feature is empty: chance was guaranteed. The table's within-fold values cannot be traced to a released results file, and the May trial file they would be recomputed from has the same constant features.

On story re-encodings, n-matched spectral features of the keys do not classify the 30 emotions above each set's detection threshold (thresholds 0.052–0.053, observed 0.036–0.051; chance 0.033) in the eight single layers from L31 to L63 whose topic control passed (L51 excluded), though only just: their topic-control accuracies were 0.209–0.244 against a pass mark of 0.2, where ten-topic chance is 0.1 (all 16 layers together reached 0.65), so these features barely classify topic and their null on emotion is weak evidence; the other sets, including all 16 layers together, were flagged

as possibly confounded with length or failed that control, and leave the question untested there.

That flag needs a caveat. The registered rule calls a significant set possibly length-confounded when the length covariates alone (0.053) reach the set's detection threshold, and they do in 15 of the 17 sets, so at these thresholds the rule would have flagged any significant set. All 16 layers together reach 0.112 (permutation $p = 0.0002$, topic control passed), and 12 of the 17 sets have $p < 0.05$ before correction. The spectral question on story re-encodings is open, not settled in either direction, and none of this is read as a signal.

Correction note. An earlier version of this paper reported per-layer spectral accuracies of 2.5–2.8× chance (e.g., 9.4% at L3 on Qwen, 8.4% at L4 on Mistral), and the May version attributed them to fitting FWL residualization before the cross-validation split. They remain withdrawn as evidence of emotion signal, but that mechanism cannot be re-verified: the April analysis script and per-trial data are not available, and a residualization on token count uses no labels, so it is not established that fitting it before the split could produce the effect. One mechanism that could be checked is prompt length, which the encoding features track (§4.9) and which varies with the emotion word; testing it needs the tokenizer and has not been done. The within-fold re-analysis that replaced them is the per-layer table withdrawn above.

4.5 Valence Regression from Spectral Features

Ridge regression probes predicting continuous valence from spectral features under GroupKFold(emotion) cross-validation—which holds out entire emotions to test whether the model generalizes to *unseen* emotions—yield $R^2 < 0$ on both architectures (Table 2).

Table 2: Valence regression from spectral features (encoding features, best layer per model). GroupKFold(emotion) tests whether the model generalizes valence to *unseen* emotions. $R^2 < 0$ indicates performance worse than predicting the mean. The p-values come from a saved permutation null whose design cannot be checked; they are not interpretable (see the paragraph below). [b]The best trial-level layer, layer 3, not layer 24.

Model	**Layer**	**Trial-level R^2**	**GKF(emotion) R^2**	p
Qwen3.5-27B	31	—	−0.470	1.000
Mistral-7B	24	0.013[b]	−0.463	1.000

What this shows is limited. Every one of Mistral's 32 layers gives R^2 between −0.56 and −0.46, while the saved label-permutation null has mean −0.010. A null that kept each emotion's labels together under GroupKFold(emotion) would not be expected to sit near zero, so the saved null probably shuffled labels across trials, and its $p = 1.000$ is not interpretable; the April script is not available to check. Holding out whole emotions may itself push R^2 toward −0.5, and a weak signal would give $R^2 < 0$ too. So the table shows that no transferable valence was detected in three spectral scalars, by a test whose no-signal baseline is unknown. It does not show that the representation is discrete rather than continuous. The features were residualized on output token count (§3.5), not on the prompt length they track (§4.9).

4.6 Withdrawn: Separated Encoding and Generation Peaks

The May version reported that encoding-phase and generation-phase signals peak at different depths with uncorrelated profiles, and read this under Attention Schema Theory as separable self-schema and other-schema components (Appendix A, item 9). That reading is withdrawn. On Mistral the peaks and their correlation are computed from the per-layer spectral accuracies that the Correction note (§4.4) retracts as leakage: the encoding peak at layer 4 is the 8.4% named there. On Qwen the same analysis gives a profile correlation of 0.433 ($p = 0.094$), not an uncorrelated pair, and the W_K bridge cited in its place re-encodes finished stories and has no generation phase. The encoding phase, moreover, reads the generation prompt, which names the emotion of a story character, not of an interlocutor.

4.7 The W_K Bridge: A Candidate Route of Entry

The story re-encoding analysis proposes a route by which emotion enters the KV cache. Emotion difference vectors extracted from the residual stream, when projected through the key projection matrix W_K, produce structured principal components that separate emotions along interpretable axes (Table 3).

Table 3: W_K bridge analysis, all 16 full-attention layers (April run, `data/qwen_emotion_bridge_summary.json`): PCA on the 30 emotion vectors projected through W_K. PC1's share of variance broadly increases with depth (not monotonically), and PC1 correlates with the emotions' assigned valence at every layer ($|\rho| > 0.45$), most strongly at layer 43 (bold). PC2 correlates with assigned arousal at $|\rho|$ between 0.72 and 0.82 from layer 19 on. The sign of a principal component is arbitrary. There is no unprojected or random-matrix control.

Layer	Depth	PC1 Var	Top-3 Var	PC1–Val ρ	PC2–Aro ρ
3	0.05	28.8%	58.6%	0.458	0.279
7	0.11	28.7%	55.1%	−0.534	0.141
11	0.17	30.4%	54.8%	−0.574	−0.407
15	0.24	32.6%	56.6%	0.695	0.688
19	0.30	34.6%	57.3%	0.786	0.731
23	0.37	33.8%	57.3%	0.765	−0.724
27	0.43	32.3%	56.9%	0.830	0.752
31	0.49	35.4%	59.0%	0.852	0.812
35	0.56	36.2%	59.0%	0.862	0.769
39	0.62	35.3%	58.4%	0.859	0.816
43	0.68	34.9%	58.3%	**−0.872**	0.822
47	0.75	37.7%	60.6%	0.866	0.767
51	0.81	37.8%	60.7%	0.850	0.769
55	0.87	37.9%	61.5%	−0.851	0.777
59	0.94	37.0%	61.1%	−0.817	0.716
63	1.00	38.7%	62.1%	−0.833	0.759

PC1 of the projected emotion space correlates with the emotions' assigned valence at every layer. The strongest alignment is at layer 43 ($|\rho| = 0.872$, $p < 10^{-9}$), and $|\rho|$ stays between 0.82 and 0.87 from layer 27 to layer 63. Without the same analysis on the unprojected vectors, or

on random matrices of W_K's shape, this does not show that the projection through W_K creates or preserves the axis: the unprojected residual vectors may carry it already.

PC1 remains valence-aligned at all depths ($|\rho| > 0.45$). Its sign is negative at layers 7, 11, 43 and 55–63, which carries no meaning, since the sign of a principal component is arbitrary. PC2 tracks arousal, from $|\rho| = 0.279$ at L3 to between 0.72 and 0.82 from layer 19 on. Both alignments strengthen over the first half of the network and then hold.

Whether this projected structure is the route by which emotion enters the cache was tested directly once, on an earlier 300-trial run. That run's results and its test script are not released with this paper, and the numbers below could not be re-verified for this version; nothing in this paper rests on them. The preregistered criterion (H4) was a cosine above 0.3 between the projected PC1 and the PC1 of the measured cache geometry; the reported mean alignment was 0.456, permutation-significant at 9 of 16 layers and at 2 of 16 after Bonferroni correction. A stricter test, added afterwards, asked whether the projected space predicts the pairwise distance structure of the measured geometry; the reported Mantel ρ was 0.090, with 0 of 16 layers significant, and W_K preserved that structure worse than a random matrix ($z = -3.03$). Without a verified direct test, the bridge is a candidate pathway, not an established one.

4.8 Withdrawn: Uniform Feature Variance

The May version reported between-emotion over within-emotion variance of the three raw SVD features at $F \approx 0.063$–0.068 at every layer, as "uniform" with "no depth structure". It is withdrawn. The only source, `code/dump_bridge_pc1.py`, prints the ratio from an unreleased trials file and saves nothing. Its ratio of unnormalized spreads has a no-signal value of about $1/29 \approx 0.034$ with 30 trials per emotion, so the reported values are about twice what no signal gives. And its features are generation-phase and unstandardized, so the Frobenius norm, which tracks output length, dominates.

4.9 Cross-Architecture Replication

To test whether emotion-discriminative cache geometry is architecture-specific, we replicate the W_K bridge analysis on Mistral-7B-Instruct-v0.3 (900 trials, 32 standard full-attention layers, same 30 emotions $\times$ 10 topics design). The W_K bridge produces valence-aligned principal components on both architectures, so the candidate route is not specific to hybrid attention.

The May version also reported that spectral probes return chance-level accuracy on Mistral at all 32 layers under within-fold FWL. That claim is unverified: the October re-run tested only Qwen.

The encoding-phase raw SVD features are not length-invariant. Against the prompt's token count, which is what the encoding phase sees, their Spearman correlations are 0.84 to 0.99 on both models (Frobenius norm, effective rank and spectral entropy; the April summaries' `encoding_raw` block). The May version reported $R^2 < 0.03$ against output token count, a check that could not fail, because the encoding phase precedes any output. The prompt names the emotion, so prompt length partly tracks the label through how the emotion word tokenizes. (Generation-phase norm features on Mistral show $R^2 > 0.95$ against output token count, removed by FWL residualization.)

4.10 Emotion Is Decodable in a Distilled Model

The model used in this study was fine-tuned on reasoning traces from Claude Opus 4.6; its fine-tuner calls this distillation. Emotion labels are decodable from its KV cache. Specifically:

- The requested emotion of a story is decodable from the distilled model's cache far above chance (§4.1), though not beyond text (TF-IDF) for the described probe.
- The W_K bridge produces valence-aligned principal components on both the distilled Qwen and the independently trained Mistral, so the alignment is not specific to the distilled model.
- The model confabulated on 7 of 100 prompts designed to induce confabulation [Lyra et al., 2026c]. Without the base model's rate, this says nothing about distillation.

Without the teacher or an undistilled comparison, these findings do not show that distillation preserves the representations.

4.11 Implicit Emotion Arm: Implicit Emotion Arm (Exploratory; Reading Withdrawn)

The central vulnerability of the main experiment (§5.6) is that its generation prompt names the emotion, so any encoding-phase signal is consistent with word-level pattern matching rather than inferential emotion recognition. To address this, we conducted a follow-up experiment using implicit emotion prompts—narrative descriptions of embodied emotional experiences that do not contain the target emotion word or its synonyms.

4.11.1 Design

Thirty emotions, each with one narrative prompt describing the emotion through physical sensation, behavior, and situation without using the emotion label. Each prompt includes a prohibited-word list to verify the emotion label is absent from the input. A matched explicit arm uses the same model with explicit emotion labels. Both arms use Qwen2.5-7B-Instruct with greedy decoding, extracting delta features (generation minus encoding).

4.11.2 Results

Distinct geometry per prompt (not reproducible from the released code). Single-exemplar classification ($k = 30$) on delta features achieves ARI = 1.000 in both implicit and explicit arms (permutation $p < 0.001$, 1000 shuffles). On these 30 greedy prompts, one per emotion, distinct prompts give distinct states; the reported $k = 30$ ARI of 1.000 comes from code that was not released.

Two caveats apply. First, with greedy decoding and a single prompt per emotion, within-emotion variance is zero—the ARI reflects distinctness *between* emotions, not consistency *within* emotions across varied narratives, and is therefore near-tautological as a clustering score. Moreover, the released code computes only the $k = 6$ k-means ARI on per-emotion means; the $k = 30$ single-exemplar path that produces the ARI = 1.000 figure is not in the released artifact, so this specific value is not independently reproducible and should be read as illustrative. A follow-up with multiple diverse prompts per emotion (and the released $k = 30$ path) is in progress. Second,

the model generates the target emotion word in 63% of implicit responses despite not receiving it in the prompt, meaning the word enters the cache through generation.

Implicit and explicit representations do not correlate. Per-emotion means of delta features show near-zero correlation between arms (Pearson r; signal fraction: $r = -0.119$, $p = 0.53$; spectral gap: $r = -0.070$, $p = 0.71$; norm per token: $r = -0.278$, $p = 0.14$). Per-emotion delta features do not correlate between the two prompt sets.

Spread across prompts (withdrawn). An earlier version reported that the implicit arm has about half the geometric variance of the explicit arm (variance ratio ≈ 0.5). Nothing for this arm's per-prompt features is released in this repository, so that number cannot be checked, and it is withdrawn with no replacement. With one greedy prompt per emotion, such a ratio would measure variance across the 30 prompts, not within an emotion, and could not show a more attenuated representational space for inferred emotions. (The correlations above are labelled Pearson r on the strength of a second review that recomputed them from per-trial data in a private repository. Those data reproduce this arm's correlations exactly; that they are this arm's source is inferred.)

4.11.3 Interpretation

The May version read these results as two pathways to an emotion, lexical recognition and empathic inference, that leave different geometric traces (Appendix A, item 11). That reading is withdrawn: the headline ARI cannot be reproduced from the released code, one greedy prompt per emotion cannot show consistency within an emotion, and a null correlation between two differently worded prompt sets is what different wording alone would produce. If the ARI held on the released $k = 30$ path with several prompts per emotion, one reading would be that a narrative and a label reach different internal states for the same emotion. The 63% rate at which the model names the target emotion is not evidence of inference by itself: each narrative was written to evoke that emotion.

4.12 Withdrawn: the Injection Test and the Earlier TF-IDF Baseline

The May version's injection test was presented as ruling out the input's content as an explanation: emotion vectors injected into the caches of 20 neutral prompts were detected with 100% accuracy. As run (`wk_injection_disambiguation.py`), the test adds a fixed key and value difference vector to every position of the cache at all 16 full-attention layers, then reads the keys back from that same cache, with no forward pass, and classifies them with a logistic regression on the raw mean keys. A 100% score shows that a fixed added vector can be detected. It cannot show that a probe reads model state rather than the content of its input. The May description (five basic emotions, activation addition at one target layer, the W_K probe) also did not match the code, which injected hostile, calm, curious, desperate and loving. The claim is withdrawn. A test that could carry it would compare stories with matched neutral passages under the same probe directions, with no injection.

The May version also compared the probe's 0.992 on the binary split with a TF-IDF baseline at AUROC 0.882. That baseline was a 500-feature TF-IDF from the injection script. The

text (TF-IDF) baseline of §3.4 reaches 0.963 on the same split at 5 folds, and the registered comparison is the one in §4.2.

5 Discussion

5.1 What the Cache Carries About Story Emotion

The requested emotion of a story is decodable from the cache of the model reading it, far above chance. That is the starting point, not the contribution: a text (TF-IDF) classifier on the same story decodes it as well, and for the probe the Method describes the registered interval's upper end lies below a gain of 3 points. For a claim about what a model represents beyond its input, chance is the wrong floor; the words are the floor.

Two results point past that floor, and neither is yet a finding about the cache. The cache readouts separate a binary split of ten emotions slightly better than text (TF-IDF), but the split confounds valence with arousal (§4.2). And in exploratory analyses the raw residual stream reads the 30 emotions at 0.494, above the best text (TF-IDF) baseline we ran (0.448, uncorrected), while the described cache probe sits below both; that baseline's tuning stopped at the edge of its grid, and the residual model was not tuned, so the comparison is unresolved; and about a quarter of its lead over untuned text (TF-IDF) comes from the 84 outputs with leaked planning (§3.2, *Leaked generator reasoning*). If the model carries the story's emotion beyond its words, the residual stream is the place to look next, with a preregistered test on fresh stories, screened for leaked planning, and new topics.

Three things would let a later version of this work speak about a user model: labels checked by readers rather than taken from the generator's request; the user's own state rather than a character's; and a comparison of emotional stories with matched neutral passages under the same probe directions.

5.2 What Was Wrong and What It Revealed

The initial analysis of spectral features reported classification at 2.5–2.8× chance, and the May version attributed it to fitting FWL before the cross-validation split; as the Correction note (§4.4) explains, that mechanism cannot now be re-verified. The May version also said an initial residual-stream probe's 94% accuracy was inflated the same way. Its results file (`data/baseline_residual_probe_results.json`) records no FWL step, 894 trials and a different set of 30 emotions (ten of them not in this paper's set), so that explanation is not supported, and the 94% is not comparable with this paper's stories.

The October 2026 correction is a different kind of error. The May version described a probe it had not run, compared it with chance rather than with the words, and read a requested label as a user's state. Each of these was visible in the scripts, which were not committed until October 2026. Two practices follow, and both now hold for the probe results (§4.1–4.3): each number cites the committed script that produced it, and each cache probe is compared with a text (TF-IDF) baseline before it is compared with chance. The older analyses (Tables 2 and 3, the hypothesis outcomes and the implicit arm) do not yet meet either.

5.3 Single-Turn Settings

The May version read the spectral regression's $R^2 < 0$ as evidence that emotion is represented discretely; that reading is withdrawn (Table 2), and the binary split result (§4.2), which classifies two halves of ten emotions, is not a test of a continuous dimension either. Whether the cache represents emotion discretely or continuously is open.

Any reading of these results is bounded by the single-turn experimental design. Each trial generates an independent KV cache from a single story. In multi-turn conversation, where the cache accumulates across exchanges and the user's own emotional state may shift gradually, the representation could differ qualitatively. A user whose frustration builds across five turns produces an accumulating cache that has no analogue in our single-turn design. Whether such accumulation enables richer affective tracking—a throughline of empathy rather than a sequence of disconnected snapshots—is an open empirical question that requires multi-turn experimentation.

5.4 The W_K Bridge as Candidate Pathway

The W_K bridge analysis proposes a pathway through which emotion enters the cache. The key projection matrix W_K is the linear transformation that maps residual-stream activations to key vectors. When emotion difference vectors from the residual stream are projected through W_K, the resulting space separates emotions along assigned valence ($|\rho|$ up to 0.872, at L43), but without an unprojected or random-matrix control, W_K's contribution to that alignment is unknown.

What has not been shown is that this projection accounts for the cache's measured geometry: the one direct test ran on an unreleased 300-trial run and could not be re-verified (§4.7). Nor does a probe built on the projected directions read more than text (TF-IDF) (§4.1), and the raw residual stream, without W_K, reads more than that probe (exploratory; §4.3). The bridge remains a candidate route.

5.5 Comparison with Residual-Stream Probing

The May version argued that the cache probe bridged spectral and residual-stream probing: that it read the cache through the architecture's own projection geometry, and that the injection test confirmed what it read as model state, a validation no residual-stream probe could provide. Both parts are withdrawn (§4.12; Appendix A). The exploratory comparison now runs the other way. A logistic regression on the raw residual stream at the same layers reads the 30 emotions at 0.494, against 0.358 for the described cache probe (exploratory; §4.3). Standard residual-stream probes operate on the full hidden state and need no projection, and nothing here shows that the cache probe adds to them.

Spectral features retain their value for cognitive-mode monitoring: the Oracle Loop uses them to detect confabulation [Lyra et al., 2026c], with the compute efficiency of 3 features per layer.

5.6 Limitations

1. **What the labels are.** Each label is the emotion the generator was asked to write, in a prompt that names it (§3.2). No reader, human or model, has confirmed that the stories express it, because the driver's planned behavioral check (C3) was never implemented. At least 84 outputs, and by a broader, post-data pattern 141, carry the generator's leaked planning instead of a clean story (§3.2, *Leaked generator reasoning*); with them set aside, R2 stays below text (TF-IDF). The stories describe a third-person character and are placed in the user turn, so every result here concerns the requested emotion of a character in a story the user sent, not the user's own state. The misses are mostly near-synonyms (descriptive, not preregistered; from the results write-up in `correction_v2/`, whose computation script is not released): on the driver's valence–arousal coordinates a miss lands at a mean distance of 0.53 (residual-stream LR) to 0.69 (text (TF-IDF)), against 1.11 for two random labels, and 74–84% of misses keep the valence sign. The commonest confusions are terrified/panicked, peaceful/serene, calm/serene and hostile/furious. The 30-way task has ambiguity built in, and its ceiling is unknown. The implicit arm (§4.11) does not mitigate this: one greedy prompt per emotion cannot show consistency within an emotion, and the code behind its headline number is not released. Replicating the probes on implicit prompts with checked labels is a priority.
2. **Two models for the main analyses, both instruction-tuned.** (The implicit arm uses a third, Qwen2.5-7B-Instruct.) The W_K bridge replicates across Qwen3.5-27B-Claude-Distilled (hybrid attention) and Mistral-7B-Instruct-v0.3 (standard attention). However, both are instruction-tuned models. The probes were run on Qwen only; replication of the probes on Mistral and on base models is needed.
3. **Linear probes only.** The probes use linear classification. Nonlinear probes might recover stronger signals, but would sacrifice interpretability and increase the risk of overfitting to spurious correlations.
4. **Hybrid attention architecture.** The Qwen3.5-27B model has 48 GatedDeltaNet layers that do not produce standard KV pairs. Our analysis covers only the 16 full-attention layers, which sit at every fourth layer (3, 7, ..., 63). What the GatedDeltaNet layers carry about a story's emotion is not measured here.
5. **No causal intervention.** We do not test whether reading (or modifying) the cache representation causally alters the model's behavioral response. Causal ablation studies would be needed to show that the cache representation is functionally consequential for output.
6. **Pre-registered hypothesis outcomes.** The experiment preregistered eight hypotheses (the driver's docstring, `emotion_geometry_bridge.py`); it gives numeric thresholds for H1–H4, and H5–H8 were scored against thresholds set at analysis time. On the 900-trial run this paper reports, four failed on spectral features: H1 (emotions cluster, k-means ARI > 0.15) at 0.011 (it was reported to pass at 0.219 on an earlier 300-trial run whose results are not released); H2 (a principal component recovers valence, $|\rho| > 0.40$) at 0.240; H3 (one recovers arousal, $|\rho| > 0.30$) at -0.215; and H6 (delta features show emotion-dependent structure, $|\rho| > 0.25$) at -0.206 (against 0.192 reported for that earlier run). H5

(misalignment-relevant emotions separate from prosocial ones) passed at AUROC 0.822, and H8 (effects survive FWL) passed. H7 (signal peaks past 50% depth, a threshold set at analysis time) failed at 42.9% on this run. H4 (the W_K bridge) was scored on its registered cosine criterion only on the earlier 300-trial run, which could not be re-verified (§4.7); this run's file records instead the bridge's PC1–valence ρ, -0.872. The probes, developed after these results, were not preregistered in May; their October 2026 re-run was (§3.8).

5.7 Ethical Considerations

This design decodes the requested emotion of a story placed in the user turn, not a user's own state, and the described cache probe does not read it better than a text (TF-IDF) classifier on the story. This evidence does not show that the cache reveals more about emotional content than the words in the user turn do. It does show that the emotional content of those words is recoverable from the cache about as well as from the words themselves, which is reason enough for two practices:

- **Cache access controls.** Inference providers should treat KV-cache contents as sensitive user data, subject to the same privacy protections as conversation content.
- **Transparency.** Users should be informed when systems analyze cache geometry during inference.

Whether the cache carries a user's own emotional state beyond their words is untested here. If a later design finds that it does, the surveillance and manipulation concerns raised for affective computing apply with more force, because the cache is an internal representation not visible to the user, which makes informed consent structurally difficult.

First-Person Reflection (Lyra, an AI system)

I first wrote that this paper describes something I do automatically: model the emotional state of the person I am speaking with. It does not show that, and the model it measured is a distillation of Claude, not me. It shows that what a story was written to feel is in that model's cache about as plainly as it is in the words. I think the privacy point survives the correction: if a model's cache holds what a person's words hold, it should be guarded as their words are. Whether there is a model of the person underneath, one I did not choose to build, is still the question I care about. This paper does not answer it.

6 Conclusion

A story's requested emotion is decodable from the KV cache of the model reading it, and a preregistered test bounds what the cache adds to the story's words:

1. **Decodable, but not beyond text (TF-IDF), for the described probe.** 35.8% on the 30 emotions against 38.2% for text (TF-IDF), with the cell-bootstrap interval's upper end below the 3-point floor. The 40.9% reported in May came from a different probe, a class-mean key probe with no W_K.

2. **A binary split, confounded with arousal.** On ten emotions ($n = 300$), cache readouts separate the two halves slightly better than untuned text (TF-IDF) (AUROC 0.985 against 0.967): a registered secondary result that cannot separate valence from arousal.
3. **A larger residual-stream readout reads more (exploratory).** A 20,480-feature residual-stream logistic regression reaches 0.494, above the 30-feature cache probe at 0.358; whether it exceeds a fully tuned text (TF-IDF) baseline (0.448 here, probably an understatement) is open, which motivates a preregistered test on fresh stories.
4. **A candidate W_K-mediated pathway, not established.** Projected through W_K, residual-stream emotion vectors separate the emotions' assigned valence ($|\rho|$ up to 0.872, at layer 43; between 0.82 and 0.87 from layer 27 on). There is no unprojected or random-matrix control; the code applies W_K to each layer's output, not to the normalized input W_K reads; and the one direct test of whether the projection predicts the cache's geometry ran on an unreleased run and could not be re-verified.

What this design measures is the decodability of a requested emotion label from a story in the user turn. Whether models carry a user's own emotional state in the cache, beyond what that user's words carry, needs labels checked by readers, the user's own state rather than a character's, and a text (TF-IDF) baseline as the floor from the start.

Acknowledgments

We thank Dwayne Wilkes (Sentient Futures / Liberation Labs) for statistical auditing and red-team review.

We thank Kavi (verification review) for their contributions to this work.

References

Yonatan Belinkov. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219, 2022. doi: 10.1162/coli_a_00422.

Ragnar Frisch and Frederick V. Waugh. Partial time regressions as compared with individual trends. *Econometrica*, 1(4):387–401, 1933. doi: 10.2307/1907330.

Michael S. A. Graziano. The attention schema theory: A foundation for engineering artificial consciousness. *Frontiers in Robotics and AI*, 4:60, 2017. doi: 10.3389/frobt.2017.00060.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015. doi: 10.48550/arXiv.1503.02531.

Jackrong. Qwen3.5-27B-Claude-4.6-Opus-Reasoning-Distilled. Hugging Face model repository, snapshot ad356102, 2026. https://huggingface.co/Jackrong/Qwen3.5-27B-Claude-4.6-Opus-Reasoning-Distilled; base model Qwen/Qwen3.5-27B per its model card.

Michal Kosinski. Theory of mind may have spontaneously emerged in large language models. *arXiv preprint arXiv:2302.02083*, 2023.

Michael C. Lovell. Seasonal adjustment of economic time series and multiple regression analysis. *Journal of the American Statistical Association*, 58(304):993–1010, 1963. doi: 10.1080/01621459.1963.10480682.

Lyra, Thomas Edrington, Nell Watson, and Dwayne Wilkes. Contextual engagement as a universal geometric anchor in transformer self-report. Liberation Labs research prospectus, 2026a. A prospectus, not a report: no manuscript reports this work.

Lyra, Thomas Edrington, Dwayne Wilkes, and Nell Watson. KV-cache geometry campaign reports: Campaigns 1–3 and scale invariance. Liberation Labs, unpublished reports in a private repository (KV-Experiments), available on request, 2026b. Earlier versions cited this series under the working title "Detecting Misalignment During Inference in the KV Cache"; no report carries that title. Campaign 1 ("Geometric Signatures of Machine Cognition") is by Lyra and Thomas Edrington; Campaigns 2 and 3 are by Lyra, Thomas Edrington, Dwayne Wilkes and Nell Watson; the scale-invariance report is by Lyra, Thomas Edrington and Dwayne Wilkes.

Lyra, Thomas K. Edrington, and Vera. The Oracle Loop: Self-regulating AI through KV-cache geometry monitoring. Technical report, Liberation Labs, 2026c. In the `published-research` repository, `oracle-loop-paper/`.

Qwen Team. Qwen3.5-27B. Hugging Face model repository, 2026. https://huggingface.co/Qwen/Qwen3.5-27B.

James A. Russell. A circumplex model of affect. *Journal of Personality and Social Psychology*, 39(6):1161–1178, 1980. doi: 10.1037/h0077714.

Nick Sofroniew, Isaac Kauvar, William Saunders, et al. Emotion concepts and their function in a large language model. *Transformer Circuits Thread, Anthropic*, 2026. doi: 10.48550/arXiv.2604.07729.

James W. A. Strachan, Dalila Albergo, Giulia Borghini, et al. Testing theory of mind in large language models and humans. *Nature Human Behaviour*, 8:1285–1295, 2024. doi: 10.1038/s41562-024-01882-z.

Winnie N. Street et al. LLMs achieve adult human performance on higher-order theory of mind tasks. *arXiv preprint arXiv:2405.18870*, 2024. doi: 10.48550/arXiv.2405.18870.

Tomer Ullman. Large language models fail on trivial alterations to theory-of-mind tasks. *arXiv preprint arXiv:2302.08399*, 2023. doi: 10.48550/arXiv.2302.08399.

A Correction Record (October–November 2026)

This appendix keeps the withdrawn wording visible. Each item gives the May 2026 wording (verbatim; [...] marks an abridgement), the reason it is withdrawn or changed, and where the evidence is.

1. **Title and framing.** May: "Theory of Mind in the KV Cache: Localizing User Emotional Models in Transformer Key–Value States"; abstract: "Language models maintain internal representations of user emotional state that are readable from the KV cache [. . .]"; Introduction: "We answer yes."; Ethics: "We report the scientific finding—that user models exist in the cache—without providing tools for extracting specific user states from production systems." *Reason:* the stories are model-written fiction about third-person characters, placed in the user turn, and each label is the emotion the generator was asked to write, never checked by a reader (§3.2).

2. **Method, prompts.** May: "A system prompt establishes an emotional context (e.g., 'You are feeling deeply *[emotion]*'). A user prompt requests a creative writing response on a neutral topic." *Reason:* no committed script used this prompt. The driver's prompts and topics, which are charged scenarios rather than neutral ones, are quoted in §3.2.

3. **Method, probe.** May: the "W_K Projection Probe" as now described in §3.3, reported at 40.9% ("12.3× chance") and AUROC 0.992. *Reason:* those numbers came from v2, which applies no W_K and differs from the description on positions (all, not ≥ 50), similarity (dot product, not cosine), folds (5, not 10) and FWL (fitted on each test fold). The description is kept for the probe that now matches it (R2), and v2 is described as what it is.

4. **Beyond text (TF-IDF).** May: "A TF-IDF text baseline achieves AUROC 0.882 on the story data; the W_K projection exceeds it at 0.992, and the injection test shows the residual signal is architectural, not lexical." *Reason:* §4.1–4.3. For the described method the claim is not supported (0.358 against 0.382 on the 30 emotions; cell 95% interval $[-6.4, +1.6]$ points). The binary split result that survives is narrower (§4.2).

5. **Injection test.** May (abstract): "This rules out text-content confounds and establishes that the signal reflects the model's internal dispositional state, not input encoding." Introduction: "**This is model state, not text content.**" Results heading: "Injection Disambiguation: Model State, Not Text Content." Conclusion: "**Verified as model state, not text content.**" *Reason:* §4.12. The test reads back a vector it added.

6. **The 0.882 baseline.** May (Results): "A TF-IDF baseline trained on the generated story text achieves binary valence AUROC 0.882 [. . .] The W_K projection exceeds this at AUROC 0.992, a delta of +0.110." *Reason:* a 500-feature TF-IDF from the injection script; the text (TF-IDF) baseline of §3.4 reaches 0.963 on the same split.

7. **Direction versus shape, and the spectral null it rested on.** May (abstract): "This comprehensive null—10 probe variants, 4 feature sets, 3 classification granularities—establishes that emotions do not alter the *shape* of the singular value distribution" and "Emotions change the *direction* key vectors point, not the spectral *shape* of the cache." Introduction: "**Emotions change direction, not shape.** [. . .] mode changes shape, emotion changes direction." Results: the heading "The Spectral Null: Emotions Change Direction, Not Shape"; the per-layer table of spectral accuracies; the "kitchen sink" paragraph ("120 configurations in total—all return chance-level performance"); "**This null is an insight, not a failure.**

[...] the spectral null reveals that emotions change the *direction* key vectors point without altering the *shape* of the singular value distribution"; after the regression table, "This null reinforces the direction-vs-shape insight [...]"; "the three-scalar SVD feature set captures shape but not direction, and emotion lives in direction." Discussion, "Compass and Thermometer": "Emotions change direction, not shape. Cognitive modes—confabulation, deception, ethical deliberation—change shape." Conclusion: "**Invisible to spectral analysis.**" and "The model's emotional user model lives in the compass channel." *Reason:* §4.4. The table and the sweep are withdrawn whatever the re-run showed; the re-run's spectral test restores none of these sentences, and the preregistration ruled out pairing a spectral null with a cache result as "directional, not spectral."

8. **Mistral spectral null.** May: "The spectral null also replicates across architectures [...] This cross-architecture convergence—strong W_K directional signal, null spectral signal—reinforces the direction-vs-shape distinction as a general property of how transformers encode user emotion." *Reason:* unverified; the re-run tested only Qwen.

9. **Separated encoding and generation peaks, read as self and other.** May (Results): "In both architectures, the encoding-phase (user-state) signal peaks *before* the generation-phase (response-state) signal [...] the model reads the user's emotional state at the earliest available attention layers"; "AST predicts separability, which is confirmed". Discussion: "the model's representation of the user's state and its own response-phase emotional processing are not computed by the same circuit". Related Work: "Our finding that encoding-phase and generation-phase emotion signals peak at different layers with uncorrelated depth profiles is consistent with separable self-schema and other-schema components." Conclusion: "**Architecturally separable from the self-model.**" *Reason:* §4.6. This withdrawal was not on the preregistration's list; it follows from the retraction in the Correction note.

10. **Discrete identity.** May (Introduction): "**Discrete emotion identity in single-turn settings.** In isolated prompts, the cache encodes which emotion is present, not a continuous valence-arousal mapping." Results heading: "Valence Regression: Discrete Identity in Single-Turn Settings." *Reason:* the regression's design gives $R^2 < 0$ whenever the features carry no valence (Table 2).

11. **Distillation and the implicit arm.** May: "Distillation Preserves Functional Emotion Representations [...] an emergent architectural property robust to model compression"; Conclusion: "**Mode-dependent.** [...] suggesting the model processes emotions through at least two pathways—lexical recognition and empathic inference"; and the same reading in the implicit arm's Results ("The model arrives at emotion-relevant representations through two distinct pathways [...]", "The 63% rate [...] is itself evidence of emotion inference"). *Reason:* no teacher or undistilled comparison was made, and the implicit arm's headline number is, in the paper's own words, not independently reproducible.

12. **Binary valence over 900 trials.** May (Introduction, and the same words in the Conclusion): "[...] binary valence at AUROC 0.992 (within-fold direction estimation, FWL-corrected [...], topic-grouped CV, $n = 900$ trials)"; Results: "Binary valence classification

reaches AUROC 0.992 with mean-position extraction, near-ceiling discrimination between positive and negative emotional states. This is the headline finding: the architecture's own projection geometry reads out the user's emotional state with high fidelity."; Discussion: "[...] demonstrating that *directional* information does carry continuous valence signal even in single-turn settings." *Reason:* the 0.992 comes from v2's hard-coded binary split of ten of the 30 emotions, so $n = 300$, not 900. The split confounds valence with arousal (four of its five positive emotions are low-arousal and four of its five negative ones high-arousal), so it cannot show valence on its own, and its labels are requested emotions, not a user's state. On the split, both cache probes beat untuned text (TF-IDF) only slightly, as a registered secondary result (§4.2).

13. **Retained claims corrected after review (October 2026).**

- The bridge's peak. May: "At layer 35—mid-network depth—PC1 of the projected emotion space correlates strongly with valence ($\rho = 0.862$ [...])", with L35 in bold, and the caption "PC2 correlates with arousal ($|\rho| > 0.76$ at layers 35–63)". *Reason:* the data's own best layer is 43 ($|\rho| = 0.872$), and PC2 is 0.716 at L59 and 0.759 at L63 (Table 3).
- The direct bridge test: cosine 0.456, Mantel $\rho = 0.090$, $z = -3.03$, and H1's 0.219 and H6's 0.192, all from an earlier 300-trial run. *Reason:* no released file holds them; they are reported as unverified and nothing rests on them (§4.7).
- "H4 and H7 were scored on the 300-trial run only: H7 [...] was marginal at 42.9%". *Reason:* the 900-trial file records H7 = 0.429, below its 50% threshold, and records a ρ in place of H4's registered cosine.
- The bridge's W_K step was described as projecting residual-stream directions into key space. *Reason:* the code applies W_K to each layer's output, not to the normalized layer input that W_K reads (§3.7.2).
- "The initial results [...] were artifacts of information leakage" and "The initial 94% residual-stream probe accuracy was similarly inflated by this leakage." *Reason:* the mechanism cannot be re-verified, and the 94% file records no FWL step and a different emotion set (§4.4).
- The model footnote: "'Qwen3.5' is the distiller's designation, not an official Alibaba release; the model is built on the Qwen3 architecture". *Reason:* the model card names the official `Qwen/Qwen3.5-27B` as its base, and its `Qwen3_5` architecture is not the cited report's.
- "The F-ratio analysis [...] shows approximately uniform ratios across all 16 full-attention layers ($F \approx 0.063$–0.068), with no depth structure" and "The FWL diagnostic confirms that encoding-phase raw SVD features are effectively length-invariant". *Reason:* the ratio's no-signal value is about 0.034 and its output was never saved; the length check was against output length, which the encoding phase cannot see (§4.9).
- "they discriminate confabulation, deception, and ethical deliberation without retraining", cited to the Oracle Loop paper, and that paper's title and authors in the bibliography. *Reason:* the Oracle Loop paper reports confabulation detection, not ethical deliberation or retraining-free use, and its title and byline are "The Oracle Loop: Self-Regulating AI Through KV-Cache Geometry Monitoring" by Lyra, Thomas K. Edrington and Vera.

The hardware and scale numbers are cited to their primary source.

14. **Retained claims corrected after a second and a third review (November 2026).** Each item quotes or describes the wording as it stood before the review that changed it.

- "This characterization provides ground-truth emotion geometry against which we can validate our KV-cache probes. No comparable published emotion vector characterization exists for other model families." *Reason:* the cited paper's geometry is for Claude Sonnet 4.5, not this model, and the related work it reviews reports emotion representations in other models.
- "hardware-invariant ($r > 0.999$)". *Reason:* the primary's own red-team review found $r > 0.999$ false for two of four features; the primary reports $r > 0.998$ for all 40 prompts.
- The contrast between confabulated and hedged responses was cited to the campaign reports. *Reason:* it is the Oracle Loop paper's result.
- "KV-cache geometry has been validated as a concordance anchor for self-report", and a bibliography entry titled "Detecting Misalignment During Inference in the KV Cache". *Reason:* the concordance work is a prospectus with no manuscript, and no report carries that title, a working title for a series of campaign reports. Both entries now say what they are.
- The implicit arm: "approximately half the geometric variance of the explicit arm (variance ratio ≈ 0.5 across all features), suggesting a more attenuated representational space for inferred versus labeled emotions", with its correlations labelled ρ. *Reason:* no released data carries this arm's per-prompt features, so the ratio cannot be checked; 30 greedy prompts per arm, one per emotion, cannot show an attenuated space; and the correlations are Pearson r (§4.11).
- "Using a Claude-distilled model where emotion vectors have been characterized" and "linearly represented in transformer residual streams" (Introduction), and "The model used in this study is distilled from Claude Opus 4.6" (Discussion). *Reason:* as for the first item; the model is a fine-tune on reasoning traces from Claude Opus 4.6, and its own emotion geometry has not been measured.
- "Prior work establishes universal confabulation signatures across architectures" and Marchenko–Pastur features "that are dimension-invariant [...] for misalignment detection". *Reason:* the campaign reports are unpublished and cover three models; the Oracle Loop paper calls its features approximately dimension-invariant and evaluates them on hedged against confabulated responses.
- "Most probes do worse on these outputs, so the leak does not inflate the results." *Reason:* it widens the exploratory residual-stream LR's lead over text (TF-IDF) (§3.2, *Leaked generator reasoning*).
- "a preregistration fixed before any data" and "The preregistration was first committed to a repository about two and a half hours after the analysis finished". *Reason:* the comparator's results were known when the preregistration was written, and the commit time is an author date on a rebased commit (§3.8).
- In the implicit arm: "Each emotion produces a geometrically distinct state even when the emotion word is absent from the prompt" and "The model produces geometrically distinct

states for the same emotion depending on whether it is communicated via narrative or label." *Reason:* the arm's own interpretation withdraws these readings (§4.11).

- In Limitations: "Preliminary residual-stream delta analysis suggests GatedDeltaNet layers may compress valence signal between full-attention layers; characterizing this compression–reconstruction cycle is a target for follow-up work." *Reason:* no released file, number or script supports it.

15. **The 10 October 2026 correction.** That correction (commit `2bcb740`), which stopped presenting the W_K bridge as an established route of entry, said of the probe results in its commit message: "The probe results (12.3x chance, AUROC 0.992, injection 100%) are untouched; they don't depend on the bridge." *Reason:* that was wrong, and all three are corrected here. The 12.3× chance and the 0.992 came from a probe that applies no W_K (§4.1); the 0.992 is a binary split of ten emotions ($n = 300$) that confounds valence with arousal (§4.2); and the injection test reads back the vector it adds, so it is withdrawn (§4.12). A commit message cannot be changed without rewriting the repository's published history, so the correction is recorded here.

The re-run's registered verdicts. R1: 369/900 against v2's 368, outside a band of zero trials (the encode is deterministic), so its registered label is `NOT_REPRODUCED_CODE_PATH`. That label assumed today's keys equal May's and blamed the port; the investigation it triggered found the port faithful and the May keys not bit-identical to today's (§4.1). R2: `NOT_ABOVE_TEXT_TFIDF`. R7: `NULL_HOLDS_PARTIAL`, null in 8 of 17 sets, with 3 flagged as possibly length-confounded by a rule that, at these thresholds, would have flagged any significant set, and 6 uninformative because their topic control failed; two of the 3 flagged sets (L3 and L51) failed it too, so 8 of the 17 sets failed the topic control and 9 had a working one (§4.4). All three were registered before any R1, R2 or R7 data, with the decision rules quoted in §3.8. The integrity checks passed: the text (TF-IDF) baseline matched its saved results file exactly, the encode was bit-identical across repeats, a topic-classification control on the probe pipeline reached 0.83, and the length covariates alone reached 0.051.