Routing Commands: Router > -> user Mode -> display/sun Pouter # disasle -> enable mode Router tonfig terminal -> global mode : Router > enable Kouter (config)# hostname iiui exit Kouter H Show running - config Router # Show Startup-Config => To save the host name in Startup-config Router/# Copy running-config startup-config iiai Show start-up config Router/# ? -> Show list of command Router/# cli > Clock clear

jiui # config t -> global mode jiui (config)# interface fast Ethernet 0/0 -> global mode jiui (confij) # ip address 10.0.0.0 255.0.0.0 (for ipaddress) ii (config) # exit ijui (config) # banner moted & Welcome to jivi & exit exit ilui # config t ilui (config)# no enable iiui > enoble iiui # config terminal
iiui (config) # enable password iiii Parmord Crit exit exit (xemove fassword) exit no enable => To enexypt a password (1)
iiui (config) # enable secret jiui Servet for encrept ass owned exit

=> Main Password iiui > enable ijui # config # line console 0
ijui (config) # lagin iiui (config-line) # password iiii ] Password no exit exit to semove passuo

Standard Access List: - (1-99) outer > en Router # Config t houter (config)# access-list 1 permit 172.16.0.0 0.0.255.255 louter (config)# interface fast Ethernet 0/0 Nouter (config-if)# ip access group 1 out any = 255.255.25 Luter# Show running - Config