

Catmandu Fixes: : CHEAT SHEET



Basics

```
add_field(my.name,patrick)
my:
  name: patrick
move_field(my.name,your.name)
your:
  name: nicolas
copy_field(your.name,your.name2)
your:
  name: nicolas
  name2: nicolas
remove_field(your.name2)
your:
  name: nicolas
rename(your,['ae'],'X')
your:
  nXmX: nicolas
```

Set

```
set_field(my.name,patrick)
my:
  name: patrick
set_array(my.array)
my:
  array: []
set_array(my.array,1,2,3,4)
my:
  array: [1,2,3,4]
set_hash(my.object)
my:
  object: {}
set_hash(my.object, a: A, b: B)
my:
  object:
    a: A
    b: B
```

Array ⇔ Hash

given:
foo: [a, A, b, B]

```
hash(foo)
foo:
  a: A
  b: B
array(foo)
foo: [ a, A, b, B ] reverse of hash
```

Strings

given:
title: catmandu

```
append(title,'?!')
title: catmandu ?!
capitalize(title)
title: Catmandu
downcase(title)
title: catmandu
prepend(title,'I love ')
title: I love catmandu
index(title,'t')
title:2
replace_all(title,['au'],'X')
title: cXtmXndX
reverse(title)
title: udnamtac
substring(title,0,3)
title: cat
trim(title)
title: catmandu (spaces removed)
upcase(title)
title: CATMANDU
```

Hint

Most fixes work in this cheat sheet work on **strings**, **numbers** and **lists**.

E.g., given as data input:

```
string: test
list:
  - test1
  - test2
```

the fix **upcase(string)** would change the **string** field:

```
string: TEST
list:
  - test1
  - test2
```

And, **upcase(list.*)** would change all the entries in the **list** field:

```
string: test
list:
  - TEST1
  - TEST2
```

Data manipulation

given:

```
numbers: [ 41, 42, 6, 6 ]
person:
  name: François
  age: 12
  date: 1918-11-11
  animals: ['Lion','Cat','Tiger']
  deep: [ 1, [2, [3, 4]] ]
  pairs:
    - key: name
      val: Albert
    - key: age
      val: 12
```

```
assoc(result,pairs.*.key, pairs.*.val)
result: { name: Albert, age: 12 }
count(numbers)
numbers: 4
compact(numbers)
numbers: [ 41, 42, 6, 6 ] (removes null values)
filter(animals,['Cc]at')
animals: [ 'Cat' ]
flatten(deep)
deep: [ 1, 2, 3, 4 ]
format(numbers,'%>10.10d %>5.5d')
numbers: 0000000041 00042
format(name,'%10s: %s')
person: "name      : François"
from_json(field)
inverse of to_json(field)
join_field(numbers, '/')
numbers: '41/42/6/6'
parse_text(date,'\d{4})-(\d{2})-(\d{2})')
date: [ '1918', '11', '11' ]
parse_text(date,'(?>year>\d{4})-(?>month>\d{2})-(?>day>\d{2})')
date:
  year: '1918'
  month: '11'
  day: '11'
paste(result,person.name,person.age)
result: "François 12"
paste(result,person.name,person.age,
join_char:',')
result: "François,12"
paste(result,person.name,~is,person.age)
result: "François is 12"
random(test,100)
test: 13 (adds a random number)
retain(numbers,person)
delete all fields except numbers and person
```

JSON Path

JSON paths are used to point to zero, one or more fields in your record. Given the data in the **yellow** box on the left:

JSON Path	Value
numbers.0	41
numbers.\$end	6
numbers.\$start	41
numbers.*	[41,42,6,6]
numbers.\$prepend	-> numbers.\$start - 1
numbers.\$append	-> numbers.\$end + 1
person.age	12
deep.1.1.0	3
.	-> select the whole record

Examples:

```
copy_field(person.age,list.$append)
list: [ 12 ]
copy_field(person.age,list.5)
list: [ ~, ~, ~, ~, ~, 12 ]
```

```
reverse(numbers)
numbers: [6,6,42,41]
sort_field(numbers)
numbers: [41,42,6,6]
sort_field(numbers,numeric:1)
numbers: [6,6,41,42]
sort_field(numbers,numeric:1,reverse:1)
numbers: [42,41,6,6]
split_field(date,'-')
date: ['1918','11','11']
sum(numbers)
numbers: 95
to_json(person)
person: '{"name": "Albert", "age": "12"}'
uniq(numbers)
numbers: [41,42,6]
url_decode(person.name)
inverse of uri_encode(...)
uri_encode(person.name)
person:
  name: Fran%C3%A7ois
vacuum()
delete all empty/undef fields in the record
```

Catmandu Fixes: : CHEAT SHEET



Conditions

A condition can be used in an if/else/end statements to have conditional execution of fixes. They can also be used as **guards** for **reject** or **select** statements. All conditions have the syntax:

if *Condition(params,...)*

```
fix(..)
fix(..)
```

end

if *Condition(params,...)*

```
fix(..)
fix(..)
```

else

```
fix(..)
```

end

unless *Condition(params,...)*

```
fix(..)
fix(..)
```

end

reject *Condition(params,...)*

select *Condition(params,...)*

Condition(params,...) **and** *fix(..)*

Condition(params,...) **or** *fix(..)*

Here is a list of all conditions implemented in Catmandu:

all_match(*JSONPath, REGEX*)

Execute the fix(es) when **all** values in the JSONPath matches the REGEX

any_match(*JSONPath, REGEX*)

Execute the fix(es) when **at least one** value in the JSONPath matches the REGEX

exists(*JSONPath*)

Execute the fix(es) when a JSONPath contains a value (a string, number, list or hash)

all_equal(*JSONPath, String*)

Execute the fix(es) when **all** values in the JSONPath are equal to a String

any_equal(*JSONPath, String*)

Execute the fix(es) when **at least one** value in the JSONPath is equal to a String

greater_than(*JSONPath, Value*)

Execute the fix(es) when **all** values in the JSONPath are greater than Value

less_than(*JSONPath, Value*)

Execute the fix(es) when **all** values in the JSONPath are less than Value

in(*JSONPath1,JSONPath2*)

Execute the fix(es) when all values in the JSONPath1 can be found in JSONPath2. E.g.

```
x: 1
```

```
nums: [3,2,1]
```

if in(*x,nums*)

add_field(*test,ok*)

end

is_true(*JSONPath*)

Execute the fix(es) when **all** the values in the JSONPath are boolean true, 1 or 'true'

is_false(*JSONPath*)

Execute the fix(es) when **all** the values in the JSONPath are boolean false, 0 or 'false'

is_array(*JSONPath*)

Execute the fix(es) when the JSONPath points to an array

is_object(*JSONPath*)

Execute the fix(es) when the JSONPath points to a hash

is_number(*JSONPath*)

Execute the fix(es) when the JSONPath contains a number

is_string(*JSONPath*)

Execute the fix(es) when the JSONPath contains a string

is_null(*JSONPath*)

Execute the fix(es) when the JSONPath contains a null value

is_valid(*data,JSONSchema,schema:file*)

Execute the fix(es) when the data is valid against a JSONSchema defined in file

CSV Data

File: lookup.csv

```
en,nl
```

```
blue,blauw
```

```
red,rood
```

```
green,groen
```

```
yellow,geel
```

```
purple,paars
```

Import / Export

Import and export fixes can be used to import values from external files into the record. Or, to export data from the record to external files and databases.

given:

```
color1: red
```

```
color2: brown
```

lookup(*color1,"lookup.csv",sep_char:","*)

```
color1: "rood"
```

lookup(*color2,"lookup.csv",default:NA*)

```
color2: NA
```

lookup(*color2,"lookup.csv",delete:1*)

```
>> color2 is deleted, because 'brown' is
not available in the lookup.csv
```

In the following examples we assume a MongoDB database is available which contains the record:

```
_id: red
```

```
color_eng: red
```

```
color_dut: rood
```

```
color_ger: rot
```

lookup_in_store(*color1,MongoDB,database_name:colors*)

```
color1:
```

```
_id: red
```

```
color_eng: red
```

```
color_dut: rood
```

```
color_ger: rot
```

lookup_in_store(*color2,MongoDB,database_name:colors,default:NA*)

```
color2: NA
```

lookup_in_store(*color2,MongoDB,database_name:colors,delete:1*)

```
>> color2 is deleted, because 'brown' is
not available in the database
```

In the following example we assume the data contains this record:

```
author:
```

```
_id: 1234
```

```
name:
```

```
first: Albert
```

```
last: Einstein
```

```
dateBirth:1879
```

add_to_store(*author,MongoDB,database_name:authors*)

The values in 'author' will be added to the MongoDB store

in general:

add_to_store(field,Store,options..)

add_to_exporter(*author,CSV,header:1,file:/tmp/data.csv*)

The values in 'author' will be added to the CSV file.

in general:

add_to_exporter(field,Exporter,options..)

export_to_string(*author,YAML*)

```
author: "_id: 1234\nname:\nfirst: Albert\nlast: Einstein\ndateBirth:"
```

in general:

export_to_string(field,Exporter,options..)

import_from_string(*author,YAML*)

```
>> the inverse of export_to_string
```

search_in_store(*query,'Solr',url:"http://localhost:8983/solr",limit:10*)

```
>> execute the string in query and
```

```
replace the field with the search results
```

import(*foo,JSON,file:data.json,data_path:data.**)

```
>> replace foo with the content found
in the JSON file at path data
```

include(*'/tmp/myfixes.txt'*)

```
>> include the fixes from a file in this
Fix script
```

Hint

Execute these fixes on the Unix command line:

```
$ catmandu
  convert JSON to
  YAML --fix test.fix < data.json > data.yml
```

where test.fix contains all your fix commands.

Read more about the Catmandu **convert** command:

```
$ catmandu help convert
```

Catmandu Fixes: : CHEAT SHEET



Select / Reject

Select and **reject** fixes are used to filter records out of a stream based on a **condition**.

reject exists(my.badfield)

reject the record if it contain my.badfield

select all_match(title,'Catmandu')

select only the records that have Catmandu in the title field

External Commands

cmd("java MyClass")

>> send the record as JSON to the STDIN of the external command and replace it with the JSON from the STDOUT

perlcode("mycommand.pl")

>> run the my command.pl on the data in the record

sleep(1,SECOND)

do nothing for one second

Logging

log("test1234",level:DEBUG)

>> send a message to the logs

error("eek!")

>> abort processing and say 'eek!'

Hint

Add more **Catmandu** fixes and commands by installing more packages:

cpanm install PACKAGE

Popular packages:

- Catmandu::Identifier
- Catmandu::MARC
- Catmandu::RDF
- Catmandu::Stat
- Catmandu::VIAF
- Catmandu::XML

Bind

Binds are wrappers for one or more fixes. They give extra control functionality for fixes such as loops.

All binds have the syntax:

do Bind(params,...)

fix(..)

fix(..)

end

The most easy Bind is probably **iterate** which iterates fixes in a loop:

do iterate(start:1, end:10, step:1 var:i)

copy_field(i,numbers.\$append

end

This bind will create the array *numbers::*

numbers: [1,2,3,4,5,6,7,8,9,10]

Here is an overview of Bind provided by the main Catmandu package:

benchmark(output:FILE)

This fix calculates the execution time of Fix functions:

do benchmark(output:/dev/stderr)

foo()

bar()

end

hashmap(

exporter:EXPORTER, [,opt:valleu,...]

store:STORE, [,opt:valleu,...]

uniq:0|1

join:CHAR

count:0|1)

Add fields 'key' and 'value' to an internal hash map and print the content to a JSON exporter when all records have been processed

do hashmap()

copy_field(isbn,key)

copy_field(id,value)

end

This will create a JSON output with isbn values as '_id' and an array of id values as 'value'

identity()

This Bind does nothing special and is mostly used to group fixes as a single operation for other binds.

do benchmark(output:/dev/stderr)

foo()

do identity()

bar()

bar()

end

end

importer(IMPORTER, [opt:value,...])

Used in standalone catmandu Fix scripts to set the importer to read data from.

#!/usr/bin/env catmandu run

do importer(OAI,url:http://somewhere.org)

retain(_id)

add_to_exporter(.,YAML)

end

iterate(

start:NUM,

end:NUM,

step:NUM,

var:NAME)

Iterate numbers from start to end with the provided step. Set the field NAME to the number and execute the fixes.

do iterate(start:1, end:10, step:1 var:i)

copy_field(i,numbers.\$append

end

list(path:JSONPath[,var:NAME])

Execute all the fixes in the context of every element in the JSONPath array

do list(path:demo)

if all_equal(.,'green')

upcase(.)

end

end

or when you need to have access to the root element

do list(path:demo,var:c)

copy_field(c,mylist,\$append)

end

maybe()

Skip fixes when one returns undef or throws an error

do maybe()

foo()

error("Help") # bar will be ignored

bar()

end

rest() # rest will be executed

timeout(

time:NUM,

units:seconds|minutes|hours)

Ignore the effect of the fixes on the data after some timeout

do timeout(time:5,unit:seconds)

add_field(foo,ok) # will be ignored

sleep(10,seconds)

set_field(foo,error) # will be ignored

end

visitor([path:JSONPath])

Execute all fixes in the context of every element in the data. This fix will set special context variables:

scalar - for every scalar value found

array - for every array value found

hash - for every hash value found

key - the field name on which the scalar array or hash is found

upcast every 'name' field in the record

do visitor()

if all_equal(key,name)

upcase(scalar)

end

end

with(path:JSONPath)

Execute all the fixes in the context of the JSONPath

do with(path:my.deep.path)

Treat path as root

create: my.deep.path.name = Patrick

add_field(name,Patrick)

end

Catmandu Fixes: : CHEAT SHEET



Catmandu::MARC

MARC PATH

MARC paths are used to point to zero or more MARC (sub)fields in your record.

given:

```
001 1234
245 $aTitle / $cName
500 $aA$aB$aC$xD
650 $aAlpha
650 $aBeta
650 $aGamma
999 $aX$aY
999 $aZ
```

```
001      = "1234"
245      = "Title / Name"
245a     = "Title / "
245$a    = "Title / "
500ax    = "ABCD"
500^x    = points to all 500 except $x
2..      = points to all 200 - 299 fields
245[1,]  = points to 245 if ind1=1
245[1,0] = points to 245 if ind1=1 ind2=0
008/35-37 = points to chars 35-37 in 008
```

marc_map(MARCPATH, JSONPath, opts)
Copy the value(s) found at MARCPATH to a JSONPath.

marc_map(245,my.title)
my.title = "Title / Name"

marc_map(245,my.title, split:1)
my.title = ["Title / ", "Name"]

marc_map(245ca,my.title)
my.title = "Title / Name"

marc_map(245ca,my.title,pluck:1)
my.title = "NameTitle / "

marc_map(245,my.title,join:"@@")
my.title = "Title / @@Name"

marc_map(650,my.subject.\$append)
my.subject = ['Alpha', 'Beta', 'Gamma']

marc_map(650/0-1,test)
test = "Al"

marc_map(999,has.f999,value:"yes ok")
has.f999 = "yes ok"

marc_add(MARCFIELD,subfield,value...)
Add a new MARC field to the record

marc_add(900,a,test,b,test2)
creates: 900 \$atest\$btest2

marc_add(009,_,12345)
creates: 009 12345 (control field)

marc_add(900,a,\$.my.field)
creates a 900 field with \$a value copied from my.field

marc_set(MARCPATH,value)
Set a value of a MARC (sub)field to a new value

marc_set(001,5678)
result: 001 5678

marc_set(245c,Test)
result: 245 \$aTitle\$cTest

marc_set(245c,\$.my.field)
the 245 field subfield \$c contains now the value copied from my.field

marc_remove(MARCPATH)
Remove (sub)fields in a MARC record

marc_remove(600)
removes all 600 fields

marc_remove(245a)
removes the 245 \$a subfield

marc_replace_all(MARCPATH,Search,Replace)
Replace all occurrences of the regular expression Search by Replace at MARCPATH

marc_replace_all(245a,Title,"Hello!")
result: 245 \$aHello !\$cName

marc_replace_all(245a,Title,\$.my.field)
the 245 field subfield \$a ever occurrence of 'Title' will be replaced by the value found in my.field

marc_replace_all(245a,'^(..)',{\$1})
result: 245 \$a{Ti}tle\$cName

marc_append(MARCPATH,value)
Add a value at the end of a MARC (sub)field

marc_append(245,".")
Add a period "." at the end of the 245 field: 245 \$aTitle\$cName.

marc_copy(MARCPATH,JSONPATH)
Copy data that match MARCPATH to an ARRAY of HASHES at JSONPATH

marc_cut(MARCPATH,JSONPATH)
Cut data that match MARCPATH into an ARRAY of HASHES at JSONPATH

marc_paste(JSONPATH,[at:MARCPATH, [equals:Search]])
Paste the data copy/cut at JSONPATH back into the MARC record. If an "at" MARCPATH is given, then the data will be copied after the MARCPATH. If an "equals" is given, then the data will be copied only if the MARCPATH matches the regex in equals.

See: https://metacpan.org/pod/Catmandu::Fix::marc_copy for examples

marc_xml(JSONPATH,[reverse:1])
Convert the MARC record found at JSONPATH to MARC XML. Or, when "reverse:1", convert the MARC XML found at JSONPATH to the internal Catmandu MARC format. To use the transformed XML with other fixes it needs to be stored in the "record" key.

marc_in_json([reverse:1])
Convert the MARC data found in the "record" key into the MARC-in-JSON format. Or, then "reverse:1", convert the MARC-in-JSON found at the "record" key back into the internal Catmandu MARC format.

Conditions

A condition can be used in if/else/end statements to have conditional execution of fixes. See "Conditions" on page 2.

Most MARC Conditions are best executed in a surrounding "marc_each" block:

```
do marc_each()
  if marc_hash(245)
    # execute for each 245 in MARC
  end
end
```

marc_has(MARCPATH)
Execute the fix(es) when the MARC file contains a MARCPATH value.

marc_match(MARCPATH,Regex)
Execute the fix(es) when the value at MARCPATH matches the Regex

Bind

Binds are wrappers for one or more fixes. They give extra control functionality for fixes such as loops. See "Bind" on page 3

marc_each()
Execute all the fix(es) in the Bind context on individual MARC fields (loop over all the fields).

```
do marc_each()
  if marc_match(720e,promotor)
    marc_map(720ab,authors.$append)
  end
end
```

marc_each(var:this)
Like marc_each, but now an implicit marc_copy of the MARC field in context has been stored in the "this" variable

```
do marc_each(var:this)
  if all_match(this.tag,300)
    # rename tag to 301
    set_field(this.tag,301)
    marc_paste(this)
  end
end
```