

CARDIOVIT AT-101

The budget-priced high-tech ECG device

Ready for networking with XML output

Possibility of data transfer to SCHILLER Data Management System SEMA-200

Performance:

- Intuitive and easy to use with direct keys
- 12-lead Resting ECG with standard ECG measurements
- Integrated graphical 3-channel LC display
- Measurements
- Easy Print: Integrated high-resolution thermal printer
- Various user-programmable report formats on internal or external printer
- Interface for external printer for printouts on standard paper
- Storage and serial data transfer for Resting ECG data to a PC (with memory option)

Options:

- Memory and data transfer to a PC or Information System
- Interpretation software
- Thrombolysis



SCHILLER eXtensible Connectivity

Optional XML Data Transmission (needs memory option):

- The AT-101 is available with the internal SCHILLER Communication Module (SCM), which transmits Resting ECG data on XML format to a PC or Information Systems via:
 - Ethernet interface; or
 - Built-in analogue modem (optional)
- This enables the AT-101 to be an integrated part of a larger systems solution
- It is possible to see from what device the data has been transferred from (serial no., identification, transfer date and time)
- Secure transmission of patient data via the Internet is possible using 1024-bit strong encryption
- Equipped with the add-on SCM Server, the SCHILLER Data Management System SEMA-200 can receive the XML output from the SCHILLER Communication Module



SCHILLER
The Art of Diagnostics

Technical Data CARDIOVIT AT-101:

System:

Dimensions: 290 x 198 x 76 mm, approx. 2.6 kg

Built-in monitor: 76 x 57 mm effective display area; 320 x 240 dots resolution

On-screen status indicators: Battery status, date, time, power source

Control panel and keyboard: User-friendly, alphanumeric keyboard, LED indicator and LC display

Power supply requirements: 220 – 240 V (nominal), 50/60 Hz; 110 – 115 V (nominal), 50/60 Hz; stand-alone operation with built-in rechargeable battery; LED indicator for mains operation, integrated power supply unit

Battery capacity: 4 hours of normal use

Power consumption: Max. 28 VA

Line frequency filter: Distortion-free suppression of superimposed 50 or 60 Hz sinusoidal interferences by means of adaptive digital filtering (SCHILLER Powerline Filter SPF)

Frequency range of digital recording system: 0 – 150 Hz (IEC/AHA)

Chart paper: Thermo-reactive, Z-folded, 80 mm wide

Printing process: High-resolution thermal head printer, 8 dots/mm (amplitude axis), 40 dots/mm (time axis) @ 25 mm/s

Interfaces: RS-232 interface; data transmission to PC (SEMA-200) and external modem connection (memory option necessary); parallel port for external printer; optional Ethernet interface and optional internal modem for XML data transmission (memory option necessary)

Memory: Possibility to save up to 40 Resting ECG measurements (Option)

Environmental conditions:

- Temperature, operating: 10° C bis 40° C
- Temperature, storage: -10° C bis 50° C
- Relative humidity: 25 % bis 95 % (no condensation)
- Pressure during operation: 700 bis 1060 hPa

Safety Standards:

Safety standard: IEC/EN 60601-1; UL 60601-1; C22.2 Nr. 601.1-M90; IEC/EN 60601-2-25; IEC/EN 60601-1-2 (EMC)

Protection class: I according to IEC/EN 60601-1 (with internal power supply)

Applied Part: CF according IEC/EN 60601-1

Conformity: CE according Directive 93/42/EEC (Medical Devices)

Classification: IIa according Directive 93/92/EEC

Technical Data for ECG:

Patient input circuit: Fully floating and isolated, defibrillation-protected (only with original SCHILLER patient cable)

Monitor display:

- 3-channel display of the selected leads
- Heart Frequency, HF
- 25, 50 mm/s
- 5, 10, 20 mm/mV
- Filter status (on/off)
- Insufficient electrode contact

Leads: 12 simultaneous leads: Standard / Cabrera

Chart printout speed: 5/10/25/50 mm/s (manual print)

Sensitivities: 5/10/20 mm/mV, either automatically adjusted or manually selected

Automatic lead programs:

- 3/6/12-channel presentations of 12 simultaneously recorded leads
- Numerous printout formats can be selected

Data record:

- Patient data (name, age, height, weight, BP), user ID
- Listing of all ECG recording conditions (date, time, filter), (optional)
- Measurement program: ECG measurements results (intervals, amplitudes, electrical axes), average complexes with measurement reference markings
- Interpretation (C, optional) with adult and pediatric guidance
- Thrombolyse Software (only in combination with C option)

Recording track: 3/6/12-channel presentation, optimal positioning on a width of 72 mm (internal printer) or A4 (external printer), automatic baseline adjustment

Filter: Myogram filter (muscle tremor filter): 25 or 35 Hz, SCHILLER

Baseline Stabilizer SBS, SCHILLER Smoothing Filter SSF

ECG amplifier:

- Simultaneous recording of all 9 active electrode signals (= 12 leads)
- Sampling frequency: 1000 Hz
- Pacemaker detection: ≥ 2 mV/ ≥ 0.1 ms

Scope of delivery for CARDIOVIT AT-101 Standard:

CARDIOVIT AT-101 Resting ECG with 12 simultaneous leads, pacemaker detection, automatic ECG measurement

Accessories:

- 1 10-lead patient cable
- 1 set of electrodes or disposable electrodes
- 1 power cable
- 1 pack chart paper
- Operating manual

Software options:

- Thrombolysis Software
- Memory for up to 40 measurements
- Computer-aided ECG interpretation for pediatric and adult ECGs (C)
- SEMA-200 PC software to save, validate and archive ECG data on PC

Hardware options:

- Equipment trolley
- External printer
- Internal SCHILLER Communication Module with optional built-in analogue modem

Technical Data are subject to change without notice.

Asia

SCHILLER Asia-Pacific
52200 Kuala Lumpur, Malaysia
Phone +603 6272 3033
sales@schiller.com.my
www.schiller-asia.com

Austria

SCHILLER Handelsgesellschaft mbH
A-4040 Linz
Phone +43 732 70 99-0
sales@schiller.at
www.schiller-austria.com

China

SCHILLER International Trading Co. Ltd.
200335 Shanghai, China
Phone +8621 6209 9627
sales@schiller.com.my
www.schiller.cn

France

SCHILLER Médical S.A.S.
F-67162 Wissembourg/Cedex
Phone +33 3 88 63 36 00
info@schiller.fr
www.schiller-france.com

France (office Paris)

SCHILLER Médical S.A.S.
F-77608 Mame la Vallée/Cedex
Phone +33 1 64 66 50 00
info@schiller.fr
www.schiller-france.com

Germany

SCHILLER Medizintechnik GmbH
D-85521 Ottobrunn
Phone +49 89 62 99 81-0
info@schillermed.de
www.schiller-germany.com

Hungary

SCHILLER-Diamed Ltd.
H-1141 Budapest
Phone +36 (1)460 95 92
schiller@t-online.hu
www.schiller-hungary.hu

India

SCHILLER Healthcare India Pvt. Ltd.
Mumbai - 400 059, India
Phone +91 22 2826 35 20
sales@schillerindia.com
www.schillerindia.com

Japan

SCHILLER Japan, Ltd.
Hiroshima 734-8551
Phone +81 82 250 2055
koji.maekawa@schiller.jp
www.schiller.jp

Poland

SCHILLER Poland Sp. z o.o.
PL-02-729 Warszawa
Phone +48 22 843 2089
schiller@schiller.pl
www.schiller.pl

Russia & C.I.S.

SCHILLER AG
125124 Moscow, Russia
Phone +7 (495) 970 11 33
mail@schiller-ag.com
www.schiller-cis.com

Spain

SCHILLER ESPAÑA, S.A.
E-28230-Las Rozas/Madrid
Phone +34 91 713 01 76
schiller@schiller.es
www.schiller-spain.com

Switzerland

SCHILLER-Reomed AG
CH-8953 Dietikon
Phone +41 44 744 30 00
sales@schiller-reomed.ch
www.schiller-reomed.com

Turkey

SCHILLER TÜRKİYE
Okmeydanı-Sisli - İstanbul
Phone +90 212 210 8681 (pbx)
sales@schiller-turkiye.com
www.schiller-turkiye.com

USA

SCHILLER America Inc.
Doral, Florida 33122
Phone +1 786 845 0620
sales@schilleramerica.com
www.schilleramerica.com

Your specialist:



SCHILLER

The Art of Diagnostics