

Coral-Chords documentation

Linus Tibert

August 4, 2025

Contents

1	Introduction	3
2	Project structure	3
2.1	Coral-Chords-Backend	3
2.2	Coral-Chords	3
3	Getting the data	3
4	Storing the data	3
5	UI stuff	3
6	Code components	3
6.1	Coral-Chords-Backend	3
6.1.1	Constants	3
6.1.2	Structs	3
6.1.3	Functions	4
6.1.4	Tests	4
6.2	Coral-Chords	4

1 Introduction

2 Project structure

2.1 Coral-Chords-Backend

2.2 Coral-Chords

3 Getting the data

4 Storing the data

5 UI stuff

6 Code components

6.1 Coral-Chords-Backend

6.1.1 Constants

`END_OF_CHORDS_DELIM` is a short but unique piece of code from the UG source HTML, which is used to mark the end of the section containing the chords and lyrics.

`START_OF_CHORDS_DELIM` the same as `END_OF_CHORDS_DELIM`, but used to mark the beginning of useable data. Note that the metadata is not included between the delimiters; it is above the start delimiter.

`HTML_BLACKLIST` is an array of strings which identify certain types of UG pages which are not downloadable; video pages for example.

`DETAIL_REGEX` is the Regex expression used to get detailed metadata from the raw HTML of a supported UG page. Each capturing group holds one property.

`TYPE_REGEX` is used to extract the type of supported page. (I.e. guitar chords, tabs, ukulele chords, bass tabs or drum tabs) This data is in the second capturing group. The first group extracts the artist's name, which is not used in the code yet.

6.1.2 Structs

`SongMetadata` is used to store optional metadata about a song. It is able to hold the capo position, tonality, tuning name and tuning details. Some of this data is not available on every supported page; in such cases, the unavailable data will an empty string. If no metadata is available at all, `SongMetadata::default()` will be used as a metadata struct.

6.1.3 Functions

6.1.4 Tests

6.2 Coral-Chords