

МИНИСТЕРСТВО НАУКИ И ВЫСШЕГО ОБРАЗОВАНИЯ РОССИЙСКОЙ ФЕДЕРАЦИИ
федеральное государственное автономное образовательное учреждение высшего образования
«САНКТ-ПЕТЕРБУРГСКИЙ ГОСУДАРСТВЕННЫЙ УНИВЕРСИТЕТ АЭРОКОСМИЧЕСКОГО
ПРИБОРОСТРОЕНИЯ»

ИНСТИТУТ ВЫЧИСЛИТЕЛЬНЫХ СИСТЕМ И ПРОГРАММИРОВАНИЯ

КАФЕДРА компьютерных технологий и программной инженерии

ОТЧЕТ
ЗАЩИЩЕН С ОЦЕНКОЙ
ПРЕПОДАВАТЕЛЬ

ассистент

должность, уч. степень, звание

подпись, дата

Кочин Д.А.

инициалы, фамилия

ОТЧЕТ О ЛАБОРАТОРНОЙ РАБОТЕ №5

«Разработка приложения с использованием thymeleaf»

по курсу: Технологии разработки серверных информационных систем

РАБОТУ ВЫПОЛНИЛ

СТУДЕНТ ГР. №

4932

29.11.21

Н.С. Иванов

подпись, дата

инициалы, фамилия

Санкт-Петербург 2021

Цель работы

Познакомится с основами написания форм с использованием Thymeleaf.

Задание:

1. Реализуйте задачи из лабораторной работы 1 средствами Thymeleaf.
2. Обратите внимание на локализацию приложения. Русский язык должен поддерживаться.

Вариант: 8. Учет трат в бюджете семьи.

Описание разрабатываемого продукта:

addCost

```
@PostMapping("add")
public ResponseEntity<String> addCost(@RequestBody CostEntity cost){
    try {
        if(costService.addCost(cost)) {
            return ResponseEntity.status(HttpStatus.CREATED).body(gson.toJson("Cost added successfully"));
        }
        throw new CostNotFoundException(gson.toJson("Cost don't found"));
    } catch (CostNotFoundException e){
        return ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        e.printStackTrace();
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body("CostController error -> " + e.getMessage() +
            "\n\n" + Arrays.toString(e.getStackTrace()));
    }
}
```

deleteCost

```
@DeleteMapping("delete/{id}")
public ResponseEntity<String> deleteCost(@PathVariable Long id){
    try {
        if (costService.deleteCost(id)) {
            return ResponseEntity.status(HttpStatus.OK).body(gson.toJson("Cost delete successfully"));
        }
        throw new CostNotFoundException("Cost don't found");
    } catch (CostNotFoundException e){
        return ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body(gson.toJson("CostController error"));
    }
}
```

putCost

```
@PutMapping("put/{id}")
public ResponseEntity<String> putCost(@RequestBody CostEntity cost){
    try {
        if(costService.putCost(cost)) {
            return ResponseEntity.status(HttpStatus.AC-
CEPTED).body(gson.toJson("Cost updated successfully"));
        }
        throw new CostNotFoundException(gson.toJson("Cost don't found"));
    } catch (CostNotFoundException e){
        return ResponseEntity.sta-
tus(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ER-
ROR).body(gson.toJson("CostController error"));
    }
}
```

getCostList

```
@GetMapping("get/all")
public ResponseEntity<Object> getCostList(){
    try {
        return ResponseEntity.status(HttpStatus.OK).body(cost-
Service.getCosts());
    } catch (Exception e){
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ER-
ROR).body(gson.toJson("CostController error"));
    }
}
```

getCost

```
@GetMapping("get/{id}")
public ResponseEntity<String> getCost(@PathVariable Long id){
    try {
        return ResponseEntity.status(HttpStatus.FOUND).body(gson.toJson(cost-
Service.getCost(id)));
    } catch (CostNotFoundException e){
        return ResponseEntity.sta-
tus(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        return ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ER-
ROR).body("CostController error");
    }
}
```

WebSecurityConfig

```
@Configuration
@EnableWebSecurity
public class WebSecurityConfig extends WebSecurityConfigurerAdapter {

    @Override
    protected void configure(HttpSecurity http) throws Exception {
```

```

        http.csrf().disable()

        .authorizeRequests()
            .antMatchers("/", "/home-page").permitAll()
            .antMatchers("/read-access-pane").hasRole("USER")
            .antMatchers("/full-access-pane").hasRole("ADMIN")
        .and()
            .formLogin()
                .loginPage("/login")
                .permitAll()
        .and()
            .logout()
                .permitAll()
        .and()
            .exceptionHandling().accessDeniedPage("/forbidden-error");
    }

    @Bean
    @Override
    protected UserDetailsService userDetailsService() {
        UserDetails user = User.withDefaultPasswordEncoder()
            .username("user")
            .password("1")
            .roles("USER")
            .build();

        UserDetails admin = User.withDefaultPasswordEncoder()
            .username("admin")
            .password("1")
            .roles("ADMIN")
            .build();

        return new InMemoryUserDetailsManager(user, admin);
    }
}

```

ForbiddenPage.html

```

<body>
<h2>Sorry, you do not have permission to view this page.</h2>
</body>

```

FullAccessPane.html

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Costs Management</title>
    <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.4.1/jquery.min.js"></script>

    <style>
        .input_form{
            width: 40%;

```

```
}

.input_form_fields{
    width: 97%;
}

button.btn{
    width:100%;
    height:100%;
    min-width:30px;
    max-width:200px;
    min-height:30px;
    max-height:30px;

    color: black;
    background-color: white;
    border-color: black;
    border-width: 1px;
    border-radius: 7px;
    font-size: 20px;
}

button.green_btn{
    width: 10%;
    height: 10%;
    color: black;
    background-color: palegreen;
    border-color: seagreen;
}

button.green_btn:hover{
    border: none;
    color: gray;
}

button.red_btn{
    width:100%;
    height:10%;

    color: white;
    background-color: palevioletred;
    border-color: darkred;
}

button.red_btn:hover{
    border: none;
    color: black;
}

button.orange_btn{
    width:100%;
    height:10%;

    color: white;
    background-color: darkorange;
    border-color: orangered;
}
```

```

button.orange_btn:hover{
    border: none;
    color: black;
}

table {
    background: #f5f5f5;
    border-collapse: separate;
    box-shadow: inset 0 1px 0 #fff;
    font-size: 20px;
    /*line-height: 24px;*/
    margin: 30px auto;
    text-align: left;
    width: 90%;
}

th {
    background: lightgray;
    border-left: 1px solid #555;
    border-right: 1px solid #777;
    border-top: 1px solid #555;
    border-bottom: 1px solid #333;
    box-shadow: inset 0 1px 0 #999;
    color: #000;
    font-weight: bold;
    padding: 10px 15px;
    position: relative;
}

th:after {
    background: linear-gradient(rgba(255,255,255,0),
    rgba(255,255,255,.08));
    content: '';
    display: block;
    height: 25%;
    left: 0;
    margin: 1px 0 0 0;
    position: absolute;
    top: 25%;
    width: 100%;
}

th:first-child {
    border-left: 1px solid #777;
    box-shadow: inset 1px 1px 0 #999;
}

th:last-child {
    box-shadow: inset -1px 1px 0 #999;
}

td {
    border-right: 1px solid #fff;
    border-left: 1px solid #e8e8e8;
    border-top: 1px solid #fff;
    border-bottom: 1px solid #e8e8e8;
}

```

```

        padding: 5px 5px;
        line-height: 5px;
        position: relative;
        transition: all 300ms;
    }

    td:first-child {
        box-shadow: inset 1px 0 0 #fff;
    }

    td:last-child {
        border-right: 1px solid #e8e8e8;
        box-shadow: inset -1px 0 0 #fff;
    }

    tr {
    }

    tr:nth-child(odd) td {
        background: #f1f1f1;
    }

    tr:last-of-type td {
        box-shadow: inset 0 -1px 0 #fff;
    }

    tr:last-of-type td:first-child {
        box-shadow: inset 1px -1px 0 #fff;
    }

    tr:last-of-type td:last-child {
        box-shadow: inset -1px -1px 0 #fff;
    }

    /*tbody: hover td {*/
    /*    color: transparent;*/
    /*    text-shadow: 0 0 3px #aaa;*/
    /*}*/

    /*tbody: hover tr: hover td {*/
    /*    color: #444;*/
    /*    text-shadow: 0 1px 0 #fff;*/
    /*}*/

</style>

</head>

<script type="text/javascript">
    $(document).ready(function () {
        refresh();
    })

    function refresh() {
        draw_table();
    }

```

```

function draw_table() {
    $.ajax({
        url: "costs/get/all",
        dataType: "json",
        contentType: "application/json",
        type: "GET",
        async: false,
        cache: false,
        success: function (data) {
            let $costs = $('#costs_table')

            let table = "<table border='1'>";
            table +=
                "<tr>\n" +
                "<th>id</th>\n" +
                "<th>Name</th>\n" +
                "<th>Price</th>\n" +
                "<th>Category</th>\n" +
                "<th>Customer</th>\n" +
                "<th>Count</th>\n" +
                "<th></th>\n" +
                "<th></th>\n" +
                "</tr>";

            for(let i=0; i<data.length; i++) {
                table +=
                    "<tr>\n" +
                    "<td>" + data[i].id + "</td>\n" +
                    "<td>" + data[i].name + "</td>\n" +
                    "<td>" + data[i].price + "</td>\n" +
                    "<td>" + data[i].category + "</td>\n" +
                    "<td>" + data[i].customer + "</td>\n" +
                    "<td>" + data[i].count + "</td>\n" +
                    "<td>\n" +
                    "<button class='btn red_btn' onclick='delete-
Cost(" + data[i].id + ")'>Delete</button>\n" +
                    "</td>\n" +
                    "<td>\n" +
                    "// " <br>" +
                    "<button class='btn orange_btn' on-
click='editCost(" + data[i].id + ")'>Edit</button>\n" +
                    "</td>\n" +
                    "</tr>";
            }

            table += "</table>";

            $costs.html(table);
        },
        error: function (error) {
            console.log(error);
        }
    });
}

function addCost() {
    $.ajax({

```



```

        url: "/costs/add/",
        dataType: "json",
        contentType: "application/json",
        type: "POST",
        async: false,
        cache: false,
        data: JSON.stringify({
            name: $("#fiendName").val(),
            price: $("#fieldPrice").val(),
            category: $("#fieldCategory").val(),
            customer: $("#fieldCustomer").val()
        }),
        success: function () {
            refresh();
        },
        error: function (error) {
            console.log(error);
        }
    });
}

function deleteCost(idCost){
    $.ajax({
        url: 'costs/delete/' + idCost,
        type: "DELETE",
        async: false,
        cache: false,
        dataType: "json",
        contentType: "application/json; charset=utf-8",
        success: function () {
            refresh();
        },
        error: function (error) {
            console.log(error);
        }
    })
}

function editCost(idCost){
    $.ajax({
        url: "/costs/put/" + idCost,
        dataType: "json",
        contentType: "application/json",
        type: "PUT",
        async: false,
        cache: false,
        data: JSON.stringify({
            id: idCost,
            name: $("#fiendName").val(),
            price: $("#fieldPrice").val(),
            category: $("#fieldCategory").val(),
            customer: $("#fieldCustomer").val()
        }),
        success: function () {
            refresh();
        },
        error: function (error) {

```

```

        console.log(error);
    }
    })
}

</script>

<body>

<div th:include="Logout"></div>

    <div style="text-align: center;">
        <h1>Costs Management</h1>
        <div>
            <form>
                <table class="input_form" border="1" cellpadding="5"
align="center">
                    <tr><th>Name</th> <td>
                        <input class="input_form_fields" type="text"
name="name" id="fiendName"> </td></tr>
                    <tr><th>Price</th> <td>
                        <input class="input_form_fields" type="text"
name="price" id="fieldPrice"> </td></tr>
                    <tr><th>Category</th> <td>
                        <input class="input_form_fields" type="text"
name="category" id="fieldCategory"> </td></tr>
                    <tr><th>Customer</th> <td>
                        <input class="input_form_fields" type="text"
name="customer" id="fieldCustomer"> </td> </tr>
                </table>
            </form>
        </div>
        <button class="right btn green_btn" type="button" onclick='add-
Cost()'>Add</button>
        <br>
        <br>
        <div id='costs_table'></div>
    </div>

</body>
</html>

```

HomePage.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
    xmlns:th="https://www.thymeleaf.org"
    xmlns:sec="https://www.thymeleaf.org/thymeleaf-extras-springsecurity3"
>

<head>
    <title>Home Page</title>
</head>

<div th:include="Logout"></div>

<div id="particles-js">

```

```
<div class="container" style="padding-left: 60px;">
  <div class="row top">
    <div class="twelve column">
      <h1>Family costs</h1>
    </div>
  </div>

  <div class="row">
    <div class="one-half column">
      <div class="pens pulled">
        <h1>Pages</h1>
        <ul>
          <li><a href="full-access-pane">Admin pane</a></li>
          <li><a href="read-access-pane">Read pane </a></li>
        </ul>
      </div>
    </div>
  </div>
</div>
</html>
```

```
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:th="https://www.thymeleaf.org"
      xmlns:sec="https://www.thymeleaf.org/thymeleaf-extras-springsecurity3">

<head>
  <title>Spring Security Example </title>
</head>

<style>
  div.error{
    color: #000000;
    background-color: palevioletred;
    text-align: center;
  }
  div.logout{
    color: #000000;
    background-color: palegreen;
    text-align: center;
  }
</style>

<body>

<div th:include="Logout"></div>
<a th:href="@{/}" >Home</a>

<div style="
position: absolute;
```

```

top: 50%;
left: 50%;
margin-right: -50%;
transform: translate(-50%, -50%);
">
    <div class="error" th:if="${param.error}">
        Invalid username and password.
    </div>

    <div class="logout" th:if="${param.logout}">
        You have been logged out.
    </div>

    <form th:action="@{/login}" method="post">
        <div><label> User Name : <input type="text" name="username"/> </la-
bel></div>
        <div><label> Password: <input type="password" name="password"/> </la-
bel></div>
        <div><input type="submit" value="Sign In"/></div>
    </form>

</div>

</body>

</html>

```

Logout.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
xmlns:th="https://www.thymeleaf.org"
    xmlns:sec="https://www.thymeleaf.org/thymeleaf-extras-springsecurity3">

<body>

<form th:action="@{/logout}" method="post">
    <label th:if="${#request.userPrincipal != null}" th:inline="text">
        You authorize as [[${#HttpServletRequest.remoteUser}]]!
    <input type="submit" value="Sign Out"/>
    </label>
</form>
</body>
</html>

```

ReadAccessPane.html

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>Costs Management</title>
    <script src="https://ajax.goog-
leapis.com/ajax/libs/jquery/3.4.1/jquery.min.js"></script>

    <style>

```

```
.input_form{
    width: 40%;
}

input{
    width: 97%;
}

button.btn{
    width:100%;
    height:100%;
    min-width:30px;
    max-width:200px;
    min-height:30px;
    max-height:30px;

    color: black;
    background-color: white;
    border-color: black;
    border-width: 1px;
    border-radius: 7px;
    font-size: 20px;
}

button.green_btn{
    width: 10%;
    height: 10%;
    color: black;
    background-color: palegreen;
    border-color: seagreen;
}

button.green_btn:hover{
    border: none;
    color: gray;
}

button.red_btn{
    width:100%;
    height:10%;

    color: white;
    background-color: palevioletred;
    border-color: darkred;
}

button.red_btn:hover{
    border: none;
    color: black;
}

button.orange_btn{
    width:100%;
    height:10%;

    color: white;
    background-color: darkorange;
}
```

```

        border-color: orangered;
    }

    button.orange_btn:hover{
        border: none;
        color: black;
    }

    table {
        background: #f5f5f5;
        border-collapse: separate;
        box-shadow: inset 0 1px 0 #fff;
        font-size: 20px;
        /*line-height: 24px;*/
        margin: 30px auto;
        text-align: left;
        width: 90%;
    }

    th {
        background: lightgray;
        border-left: 1px solid #555;
        border-right: 1px solid #777;
        border-top: 1px solid #555;
        border-bottom: 1px solid #333;
        box-shadow: inset 0 1px 0 #999;
        color: #000;
        font-weight: bold;
        padding: 10px 15px;
        position: relative;
    }

    th:after {
        background: linear-gradient(rgba(255,255,255,0),
        rgba(255,255,255,.08));
        content: '';
        display: block;
        height: 25%;
        left: 0;
        margin: 1px 0 0 0;
        position: absolute;
        top: 25%;
        width: 100%;
    }

    th:first-child {
        border-left: 1px solid #777;
        box-shadow: inset 1px 1px 0 #999;
    }

    th:last-child {
        box-shadow: inset -1px 1px 0 #999;
    }

    td {
        border-right: 1px solid #fff;
        border-left: 1px solid #e8e8e8;
    }

```

```

        border-top: 1px solid #fff;
        border-bottom: 1px solid #e8e8e8;
        padding: 5px 5px;
        line-height: 5px;
        position: relative;
        transition: all 300ms;
    }

    td:first-child {
        box-shadow: inset 1px 0 0 #fff;
    }

    td:last-child {
        border-right: 1px solid #e8e8e8;
        box-shadow: inset -1px 0 0 #fff;
    }

    tr {
    }

    tr:nth-child(odd) td {
        background: #f1f1f1;
    }

    tr:last-of-type td {
        box-shadow: inset 0 -1px 0 #fff;
    }

    tr:last-of-type td:first-child {
        box-shadow: inset 1px -1px 0 #fff;
    }

    tr:last-of-type td:last-child {
        box-shadow: inset -1px -1px 0 #fff;
    }

    /*tbody:hover td {*/
    /*    color: transparent;*/
    /*    text-shadow: 0 0 3px #aaa;*/
    /*}*/

    /*tbody:hover tr:hover td {*/
    /*    color: #444;*/
    /*    text-shadow: 0 1px 0 #fff;*/
    /*}*/

</style>

</head>

<script type="text/javascript">
    $(document).ready(function () {
        refresh();
    })

    function refresh() {
        draw_table();
    }

```

```

    }

    function draw_table(){
        $.ajax({
            url: "costs/get/all",
            dataType: "json",
            contentType: "application/json",
            type: "GET",
            async: false,
            cache: false,
            success: function (data) {
                let $costs = $('#costs_table')

                let table = "<table border='1'>";
                table +=
                    "<tr>\n" +
                    "    <th>id</th>\n" +
                    "    <th>Name</th>\n" +
                    "    <th>Price</th>\n" +
                    "    <th>Category</th>\n" +
                    "    <th>Customer</th>\n" +
                    "    <th>Count</th>\n" +
                    "</tr>";

                for(let i=0; i<data.length; i++) {
                    table +=
                        "<tr>\n" +
                        "    <td>" + data[i].id + "</td>\n" +
                        "    <td>" + data[i].name + "</td>\n" +
                        "    <td>" + data[i].price + "</td>\n" +
                        "    <td>" + data[i].category + "</td>\n" +
                        "    <td>" + data[i].customer + "</td>\n" +
                        "    <td>" + data[i].count + "</td>\n" +
                        "</tr>";
                }

                table += "</table>";

                $costs.html(table);
            },
            error: function (error) {
                console.log(error);
            }
        });
    }
}

</script>

<body>

<div th:include="Logout"></div>

<div style="text-align: center;">
    <h1>Costs Management</h1>
    <div id='costs_table'></div>
</div>

```



```
</body>  
</html>
```

Выводы

- Thymeleaf существенно расширяет возможности написания форм.

Приложение:

```
// @filename \src\main\java\suai\trsis2021\lab4\Lab4Application.java
package suai.trsis2021.lab4;
```

```
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
```

```
@SpringBootApplication
public class Lab4Application {
```

```
    public static void main(String[] args) {
        SpringApplication.run(Lab4Application.class, args);
    }
}
```

```
// @filename \src\main\java\suai\trsis2021\lab4\controller\CostController.java
package suai.trsis2021.lab4.controller;
```

```
import com.google.gson.Gson;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import suai.trsis2021.lab4.entity.CostEntity;
import suai.trsis2021.lab4.exceptions.CostNotFoundException;
import suai.trsis2021.lab4.service.CostService;
```

```
import java.util.Arrays;
```

```
@RestController
@RequestMapping("/costs")
public class CostController {
```

```
    @Autowired
    private CostService costService;
    private static final Gson gson = new Gson();

    @PostMapping("add")
    public ResponseEntity<String> addCost(@RequestBody CostEntity cost){
        try {
            if(costService.addCost(cost)) {
                return ResponseEntity.status(HttpStatus.CREATED).body(gson.toJson("Cost added successfully"));
            }
        }
    }
}
```

```

        throw new CostNotFoundException(gson.toJson("Cost don't found"));
    } catch (CostNotFoundException e){
        return
        ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        e.printStackTrace();
        return
        ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body("CostController error
-> " + e.getMessage() +
            "\n\n" + Arrays.toString(e.getStackTrace()));
    }
}

```

```

@DeleteMapping("delete/{id}")
public ResponseEntity<String> deleteCost(@PathVariable Long id){
    try {
        if (costService.deleteCost(id)){
            return ResponseEntity.status(HttpStatus.OK).body(gson.toJson("Cost delete
successfully"));
        }
        throw new CostNotFoundException("Cost don't found");
    } catch (CostNotFoundException e){
        return
        ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        return
        ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body(gson.toJson("CostCon
troller error"));
    }
}

```

```

@PutMapping("put/{id}")
public ResponseEntity<String> putCost(@RequestBody CostEntity cost){
    try {
        if(costService.putCost(cost)) {
            return ResponseEntity.status(HttpStatus.ACCEPTED).body(gson.toJson("Cost
updated successfully"));
        }
        throw new CostNotFoundException(gson.toJson("Cost don't found"));
    } catch (CostNotFoundException e){
        return
        ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    } catch (Exception e){
        return
        ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body(gson.toJson("CostCon
troller error"));
    }
}

```

```

    }
}

@GetMapping("get/all")
public ResponseEntity<Object> getCostList(){
    try {
        return ResponseEntity.status(HttpStatus.OK).body(costService.getCosts());
    }catch (Exception e){
        return
ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body(gson.toJson("CostCon
troller error"));
    }
}

@GetMapping("get/{id}")
public ResponseEntity<String> getCost(@PathVariable Long id){
    try {
        return
ResponseEntity.status(HttpStatus.FOUND).body(gson.toJson(costService.getCost(id)));
    }catch (CostNotFoundException e){
        return
ResponseEntity.status(HttpStatus.NOT_FOUND).body(gson.toJson(e.getMessage()));
    }catch (Exception e){
        return
ResponseEntity.status(HttpStatus.INTERNAL_SERVER_ERROR).body("CostController
error");
    }
}
}

```

```

// @filename \src\main\java\suai\trsis2021\lab4\controller\WebController.java
package suai.trsis2021.lab4.controller;

```

```

import lombok.extern.slf4j.Slf4j;
import org.springframework.http.ResponseEntity;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.ResponseBody;
import org.springframework.web.bind.annotation.RestController;
import org.springframework.web.servlet.view.RedirectView;

import java.io.File;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;

```

```

import java.nio.file.Path;

@Controller
public class WebController {

    @GetMapping("")
    public RedirectView redirect(){
        return new RedirectView("/home-page");
    }

    @RequestMapping("/login")
    public String login(){
        return "LoginPage";
    }

    @GetMapping("/home-page")
    public String homePage() {
        return "HomePage";
    }

    @GetMapping("/full-access-pane")
    public String getAdminPage(){
        return "FullAccessPane";
    }

    @GetMapping("/read-access-pane")
    public String getReadPage() {
        return "ReadAccessPane";
    }

    @GetMapping("/forbidden-error")
    public String getForbiddenPage() {
        return "ForbiddenPage";
    }
}

// @filename \src\main\java\suai\trsis2021\lab4\entity\CostEntity.java
package suai.trsis2021.lab4.entity;

import lombok.*;
import org.hibernate.Hibernate;

import javax.persistence.Entity;
import javax.persistence.GeneratedValue;

```

```
import javax.persistence.GenerationType;
import javax.persistence.Id;
import java.util.Objects;
```

```
@Entity(name = "cost_entity")
public class CostEntity {
    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    @Getter @Setter private Long id;
    @Getter @Setter private String name;
    @Getter @Setter private Integer price;
    @Getter @Setter private String category;
    @Getter @Setter private String customer;
    @Getter @Setter private Integer count;
```

```
    public CostEntity() {
        count = 1;
    }

    public void countUp(){
        count += 1;
    }

    public void countDown(){
        count -= 1;
    }
}
```

```
// @filename
\src\main\java\suai\trsis2021\lab4\exceptions\CostNotFoundException.java
package suai.trsis2021.lab4.exceptions;
```

```
public class CostNotFoundException extends Exception{
    public CostNotFoundException(String message) {
        super(message);
    }
}
```

```
// @filename \src\main\java\suai\trsis2021\lab4\model\Cost.java
package suai.trsis2021.lab4.model;
```

```
import lombok.*;
import suai.trsis2021.lab4.entity.CostEntity;
```

```

public class Cost {

    public static Cost toModel(CostEntity entity){
        Cost cost = new Cost();
        cost.id = entity.getId();
        cost.name = entity.getName();
        cost.price = entity.getPrice();
        cost.category = entity.getCategory();
        cost.customer = entity.getCustomer();
        cost.count = entity.getCount();
        return cost;
    }

    @Getter @Setter private Long id;
    @Getter @Setter private String name;
    @Getter @Setter private Integer price;
    @Getter @Setter private String category;
    @Getter @Setter private String customer;
    @Getter @Setter private Integer count;

    public Cost() {
        count = 1;
    }

    public void countUp(){
        count += 1;
    }

    public void countDown(){
        count -= 1;
    }

}

```

```

// @filename \src\main\java\suai\trsis2021\lab4\repository\CostRepository.java
package suai.trsis2021.lab4.repository;

```

```

import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.data.jpa.repository.Modifying;
import org.springframework.data.jpa.repository.Query;
import org.springframework.stereotype.Repository;
import suai.trsis2021.lab4.entity.CostEntity;

```

```

import java.util.List;
import java.util.Optional;

```

```
@Repository
public interface CostRepository extends JpaRepository<CostEntity, Long> {
```

```
    @Modifying
    @Query("update cost_entity c " +
        "set c.name = ?1, " +
        "    c.price = ?2," +
        "    c.category = ?3," +
        "    c.customer = ?4," +
        "    c.count = ?5 " +
        "where c.id = ?6")
    void updateCostById(String name,
        Integer price,
        String category,
        String customer,
        Integer count,
        Long id);

    List<CostEntity> findByName(String name);
    Optional<CostEntity> findById(Long id);
}
```

```
// @filename \src\main\java\suai\trsis2021\lab4\service\CostService.java
package suai.trsis2021.lab4.service;
```

```
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;
import suai.trsis2021.lab4.entity.CostEntity;
import suai.trsis2021.lab4.exceptions.CostNotFoundException;
import suai.trsis2021.lab4.model.Cost;
import suai.trsis2021.lab4.repository.CostRepository;
```

```
import java.util.LinkedList;
import java.util.List;
import java.util.Optional;
```

```
@Service
@Transactional
public class CostService {
```

```
    @Autowired
    private CostRepository costRepository;
```



```

public boolean addCost(CostEntity cost){
    if(cost.getName() == null ||
        cost.getPrice() == null ||
        cost.getCustomer() == null ||
        cost.getCategory() == null) {
        return false;
    }

    try {
        CostEntity c = findCostEntity(cost);
        if(c == null){
            costRepository.save(cost);
        }
        else{
            c.countUp();
            updateCostById(c);
        }
        return true;
    }
    catch (Exception e){
        e.printStackTrace();
        return false;
    }
}

public boolean deleteCost(Long id){
    try {
        Optional<CostEntity> c = costRepository.findById(id);
        if(c.isEmpty()){
            return false;
        }

        CostEntity cost = c.get();
        if(cost.getCount() > 1){
            cost.countDown();
            updateCostById(cost);
        }
        else{
            costRepository.deleteById(id);
        }
        return true;
    }
    catch (Exception e){
        return false;
    }
}

```

```

public boolean putCost(CostEntity cost){
    if(cost.getName() == null ||
        cost.getPrice() == null ||
        cost.getCustomer() == null ||
        cost.getCategory() == null) {
        return false;
    }

    Optional<CostEntity> c = costRepository.findById(cost.getId());
    if(c.isEmpty()){
        return false;
    }

    CostEntity costEntity = c.get();
    costEntity.setName(cost.getName());
    costEntity.setPrice(cost.getPrice());
    costEntity.setCategory(cost.getCategory());
    costEntity.setCustomer(cost.getCustomer());
    updateCostById(costEntity);
    return true;
}

public List<Cost> getCosts(){
    List<Cost> costs = new LinkedList<>();
    costRepository.findAll().forEach(e -> costs.add(Cost.toModel(e)));
    return costs;
}

public Cost getCost(Long id) throws CostNotFoundException {
    var cost = costRepository.findById(id);
    if(cost.isEmpty()){
        throw new CostNotFoundException("Cost don't found");
    }
    return Cost.toModel(cost.get());
}

private boolean equalsCosts(CostEntity e1, CostEntity e2){
    return e1.getName().equals(e2.getName()) &&
        e1.getCustomer().equals(e2.getCustomer()) &&
        e1.getPrice().equals(e2.getPrice()) &&
        e1.getCategory().equals(e2.getCategory());
}

public CostEntity findCostEntity(CostEntity cost) {
    for (var c : costRepository.findByName(cost.getName())) {

```

```

        if (equalsCosts(c, cost)) {
            return c;
        }
    }
    return null;
}

private void updateCostById(CostEntity cost){
    costRepository.updateCostById(
        cost.getName(),
        cost.getPrice(),
        cost.getCategory(),
        cost.getCustomer(),
        cost.getCount(),
        cost.getId()
    );
}
}

```

```

// @filename \src\main\java\suai\trsis2021\lab4\util\WebSecurityConfig.java
package suai.trsis2021.lab4.util;

```

```

import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import
org.springframework.security.config.annotation.authentication.builders.AuthenticationMa
nagerBuilder;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import
org.springframework.security.config.annotation.web.configuration.EnableWebSecurity;
import
org.springframework.security.config.annotation.web.configuration.WebSecurityConfigurer
Adapter;
import org.springframework.security.core.Authentication;
import org.springframework.security.core.userdetails.User;
import org.springframework.security.core.userdetails.UserDetails;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.provisioning.InMemoryUserDetailsManager;
import org.springframework.web.bind.annotation.GetMapping;

import java.util.Arrays;

@Configuration
@EnableWebSecurity
public class WebSecurityConfig extends WebSecurityConfigurerAdapter {

```

```

@Override
protected void configure(HttpSecurity http) throws Exception {
    http.csrf().disable()

        .authorizeRequests()
            .antMatchers("/", "/home-page").permitAll()
            .antMatchers("/read-access-pane").hasRole("USER")
            .antMatchers("/full-access-pane").hasRole("ADMIN")
        .and()
            .formLogin()
                .loginPage("/login")
                .permitAll()
        .and()
            .logout()
                .permitAll()
        .and()
            .exceptionHandling().accessDeniedPage("/forbidden-error");
}

```

```

@Bean
@Override
protected UserDetailsService userDetailsService() {
    UserDetails user = User.withDefaultPasswordEncoder()
        .username("user")
        .password("1")
        .roles("USER")
        .build();

    UserDetails admin = User.withDefaultPasswordEncoder()
        .username("admin")
        .password("1")
        .roles("ADMIN")
        .build();

    return new InMemoryUserDetailsManager(user, admin);
}
}

```