main

August 21, 2021

1 GO analysis using GOATOOLS

```
[1]: import functools
  import pandas as pd
  import collections as cx
  from pybiomart import Dataset
  # GO analysis
  from goatools.base import download_go_basic_obo
  from goatools.base import download_ncbi_associations
  from goatools.obo_parser import GODag
  from goatools.anno.genetogo_reader import Gene2GoReader
  from goatools.goea.go_enrichment_ns import GOEnrichmentStudyNS
```

```
[2]: Ofunctools.lru_cache()
     def get_database():
         dataset = Dataset(name="hsapiens_gene_ensembl",
                           host="http://www.ensembl.org",
                           use_cache=True)
         db = dataset.query(attributes=["ensembl_gene_id",
                                        "external_gene_name",
                                         "entrezgene_id"],
                            use_attr_names=True).dropna(subset=['entrezgene_id'])
         return db
     @functools.lru_cache()
     def get_deg():
         fn = '../../_m/genes/diffExpr_EAvsAA_FDR05.txt'
         return pd.read_csv(fn, sep='\t')
     @functools.lru_cache()
     def convert2entrez():
         df = get_deg()
         if 'EntrezID' in df.columns:
             return df.rename(columns={'EntrezID': 'entrezgene_id'})
         else:
```

```
[3]: def obo_annotation(alpha=0.05):
         # database annotation
         fn_obo = download_go_basic_obo()
         fn_gene2go = download_ncbi_associations() # must be qunzip to work
         obodag = GODag(fn_obo) # downloads most up-to-date
         anno_hs = Gene2GoReader(fn_gene2go, taxids=[9606])
         # get associations
         ns2assoc = anno_hs.get_ns2assc()
         for nspc, id2gos in ns2assoc.items():
             print("{NS} {N:,} annotated human genes".format(NS=nspc, N=len(id2gos)))
         goeaobj = GOEnrichmentStudyNS(
             get_database()['entrezgene_id'], # List of human genes with entrez IDs
             ns2assoc, # geneid/GO associations
             obodag, # Ontologies
             propagate_counts = False,
             alpha = alpha, # default significance cut-off
             methods = ['fdr_bh'])
         return goeaobj
     def run_goea(direction):
         if direction == "Up":
             df = get_upregulated()
         elif direction == "Down":
             df = get_downregulated()
         else:
             df = convert2entrez()
         geneids_study = {z[0]:z[1] for z in zip(df['entrezgene_id'], df['Symbol'])}
         goeaobj = obo_annotation()
         goea_results_all = goeaobj.run_study(geneids_study)
         goea_results_sig = [r for r in goea_results_all if r.p_fdr_bh < 0.05]</pre>
```

```
ctr = cx.Counter([r.NS for r in goea_results_sig])
print('Significant results[{TOTAL}] = {BP} BP + {MF} MF + {CC} CC'.format(
    TOTAL=len(goea_results_sig),
    BP=ctr['BP'], # biological_process
    MF=ctr['MF'], # molecular_function
    CC=ctr['CC'])) # cellular_component

if direction == "Up":
    label = "upregulated"
elif direction == "Down":
    label = "downregulated"
else:
    label = "allDEG"
goeaobj.wr_xlsx("GO_analysis_%s.xlsx" % label, goea_results_sig)
goeaobj.wr_txt("GO_analysis_%s.txt" % label, goea_results_sig)
```

1.1 Gene ontology

```
[4]: for direction in ["All", "Up", "Down"]:
         run_goea(direction)
    requests.get(http://purl.obolibrary.org/obo/go/go-basic.obo, stream=True)
      WROTE: go-basic.obo
    FTP RETR ftp.ncbi.nlm.nih.gov gene/DATA gene2go.gz -> gene2go.gz
      gunzip gene2go.gz
    go-basic.obo: fmt(1.2) rel(2021-08-18) 47,217 GO Terms
    HMS:0:00:04.387035 330,313 annotations, 20,685 genes, 18,684 GOs, 1 taxids READ:
    MF 18,190 annotated human genes
    BP 18,505 annotated human genes
    CC 19,422 annotated human genes
    Load BP Gene Ontology Analysis ...
     70% 20,236 of 29,107 population items found in association
    Load CC Gene Ontology Analysis ...
     74% 21,428 of 29,107 population items found in association
    Load MF Gene Ontology Analysis ...
     70\% 20,354 of 29,107 population items found in association
    Run BP Gene Ontology Analysis: current study set of 2955 IDs ... 82% 1,852 of
    2,260 study items found in association
     76% 2,260 of 2,955 study items found in population(29107)
    Calculating 12,429 uncorrected p-values using fisher
      12,429 GO terms are associated with 17,848 of 29,107 population items
       4,987 GO terms are associated with 1,852 of 2,955 study items
```

```
METHOD fdr_bh:
      19 GO terms found significant (< 0.05=alpha) ( 15 enriched +
purified): statsmodels fdr_bh
     261 study items associated with significant GO IDs (enriched)
      52 study items associated with significant GO IDs (purified)
Run CC Gene Ontology Analysis: current study set of 2955 IDs ... 86% 1,945 of
2,260 study items found in association
76% 2,260 of 2,955 study items found in population(29107)
Calculating 1,753 uncorrected p-values using fisher
   1,753 GO terms are associated with 18,711 of 29,107 population items
     876 GO terms are associated with 1,945 of 2,955 study items
 METHOD fdr_bh:
      55 GO terms found significant (< 0.05=alpha) ( 55 enriched +
purified): statsmodels fdr_bh
   1,820 study items associated with significant GO IDs (enriched)
       O study items associated with significant GO IDs (purified)
Run MF Gene Ontology Analysis: current study set of 2955 IDs ... 84% 1,894 of
2,260 study items found in association
76% 2,260 of 2,955 study items found in population(29107)
Calculating 4,420 uncorrected p-values using fisher
   4,420 GO terms are associated with 17,838 of 29,107 population items
   1,624 GO terms are associated with 1,894 of 2,955 study items
 METHOD fdr_bh:
      13 GO terms found significant (< 0.05=alpha) ( 10 enriched +
                                                                     3
purified): statsmodels fdr_bh
   1,589 study items associated with significant GO IDs (enriched)
      29 study items associated with significant GO IDs (purified)
Significant results[87] = 19 BP + 13 MF + 55 CC
     87 items WROTE: GO_analysis_allDEG.xlsx
     87 GOEA results for 1952 study items. WROTE: GO_analysis_allDEG.txt
 EXISTS: go-basic.obo
 EXISTS: gene2go
go-basic.obo: fmt(1.2) rel(2021-08-18) 47,217 GO Terms
HMS:0:00:04.604500 330,313 annotations, 20,685 genes, 18,684 GOs, 1 taxids READ:
gene2go
MF 18,190 annotated human genes
BP 18,505 annotated human genes
CC 19,422 annotated human genes
Load BP Gene Ontology Analysis ...
70% 20,236 of 29,107 population items found in association
Load CC Gene Ontology Analysis ...
74% 21,428 of 29,107 population items found in association
```

Load MF Gene Ontology Analysis ...

```
70% 20,354 of 29,107 population items found in association
```

```
Run BP Gene Ontology Analysis: current study set of 1546 IDs ... 78%
                                                                      857 of
1,097 study items found in association
71% 1,097 of 1,546 study items found in population(29107)
Calculating 12,429 uncorrected p-values using fisher
  12,429 GO terms are associated with 17,848 of 29,107 population items
   3,085 GO terms are associated with 857 of 1,546 study items
 METHOD fdr bh:
      25 GO terms found significant (< 0.05=alpha) ( 23 enriched +
                                                                     2
purified): statsmodels fdr_bh
     168 study items associated with significant GO IDs (enriched)
       6 study items associated with significant GO IDs (purified)
Run CC Gene Ontology Analysis: current study set of 1546 IDs ... 82%
                                                                      902 of
1,097 study items found in association
71% 1,097 of 1,546 study items found in population(29107)
Calculating 1,753 uncorrected p-values using fisher
   1,753 GO terms are associated with 18,711 of 29,107 population items
     559 GO terms are associated with
                                         902 of 1,546 study items
 METHOD fdr bh:
      16 GO terms found significant (< 0.05=alpha) ( 16 enriched +
purified): statsmodels fdr_bh
     627 study items associated with significant GO IDs (enriched)
       O study items associated with significant GO IDs (purified)
Run MF Gene Ontology Analysis: current study set of 1546 IDs ... 80%
                                                                      880 of
1,097 study items found in association
71% 1,097 of 1,546 study items found in population(29107)
Calculating 4,420 uncorrected p-values using fisher
   4,420 GO terms are associated with 17,838 of 29,107 population items
     980 GO terms are associated with
                                      880 of 1,546 study items
 METHOD fdr_bh:
      10 GO terms found significant (< 0.05=alpha) ( 9 enriched +
purified): statsmodels fdr bh
     680 study items associated with significant GO IDs (enriched)
       1 study items associated with significant GO IDs (purified)
Significant results[51] = 25 BP + 10 MF + 16 CC
     51 items WROTE: GO_analysis_upregulated.xlsx
                          816 study items. WROTE: GO_analysis_upregulated.txt
     51 GOEA results for
 EXISTS: go-basic.obo
 EXISTS: gene2go
go-basic.obo: fmt(1.2) rel(2021-08-18) 47,217 GO Terms
HMS:0:00:04.492485 330,313 annotations, 20,685 genes, 18,684 GOs, 1 taxids READ:
gene2go
MF 18,190 annotated human genes
BP 18,505 annotated human genes
CC 19,422 annotated human genes
```

```
Load BP Gene Ontology Analysis ...
70% 20,236 of 29,107 population items found in association
Load CC Gene Ontology Analysis ...
74\% 21,428 of 29,107 population items found in association
Load MF Gene Ontology Analysis ...
 70% 20,354 of 29,107 population items found in association
Run BP Gene Ontology Analysis: current study set of 1409 IDs ... 86%
                                                                      995 of
1,163 study items found in association
83% 1,163 of 1,409 study items found in population(29107)
Calculating 12,429 uncorrected p-values using fisher
  12,429 GO terms are associated with 17,848 of 29,107 population items
   3,358 GO terms are associated with 995 of 1,409 study items
 METHOD fdr_bh:
       9 GO terms found significant (< 0.05=alpha) ( 6 enriched +
                                                                     3
purified): statsmodels fdr_bh
     135 study items associated with significant GO IDs (enriched)
      13 study items associated with significant GO IDs (purified)
Run CC Gene Ontology Analysis: current study set of 1409 IDs ... 90% 1,043 of
1,163 study items found in association
83% 1,163 of 1,409 study items found in population(29107)
Calculating 1,753 uncorrected p-values using fisher
   1,753 GO terms are associated with 18,711 of 29,107 population items
     695 GO terms are associated with 1,043 of 1,409 study items
 METHOD fdr_bh:
      41 GO terms found significant (< 0.05=alpha) ( 41 enriched +
purified): statsmodels fdr_bh
     966 study items associated with significant GO IDs (enriched)
       O study items associated with significant GO IDs (purified)
Run MF Gene Ontology Analysis: current study set of 1409 IDs ... 87% 1,014 of
1,163 study items found in association
83% 1,163 of 1,409 study items found in population(29107)
Calculating 4,420 uncorrected p-values using fisher
  4,420 GO terms are associated with 17,838 of 29,107 population items
   1,101 GO terms are associated with 1,014 of 1,409 study items
 METHOD fdr_bh:
      12 GO terms found significant (< 0.05=alpha) ( 11 enriched +
purified): statsmodels fdr_bh
     876 study items associated with significant GO IDs (enriched)
       O study items associated with significant GO IDs (purified)
Significant results[62] = 9 BP + 12 MF + 41 CC
     62 items WROTE: GO_analysis_downregulated.xlsx
     62 GOEA results for 1034 study items. WROTE: GO_analysis_downregulated.txt
```

[]:[