

# main\_plot

August 23, 2021

## 1 Visualize GO analysis

```
[1]: import numpy as np
import pandas as pd
```

```
[2]: def get_top_GO(fn, label):
    df = pd.read_excel(fn).sort_values('p_uncorrected').head(10)
    df['Log10'] = -np.log10(df['p_fdr_bh'])
    df['Tissue'] = label
    return df
```

```
[3]: config = {
    'Caudate': 'GO_analysis_mashr_caudate.xlsx',
    'Dentate Gyrus': 'GO_analysis_mashr_dentate_gyrus.xlsx',
    'DLPFC': 'GO_analysis_mashr_dlpfc.xlsx',
    'Hippocampus': 'GO_analysis_mashr_hippocampus.xlsx',
}

df = pd.DataFrame()
for bias in ["Caudate", "Dentate Gyrus", "DLPFC", "Hippocampus"]:
    df = pd.concat([df, get_top_GO(config[bias], bias)], axis=0)

fac = []
for ii in range(df.shape[0]):
    xx, yy = df[['ratio_in_study']].iloc[ii, 0].split('/')
    fac.append((int(xx) / int(yy)) * 2)

df['geneRatio'] = fac
print(np.min(fac), np.max(fac))
```

0.020497803806734993 1.302325581395349

```
[4]: df.to_csv("GO_analysis_top10_mashr.tsv", sep='\t', index=False)
```

### 1.1 Plot

```
[5]: %load_ext rpy2.ipython
```

```
[6]: %%R -i df
library(ggplot2)
library(tidyverse)

save_plot <- function(p, fn, w, h){
  for(ext in c('.svg', '.png', '.pdf')){
    ggsave(file=paste0(fn,ext), plot=p, width=w, height=h)
  }
}

plot_G0 <- function(){
  cbPalette <- ggpubr::get_palette(palette = "npg", 4)
  gg1 = df %>%
    ggplot(aes(x=Log10, y=name, color=Tissue, size=geneRatio)) +
    geom_point(shape=18, alpha=0.8) + labs(y='', x='-Log10 (FDR)') +
    theme_bw(base_size=15) +
    scale_colour_manual(name="Ancestry", values=cbPalette,
                        labels=c("Caudate", "Dentate Gyrus",
                                "DLPFC", "Hippocampus")) +
    geom_vline(xintercept = -log10(0.05), linetype = "dotted") +
    theme(axis.title=element_text(face='bold'),
          strip.text=element_text(face='bold'))
  return(gg1)
}
```

R[write to console]: Want to understand how all the pieces fit together? Read R for Data


Science: <https://r4ds.had.co.nz/>

R[write to console]: Attaching packages  
tidyverse 1.3.1

R[write to console]: tibble 3.1.2 dplyr 1.0.7  
tidyr 1.1.3 stringr 1.4.0  
readr 1.4.0 forcats 0.5.1  
purrr 0.3.4

R[write to console]: Conflicts  
tidyverse\_conflicts()  
dplyr::filter() masks stats::filter()  
dplyr::lag() masks stats::lag()

```
[7]: %%R
gg1 = plot_G0()
print(gg1)
save_plot(gg1, "ancestry_mashr_G0_top10_stacked", 8, 6)
```



[ ]: