

Sample

Name : GNP14.3.16_1.24_10k
Mesured On : 14.03.2016 12:48
by : -- **logged as** : Admin
Comments from admin :


SOP

Name	: Default	Resolution	: MEDIUM
Laser Power	: 60%	Electrode Distance	: 5 mm
# Measure per sequence : 10		pH	: unknown
		Temperature	: 25.0 °C

Zeta potential calculation:

Solvant	: Water	Henry function: Smoluchowski
Dielectric Constant : 78.06		Viscosity: 0.888 cP

Mobility



Sequence

$\langle m \rangle: 0.1 (\mu\text{m.cm/V.s})$ S: 0.06 $\langle Z \rangle: 1.25(\text{mV})$ S: 0.82

14.03.2016 12:51

Temperature: 25.0 °C **pH** : unknown

Dielectric Constante : 78.06

Viscosity : 0.888 cP

Conductivity indicator : 4.951 V


Applied field : 19.05 V/cm

Reference intensity : 449 kcps

Scattering intensity : 370 kcps

Carrier frequency : 8030 Hz

Mobility



Values

#	Valid	Raw		Fit			
		μ ($\mu\text{m.cm/V.s}$)	Z (mV)	μ ($\mu\text{m.cm/V.s}$)	S	Z (mV)	S
Avg		0.1	1.25	0.08	0.27	1.06	3.48
1	þ	0.14	1.79	0.1	0.24	1.26	3.02
2	þ	0.14	1.79	0.12	0.23	1.5	2.94
3	þ	0	0	0.07	0.24	0.87	3.15
4	þ	0	0	0.05	0.26	0.6	3.38
5	þ	0.14	1.79	0.07	0.3	0.89	3.84
6	þ	0	0	0.09	0.33	1.19	4.22
7	þ	0.14	1.79	0.1	0.3	1.31	3.87
8	þ	0.14	1.79	0.08	0.26	1.07	3.3
9	þ	0.14	1.79	0.04	0.26	0.53	3.31
10	þ	0.14	1.79	0.1	0.29	1.34	3.79